

CONSTRUCTION PLANS FOR

PINO YARDS INTERIM DRAINAGE IMPROVEMENTS

DRAWING INDEX

SHEET TITLE	S	HEET NO.
COVER SHEET		1
PLAN VIEW		2
CROSS-SECTIONS AND DETAILS		3
SPILLWAY PLAN AND SECTIONS		4


DRAINAGE DESIGN NOTE:

DRAINAGE DESIGN IS FOR EXISTING CONDITION FLOW

AND IS NOT INTENDED FOR FUTURE SITE DEVELOPMENT,


DESIGN INTENT IS FOR DRAINAGE COLLECTION

AND OIL SEPARATION



GENERAL NOTES

- ALL VORK DETAILED ON THESE PLANS TO BE PERFORMED UNDER CONTRACT SHALL, EXCEPT AS OTHERWISE STATED OR PROVIDED FOR HEREIN, BE CONSTRUCTED IN ACCORDANCE WITH THE CITY OF ALBUQUERQUE STANDARD SPECIFICATIONS FOR PUBLIC WORKS CONSTRUCTION (1986) INCLUDING CURRENT UPDATES (MAY ALSO BE REFERRED TO AS THE STANDARD SPECIFICATIONS).
- TWO (2) WORKING DAYS PRIOR TO ANY EXCAVATION, CONTRACTOR MUST CONTACT LINE LOCATING SERVICE, 260-1990, FO LOCATION OF EXISTING UTILITIES.
- 3. ALL UTILITIES SHOWN AND ANY OTHER UTILITIES THAT ARE NOT SHOWN ON THE PLANS BUT ARE WITHIN THE CONSTRUCTION AREA SHALL BE LOCATED, IDENTIFIED AND PROTECTED BY THE CONTRACTOR AT ALL TIMES DURING CONSTRUCTION. THE CONTRACTOR SHALL VERIFY ALL DIMENSIONS AND CONDITIONS SHOWN ON DRAWINGS PRIOR TO STARTING WORK AND SHALL NOTIFY THE ENGINEER OF ANY DISCREPANCIES OR INCONSISTENCIES.
- 4. PRIOR TO CONSTRUCTION, THE CONTRACTOR SHALL VERIFY THE HORIZONTAL AND VERTICAL LOCATIONS OF ALL OBSTRUCTIONS. SHOULD A CONFLICT EXIST, THE CONTRACTOR SHALL NOTIFY THE ENGINEER SO THAT THE CONFLICT CAN BE RESOLVED WITH MINIMUM AMOUNT OF DELAY.
- 5. ALL WORK SHALL BE DONE BY QUALIFIED PERSONNEL IN AN APPROVED STANDARD OF PRACTICE
- 6. THE COST OF ADDITIONAL DESIGN WORK DUE TO ERRORS AND OMISSIONS IN CONSTRUCTION SHALL BE BORNE BY THE CONTRACTO
- 7. SURVEY MONUMENTS. THE CONTRACTOR SHALL NOTIFY THE ENGINEER NOT LESS THAN SEVEN (7) DAYS PRIOR TO STARTING WORK IN ORDER THAT THE ENGINEER MAY TAKE NECESSARY MEASURES TO INSURE THE PRESERVATION OF SURVEY MONUMENTS. CONTRACTOR SHALL NOT DISTURB PERMANENT SURVEY MONUMENTS WITHOUT THE CONSENT OF THE ENGINEER AND SHALL NOTIFY THE ENGINEER AND BEAR THE EXPENSE OF REPLACING ANY THAT MAY BE DISTURBED WITHOUT PERMISSION. REPLACEMENT SHALL BE DONE ONLY BY THE ENGINEER. WHEN A CHANGE IS MADE IN THE FINISHED ELEVATION OF THE PAVEMENT OF ANY ROADWAY IN WHICH A PERMANENT SURVEY MONUMENT IS LOCATED, CONTRACTOR SHALL, AT HIS OWN EXPENSE, ADJUST THE MONUMENT COVER TO THE NEW GRADE UNLESS OTHERWISE SPECIFIED. REFER TO SECTION 4.4 OF THE SPECIFICATION.
- 8. CONCRETE. CONCRETE FOR THIS PROJECT SHALL BE AS GIVEN IN THE STANDARD SPECIFICATIONS AND THE SUPPLEMENTAL TECHNICAL SPECIFICATIONS.
- 9. COMPACTION. COMPACTION UNDER AND BEHIND PAVING AND CONCRETE STRUCTURES SHALL BE 95% OF MAXIMUM DRY DENSITY PER ASTM D-1557 AND SHALL EXTEND 2 FEET BEYOND THE STRUCTURES OR THE EDGE OF PAVING EXCEPT THAT COMPACTION ADJACENT TO THE OIL SEPARATOR SIDEWALLS SHALL BE AT 90%. COMPACTION UNDER THE POND LINER SHALL BE 90%.
- 10. LAYOUT. THE PROJECT IS DESIGNED TO BE LAID OUT BY MEASUREMENTS FROM EXISTING FENCE LINES RATHER THAN BY BEARINGS
- 11. ELEVATIONS. ELEVATIONS SHOWN ARE BASED ON THE ASSUMED TBM ELEVATION OF 100.00.
- 12. STORED MATERIAL. THE CITY OF ALBUQUERQUE SHALL REMOVE STORED MATERIAL FROM THE CONSTRUCTION AREA PRIOR TO THE START OF CONSTRUCTION.
- 13. DRAINAGE. THE CONTRACTOR SHALL ENSURE THAT ALL PERMANENT WORK IS CARRIED ON IN AREAS FREE FROM WATER. SEE THE SUPPLEMENTAL TECHNICAL SPECIFICATIONS.
- 14. EROSION. THE CONTRACTOR SHALL NSURE THAT HIS ACTIVITIES DO NOT PRODUCE EROSION ONTO OR ON PUBLIC OR PRIVATE PROPERTY, INCLUDING STREETS, ROADS, AND ARROYOS.
- 15. PAVEMENT REMOVAL. THE PAVING TO BE REMOVED UNDER THIS PROJECT HAS GENERALLY BEEN CONTAMINATED WITH ENGINE AND HYDRAULIC OIL. THE CONTRACTOR SHALL DISPOSE OF THE ASPHALT IN A EID PERMITTED LANDFILL.
- 16. MAINTENANCE. THE OWNER IS RESPONSIBLE FOR MAINTAINING THE OIL/WATER SEPARATOR IN GOOD CONDITION AND REMOVING OIL AND GRIT. AT A MINIMUM THE SEPARATOR SHOULD BE CLEANED IN MAY AND NOVEMBER EACH YEAR AND AFTER EVERY MAJOR STORM. THE SEPARATOR IS DESIGNED TO BE CLEANED FROM OUTSIDE THE PONDING AREA BY USE OF A TRUCK-MOUNTED VACUUM CLEANER (VACTOR).
- 17. CONSTRUCTION SIGNS. NO CONSTRUCTION SIGNS ARE REQUIRED FOR THIS PROJECT UNDER SPECIAL PROVISIONS SECTION 3.
- 18. PAVEMENT REMOVAL DOCUMENTATION. THE CONTRACTOR WILL SUPPLY THE CITY WITH WRITTEN PROOF DOCUMENTING THE QUANTITY OF ASPHALT REMOVED AND DELIVERED TO THE EID PERMITTED LANDFILL, THE TIME OF DELIVERY, AND THE LOCATION FROM WHICH IT WAS REMOVED. THE CONTRACTOR WILL NOTIFY THE PROJECT MANAGER BEFORE THE ASPHALT IS HAULED OFFSITE.



RESOURCE
TECHNOLOGY
INCORPORATED

APPROVED FOR CONSTRUCTION

2-7-91

PROJECT NO.

4094.90

SHEET



