

## GENERAL NOTES

- A) COORDINATE WITH MECHANICAL, ELECTRICAL & PLUMBING
- B) ALL INTERIOR DIMENSIONS ARE TO FACE OF STUD, UNLESS NOTED OTHERWISE
- C) ALL EXTERIOR DIMENSIONS ARE TO FACE OF STUD, UNLESS NOTED OTHERWISE
- D) REFER TO ENLARGED PLANS FOR WALL TYPES AND DIMENSIONS WITHIN DETAILED AREAS
- E) COORDINATE FINAL LOCATION OF FIRE EXTINGUISHERS WITH FIRE MARSHAL
- F) REFER TO A-601 FOR DOOR AND FRAME TYPES
- F) UNDER FLOOR UTILITES COMPLETED IN TENANT IMPROVEMENT

## KEYED NOTES 🤇

- EXTERIOR WALL VARIES IN THICKNESS AND FORM REFER TO ELEVATIONS FOR ADDL. INFORMATION
  ALUMINUM STOREFRONT
- 3. STEEL COLUMN PER STRUCTURAL
- 4. TWO COAT SYNTHETIC STUCCO W/ CRACKMASTER OVER 1" RIGID INSULATION ADHERED TO 1/2" SHEATHING OVER 2X WOOD FURRING OVER 2X8 WOOD STUDS @ 16" O.C.
- 5. GAS/ELECTRIC METER
- 6. KNOX BOX
- 7. ROOF DRAIN WITHIN WALL
- 8. DOOR PER SCHEDULE
- 9. 10" DIAMETER WOOD COLUMN TYP

## 10. OUTLINE OF SHADE STRUCTURE ABOVE

11. YARD WALL (42" MIN TALL) - EXTERIOR CEMENT PLASTER OVER 7 5/8" CMU WALL BOTH SIDES - PAINT TO MATCH STRUCTURE. SEE DETAIL A2/AS-106 & ELEVATIONS SHEET A-201 FOR ADDITIONAL INFORMATION

12. OUTLINE OF STRUCTURE ABOVE

13. RECESSED ALCOVE AT WALL

- 14. PROVIDE ELECTRICAL AT EXITS FOR FUTURE EXIT SIGNAGE
- 15. BRASS COW TONGUE @ ROOF DRAIN DOWNSPOUT TO OPTIONAL CONCRETE CHANNEL
- 16. ELECTRICAL OR PLUMBING PENETRATION AT SLAB SEE SHEET A-100.
- 17. KEY OPERATED TAMPER PROOF HOSE BIBB LOCATION AT EXTERIOR WALL
- 18. FUTURE DEMISING WALL FOR REFERENCE ONLY SEE TENANT IMPROVEMENT DRAWINGS 19. OUTLINE OF ROOF ACCESS HATCH ABOVE & FUTURE LOCATION OF ROOF ACCESS LADDER

20. FIRE PLACE AT YARD WALL

- 21. PAINTED STEEL FENCE 42" TALL SEE D6 / AS-105
- 22. FACTORY PAINTED METAL DOWNSPOUT
- 23. FIRE RISER LOCATION CENTER LINE

