

DRAINAGE REPORT FOR
TRACT B-8
SUBDIVISION AT SEVEN BAR NORTH

APRIL 10, 1998



BOHANNAN HUSTON

Courtyard One

7500 JEFFERSON NE

Albuquerque

NEW MEXICO 87109

voice 505.823.1000

fax 505.821.0017

Prepared for

BROWN/NZ DEVELOPMENT JOINT VENTURE
C/O BROWN & ASSOCIATES
3411 CANDELARIA NE
ALBUQUERQUE, NEW MEXICO 87107

Prepared by

BOHANNAN HUSTON
COURTYARD I
7500 JEFFERSON NE
ALBUQUERQUE, NEW MEXICO 87109

PREPARED BY:



John C. Alexander, P.E. Date 4-10-98



TABLE OF CONTENTS

	PAGE
I. INTRODUCTION.....	1
II. PURPOSE.....	1
III. HYDROLOGIC/HYDRAULIC COMPARISON BETWEEN REPORTS	1
IV. CONCLUSION	2

FIGURES

- FIGURE 1 - VICINITY MAP
FIGURE 2 - CURB TYPE IDENTIFICATION

APPENDIX

- APPENDIX A - JUNE 1995 HYDROLOGIC CALCULATIONS
APPENDIX B - MARCH 1998 HYDROLOGIC CALCULATIONS
APPENDIX C - INFRASTRUCTURE LIST
APPENDIX D - EPA FORM (NOI)

PLATES

- PLATE 1 - PREVIOUSLY PROPOSED CONDITION BASIN MAP (JUNE 1995)
PLATE 2 - PREVIOUS SUBDIVISION SITE GRADING AND DRAINAGE PLAN (JUNE 1995)
PLATE 3 - PROPOSED SUBDIVISION SITE GRADING AND DRAINAGE PLAN (MARCH 1998)
PLATE 4 - PREVIOUS PRELIMINARY PLAT (JUNE 1995)
PLATE 5 - PROPOSED PRELIMINARY PLAT (MARCH 1998)

I. INTRODUCTION

This report summarizes the revisions made to a previously submitted and approved Drainage Report. The previous report, "Revised Drainage Report for Tracts B-7, B-8, and B-9 Subdivision at Seven Bar North," dated June 1995 is in City A-13/D-7 file. These revisions are an increased lot count in Tract B-8 only from 53 lots in the June 1995 report to 58 lots in this revised report. Streets have remained essentially identical in layout between the two reports. We have included pertinent maps and plans from the 1995 report for your convenience and comparison.

II. PURPOSE

The purpose of this report is to obtain approval for the revised preliminary and final plat, grading plan, building permit, and work order for Tract B-8. Development of Tract B-8 will occur in one phase, to be called "Catamount at Seven Bar North."

The preliminary plat and grading plan is anticipated to be heard at DRB on May 5, 1998. For clarity's and reduced paperwork's sake, we have not attempted to revise and resubmit the bulky previous report, but instead are submitting this report as an "addendum" that provides new calculations and materials only in areas where drainage conditions have changed.

III. HYDROLOGIC/HYDRAULIC COMPARISON BETWEEN REPORTS

All information pertaining to "Tract B-8" in the June 1995 report remains essentially unchanged except for lot density. It has changed from 3.56 to 3.89 dwelling units per acre. An analysis of impervious area was performed to compare the actual difference of the two fully developed conditions. The results show a negligible increase of only 0.3 cfs over the entire site in the 100-year, 6-hour storm event. Accordingly, there is no need to revise the vast majority of the storm drain/street drainage system calculations of the previous report. The results of the analysis are in the Appendix in a spreadsheet format.



As previously mentioned, we have enclosed plans and plats from the June 1995 and March 1998 reports in the Appendix for comparison and reference. The developed storm drainage system proposed and approved in the June 1995 report has not changed. The horizontal and vertical alignments of the residential streets have not changed except for the minor extension of the cul-de-sac road (which continues its previous slope of 8%). Essentially, we have moved lot lines and added five lots to the site. Due to the revised lot configuration, the majority of the pads have changed elevation only +/- one foot. We still incorporate split level pads and backyard ponds at some lots. Calculations for the backyard ponds are included in Appendix B.

Please refer to Plate 3, Proposed Subdivision Site Grading and Drainage Plan (March 1998). Tie slopes will be kept to a 3:1 maximum. The runoff from the east boundary (Tract B-9) will sheet flow to an existing pond near Sierrita Road as described in the 1995 report. Runoff from the northern boundary tie slope, north of Westside Boulevard's temporary asphalt curb, is confined within the Westside Boulevard right-of-way and conveyed via an earthen channel to an existing beehive covered manhole. The runoff from Westside Boulevard's asphalt is conveyed by the south curb and gutter to an existing pair of inlets located just east of the Westside Boulevard and Seven Bar Loop Road intersection.

IV. CONCLUSION

In conclusion, the increase in lot density and revised pad elevations has a negligible impact on the hydrological and hydraulic calculations on the previously approved drainage plan. Therefore, we recommend that this revised plan be approved for revised preliminary and final plat grading plan, building permit and work order for Tract B-8.

PEAK DISCHARGE, CFS/ACRE				
EVENT	A	B	C	D
100-YR (1)	1.29	2.03	2.87	4.37
10-YR (2)	0.24	0.76	1.49	2.89
3	0.44	0.67	0.99	1.97
4	0	0.22	0.44	1.24
2	0.24	0.76	1.49	2.89

[illegible]

MARCH, 1998

PEAK DISCHARGE, CFS/ACRE

EVENT	A	B	C	D
100-YR (1)	1.29	2.03	2.87	4.37
10-YR (2)	0.24	0.76	1.49	2.89
3	0.44	0.67	0.99	1.97
4	0	0.22	0.44	1.24
2	0.24	0.76	1.49	2.89

FULLY DEVELOPED CONDITIONS:

SUMMARY OF HYDROLOGIC DATA

SUMMARY OF HYDROLOGIC DATA										RATIONAL METHOD		
BASIN ID	AREA AC	AREA SQ. MI.	AREA A	% LAND TREATMENT			TIME TO PEAK	10-YR DISCHARGE CFS/AC	Q (10YR) CFS	COMPOSITE C	I (IN/HR)	Q (100YR) (CFS)
				B	C	D						
8A	3.756	0.0059	3.4	20.7	20.7	55.2	0.1333	2.07	7.8	0.74	4.70	13.0
8B	3.832	0.0060	2.6	26.7	26.7	44.0	0.1333	1.88	7.2	0.69	4.70	12.5
8C	3.768	0.0059	2.9	24.1	24.1	48.8	0.1333	1.96	7.4	0.71	4.70	12.6
8D	2.560	0.0040	5.4	10.2	10.2	74.3	0.1333	2.39	6.1	0.81	4.70	9.8
8E	1.698	0.0027	3.2	20.1	20.1	56.5	0.1333	2.09	3.6	0.74	4.70	5.9
SUMS												53.8

HYDROLOGIC DATA-SEVEN BAR NORTH TRACT 8
MARCH, 1998

IMPERVIOUS AREA DATA										ROADWAY CALCULATIONS									
LOT WIDTH		(IN FEET)		50	55	60	65	70	75	80	ROADWAY	TYPE 1	TYPE 2	TYPE 3	TYPE 4	TOTAL LENGTH		NUMBER OF	
PAD WIDTH				40	45	50	55	60	65	70	F-P WIDTH	28	51	26	0			CUL 1	
PAD DEPTH				65	65	65	65	65	65	65	SIDEWALK	4	4	4	0			0	
DRIVEWAY		(20' x20')		400	400	400	400	400	400	400	RADIUS				0			40	
(INCLUDED WITH ROAD)				200	220	240	260	280	300	320									
(NOT INCLUDED WITH		(10' x10')		100	100	100	100	100	100	100									
BACKYARD PONDING)				3300	3645	3990	4335	4680	5025	5370		36	59	34	0			5027	
TOTAL IMPERVIOUS				sq.ft./lot sq.ft./lot sq.ft./lot sq.ft./lot sq.ft./lot sq.ft./lot							sq.ft./ft sq.ft./ft sq.ft./ft sq.ft./ft sq.ft./ft sq.ft./ft							sq.ft	
CALCULATIONS																			
Q(100YR) (CFS)	BASIN ID	AREA		PERCENT		TOTAL NUMBER OF				TOTAL LENGTH				NUMBER OF					
		TYPE D	AC	TYPE D	AC	50'	55'	60'	65'	70'	75'	80'	TYPE 1	TYPE 2	TYPE 3	TYPE 4	ROADWAY PER BASIN	CUL-DE-SACS PER BASIN	
13.0	8A	2.07		55.2		0	0	0	6	5	3	0	600	61	0	0	0	0.13	
12.5	8B	1.69		44.0		0	0	0	8	3	0	0	639	0	0	0	0	0.34	
12.6	8C	1.84		48.8		0	0	0	7	5	0	0	644	0	0	0	0	0.64	
9.8	8D	1.90		74.3		0	0	0	4	10	1	0	0	0	255	0	0	1.00	
5.9	8E	0.96		56.5		0	0	0	2	2	2	0	362	0	0	0	0	0.13	
53.8								27	25	6	0	58							

BACKYARD PONDS

ASSUMING: (50% treatment "B" and 50% treatment "C") X (Backyard Area) + (100 sf X Treatment "D")
for 10 day, 100 year volumes

$$V(10) = \frac{V(360) + Ad*(P(10) - P(360))}{12 \text{ in/ft}} \quad \text{Where: E is the weighted excess percipitation} \quad \text{eq. a-7 DPM}$$

A is the area in each treatment type

E for treatment "B" and "C" portions:

$$E = \frac{EaAa+EbAb+EcAc+EdAd}{Aa+Ab+Ac+Ad} \quad \text{eq. a-5 DPM}$$

Given: $Ea = n/a$ $P10 = 3.67$
 $Eb = 0.67$ $P360 = 2.20$
 $Ec = 0.99$
 $Ed = 1.97$

$$E = \frac{[.67+.99]}{2*(12)} = 0.069 \text{ ft} \quad (\text{converts inches to feet})$$

$$V(10) = [(X \text{ BACKYARD AREA} - 100 \text{ sf}) \times E] + 100 \text{ sf} * [(1.97) + (3.67-2.20)]/12 \quad \text{eq. a-9 DPM}$$

CATAMOUNT AT SEVEN BAR NORTH

LOT # UNIT B-7	BACKYARD AREA (SQ. FT.)	REQUIRED V (10) (CU. FT.)	POND DIMENSION (FT.) (AVG. WIDTHS)				POND VOLUME (CU. FT.)	C	I	Q(10) CFS
			L	W1	W2	D				
23	7400	539	41	28	25	0.5	543	0.52	4.7	0.42
31	3020	237	29	18	15	0.5	239	0.52	4.7	0.17
32	2250	184	35	12	9	0.5	184	0.52	4.7	0.13
40	1160	109	26	10	7	0.5	111	0.52	4.7	0.07
41	1040	100	24	10	7	0.5	102	0.52	4.7	0.06
48	4960	371	38	21	18	0.5	371	0.52	4.7	0.28
(triangular pond 3:1 slope)			L1	L2	L3	D				
54	7090	518	36	36	51	1.0	596	0.52	4.7	0.40
55	3120	244	34	16	13	0.5	247	0.52	4.7	0.18
56	4245	322	35	20	17	0.5	324	0.52	4.7	0.24
57	3720	285	35	18	15	0.5	289	0.52	4.7	0.21

TOTAL = 2.13

