CITY OF ALBUQUERQUE



Planning Department Transportation Development Services Section

December 5, 2007

George R. Rainhart, Registered Architect 2325 San Pedro NE, Ste. 2-B Albuquerque, NM 87110

Re:

Certification Submittal for Final Building Certificate of Occupancy for

Ventana Square G4-A, [B-10 / D3C]

6541 Paradise Blvd NW

Architect's Stamp Dated 12/04/07

Dear Mr. Rainhart:

Sincerely

P.O. Box 1293

The TCL / Letter of Certification submitted on December 4, 2007 is sufficient for acceptance by this office for final Certificate of Occupancy (C.O.). Notification has been made to the Building and Safety Section.

Albuquerque

New Mexico 87103

www.cabq.gov

Nilo E. Salgado Fernandez, P.E.

Seniør Traffic Engineer

Development and Building Services

Planning Department

C:


Engineer Hydrology file CO Clerk

TRAFFIC CERTIFICATION

i Comp.	NIMBE OD NIMBA	-K E00	OF
I, CHENGE CAMHACT	NMPE OR NMRA		, OF
THE FIRM GEORGE PAINT	STEP STEP STANISHALL		
11110 11100 20 1 11110 10 11 12 2	SIGN SUBSTANTIAL		
Tree of the tree tree is a second	ESIGN INTENT OF TH		
	ECORD INFORMATION		THE
	ENT HAS BEEN OBTA		
	FIRM GEORGE PLINHA		
		HE PROJECT SIT	
A.3.07	ND HAVE DETERMIN	ED BY VISUAL	INSPECTION
THAT THE SURVEY DATA P	ROVIDED IS REPRESI	ENTATIVE OF A	CTUAL SITE
CONDITIONS AND IS TRUE	AND CORRECT TO TH	HE BEST OF MY	
KNOWLEDGE AND BELIEF.	THIS CERTIFICATION	N IS SUBMITTEI) IN
SUPPORT OF A REQUEST FO	OR CERTIFICATE OF	OCCUPANCY	
	•	1	
THE RECORD INFORMATION	N PRESENTED HEREC	ON IS NOT NECE	SSARILY
COMPLETE AND INTENDED	ONLY TO VERIFY SU	JBSTANTIAL CO	MPLIANCE
OF THE TRAFFIC ASPECTS (OF THIS PROJECT. TH	IOSE RELYING (ON THE
RECORD DOCUMENT ARE A	ADVISED TO OBTAIN	INDEPENDENT	. `
VERIFICATION OF ITS ACCU	JRACY BEFORE USIN	G IT FOR ANY C	OTHER
PURPOSE.			
OF NEW MAN			
	\		
(5)	· \		
GEORGE R.			
RAINHART. NO. 580	<i>]</i>]		
(E)	//		
A RECHITE			
- AND ARCH	ENGINEER	R'S OR ARCHITE	ECT'S STAMP
Signature of Engineer or Archite			



GEORGE RAINHART, ARCHITECT & ASSOCIATES P.C. HYDROLOGY SE 2325 SAN PEDRO NE SUITE 2-B ALBUQUERQUE, NEW MEXICO 87110 PHONE: 505-884-9110 FAX: 505-837-9877 Email: graa@gra-arch.com



General architecture character for pad structures is to follow the general design concept depicted on elevators of major stores and shops, pad buildings will be coementitious finish with a cementitious or split face cmu dado band. the main building walls must be colored to match color benjamin moore (#2) bm951 and (#1) bm1032. if the building extends below finish floor that area will also be covered with color #2. structures are to be predominately flat-roofed however partial building areas such as portals or small extensions of building functions adjacent to the major building mass may have sloped roofs. These roofs are to building wall below the top of the main building parapet. Architectural entry element roofs may extend above the parapet wall top-and-area to relate to the entry format of the main buildings. Building heights are limited to 35' parapet heights for major building walls, and 26' parapet heights for pad building walls

Shall include the following elements to provide uniform standards for all pads. each pad to follow building elevations provided. —the lower 3'-4" of the area of vertical walls and landscape walls shall be four or eight inch split face amu or stucco. color #2. --four or eight inch split face or accent block. color #1 --fuel canopies to be cementitious finish color #1 lighting to be entirely recessed in soffit of fuel canopies.(max 50ft candles) --each pad development to provide an outdoor paved and landscaped patio space with outdoor furniture, such as bench

All mechanical equipment will be screened from view of the adjacent parking area and public right-of-way. In addition, if it is determined that the mechanical unit can be observed from the residential area horizontal screening per the attached

color #3 marbled terra cotta concrete tile roofing, trim & accents (med)

Drive up pick up windows to be screened with a 5' high opaque wall and 5' wide (minimum) landscape area with evergreen trees at 10' on center and 10' high (minimum). A berm of the same height as the wall may be provided in lieu of

Except as noted under awnings all signage will be internally illuminated individual type lettering not to exceed 6 percent of the wall area of each building elevation or ten percent of the wall area of the shop building. Letters are to be back lit. No exposed neon. Neon must be within solid opaque faced metal channel lettering can type signs are prohibited. Any special logos associated with a specific tenant are to be provided in a non-illuminated fashion for specific approval.

Landscaping of the pads will be from the same landscaping pallet and concept as

Awnings are permitted above window areas. Awnings with painted or embossed corporate logos or signage are permitted provided the area when added to all other wall signage does not exceed 6 percent of the area of building wall. Illumination of awnings must be from pendant mounted fixtures located . above the awning. accent colors on awnings are to be compatible with the general color palette and samples of the proposed awning colors are to provided with each submittal.

Service areas such as refuse locations and compactors are to be totally screened from the view of the adjacent residential area, public rights-of-way and the adjacent monument area. Free-standing dumpster and compactor locations are to be gated. Screening material to match building wall color and material.REFER TO

Site lighting for pad structures is to match the site lighting provided for the main parking area. pad site lighting not to exceed 20' to fixture. Main parking area lighting not to exceed 20' to fixture. Exposed, i.e. unshield light fixtures are prohibited. All lamps must be shielded shoe box type fixtures. Maximum light level under fuel canopies to be 50ft candles, from totally recessed lighting.

250 sf x 16' tall architecturally coordinated signs are permitted, one each at the paradise blvd. entry to G. and one on Paseo del Norte frontage. Each pad building

All traffic requirements have been met per May 31,1998 agreement between the city

The allowed parking shall be equal to the required parking plus 10% maximum ADA requirements shall be located adjacent to building entries

Concept: If one of the approved schematic alternate use plans is selected for development in lieu of the approved Site Plan for Building Permit, a complete Site Plan for Building Permit Purposes will be prepared and submitted to the DRB for review and approval. (EPC review not required unless the plan for development does not match one of the alternate schematic plans).

-	○ KADIUS INFURMATION:		Albuquerque 🚓 💎
	1 RADIUS = 2'-0"	⟨7⟩ RADIUS = 25'-0"	Albuquerque & & & & & & & & & & & & & & & & & & &
_	⟨2⟩ RADIUS = 3'-0"	⟨8⟩ RADIUS = 35'-0"	JUL 18 2007
`	③ RADIUS = 5'-0"	(9) RADIUS = 40'-0"	T (7) (^
	(4) RADIUS = 10'-0"	① RADIUS = 50'-0"	I.B.C. Plan Check Section
	(5) RADIUS = 15'-0"	1 RADIUS = 60'-0"	

LEGAL DESCRIPTION: FOR ALL OR A PORTION OF TRACTS G1,G2,G4, VENTANA DE SQUARE AT VENTANA RANCH, ZONED SU-1 FOR RESTRICTED C-2 USES, LOCATED AT THE NORTHEAST CORNER OF UNIVERSE BLVD. NW AND PARADISE BLVD. NW. APPROXIMATELY 9.13 ACRES. (B-10 CARMEN MARRONE, STAFF PLANNER.

RAINHART

No. 580

11/15/2005 SCALE: G-1A&G-2A

