



- SWPPP
- Stormwater
- Erosion Control
- Reclamation
- Seeding

www.e2rc.com | 505.867.4040

[illegible]

GAMMA DEVELOPMENT, LLC
ASCENSION SUBDIVISION
ALBUQUERQUE, NM

DESIGNED BY:
KELLEY FETTER

DRAWN BY:
CHLOE FETTER PINNEY

SHEET:

COVER

THE NPDES COMPLIANCE SWPPP DRAWING AND ASSOCIATED DOCUMENTATION IS AND SHALL BE CONSIDERED A LIVING DOCUMENT ALLOWING FOR MODIFICATIONS AS SITE CONDITIONS CHANGE OR DICTATE.

MINIMUM REQUIREMENTS TO FURTHER DEVELOP OR MODIFY THIS STORMWATER POLLUTION PREVENTION PLAN (SWPPP) DRAWING SHALL BE BASED ON THE CURRENT EDITION OF THE NEW MEXICO STATE HIGHWAY AND TRANSPORTATION DEPARTMENT (NMSHTD), NPDES LAW AND CITY OF ALBUQUERQUE ORDINANCE § 14-5-2-11.

LOCATE TEMPORARY WASHOUT, ANCHORED TOILETS, CONSTRUCTION ENTRANCE AND PARKING, STAGING, REFUELING, TRASH CONTAINMENT AREA TO MINIMIZE SITE DISTURBANCE DURING CONSTRUCTION ACTIVITY.

ALL EROSION AND SEDIMENT CONTROL (ESC) WORK ON THESE PLANS, EXCEPT AS OTHERWISE STATED OR PROVIDED HEREON SHALL BE PERMITTED, CONSTRUCTED, INSPECTED, AND MAINTAINED IN ACCORDANCE WITH:

ALL TEMPORARY SEDIMENT AND EROSION CONTROL MEASURES MUST BE INSTALLED PRIOR TO BEGINNING ANY EARTH MOVING ACTIVITIES EXCEPT AS SPECIFIED HEREON IN THE PHASING PLAN. CONSTRUCTION OF EARTHEN BMPS SUCH AS SEDIMENT TRAPS, SEDIMENT BASINS, AND DIVERSION BERMS SHALL BE COMPLETED AND INSPECTED PRIOR TO ANY OTHER CONSTRUCTION OR EARTHWORK. SELF-INSPECTION IS REQUIRED AFTER INSTALLATION OF THE BMPS AND PRIOR TO BEGINNING CONSTRUCTION.

BMPS SHALL BE INSPECTED AND MAINTAINED UNTIL ALL DISTURBED AREAS ARE STABILIZED. UNLESS OTHERWISE SPECIFIED, NATIVE GRASS SEEDING AND MULCH PER COA STD 1012 IS REQUIRED FOR FINAL STABILIZATION PRIOR TO REMOVAL OF BMPS AND DISCONTINUATION OF INSPECTIONS.

NPDES ID: NMR1002JR AND NMR10030E

ADDRESS: 8820 HORIZON BLVD., ALBUQUERQUE, NM

GPS COORDINATE: 35.189731, -106.601514

DISTURBED ACREAGE: INFRASTRUCTURE - 7.75 ACRES, VERTICAL - 5.14 ACRES

RECEIVING WATERS: INTERMITTENT STREAMBED/RIVERINE, 0.00 MILES FROM THE PROJECT. NORTH DIVERSION CHANNEL, 0.02 MILES FROM THE PROJECT.

IMPAIRED/TIERED WATERS: N/A

ENDANGERED SPECIES: YELLOW-BILLED CUCKOO, 1.19 MILES FROM THE PROJECT.
RIO GRANDE SILVERY MINNOW, 1.66 MILES FROM THE PROJECT.

HISTORIC PRESERVATION: HISTORIC PROPERTIES ARE NOT PRESENT.

FINAL STABILIZATION TYPE: ASPHALT PAVING, SIDEWALKS, CURBS, GUTTERS AND VERTICAL STRUCTURES.

REGULATING AUTHORITY: ENVIRONMENTAL PROTECTION AGENCY (EPA)

REGULATING PERMIT: 2017 CONSTRUCTION GENERAL PERMIT

PROJECT OWNER:
GAMMA DEVELOPMENT, LLC
9798 COORS BLVD NW
ALBUQUERQUE, NM 87114

HOMEBUILDER:
 TQM, LLC
 9798 COORS BLVD NW BLDG C, STE 400
 ALBUQUERQUE, NM 87114

OWNER CONTACT:
BRIAN MCCARTHY
(505) 991-0252
BRIAN@ABRAZOHOMES.COM

**HOMEBUILDER CONTACT:
BRIAN MCCARTHY
(505) 991-0252
BRIAN@ABRAZOHOMES.COM**

GENERAL CONTRACTOR (GC):
GAMMA DEVELOPMENT, LLC
9798 COORS BLVD NW
ALBUQUERQUE, NM 87114

GC CONTACT:
CHRIS SCOTT
(505) 796-6119
CK@ABRAZOHOMES.COM



- SWPPP
- Stormwater
- Erosion Control
- Reclamation
- Seeding

www.e2rc.com | 505.867.4040


[illegible]

**GAMMA DEVELOPMENT, LLC
ASCENSION SUBDIVISION
SWPPP NOTES**

DESIGNED BY:
KELLEY FETTER

DRAWN BY:
CHLOE FETTER PINNEY


SHEET:
GENERAL
NOTES




NTS

SETTLE WATTLE IN A 2-3" TRENCH, COMPACT EXCAVATED
SOIL ON UPSLOPE SIDE

2-3" OF STAKE REMAINS EXPOSED



NTS

 DRIVE STAKES PERPENDICULAR TO THE SLOPE FACE AND THROUGH THE MIDDLE OF THE WATTLE LEAVING AT LEAST 2-3" OF THE STAKE ABOVE THE WATTLE.

2"x2" by 14 Ga. wire or equivalent, if standard strength fabric used

Filter fabric

FLOW →

2' min

12" min

Backfill trench with native soil or 3/4" - 1.5" washed gravel

Minimum 4"x4" trench

2"x2" wood posts, steel fence posts, or equivalent

NTS

Professional Engineer Seal for Kelley Vincent, New York, No. 13450, dated 5/28/20.

[illegible]

ACENSION SUBDIVISION BMP DETAILS


DESIGNED BY:
KELLEY FETTER

DRAWN BY:
CHLOE FETTER PINNEY

SHEET:

3

www.e2rc.com | 505.867.4040




SPOILS PILE PROTECTION

PLACE WATTLES IN FUTURE LOCATIONS OF SPOILS STOCKPILES PRIOR TO CONSTRUCTION.

PLACE WATTLES CONTINUOUSLY ALONG THE EXTENT OF THE SPOILS STOCKPILE.

ANCHOR THE WATTLES USING A MINIMUM OF 1" X 2" X 18" WOODEN STAKES OR SAND BAGS.

ONCE/IF THE SPOILS STOCKPILE IS DEPLETED OR MOVED, REMOVE THE WATTLES AND REUSE THEM IN THE NEXT LOCATION.




OPEN TRENCH SPOILS PILE PROTECTION

PLACE WATTLES CONTINUOUSLY ALONG THE EXTENT OF THE UTILITY TRENCH AND FUTURE LOCATION OF THE SPOILS STOCKPILE PRIOR TO EXCAVATION OF THE UTILITY.

WATTLES ARE TO REMAIN ANCHORED IN PLACE UNTIL THE UTILITY TRENCH IS BACKFILLED.

ANCHOR THE WATTLES USING A MINIMUM 1"X2"X18" WOODEN STAKE OR SANDBAGS.

ONCE THE TRANCH IS BACKFILLED, WATTLES MAY BE REMOVED AND REUSED IN THE NEXT SECTION OF EXCAVATION PROVIDED THEY ARE IN GOOD CONDITION.




ROCK CHECK DAM

PLACE CHECK DAMS AT REGULARLY SPACED INTERVALS ALONG SWALE OR DRAINAGE DITCH.

HEIGHTS SHOULD ALLOW FOR POOLS TO DEVELOP UPSTREAM OF EACH CHECK DAM.

IF MULTIPLE DAMS ARE USED, THE TOP OF THE LOWER DAM SHOULD BE THE SAME HEIGHT AS THE ELEVATION AS THE TOE OF THE UPPER DAM.




RUNDOWN DETAIL

8' MAX SPACING BETWEEN STAKES

PLACE WATTLES AT THE TOE OF SLOPE. THE RIP RAP OR CONCRETE RUNDOWN SHOULD ABUT THE WATTLE.

ANCHOR THE WATTLES WITH WOODEN STAKES. DRIVE THE STAKE A MINIMUM OF 12" INTO THE MIDDLE OF THE WATTLE AND SOIL UNDERNEATH.

2-3" OF THE WOODEN STAKE SHOULD BE PRESENT ABOVE THE WATTLE.



EARTHEN BERM

CONSTRUCT AN EARTHEN BERM DOWN HILL OF THE AREA TO BE CONTROLLED.

BERM SHOULD BE A MINIMUM 12" HIGH AND 12" WIDE.

USE EQUIPMENT TO COMPACT EARTHEN BERM BY ROLLING OVER BERM TO MINIMIZE SPREAD.



DATE	REVISION ITEM	#

ASCENSION SUBDIVISION BMP DETAILS

DESIGNED BY:
KELLEY FETTER
DRAWN BY:
CHLOE FETTER PINNEY



SHEET:

4



SWPPP
Stormwater
Erosion Control
Reclamation
Seeding

www.e2rc.com | 505.867.4040




THE MAT SHOULD EXTEND A MINIMUM OF 1" PAST ALL EDGES OF THE INLET. PLACE MAT AGAINST THE CURB INLET.

PLACE WATTLES ON TOP OF THE MAT CLOSEST TO THE INLET OPENING AND CURB.

THE MAXIMUM HEIGHT OF THE PROTECTIVE BARRIER MUST BE LOWER THAN THE TOP OF THE CURB OPENING. THIS ALLOWS OVERFLOW INTO THE INLET DURING LARGE PRECIPITATION EVENTS.

ANCHOR THE BARRIER NETTING OVER THE CURB WITH WOODEN STAKES IF ABLE. IF UNABLE TO DO THAT ANCHOR THE WATTLE WITH SAND BAGS ON EACH END.



CUTBACK CURB

NTS

CUTBACK CURBS SHOULD TYPICALLY BE INSTALLED AT THE SITE ENTRANCE WHEN ACCESS IS NEEDED.

SOIL SHOULD BE CUT BACK FROM BEHIND THE CURB, SIDEWALK OR ROADWAY 3-4" DOWN FROM THE TOP OF THE HARDSCAPE.

BRING THE SOIL BACK 3-4 FT FROM THE HARDSCAPE TO FORM THE SEDIMENT TRAP.

THE DEPTH AND LENGTH OF THE EXCAVATED AREA CAN BE INCREASED IF MORE STORAGE IS NEEDED.

INSPECT BMPs PRIOR TO FORCAST PRCIPITATION, DAILY DURING PRECIPITATION EVENTS, AFTER PRECIPITATION EVENTS AND THROUGH THE LIFE OF THE PROJECT.

MAINTAIN PROPER DEPTH AND LENGTH OF THE CUTBACK FOR THE DURATION OF THE PROJECT.

KEEP CUTBACK AREA CLEAN AND FREE OF TRASH AND DEBRIS.

CUTBACK CURB BMP ONLY REMAINS EFFECTIVE FOR A LIMITED TIME. SHOULD NOT BE USED FOR MORE THAN 4 MONTHS AND SHOULD BE USED IN CONJUNCTION WITH OTHER BMPs.



www.e2rc.com | 505.867.4040

SWPPP
Stormwater
Erosion Control
Reclamation
Seeding




				DATE
				REVISION ITEM
				#

ASCENSION SUBDIVISION
BMP DETAILS

DESIGNED BY:
KELLEY FETTER
DRAWN BY:
CHLOE FETTER PINNEY

SHEET:

5




LOCATE WASHOUT AT LEAST 50 FT FROM STORMDRAINS, OPEN DITCHES, WATER BODIES OR PROJECT PERIMETER. A SIGN SHOULD BE INSTALLED ADJACENTLY TO THE WASHOUT.

WASH OUT WASTE INTO THE WASHOUT WHERE THE CONCRETE CAN SET, BE BROKEN UP AND DISPOSED OF CORRECTLY.

DO NOT CREATE RUNOFF BY DRAINING WATER TO BERMED AREA OR BY COLLECTING THE WATER WASTE WHEN WASHING CONCRETE TO REMOVE PARTICLES AND EXPOSE THE AGGREGATE.


DO NOT WASH SWEEPINGS FROM EXPOSED AGGREGATE CONCRETE INTO THE STREET, STORMDRAIN SYSTEMS OR OFF THE PROJECT SITE.



PORTABLE TOILET STAKING


PLACE THE PORTABLE TOILET ON LEVEL GROUND. A FLAT
PAVED SURFACE IS BEST IF AVAILABLE.

DRIVE THE STAKES OVER THE SKIDS OF THE PORTABLE
TOILET, AROUND ALL SIDES.



NPDES POSTING BOARD

NPDES Permit must be positioned at the most active part of the project where it can be viewed by the public (e.g. project entrance).



STABILIZED CONSTRUCTION ENTRANCE

CONSTRUCT THE ENTRANCE ON A LEVEL SURFACE WHERE AN UNPAVED ROAD MEETS A PAVED ROAD. TYPICALLY AT PROJECTS ACCESS AREA.

GRADE THE ENTRANCE TOWARD THE CONSTRUCTION SITE
TO PREVENT RUNOFF.

INSPECT THE ENTRANCE TO KEEP TRASH AND DEBRIS OUT OF THE WAY.

AFTER PRECIPITATION EVENTS, INSPECT THE ENTRANCE FOR ANY REPAIRS THAT MAY BE NEEDED.




ASCENSION SUBDIVISION BMP DETAILS

DESIGNED BY:
KELLEY FETTER

DRAWN BY:
CHLOE FETTER PINNEY

SHEET:

6




DRAWING KEY



SWPPP
Stormwater
Erosion Control
Reclamation
Seeding


www.e2rc.com | 505.867.4040

IMPLEMENTATION	
BMP INSTALL	BMP REMOVE
1/31/20	
FINAL STABILIZATION	




INLET PROTECTION

IMPLEMENTATION	
BMP INSTALL	BMP REMOVE
11/26/19	
FINAL STABILIZATION	




STABILIZED CONSTRUCTION ENTRANCE



NPDES PERMITTING


IMPLEMENTATION	
BMP INSTALL	BMP REMOVE
11/26/19	
FINAL STABILIZATION	

IMPLEMENTATION	
BMP INSTALL	BMP REMOVE
11/26/19	
FINAL STABILIZATION	



SILT FENCE

IMPLEMENTATION	
BMP INSTALL	BMP REMOVE
FINAL STABILIZATION	



CUTBACK CURB



SWPPP
Stormwater
Erosion Control
Reclamation
Seeding

www.e2rc.com | 505.867.4040



DATE	REVISION ITEM	#

ASCENSION SUBDIVISION TESCP

DESIGNED BY:
KELLEY FETTER
DRAWN BY:
CHLOE FETTER PINNEY

SHEET:

7

