


CORRALES MAIN CANAL RELOCATION

LOT 1, STOUT SUBDIVISION
CITY OF ALBUQUERQUE,
BERNALILLO COUNTY, NM

INDEX TO DRAWINGS

SHEET NO.	DESCRIPTION
1	COVER SHEET AND INDEX TO DRAWINGS
2	GENERAL NOTES
3	CHANNEL PLAN AND PROFILES
4	DETAILS
5	DETAILS AND SPECIFICATIONS
6	SPECIFICATIONS
7	SPECIFICATIONS





VICINITY MAP ZONE ATLAS
C/D-13

MRGCD GENERAL CONSTRUCTION NOTES


1. ANY WORK TO BE PERFORMED WITHIN THE MIDDLE RIO GRANDE CONSERVANCY DISTRICT (M.R.G.C.D.) RIGHT-OF-WAY SHALL BE CLOSELY COORDINATED WITH THE M.R.G.C.D. ENGINEERING DEPARTMENT AND APPROPRIATE FIELD OFFICE. PHONE: (505) 247-0234.
2. NO WORK IS TO BE DONE ON FACILITIES OR STRUCTURES BELONGING TO, OR OPERATED BY, THE M.R.G.C.D. BETWEEN MARCH 1 AND OCTOBER 31 INCLUSIVE. HOWEVER, WORK MAY BE PERMITTED BY THE M.R.G.C.D. IF IT CAN BE SHOWN THAT THE WORK WILL NOT INTERFERE WITH OPERATIONS OF THE M.R.G.C.D. FACILITY. ALL WORK TO BE DONE WITHIN THE M.R.G.C.D. FACILITIES MUST BE APPROVED BY THE M.R.G.C.D. ENGINEER PRIOR TO COMMENCING WORK.
3. THE CONTRACTOR SHALL NOT STORE EQUIPMENT, NEW MATERIALS OR DEBRIS WITHIN DISTRICT RIGHT-OF-WAY WHICH MAY INTERFERE WITH OPERATIONS AND MAINTENANCE OF THE M.R.G.C.D. FACILITY.
4. THE CONTRACTOR SHALL NOT SERVICE VEHICLES OR EQUIPMENT WITHIN M.R.G.C.D. RIGHT-OF-WAY.
5. SEEDING OF DISTURBED AREA WITHIN M.R.G.C.D. RIGHT-OF-WAYS IS REQUIRED PER THE M.R.G.C.D. SEEDING SPECIFICATIONS.
6. THE CONTRACTOR MUST MAINTAIN A MINIMUM COVER OF 3' OVER ALL CULVERT CROSSINGS USED FOR ACCESS TO THE PROJECT SITE.
7. THE CONTRACTOR IS RESPONSIBLE FOR REPAIRING AND/OR REPLACEMENT OF ANY STRUCTURES REMOVED AND/OR DAMAGED DUE TO THE CONTRACTORS ACTIVITIES WITHIN THE DISTRICTS RIGHT-OF-WAY. SHOULD ANY TURNOUTS, CULVERT PIPES AND/OR STRUCTURES REQUIRE REPLACEMENT DUE TO LEAKAGE AND/OR DAMAGE BY THE CONTRACTOR, NEW TURNOUTS, AND NEW CULVERT PIPES AND OR NEW STRUCTURES SHALL REPLACE THE DAMAGED ITEM. REPAIRS AND/OR REPLACEMENTS WITHIN THE DISTRICTS RIGHT-OF-WAY MUST COMPLY WITH THE DISTRICTS SPECIFICATIONS.
8. ALL DAMAGED CULVERT CROSSINGS AND CULVERT CROSSINGS REMOVED AND/OR DISTURBED MUST BE RESTORED AND/OR REPLACED TO THE SATISFACTION OF THE M.R.G.C.D. AND COMPLY WITH M.R.G.C.D. SPECIFICATIONS.
9. ALL SALVAGEABLE CULVERTS, IRRIGATION GATES, ETC. MUST BE RETURNED TO THE M.R.G.C.D.
10. THE CONTRACTOR IS RESPONSIBLE FOR EXECUTING A "SPECIAL USE LICENSE AGREEMENT" WITH THE M.R.G.C.D. PRIOR TO CONSTRUCTION.

REV.	SHEETS	CITY ENGINEER	DATE	USER DEPT.	DATE	USER DEPT.	DATE



APPROVED FOR CONSTRUCTION (MUNICIPAL) DATE 4/16/03


APPROVED FOR CONSTRUCTION (MUNICIPAL) DATE 4-16-03

BUILDING
ENGINEERING
AND
MUNICIPAL
DESIGNS


855 POLARIS BLVD., SE
RIO RANCHO, NM 87124
PHONE (505) 896-0391
FAX (505) 994-3952
beamdesigns@qwest.net

PROJECT NO.



SHEET OF 1 7

GENERAL CONSTRUCTION NOTES

GENERAL

CONTRACTOR IS RESPONSIBLE FOR OBTAINING ALL REQUIRED CONSTRUCTION PERMITS, INCLUDING A TOP SOIL DISTURBANCE PERMIT, PRIOR TO START OF CONSTRUCTION.

ALL WORK ON THIS PROJECT SHALL BE PERFORMED IN ACCORDANCE WITH APPLICABLE FEDERAL, STATE, AND LOCAL LAWS, ORDINANCES, AND REGULATIONS CONCERNING CONSTRUCTION SAFETY AND HEALTH.

REFERENCES MADE TO STANDARD SPECIFICATIONS REFER TO NEW MEXICO STATE HIGHWAY DEPARTMENT STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION, 1994 EDITION.

THE CONTRACTOR SHALL NOT INSTALL ITEMS AS SHOWN ON THESE PLANS WHEN IT IS OBVIOUS THAT FIELD CONDITIONS ARE DIFFERENT THAN SHOWN IN THE PLANS. SUCH CONDITIONS SHALL BE BROUGHT TO THE ATTENTION OF THE ENGINEER IN A TIMELY MANNER. IN THE EVENT THE CONTRACTOR DOES NOT NOTIFY THE ENGINEER IN A TIMELY MANNER, THE CONTRACTOR ASSUMES FULL RESPONSIBILITY AND EXPENSE FOR ANY REVISIONS NECESSARY, INCLUDING ENGINEERING DESIGN FEES.

EXISTING SITE IMPROVEMENTS WHICH ARE DAMAGED OR DISPLACED BY THE CONTRACTOR SHALL BE REMOVED AND REPLACED BY THE CONTRACTOR AT THE CONTRACTOR'S EXPENSE. REPAIRS SHALL BE APPROVED BY THE OWNER PRIOR TO CONSTRUCTION OF THE REPAIRS. REPAIRS SHALL BE ACCEPTED BY THE OWNER PRIOR TO FINAL PAYMENT.

EXISTING FENCING THAT IS NOT DESIGNATED FOR REMOVAL SHALL NOT BE DISTURBED. ANY FENCING THAT IS DISTURBED OR ALTERED BY THE CONTRACTOR SHALL BE RESTORED TO ITS ORIGINAL CONDITION AT THE CONTRACTOR'S EXPENSE. IF THE CONTRACTOR DESIRES TO REMOVE FENCING TO ACCOMMODATE CONSTRUCTION ACTIVITIES, THE CONTRACTOR SHALL OBTAIN THE OWNER'S WRITTEN PERMISSION BEFORE THE FENCE IS REMOVED. CONTRACTOR SHALL RESTORE THE FENCE TO ITS ORIGINAL CONDITION AT THE EARLIEST OPPORTUNITY. WHILE ANY FENCING IS REMOVED, THE CONTRACTOR SHALL BE SOLELY RESPONSIBLE FOR SECURITY OF THE SITE UNTIL THE FENCE IS RESTORED.

WORK WITHIN ADJACENT RIGHT-OF-WAY

PRIOR TO BEGINNING ANY CONSTRUCTION ACTIVITIES WITHIN ADJACENT RIGHT-OF-WAYS OR WITHIN PROPERTY NOT OWNED BY THE OWNER OF THE PROJECT SITE, THE CONTRACTOR SHALL ASSURE THAT ALL PERMITS AND PERMISSIONS REQUIRED HAVE BEEN OBTAINED IN WRITING.

SURVEY MONUMENTS, PROPERTY CORNERS, BENCHMARKS

THE CONTRACTOR SHALL NOTIFY THE OWNER AT LEAST SEVEN DAYS BEFORE BEGINNING ANY CONSTRUCTION ACTIVITY THAT COULD DAMAGE OR DISPLACE SURVEY MONUMENTS, PROPERTY CORNERS, OR PROJECT BENCHMARKS SO THESE ITEMS MAY BE RELOCATED.

ANY SURVEY MONUMENTS, PROPERTY CORNERS, OR BENCHMARKS THAT ARE NOT IDENTIFIED FOR RELOCATION ARE THE RESPONSIBILITY OF THE CONTRACTOR TO PRESERVE AND PROTECT. RELOCATION OR REPLACEMENT OF THESE ITEMS SHALL BE DONE BY THE OWNER'S SURVEYOR AT THE EXPENSE OF THE CONTRACTOR.

DIMENSIONS

ALL DIMENSIONS TO CURBS ARE TO THE FLOWLINE UNLESS OTHERWISE NOTED.

ALL STATIONING IS TO THE CENTERLINE OF THE RIGHT-OF-WAY UNLESS OTHERWISE NOTED.

ALL SLOPES AND GRADES ARE IN PERCENT UNLESS OTHERWISE NOTED.

CURB ELEVATIONS ARE SHOWN AT THE FLOW LINE UNLESS OTHERWISE NOTED. SEE THE DETAIL SHEET TO DETERMINE THE CURB HEIGHT ABOVE FLOW LINE.

SOILS

UNLESS OTHERWISE SPECIFIED, SUBGRADE, ENGINEERED FILL, AND STRUCTURAL FILL SHALL BE COMPACTED TO THE FOLLOWING SPECIFICATIONS OF THE ASTM D-1557 MAXIMUM DRY DENSITY.

MATERIAL LOCATION	PERCENT COMPACTION
STRUCTURAL FILL IN THE BUILDING AREA	95%
SUBBASE FOR SLAB SUPPORT	95%
MISCELLANEOUS BACKFILL BELOW STRUCTURAL FILL OR ROADWAY PAVEMENT	95%
MISCELLANEOUS BACKFILL BELOW UNPAVED, NON-BUILDING AREAS	90%
ROADWAY PAVEMENT SUBGRADE	95%
SIDEWALK SUBGRADE	90%
CURB AND GUTTER SUBGRADE	95%

PAVEMENT

WHEN ABUTTING NEW PAVEMENT TO EXISTING PAVEMENT, CUT EXISTING PAVEMENT EDGE TO A NEAT, STRAIGHT LINE AS NECESSARY TO REMOVE ANY BROKEN OR CRACKED PAVEMENT AND MATCH NEW PAVEMENT ELEVATION TO EXISTING.

ALL UTILITIES AND UTILITY SERVICE LINES SHALL BE INSTALLED AND APPROVED PRIOR TO PAVING.

ALL WATER VALVE BOXES AND ELECTRICAL, TELEPHONE, TELEVISION, AND SEWER MANHOLES IN THE CONSTRUCTION AREA SHALL BE ADJUSTED TO FINISHED GRADE BEFORE PAVING.

WHEN SIDEWALK OR CURB AND GUTTER IS REMOVED, IT SHALL BE REMOVED TO EXISTING CONSTRUCTION JOINTS. CUTTING OR BREAKING SHALL NOT BE ALLOWED.

UTILITIES

IF ANY UTILITY LINES, PIPELINES, OR UNDERGROUND UTILITY LINES ARE SHOWN ON THESE DRAWINGS, THEY ARE SHOWN IN AN APPROXIMATE LOCATION ONLY BASED ON THE INFORMATION PROVIDED TO THE ENGINEER BY OTHERS. THIS INFORMATION MAY BE INACCURATE OR INCOMPLETE. ADDITIONALLY, UNDERGROUND LINES MAY EXIST THAT ARE NOT SHOWN. THE CONTRACTOR SHALL VERIFY THE LOCATION OF ANY UTILITY LINE, PIPELINE, OR UNDERGROUND UTILITY LINE IN OR NEAR THE AREA OF THE WORK IN ACCORDANCE WITH CHAPTER 62, ARTICLE 14-1, THROUGH 14-8, NMSA 1978.

THE CONTRACTOR SHALL CONTACT THE STATEWIDE UTILITY LOCATOR SERVICE AT 1-800-321-2537 AT LEAST TWO WORKING DAYS BEFORE BEGINNING CONSTRUCTION. AFTER THE UTILITIES ARE SPOTTED, THE CONTRACTOR SHALL EXPOSE ALL PERTINENT UTILITIES TO VERIFY THEIR VERTICAL AND HORIZONTAL LOCATION. IF A CONFLICT EXISTS BETWEEN EXISTING UTILITIES AND PROPOSED CONSTRUCTION, THE CONTRACTOR SHALL NOTIFY THE ENGINEER SO THAT THE CONFLICT CAN BE RESOLVED WITH MINIMAL DELAY.

THE CONTRACTOR SHALL EXERCISE DUE CARE TO AVOID DISTURBING ANY EXISTING UTILITIES, ABOVE OR BELOW GROUND. UTILITIES THAT ARE DAMAGED BY CARELESS CONSTRUCTION SHALL BE REPAIRED OR REPLACED AT THE CONTRACTOR'S EXPENSE.

EXISTING VALVES SHALL ONLY BE OPERATED BY THE UTILITY COMPANY. CONTRACTOR SHALL NOTIFY THE UTILITY A MINIMUM OF TWO WORKING DAYS BEFORE ANY VALVE, NEW OR EXISTING, NEEDS TO BE OPERATED.

THE CONTRACTOR SHALL COORDINATE ANY REQUIRED UTILITY INTERRUPTIONS WITH THE OWNER AND AFFECTED UTILITY COMPANY A MINIMUM OF THREE WORKING DAYS BEFORE THE INTERRUPTION.

THE CONTRACTOR SHALL MAINTAIN A RECORD DRAWING SET OF PLANS AND PROMPTLY LOCATE ALL UTILITIES, EXISTING OR NEW, IN THEIR CORRECT LOCATION, HORIZONTAL AND VERTICAL. THIS RECORD SET OF DRAWINGS SHALL BE MAINTAINED ON THE PROJECT SITE AND SHALL BE AVAILABLE TO THE OWNER AND ENGINEER AT ANY TIME DURING CONSTRUCTION.

EROSION CONTROL, ENVIRONMENTAL PROTECTION, AND STORM WATER POLLUTION PREVENTION PLAN

THE CONTRACTOR SHALL CONFORM TO ALL CITY, COUNTY, STATE, AND FEDERAL DUST AND EROSION CONTROL REGULATIONS. THE CONTRACTOR SHALL OBTAIN AND PREPARE ANY DUST CONTROL OR EROSION CONTROL PERMITS REQUIRED FROM THE REGULATORY AGENCIES.

THE CONTRACTOR SHALL PROMPTLY REMOVE ANY MATERIAL EXCAVATED WITH THE PUBLIC RIGHT-OF-WAY OR ADJACENT PROPERTY TO KEEP IT FROM WASHING OFF THE PROJECT SITE.

THE CONTRACTOR SHALL ENSURE THAT NO SOIL ERODES FROM THE SITE ONTO ADJACENT PROPERTY BY CONSTRUCTION OF TEMPORARY EROSION CONTROL BERMS OR INSTALLING SILT FENCES AT THE PROPERTY LINES AND WETTING THE SOIL TO PREVENT IT FROM BLOWING.

WATERING, AS REQUIRED FOR CONSTRUCTION DUST CONTROL, SHALL BE CONSIDERED INCIDENTAL TO CONSTRUCTION AND NO MEASUREMENT OR PAYMENT SHALL BE MADE. CONSTRUCTION AREAS SHALL BE WATERED FOR DUST CONTROL IN COMPLIANCE WITH GOVERNMENT ORDINANCES. THE CONTRACTOR SHALL BE RESPONSIBLE FOR LOCATING AND SUPPLYING WATER AS REQUIRED.

ANY AREAS DISTURBED BY CONSTRUCTION AND NOT COVERED BY LANDSCAPING OR IMPERVIOUS SURFACES SHALL BE REVEGETATED WITH RECLAMATION SEEDING.

THE CONTRACTOR SHALL PROPERLY HANDLE AND DISPOSE OF ALL ASPHALT REMOVED ON THE PROJECT BY HAULING IT TO AN APPROVED DISPOSAL SITE IN ACCORDANCE WITH THE REQUIREMENTS OF THE NEW MEXICO SOLID WASTE ACT.

ALL WASTE PRODUCTS FROM THE CONSTRUCTION SITE, INCLUDING ITEMS DESIGNED FOR REMOVAL, CONSTRUCTION WASTE, CONSTRUCTION EQUIPMENT WASTE PRODUCTS (OIL, GAS, TIRES, ETC.), GARBAGE, GRUBBING, EXCESS CUT MATERIAL, VEGETATIVE DEBRIS, ETC., SHALL BE APPROPRIATELY DISPOSED OF OFFSET AT NO ADDITIONAL COST TO THE OWNER. IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO OBTAIN ANY PERMITS REQUIRED FOR HAUL OR DISPOSAL OF WASTE PRODUCTS, IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO ENSURE THAT THE WASTE DISPOSAL SITE COMPLIES WITH GOVERNMENT REGULATIONS REGARDING THE ENVIRONMENT, ENDANGERED SPECIES, AND ARCHAEOLOGICAL RESOURCES.

THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE CLEANUP AND REPORTING OF SPILLS OF HAZARDOUS MATERIALS ASSOCIATED WITH THE CONSTRUCTION SITE. HAZARDOUS MATERIALS INCLUDE GASOLINE, DIESEL FUEL, MOTOR OIL, SOLVENTS, CHEMICALS, PAINT, ETC. WHICH MAY BE A THREAT TO THE ENVIRONMENT. THE CONTRACTOR SHALL REPORT THE DISCOVERY OF PAST OR PRESENT SPILLS TO THE NEW MEXICO EMERGENCY RESPONSE AT 1-800-219-6157.

THE CONTRACTOR SHALL COMPLY WITH ALL APPLICABLE REGULATIONS CONCERNING SURFACE AND UNDERGROUND WATER, CONTACT WITH SURFACE WATER BY CONSTRUCTION EQUIPMENT AND PERSONNEL SHALL BE MINIMIZED. EQUIPMENT MAINTENANCE AND REFUELING OPERATIONS SHALL BE PERFORMED IN AN ENVIRONMENTALLY SAFE MANNER IN COMPLIANCE WITH GOVERNMENT REGULATIONS.

THE CONTRACTOR SHALL COMPLY WITH ALL APPLICABLE REGULATIONS CONCERNING CONSTRUCTION NOISE AND HOURS OF OPERATION.

ACCESSIBLE FACILITIES

ALL SURFACES ALONG ACCESSIBLE ROUTES AND FOR HANDICAP RAMPS SHALL BE STABLE FIRM, SLIDE RESISTANT AND SHALL COMPLY WITH UNIFORM FEDERAL ACCESSIBILITY STANDARDS, PARAGRAPH 4.5.

LONGITUDINAL SLOPES ALONG ACCESSIBLE ROUTE SIDEWALKS, EXCEPT AT HANDICAP RAMPS, SHALL NOT BE STEEPER THAN 1:20. CROSS SLOPES ALONG ACCESSIBLE ROUTE SIDEWALKS EXCEPT AT HANDICAP RAMPS, SHALL NOT BE STEEPER THAN 1:48. SLOPES IN ACCESSIBLE PARKING SPACES, ACCESS AISLES, AND PASSENGER LOADING ZONES SHALL NOT BE STEEPER THAN 1:48 IN ALL DIRECTIONS.

THE SITE SHALL COMPLY WITH ANSI A117.1-1992, "ACCESSIBLE AND USABLE BUILDINGS AND FACILITIES".

TRAFFIC CONTROL

THE CONTRACTOR SHALL PROVIDE ALL REQUIRED TRAFFIC CONTROL PLANS. ALL SIGNS, BARRICADES, CHANNELIZATION DEVICES, SIGN FRAMES AND ERECTION OF SUCH DEVICES SHALL CONFORM TO THE REQUIREMENTS OF "MANUAL OF UNIFORM TRAFFIC CONTROL DEVICES FOR STREETS AND HIGHWAYS" LATEST EDITION. PRIOR TO CONSTRUCTION, TRAFFIC CONTROL PLANS SHALL BE APPROVED BY THE GOVERNING AUTHORITY.

ABBREVIATIONS

BM	=	BENCHMARK
CATV	=	CABLE TELEVISION LINE
CMP	=	CORRUGATED METAL PIPE
COA	=	CITY OF ALBUQUERQUE
CONC	=	CONCRETE
CL	=	CENTERLINE
DIA	=	DIAMETER
DTL	=	DETAIL
DWG	=	DRAWING
ELEV	=	ELEVATION
EX	=	EXISTING
FG	=	FINISHED GRADE
FH	=	FIRE HYDRANT
FL	=	FLOW LINE
G	=	GAS PIPE
GV	=	GATE VALVE
INV	=	INVERT ELEVATION
LF	=	LINEAL FEET
MH	=	MANHOLE
NG	=	NATURAL GROUND
OE	=	OVERHEAD ELECTRIC LINE
OT	=	OVERHEAD TELEPHONE LINE
PCC	=	PORTLAND CEMENT CONCRETE
PP	=	POWER POLE
PROP	=	PROPOSED
PVC	=	POLYVINYL CHLORIDE PIPE
RCP	=	REINFORCED CONCRETE PIPE
RD	=	ROOF DRAIN
R/W	=	RIGHT-OF-WAY
S	=	SLOPE
SAS	=	SANITARY SEWER
SD	=	STORM DRAIN
STA	=	STATION
STD	=	STANDARD
SW	=	SIDEWALK
TA	=	TOP OF ASPHALT PAVEMENT
TC	=	TOP OF CONCRETE SLAB (PAVEMENT)
TCC	=	TOP OF CONCRETE CURB
TG	=	TOP OF GRATE
TS	=	TOP OF SIDEWALK
TSC	=	TOP OF SHOT CRETE
TOW	=	TOP OF WALL
TYP	=	TYPICAL
UE	=	UNDERGROUND ELECTRIC
UT	=	UNDERGROUND TELEPHONE
W	=	WATER
WM	=	WATER METER
WV	=	WATER VALVE

LEGEND

(S 83°39'25" W)	RECORD BEARING AND DISTANCES	→	DOWN GUY
N 00°07'27" W	MEASURED BEARING AND DISTANCES	○ LP	LIGHT POLE
⊙	FOUND AND USED MONUMENT	□ □	YARD LIGHT
- -// - -	EX WOOD FENCE	UG	UNDERGROUND
zzzzzz	EX RAILROAD RETAINING WALL	-W-S-G-E-	UTILITY (WATER, SEWER, ELEC., GAS, ETC.)
x G 89.5	EX SPOT ELEV.	- - - - -	FIBER OPTIC COMMUNICATION 4" CONDUIT
◆ FL 09.3	PROP SPOT ELEV.	□	UTILITY RISER
- -5160 - -	EX CONTOUR LINE	○ FP	FLAG POLE
⊕	POWER POLE	○ V	VENT

⊕ GM	GAS METER
⊕	EX FIRE HYDRANT
⊕	PROP FIRE HYDRANT
⊕	EX WATER VALVE
⊕	PROP WATER VALVE
○	EX SD MANHOLE
○	PROP SD MANHOLE
⊕	EX SAS MANHOLE
●	PROP SAS MANHOLE

□	EX SD INLET
■	PROP SD INLET
CONC	CONCRETE
⊕	EX SIGN
⊕	EX WATER METER
⊕	PROP WATER METER
⊕	PLANTER
⊕	PROPOSED TREE
●	EXIST. TREE

BUILDING
ENGINEERING
AND
MUNICIPAL
DESIGNS

BEAM
DESIGNS

855 POLARIS BLVD., SE
RIO RANCHO, NM 87124
PHONE (505) 896-0391
FAX (505) 994-3952
beamdesigns@quest.net

ALBUQUERQUE METROPOLITAN FLOOD CONTROL AUTHORITY (AMAFCA)

AND
MIDDLE RIO GRANDE CONSERVANCY DISTRICT (MRGCD)

TITLE: LOT 1, STOUT SUBDIVISION
CORRALES MAIN CANAL RELOCATION
GENERAL NOTES


APPROVED FOR CONSTRUCTION (MRGCD) DATE 4/29/03

APPROVED FOR CONSTRUCTION (AMAFCA) DATE 4-16-03

PROJECT NO. MAP NO. CD-13

NO.	DATE	REVISIONS	DESIGN
DESIGNED BY	DATE	DATE	DATE
DRAWN BY	DATE	DATE	DATE
CHECKED BY	DATE	DATE	DATE

SHEET OF 2 7



EXISTING CANAL CENTERLINE CURVE DATA

CURVE NUMBER	ARC LENGTH (FT)	DELTA	RADIUS (FT)	CH. LENGTH (FT)	CH. BRNG	TANGENT (FT)
CE1	142.87	23°23'17"	350.00	141.88	S 49°14'05" W	72.44
CE2	91.00	36°23'59"	143.24	89.48	S 42°43'44" W	47.09
CE3	119.03	71°25'01"	95.49	111.47	S 11°10'47" E	68.64
CE4	139.12	83°28'23"	95.49	127.14	S 05°09'06" E	85.19



PROPOSED CANAL CENTERLINE CURVE DATA

CURVE NUMBER	ARC LENGTH (FT)	DELTA	RADIUS (FT)	CH. LENGTH (FT)	CH. BRNG	TANGENT (FT)
CN1	SAME AS CE1					
CN2	78.33	60°54'06"	73.69	74.69	S 30°28'40" W	43.32
CN3	363.69	36°33'29"	570.00	357.56	S 18°18'21" W	188.28

NEW PL. LINE TABLE
NO. DELTA BEARING
L1 N 89°57'21" W 41.17'
L2 S 11°10'47" E 48.87'
L3 N 89°57'21" E 13.88'
L4 N 89°57'21" E 58.87'

NEW PL. CURVE TABLE
NO. DELTA BEARING
C1 N 11°25'11" E 146.00'
C2 S 18°18'21" W 188.28'

GRAPHIC SCALE (1 INCH = 100 FEET)



VICINITY MAP C/D-13


PROPOSED RELOCATION OF THE M.R.G.C.D. CORRALES MAIN CANAL WITHIN LOT 1 (ONE) OF THE CORRECTED SUBDIVISION PLAT FOR STOUT SUBDIVISION, SECTIONS 18 & 19, T.11N., R.3E., N.M.P.M. BERNALILLO COUNTY, NEW MEXICO

CONTOUR/DESIGN NOTE
EXISTING CONTOURS ARE APPROXIMATELY 3' HIGHER IN ELEVATION THAN ELEVATIONS SHOWN ON EXISTING CHANNEL AS-BUILT DRAWINGS. THIS DESIGN IS BASED ON THE AS-BUILT DRAWINGS AND SUBTRACTING 3' FROM EXISTING CONTOURS.

CONSTRUCTION NOTES:

DOWELS SHALL BE DRILLED PARALLEL TO CHANNEL CENTERLINE.

DOWELS SHALL NOT BE EPOXIED INTO EXISTING CONCRETE.



1 CONNECTION TO EXISTING 7\"/>

BUILDING ENGINEERING AND MUNICIPAL DESIGNS
855 POLARIS BLVD., SE RIO RANCHO, NM 87124
PHONE: (505) 896-0391
FAX: (505) 894-3862
beamdesigns@qwest.net


ALBUQUERQUE METROPOLITAN FLOOD CONTROL AUTHORITY (AMFCA) AND MIDDLE RIO GRANDE CONSERVANCY DISTRICT (MRGCD)

TITLE: LOT 1, STOUT SUBDIVISION CORRALES MAIN CANAL RELOCATION CHANNEL PLAN & PROFILE


APPROVED FOR CONSTRUCTION (MRFCA) DATE 4-16-03
APPROVED FOR CONSTRUCTION (AMFCA) DATE 4-16-03

PROJECT NO. MAP NO. C/D-13 SHEET OF 3 7

JAN 13 2004
HYDROLOGY SECTION



CANAL(Final)A.DWG 04/10/03



SUPPLEMENTAL TECHNICAL SPECIFICATIONS

The following revisions and/or additions to the Technical Specification of the Standard Specifications are hereby made a part of the contract document.

COMPACTION REQUIREMENTS: The following special compaction test reference modifies all sections of the New Mexico State Highway and Transportation Department Standard Specifications for Highway and Bridge Construction, 1994 Edition.

Reference to AASHTO T-99 and AASHTO T-224 for establishing laboratory density for compaction control is hereby amended to read as ASTM D-1557 (Modified Proctor). ASTM D-1557 (Modified Proctor) will be the method used for establishing laboratory density for compaction control for this project.

Supplemental Technical Specifications
To New Mexico State Highway and Transportation Department
Standard Specifications, 1994 Edition

Table of Contents

Section	Description
201	Clearing and Grubbing
203	Excavation, Borrow and Embankment
205	Stripping
207	Subgrade Preparation
510	Portland Cement Concrete
516	4000 psi Tinted Slope Paving
540	Steel Reinforcement
603	Temporary Erosion and Sediment Control
624	Drainage Channel Expansion Joints
625	Shotcrete
628	Protection of Project from Water During Construction
902	Submittals
1012	MRCGD Native Grass Seeding

SECTION 201 CLEARING AND GRUBBING

201.33 SCALPING

- Delete the first sentence and replace with the following: The Contractor shall scalp areas where excavations, foundation treatment or embankment is to be performed.
- Add the following to the end of Section 201.33: All material scalped shall be salvaged and stockpiled. The Contractor shall not scalp the stockpile area. The stockpiling of the scalped material will be directed by the Project Manager.

201.5 BASIS OF PAYMENT

- Delete the wording in this section and replace with the following: The accepted quantity of clearing and grubbing will be paid for at the contract unit price per acre.

Payment will be made under:

Pay Item	Pay Unit
Clearing and Grubbing	AC

SECTION 203 EXCAVATION, BORROW AND EMBANKMENT

203.11

- In the first sentence add the words "backfill, fill construction" following the phrase "construction embankment".

203.3 CONSTRUCTION REQUIREMENTS

- In the first sentence remove "roadway, intersections and entrances" and replace with "channel and storm drain appendages".

203.32 EXCAVATION

- Delete the entire section and substitute the following: Unclassified excavation shall be to the lines and grades shown on the plans and shall be finished to reasonably smooth and uniform surfaces. The Contractor shall notify the Project Manager sufficiently in advance of beginning excavation operations so cross section elevations and measurements of ground surfaces may be taken per Section 105-Control of Work, Supplemental General Provisions.
- All clearing and grubbing shall be done before excavation operations begin. No material may be stockpiled within 20 feet of an area designated for unclassified excavation.
- Cut sections shall be finished to reasonably smooth and uniform surfaces. The Project Manager may require the Contractor to remove unsuitable materials beyond the lines of cut shown on the plans, and backfill these areas with approved material. The Contractor shall conduct his operations for the removal of unsuitable materials in such a way that the Project Manager can take the necessary cross-sections before the backfill is placed.

203.33 ROCK CUTS

- Delete this section in its entirety.

203.34 BORROW

- Add to the first paragraph: Prior to the removal of any embankment material from a borrow area, the Contractor shall scalp the area according to the provisions of Section 201 - CLEARING AND GRUBBING and then take the necessary cross-sections. Measurement of the borrow quantity shall not include the volume of material removed by the clearing and grubbing. Borrow will not be paid as a separate bid item.

203.35 EMBANKMENT

- Add the following paragraph: (c) **Channel Embankment.** Prior to construction of embankment, scalping shall be accomplished as required by Section 201.33 SCALPING.
- The embankment fill materials should be free of vegetation, debris, and other deleterious material and otherwise meet the following requirements as determined in accordance with ASTM D-422. Prior to placing any fill material the contractor shall scarify and compact the existing ground to a depth of 8 inches. This treatment shall be incidental to channel excavation and bridge work. No fill material shall be placed on any part of the embankment foundation until such areas have been inspected and approved. Maximum aggregate sizes shall not exceed 4" in diameter and a minimum 5 to 10 percent material passing the No. 200.
- This gradation shall be obtained by blending the excavated materials as required. The plasticity index shall not exceed 12 as determined by ASTM D-4318.
- Prior to compaction, all selected fill materials shall be brought to or above optimum moisture. This shall be accomplished by either presoaking the excavation area or mechanically mixing water with the embankment materials on-grade.
- All fill material shall be placed in continuous horizontal lifts and properly compacted. The rolled surfaces of all layers of earth fill shall be so constructed as to provide a firm bond with the overlying layer and prevent development of a stratified structure.
- The difference in elevations between adjacent areas of compacted fill shall not exceed 5 feet at any time during embankment construction.
- Materials designated by the Project Manager as unsuitable for use in the channel embankment shall be removed and disposed of at a site selected by the Project Manager. Any boulders greater than two feet in diameter shall be stockpiled on site as directed by the Project Manager.

203.36 SUB EXCAVATION

- Delete the wording in this paragraph in its entirety and substitute the following: All excess or unsuitable excavated material that cannot be used in embankment shall be disposed of at locations approved by the Project Manager. The cost of disposal of waste material shall be included in the unit price for unclassified excavation.

203.37 MOISTURE AND DENSITY CONTROL

- Delete the wording in paragraph one and substitute the following: All embankments, except spoil or stockpiled areas shall be constructed with moisture control.
- Delete the second, third, fourth, fifth, sixth and seventh paragraphs. Add the following section: 203.37.1 MOISTURE AND DENSITY CONTROL FOR CHANNEL CONSTRUCTION.

(a) **Moisture Conditioning.** Fill materials shall be moistened prior to compacting. Moisture content shall range between optimum moisture and + 2% of optimum moisture content as determined by ASTM D-1557. Moisture shall be distributed uniformly throughout each lift.

(b) **Fill Placement.** Fill material shall be blended as necessary to produce a homogeneous material. Fill material shall be spread in horizontal lifts no greater than eight inches in uncompacted thickness and in no case thicker than can be properly compacted with the equipment to be utilized. If fill is to be placed on slopes steeper than 5:1 (horizontal: vertical) the natural ground shall be benched with minimum three foot wide benches at maximum two foot vertical intervals.

(c) **Compaction.** Structural fill shall be mechanical compacted to a minimum relative density of 95% of the maximum dry density as determined by ASTM D-1557. Compaction by flooding and jetting is specifically prohibited unless authorized in advance by the Owner or his representative and the Geotechnical Engineer.

203.37.2 BASIS OF PAYMENT

- Delete the wording in this section in its entirety and substitute the following: All items in this section will be paid for as Unclassified Excavation. Unclassified Excavation payment will only be made for the excavation of in-place materials. No payment will be made for excavation of stockpiled materials, structural excavation of previously placed materials and over depth cuts. No payment will be paid for haul. Payment for unclassified excavation will include the cost for all earthwork including excavation compaction, structural backfill, foundation treatment, moisture control, and hauling material to the embankment, disposing of excess excavation material off site or as designated on the plans. Quantities will be measured by the average end area method. Measurements may be made by field survey or aerial photography. Survey shall be taken after completion of the clearing and grubbing has been approved. Any excess material will be disposed of off-site at the direction of the Project Engineer. For Unclassified Excavation, payment will be under:

Pay Item	Pay Unit
Unclassified Excavation	CY

SECTION 205 STRIPPING

205.31 DESCRIPTION

- Delete in entirety and substitute the following: The stripping material shall be salvaged and stockpiled. The salvaged stripping material shall be spread in a uniform layer on the earthen slopes and embankment prior to seeding embankment.

205.5 BASIS OF PAYMENT

- Delete subparagraphs 205.051 and replace with the following: No separate payment will be made for stripping or placement of stripping material.

SECTION 207 SUBGRADE PREPARATION

- In Section 207.31 replace the words "AASHTO T 99 and AASHTO 224" with the words "ASTM D-1557 (Modified Proctor)".
- In the first sentence of Section 207.31 replace "100" with 95 and replace "95" with 90.
- Add the following section: 207.33 Subgrade Preparation for Channel Lining. All earth surfaces that will receive concrete shall be first compacted to minimum relative density of 95% of the maximum dry density as determined by ASTM D-1557. Subgrade preparation for channel lining shall be a minimum of 8 inches below the lines and grades shown on the plan. Subgrade preparation for the roadway shall be 6 inches minimum below the lines and grades shown on the plan. Where it becomes necessary to excavate beyond normal lines of excavation in order to remove boulders, unsuitable materials or other interfering objects, the voids remaining after the removal of such boulders, unsuitable materials or interfering objects shall be backfilled with suitable material or lean fill, as approved by the Project Manager, compacted to a density of not less than 95%.

SECTION 510 PORTLAND CEMENT CONCRETE

510.11 GENERAL

- In the second sentence, replace "Central Materials Laboratory" with "Project Manager".
- Tint shall be Bayferrox, Sand Beige, at 1 lb. per sack of cementitious material for concrete slope paving and 4000 psi tinted structural concrete as shown on the plan.

510.121 CONCRETE CLASS SUBSTITUTIONS

- Delete this section in its entirety.

510.13 MIX DESIGN

- Delete this section in its entirety and substitute the following: The Contractor shall be responsible for the concrete mix design. Failure of all mixed concrete to meet specification requirements will be considered grounds to reject said concrete. Proportioning of the concrete mix must be based on Section 510.312 Design Option B.

510.2 MATERIALS

- Replace reference to the "Central Materials Laboratory" with "Project Manager".

510.25 WATER

- Delete the first paragraph in its entirety.

510.28 FLY ASH

- Delete this section in its entirety and substitute the following: Fly ash must be added in the proportion of 25 lbs. of fly ash to 100 lbs. of cement.

BUILDING ENGINEERING AND MUNICIPAL DESIGNS				855 POLARIS BLVD., SE RIO RANCHO, NM 87124 PHONE (505) 806-0391 FAX (505) 994-3852 beamdesigns@quest.net	
ALBUQUERQUE METROPOLITAN FLOOD CONTROL AUTHORITY (AMAFCA) AND MIDDLE RIO GRANDE CONSERVANCY DISTRICT (MRGCD)					
TITLE: LOT 1, STOUT SUBDIVISION CORRALES MAIN CANAL RELOCATION DETAILS AND SPECIFICATIONS					
APPROVED FOR CONSTRUCTION (MRCGD)		DATE		NO./DAY/YR.	
APPROVED FOR CONSTRUCTION (AMAFCA)		DATE		NO./DAY/YR.	
PROJECT NO.		MAP NO.		SHEET OF	
CD-13		5		7	

2) Fly ash shall meet the requirements of ASTM C-618, Pozzolan Class F, except the requirements shown on Table 2, "Physical Requirements" shall be amended as follows:

Fineness:	
Surface area, min. cm ² /cm ³	5000
Pozzolanic Activity Index:	
with Portland Cement at 28 days	
minimum percent of control	50
Reactivity with cement alkali's:	
Reduction of Mortar expansion at	
14 days, minimum center	60

510.281 SOURCE APPROVAL AND ACCEPTANCE

- 1) Delete the last sentence of this section.

510.282 SOURCES ON APPROVED LIST

- 1) Delete this section in its entirety and substitute the following: Fly ash that is on the current NMSHTD Central Materials Laboratory approved list will be considered to be pre-approved provided that a copy of such approval is included in the mix design submittal.

510.29 AGGREGATE TESTING

- 1) Delete this section in its entirety.

510.31 PROPORTIONING

- 1) Delete the wording in the first paragraph and substitute the following: After the component materials have been approved, the concrete mix design will be determined.
2) Delete the last paragraph.

510.311 MIX DESIGN OPTION A

- 1) Delete this section in its entirety.

510.312 MIX DESIGN OPTION B

- 1) Delete this section in its entirety and substitute the following: The Contractor shall make arrangements with an independent testing laboratory to determine the proportions by means of trial mixes, including air-entrainment agent and fly ash, which will be necessary to meet the requirements of Section 510 - Portland Cement Concrete. Each mix design must be certified as correct by a professional civil engineer licensed by the State of New Mexico. Prior to any concrete being placed, copies of all test data, including the 28 day flexural and compressive strengths, shall be submitted to the Project Manager for review. If the concrete is being supplied by a commercial supplier (a concrete supplier that has been producing and selling concrete from a fixed location for a period of five years), mix designs may be established on an annual basis for each class of concrete.
- 2) Concrete mix design submittals shall include but not be limited to:
1. Class of Concrete
 2. List of Materials
 3. Material Test Results for the Following:
 - a. Graduations
 - b. Bulk SSD specific quantities
 - c. Fineness modulus (fine aggregate)
 - d. Soundness Loss (coarse aggregate)
 - e. Concrete temperature
 - f. Slump
 - g. Unit weights
 - h. Cylinder breaks at 7, 14 and 28 days
 4. Water/cementitious material ratio
 5. Condition of aggregate source
 6. Procedure

510.313 ADJUSTMENTS TO APPROVED MIX DESIGNS

- 1) Delete this section in its entirety.

510.4 CONCRETE STRENGTH

- 1) Delete this section in its entirety.

510.5 PRICE ADJUSTMENTS

- 1) Delete this section in its entirety.

510.6 MEASUREMENT AND PAYMENT

- 1) For Structural Concrete, payment will be made under:

Pay Item	Pay Unit
Structural Concrete 4000 psi (tinted)	CY
Structural Concrete 4000 psi	CY

SECTION 516 4000 PSI TINTED SLOPE PAVING (Added Section)

516.102 DESCRIPTION

- 1) This work shall consist of the construction of six and eight inch tinted thick concrete slope pavement, in substantial compliance with the specifications and the lines and grades shown on the plans or established by the Project Manager.

516.20 CONSTRUCTION REQUIREMENTS

516.21 GENERAL

- 1) All excavation shall be made in accordance with Section 203. All sub-grade preparation required for concrete slope pavement shall be done in accordance with applicable provisions of Section 207. The concrete, reinforcing steel, curing compound, urethane sealant, Eva-Seal, Plastozote or approved equals, and other materials used in the construction of concrete channel lining shall conform to applicable requirements of these specifications.
- 2) Rebar for channel lining shall be supported on individual high chairs with sand plates. The chairs shall be on, a maximum spacing of five foot centers in all directions.
- 3) All rebar shall be grade 60 rebar and conform to Section 540 STEEL REINFORCEMENT.
- 4) All bar reinforcement shall be deformed bars of Grade 60 and shall conform to the requirements of AASHTO M31, including supplementary requirements. Reinforcement size and grade shall conform to that shown on the plan set for each application.
- 5) The primary bar reinforcement for the reinforced concrete channel shall be that shown on the plan set. The use of deformed Welded Wire Reinforcement (WWR) will be allowed for channel reinforcement. Maximum yield strength of 80,000 psi will be allowed for the WWR in the calculation of reduction in steel cross-sectional area using the equivalent strength procedure. All lapped splices shall be calculated using Grade 60 rebar diameters. All WWR shall be approved by the Project Manager prior to installation. The surface of all WWR shall be free of rust and debris prior to concrete placement.

516.22 FORMS

- 1) Form material shall be free from warp, with smooth and straight upper edges. Timber forms may be used for forming curved sections but shall not be used for straight work unless authorized in writing by the Project Manager. Metal forms for such work being of a gauge that will provide proper rigidity and strength for the purpose for which they intended. The forms shall be of sufficient rigidity and strength and braced such that the forms remain in both horizontal and vertical alignment until their removal.
- 2) Form material shall be thoroughly clean at the time it is used and shall be given a coating of light oil or other suitable material immediately prior to the placing of the concrete.

516.23 PLACING AND FINISHING CONCRETE

- 1) The concrete shall be placed on a thoroughly dampened subgrade sufficiently moist to insure that no moisture will be absorbed from the fresh concrete. After placement, the concrete shall be screeded, floated and given a double tined finish. The plane surfaces shall not vary more than 1/2 inch when measured with a 10 foot straight edge. The finish surface shall not vary more than 0.1" from the established finish grade.

- 2) Concrete shall be placed by means of a concrete pump with sufficient boom length to reach all portions of the channel at each set up.
- 3) The temperature of the mixed concrete shall be not more than 90 degrees F at the time of placing.

- 4) Slope paving concrete shall not be cast unless the combination of air temperature, temperature of fresh concrete, relative humidity and wind velocity at the site are such that the rate of evaporation is less than 0.20 pounds per square foot per hour as determined by the procedure in Section 509.034.
- 5) Concrete mixing placement and finishing shall be in accordance with Section 451.033 paragraph (d) Handling, Measuring and Batching Materials except as modified herein.
- 6) If a sawed joint is utilized for the longitudinal joint in the channel lining, this joint shall be constructed in accordance with the following:

- a) Longitudinal Contraction Joint: Longitudinal contraction joints shall consist of planes of weakness created by forming or cutting grooves in the surface of the pavement and shall include reinforcing as shown on the plans.
 - b) Sawed contraction joints shall be created by sawing grooves in the surface of the pavement, of the dimensions and at the spacing and lines shown on the plans, with an approved concrete saw. After each joint is sawed, the saw cut and adjacent concrete surface shall be thoroughly cleaned and sealed with urethane sealant. Sonalastic NP-1 sealant or approved equal.
 - c) Sawing of the joints shall commence as soon as the concrete has hardened sufficiently to permit sawing without excessive raveling, usually 4 to 12 hours. All joints shall be sawed before uncontrolled shrinkage cracking takes place. If necessary, the sawing operations shall be carried on both during the day and night, regardless of whether conditions. The sawing of any joint shall be omitted if a crack occurs at or near the joint location prior to sawing. Sawing shall be discontinued when a crack develops ahead of the saw. In general, all joints shall be sawed in sequence. If extreme conditions exist which make it impractical to prevent erratic cracking by early sawing, the contraction joint groove shall be formed.
- 7) Concrete curing shall be in accordance with Section 510.240, paragraph 510.241 Liquid Membrane Forming Curing Compound, and Curing Concrete Pavement in Cold Water.
- 8) The use of a canal or slope paving machine is encouraged. Such machine must meet the following conditions:
- a) It shall be of the type having rollers and augers and shall also have vibrating pans, or spud-type vibrators capable of vibrating at 3500 impulses per minute.
 - b) The machine shall be in good repair and properly maintained. Fuel tanks must be full before placing over concrete, and should be of sufficient capacity to preclude refueling during concrete placement.
 - c) Rolls must be strong enough and sufficiently anchored to prevent flexing or bending when the machine is operated. Rolls must be kept clean during paving operations.
 - d) Only authorized operation(s) will be allowed on the machine while in operation.
 - e) Follow manufacturer's guidance regarding set-up and operation.

- 9) A dry run shall be made before concrete is placed to check grades and lines and proper operation.
- 10) Concrete placement shall include the following techniques:
- a) Concrete must be placed starting downstream and working upstream. This requirement is intended for each concrete placement when applicable and not intended to direct the activities for the overall project.
 - b) A concrete pump shall be used. Provision shall be made for a spare pump or crane with bucket. Placement on slopes shall be from toe of slope to top after bottom section has been placed.
 - c) Concrete shall be placed close to the final position, and to its full thickness.
 - d) Do not place concrete more than 12 feet in front of the machine.
- 11) The heights of the concrete roll in front of the augers shall be at least one-half the diameter of the auger.
- 12) Augers shall be adjusted up or down to maintain a roll of concrete one-inch high on the front or leading end of the finished rollers.
- 13) The rear of the machine should be raised slightly (about 1/8 inch) to allow grout on the side of the finishing rollers to feather itself out and leave a smooth finish.
- 14) The machine shall be advanced such that all concrete receives at least three passes of the rollers.

516.24 TOLERANCE IN PAVEMENT THICKNESS

516.24.1

- 1) Acceptance of the finished channel lining with respect to thickness shall be on the basis of random core sampling, as designated by the Project Manager. A minimum of two core samples will be taken from longitudinal lengths of channel not to exceed 300 linear feet, or from a one day's placement of concrete not to exceed 300 linear feet. If deficiencies are noted, the Project Manager may require additional core samples to be taken. All coring required by the Project Manager shall be at the Owner's expense.
- 2) Should the Contractor desire to have additional core samples taken these samples would be taken at the Contractor's expense.

516.24.3

- 1) Deduction for a deficiency in thickness shall be made according to Table 516.24.3. Thickness deficiency shall be based on the average thickness of the number of samples taken within the specified length of channel.

516.24.4

- 1) It shall be the responsibility of the person requesting the core sampling to have the core holes immediately filled with fresh concrete. This concrete shall be of the same concrete mix and of equal compressive strength as the original concrete.

516.24.5

- 1) Any concrete lining that is noted to be deficient in thickness at or more than the reject level on Table 516.24.3 shall be removed and replaced at the Contractor's expense.

516.24.6

- 1) For information purposes only, the Project Manager may have the core samples tested for compressive strength.

TABLE 516.24.3 DEDUCTIONS FOR DEFICIENCY IN THICKNESS

(Average thickness per core measured in accordance with ASTM C-174)

Design thickness shown on the plan set

Bridge Deck 5"

Tinted Slope Paving 6"

Tinted Slope Paving 8"

Thickness Deficiency	Percentage of Contract Price Allowed
0 to 1/4 inch	100
1/4 to 1/2 inch	94
1/2 to 3/4 inch	88
3/4 to 1 inch	82
Greater than 1 inch	Reject

*Design Thickness

516.30 METHOD OF MEASUREMENT

- 1) All portions of the trapezoidal channel lining and any slabs less than or equal to one-foot thick shall be considered slope paving and be governed by this section of the specifications. Concrete slope paving shall be measured by the square yard of exposed surface area.
- 2) Concrete rundowns shall be measured by each square yard of exposed surface area. Cut off walls associated with concrete rundowns shall be measured by the cubic yard of non-tinted structural concrete calculated by the line and grades shown on the plan set. All payments shall include all labor, material, excavation, backfill, and jointing material required to complete the work in place to the interface with the slope paving.

516.40 BASIS OF PAYMENT

- 1) The accepted quantities of tinted slope paving and rundowns will be paid for at the contract unit price per square yard constructed excluding cutoff walls and shall include the Portland Cement, aggregate, concrete coloring (when required), admixtures, reinforcing steel, earthwork, curing compound and any other operations necessary to complete the concrete in place not separately paid for. Tinted concrete is required for all exposed slope paving. It is also required for all rundowns and rundown access ramp.
- 2) The accepted quantities of tinted slope paving shall be paid for at the contract price per square yard exposed surface. Payment for concrete slope paving shall be considered just compensation for completing the concrete slope paving in place including thickened sections of joints, top and toe of slopes, joint materials and materials and operations and reinforcing steel.

Payment shall be made under:

Pay Item	Pay Unit
4000 psi Tinted Channel Lining 8 inches thick	SY
4000 psi Tinted Channel Lining 6 inches thick	SY

SECTION 540 STEEL REINFORCEMENT

540.21 BAR REINFORCEMENT

- 1) Delete this section in its entirety and replace as follows:
Primary bar reinforcement shall be deformed bars of Grade 60 and shall conform to the requirements of AASHTO M31, including supplementary requirements. Field bending of Grade 60 bars will not be permitted. All ties and stirrup bar reinforcement shall be deformed bars of Grade 40 or Grade 60 and shall conform to the requirements of AASHTO M31, including supplementary requirements. Reinforcement size and grade shall conform to that shown on the plot set for each application.

The primary bar reinforcement concrete channel shall be that shown on the plan set. The use of deformed Welded Wire Reinforcement (WWR) will be allowed for channel reinforcement. Maximum yield strength of 80,000 psi will be allowed for the WWR in the calculation of reduction in steel cross-sectional area using the equivalent strength procedure. The use of WWR will decrease the rebar spacing of the channel reinforcement. All lapped splices shall be calculated using Grade 60 rebar diameters. All WWR shall be approved by the Project Manager prior to installation. The surface of all WWR shall be free or rust and debris prior to concrete placement.

540.34 SPLICING

- 1) Delete this section in its entirety and replace as follows:
Reinforcement shall be furnished in the full length indicated on the plans, unless otherwise included in a reinforcing bar submittal by the Contractor and approved by the Project Manager. Bars in lapped splices shall be placed and securely tied in a manner that will maintain not less than the minimum distance to the surface of the concrete shown on the plans.

540.36 REINFORCING BAR PLACEMENT

- 1) Delete the fourth paragraph and add the following sentence:
Steel chairs used to support the bottom mat shall have individual sand plates and be on a maximum of 5' x 5' spacing.

540.361 REINFORCING BAR PLACEMENT TOLERANCES

- 1) Delete this section in its entirety and substitute the following:
With the exception of slabs and footings cast on earth and of tie bars where specified, the minimum clear coverage of reinforcement shall be two (2) inches, and the structures shall be formed. The minimum clear coverage for all slabs and footings cast on earth shall be three (3) inches.

Variations in spacing between adjacent bars shall not exceed 1/4 inch or one twenty-fourth (1/24) of the spacing dimension shown in the plans, whichever is greater.

540.4 and 540.5

- 1) Delete this section entirely and replace with the following:
540.4 and 540.5 MEASUREMENT AND PAYMENT. Steel reinforcement, fabrication, and installation will not be paid for separately but will be considered incidental to other contract items to which it relates.

SECTION 603

TEMPORARY EROSION AND SEDIMENT CONTROL

603.12 POLLUTION PREVENTION PLAN

- 1) Add the following to the second paragraph:
This work includes the filing of the Notice of Intent, building structural measures as required by the contract documents, maintaining structural measures, monitoring and inspection of structural measures and inspection of the entire site, recording keeping and filing the Notice of Termination after acceptance of the project.

603.13. NOTICE OF INTENT

- 1) Delete this paragraph and substitute the following paragraph:
The Contractor shall comply with the United States Environmental Protection Agency NPDES General Permits for Storm Water Discharges from Construction Sites. The Contractor shall submit to the Project Manager, two days prior to the pre-construction conference, a "Notice of Intent" form (NOI) as contained in the EPA regulations. Work may begin 48 hours after submittal of NOI. After completion and acceptance of the project, and prior to the final payment, the Contractor shall submit a "Notice of Termination" (NOT) to EPA. A blank NOI and NOT are contained in the SWPPP section.

603.32. CONTRACTOR'S OPERATIONS

- 1) Add the following paragraph to the end of the section:
The Contractor agrees to maintain existing silt fence on the Project at no additional costs. The Contractor agrees to install additional erosion control measures as conditions indicate, or as directed by other regulatory agencies, in a timely manner as dictated by the circumstances. Contractor and Owner will negotiate in good faith for equitable compensation for furnishing, installing and maintaining such additional erosion control measures.

603.38. CHANGES AND REVISIONS REQUIRED BY OTHER REGULATORY AGENCIES (New Section)

If, during the course of the project, meetings are required to address changes or revisions to the Storm Water Pollution Prevention Plan, that are due to circumstances beyond the Contractor's control, Owner and the Contractor's representative shall both attend such meetings and work together with the regulatory agencies for resolutions of any such problems. The Contractor's representative shall have authority to enter into agreements, approve change orders and commit contractor resources to comply with the NPDES General Permit Provisions.

603.39. COMPLIANCE WITH NPDES PERMIT REQUIREMENTS (New Section)

In the event the Contractor fails to comply with the permit requirements after written notice to comply with such, AMAFCA retains the right to enter upon the project site and perform corrective measures. The cost of such corrective measures shall be the responsibility of, and shall be paid by, the Contractor. AMAFCA shall be entitled to deduct such costs from remaining contract amounts, and if insufficient contract amounts exist, the Contractor shall reimburse AMAFCA for any deficiency.

603.41. METHOD OF MEASUREMENT

- 1) Delete the section and substitute the following paragraph:
The compliance with the Storm Water Pollution Prevention Plan, filing of Notice of Intent, maintenance and inspection of structural measures included in the Bid Proposal, inspection of the site, record keeping, and filing of Notice Termination will be paid on a

lump sum basis with one half the lump sum paid when the Notice of Intent is filed, and with the remaining amount paid as a percentage of the contract. Payment for this item is limited to a total of one percent (1%) of the contract.

603.51. BASIS OF PAYMENT

- 1) Delete the section and substitute the following paragraph:
Items of work defined herein must comply with the United States Environmental Protection Agency NPDES General Permits for Storm Water Discharges from Construction Sites, will be described on the bid proposal as "NPDES Storm Water Permitting." They will be paid for as follows:

Payment Item	Pay Unit
NPDES Permitting	Lump Sum
Silt Fence	Linear Feet
Straw Bale	Each

SECTION 624 DRAINAGE CHANNEL EXPANSION JOINTS (Added Section)

624.01 GENERAL

- 1) All joint sealing compounds shall be used when shown on the plans and be installed based on the following criteria and the manufacturer's instructions. All suggested materials may be replaced by other materials if approved equal by the Engineer.

624.02. MATERIALS

624.021. URETHANE SEALANT

- 1) Sonalastic NP1 or SL-1 a two-component, self-priming urethane sealant produced by Sonabone Building Projects Divisions of Contech, Inc., or approved equal by the Project Manager, shall be used where called out on the plan. The sealant shall conform to specification ASTM C-920-72.
- (a) Preparation and Application. Immediately prior to application, joints shall be cleaned with power driven wire brushes to remove laitance, curing compound, or other bond inhibitors. If the joints are backed with anything other than closed cell Polyethylene rod, a bond breaker such as polyethylene sheeting must be used to prevent third surface adhesion.

Joint surfaces must be primed and dry to the touch before the sealant is applied. Sealant shall be extruded at the bottom of the joint groove and tamped to work the sealant into close contact with the joint surfaces to eliminate air bubbles. Any sealant that does not cure properly, fails to establish a satisfactory bond, is damaged by the Contractor's operations, or is not satisfactory in the opinion of the Project Manager, must be removed and the joint re-cleaned and resealed. The sealant shall not be applied when the air temperature is below 40 degree Fahrenheit.

- (b) Bonding Agent. The bonding agent to be used to bond Sonalastic NP to the concrete or mortar nosing shall be No. 1993 Primer, a one-component solvent based system, or approved equal by the Project Manager.

624.03 MEASUREMENT AND PAYMENT

There shall be no separate measurement or payment for the concrete joint material and shall be considered incidental to other contract items.

SECTION 625 SHOTCRETE

Delete Section 625 and replace with the following:

625.1 DESCRIPTION

- 625.11 This work shall consist of construction of the concrete emergency spillway lining utilizing the shotcrete process, including mixing, placing, finishing, testing and curing as shown in the contract in compliance with these specifications.

- 625.12 The requirements of Section 510 - Portland Cement Concrete and Section 511 - Concrete Structures shall apply where appropriate and not expressly modified by these specifications.

625.2 MATERIALS

- 625.21 All requirements of Section 510 - Portland Cement Concrete shall apply except as modified herein. Shotcrete shall have a minimum compressive strength of 3,500 PSI at 28 days, 5-8% air content at the pump and a slump of 1-1/2" to 3" at the pump. Shotcrete shall be tinted in accordance with Subsection 625.211 of these specifications.

- 625.211 Tinted concrete will be made by the addition of an approved concrete coloring agent to the concrete mix. The coloring agent will be added in addition to other concrete ingredients and no reductions to other ingredients will be made.

The concrete coloring for use on this project shall be Bayferrox, Sand Beige, Color numer 0064, or Approved Equal. The coloring agent shall be added at a rate of one (1) pound per sack of cement, per the manufactures specifications.

The design mixes must be submitted by the Contractor for approval by the Project Manager prior to placement.

Coordination with the General contractor, shotcrete subcontractor, AMAFCA Project Manager will be required prior to any shotcrete placement.

- 625.22 Coarse Aggregate. Coarse aggregate shall meet the following gradation requirements.

Sieve Size	1. Percent Passing
1/2 inch	100
3/8 inch	85-100
No. 4	10-30
No. 8	0-10
No. 16	0-5

BUILDING ENGINEERING AND MUNICIPAL DESIGNS	BEAM DESIGNS	655 POLARIS BLVD., SE RIO RANCHO, NM 87124 PHONE (505) 896-0381 FAX (505) 994-3952 beamdesigns@quest.net
--	------------------------	--

ALBUQUERQUE METROPOLITAN FLOOD CONTROL AUTHORITY (AMAFCA) AND MIDDLE RIO GRANDE CONSERVANCY DISTRICT (MRGCD)

TITLE LOT 1, STOUT SUBDIVISION CORRALES MAIN CANAL RELOCATION SPECIFICATIONS

PROJECT NO.	APP NO.	SHEET OF
CD-13	6	7

CANAL-DTL(final1A).DWG 04/10/03