CITY OF ALBUQUERQUE

Planning Department
Suzanne Lubar, Director



Mayor Richard J. Berry

September 28, 2015

Mark Goodwin, PE Mark Goodwin & Associates, PA. PO Box 90606 Albuquerque, NM 87199

Re: Massey Warehouse-Phase 2

8410 Washington St.

Grading and Drainage Plan

Engineer's Stamp dated: 11/22/2016 (C17D003)

Dear Mr. Goodwin,

Based on the information provided in your submittal received 11/23/2016, the above referenced Grading and Drainage Plan is approved for Building Permit.

PO Box 1293 Please attach a copy of this approved plan to the construction sets in the permitting

process prior to sign-off by Hydrology.

Prior to Certificate of Occupancy release, Engineer Certification per the DPM checklist

Albuquerque will be required.

New Mexico 87103 If you have any questions, you can contact me at 924-3986 or Rudy Rael at 924-3977.

www.cabq.gov

Abiel Carrillo, P.E.

Sincerely,


Principal Engineer, Hydrology

Planning Department

RR/AC

 \mathbf{C}

File



City of Albuquerque

Planning Department

Development & Building Services Division

DRAINAGE AND TRANSPORTATION INFORMATION SHEET (REV 09/2015)

Project Title: Massey Warehouse- Phase 2	Building Permit #:	City Drainage #: CITDC
DRB#:		Work Order#:
Legal Description: LTF-1 Plat of lands of Los Angeles Investors lots E-1, E-2, 8	ֆ F-1	
City Address: 8410 Washington St Abq, NM, 87113		
Engineering Firm: Mark Goodwin & Associates		Contact: Hıram L Crook
Address: PO Box 90606, Abq, NM, 87199		
Phone#: (505) 898-2200 Fax#: (505) 797-9539		E-mail: Hiram@goodwinengineers.com
Owner: Jerry Mosher		Contact:
Address: 4441 Anaheim Ave NE, Abq, NM 87113		
Phone#: (505) 822-5468 Fax#:	· ····	E-mail: jerry@mosherent.com
Architect: N/A		Contact:
Address:		
Phone#: Fax#:		E-mail:
Other Contact:		Contact:
Address:		
Phone#: Fax#:		E-mail:
DEPARTMENT: X HYDROLOGY/ DRAINAGE TRAFFIC/ TRANSPORTATION MS4/ EROSION & SEDIMENT CONTROL TYPE OF SUBMITTAL: ENGINEER/ ARCHITECT CERTIFICATION CONCEPTUAL G & D PLAN X GRADING PLAN DRAINAGE MASTER PLAN DRAINAGE REPORT CLOMR/LOMR TRAFFIC CIRCULATION LAYOUT (TCL)	BUILDING PACE CERTIFICAT PRELIMINAL SITE PLAN FOUNDATION SIA/ RELEAS FOUNDATION	SE OF FINANCIAL GUARANTEE ON PERMIT APPROVAL ERMIT APPROVAL OVAL
TRAFFIC CIRCULATION LAYOUT (TCL)	GRADING/ P	AD CERTIFICATION
TRAFFIC IMPACT STUDY (TIS) EROSION & SEDIMENT CONTROL PLAN (ESC)	WORK ORDER CLOMR/LOM	
OTHER (SPECIFY)	PRE-DESIGN I OTHER (SPE	MEETING CIFY)
IS THIS A RESUBMITTAL?: X Yes No		
DATE SUBMITTED: November 22, 2016 By: Hiram L	_ Crook	MEGEIVEN
OA STAFF ELECTRONIC SUBMITTAL RECEIVED		LAND DEVELOPMENT SECTION

Carrillo, Abiel X.

From:

Carrillo, Abiel X.

Sent:

Wednesday, November 02, 2016 4:44 PM

To:

D. Mark Goodwin (mark@goodwinengineers.com)

Subject:

Massey - Phase 2 - C17D003 - Stamp Date 10-10-2016

Mr. Goodwin,

This email is being sent in lieu of a formal letter attached to this email to help expedite the review of initial submittals. A reply to this email will not substitute a resubmittal.


Based on the information provided in your submittal, received 10-13-2016, the above-referenced Grading and Drainage Plan cannot be approved for Building Permit until the following comments are addressed:

- 1. The Hydrology Notes mention that the pond at the west end of the site will have enough volume to manage the first flush volume. The volume required needs to be shown on the plan, since the masterplan is dated prior to the date of the first flush ordinance.
 - a. The pond does not appear to be designed to retain any volume; the outfall invert is set at the same elevation as the pond bottom.
- 2. Place rip rap or other erosion control element upstream of the sidewalk piping along the southern swale to prevent clogging and conveyance to the adjacent property.
- 3. Will the site be graveled? Based on aerial photos it appears that the area between the Building E and the gate is a dirt lot used by a lot of trucks. A track pad (rip rapped pad) just inside of the gate should be considered to minimize sediment tracking onto the paved portion of the site (not a requirement, but may minimize maintenance of the ponds).

Any question just let me know.

Abiel Carrillo, PE, CFM

Principal Engineer - Hydrology
Planning Department
Development Review Services Division
City of Albuquerque
505-924-3986
acarrillo@cabq.gov
600 2nd Street NW
Albuquerque, NM 87102



COA STAFF

ELECTRONIC SUBMITTAL RECEIVED ____

City of Albuquerque

Planning Department

Development & Building Services Division

DRAINAGE AND TRANSPORTATION INFORMATION SHEET (REV 09/2015)

Project Title: Massey Warehouse- Phase 2	Building Permit #	City Drainage #: CTTDC
DRB# EPC#		Work Order#:
Legal Description: LTF-1 Plat of lands of Los Angeles Investors lots E-1, E-2, &	k F-1	
City Address: 8410 Washington St. Abq, NM, 87113	<u> </u>	
Engineering Firm: Mark Goodwin & Associates		Contact: Hıram L Crook
Address: PO Box 90606, Abq, NM, 87199		
Phone# (505) 898-2200 Fax#. (505) 797-9539		E-mail: Hıram@goodwınengıneers.com
Owner: Jerry Mosher		Contact:
Address: 4441 Anaheim Ave NE, Abq, NM 87113		
Phone# (505) 822-5468 Fax#	······································	E-mail: jerry@mosherent.com
Architect: N/A		Contact:
Address:		· · · · · · · · · · · · · · · · · · ·
Phone# Fax# ·		E-mail:
Other Contact:		Contact:
Address:		
Phone#· Fax#.		E-mail:
TRAFFIC/ TRANSPORTATION MS4/ EROSION & SEDIMENT CONTROL		ERMIT APPROVAL E OF OCCUPANCY
TYPE OF SUBMITTAL:	DD CLINAINIA D	N. DI AT ADDDONAL
ENGINEER/ ARCHITECT CERTIFICATION (\)		RY PLAT APPROVAL OR SUB'D APPROVAL
		OR BLDG. PERMIT APPROVAL
CONCEPTUAL G & D PLAN	FINAL PLAT	
X GRADING PLAN		SE OF FINANCIAL GUARANTEE
DRAINAGE MASTER PLAN	<u> </u>	N PERMIT APPROVAL
DRAINAGE REPORT	70.011	ERMIT APPROVAL
	\SØ-19 APPRO	DVAL
TRAFFIC CIRCULATION LAYOUT (TCL) TRAFFIC IMPACT STUDY (TIS) LAND DEVELOPMENT	ENT SECTIONING PER	MIT APPROVAL AD CERTIFICATION
TRAFFIC IMPACT STUDY (TIS)	WORK ORDER	RAPPROVAL
EROSION & SEDIMENT CONTROL PLAN (ESC)	CLOMR/LOM	
OTHER (SPECIFY)	DDE DECICALA	
· · · · · · · · · · · · · · · · · · ·	PRE-DESIGN NOTHER (SPE	
	OTHER (SPE	CIFY)
IS THIS A RESUBMITTAL? Yes X No		
IS THIS A RESUBMITTAL? YesX_ No		
IS THIS A RESUBMITTAL? YesXNo DATE SUBMITTED: October 11, 2016 By: Hiram L	Crook	



City of Albuquerque

P.O. BOX 1293 ALBUQUERQUE, NEW MEXICO 87103

February 5, 2001

D. Mark Goodwin, P.E. MARK GOODWIN & ASSOC. P.O. Box 90606 Albuquerque, NM 87199

Grading and Drainage Certification RE:

Massey Warehouse Project - For Bldgs. "A" & "B" Only

(C-17/D003) (Washington St.) Engineer's Stamp dated 2/2/2000

Engineers Certification dated 2/2/2001

Dear Mr. Goodwin:

Based upon the information provided in your Engineers Certification submittal dated 2/2/2001, the above referenced site is approved for Permanent Certificate of Occupancy.

This permanent Certificate of Occupancy is for Buildings "A" and "B" ONLY. If I can be of further assistance, please contact me at 924-3986.

Sincerely, Brookly L. Brighan Bradley L. Bingham, PE

Senior Civil Engineer, PWD

Vickie Chavez, COA Teresa Martin, COA

PURPOSE OF REPORT

The entire Massey Project is to construct 5 buildings with 3 offices each. 'At this time, only buildings A and B will be constructed. This report is being submitted for drainage approval. Please note, traffic circulation for this project was approved by Mike Zamora on January 24, 2000.

EXISTING CONDITIONS

The site is located on the enclosed Zone Atlas Map C-17 and is zoned SU-2, M-1. The property is bounded on the west by Washington Street, on the north and south by undeveloped land, and on the east by businesses on the west side of Jefferson.

A drainage swale runs from the north to the south at the midpoint between Washington Street and Jefferson Street. This swale is along the eastern edge of the property and prevents off-site flows from entering this property. This site has a uniform grade of 2.2% from east to west. The site is not within the 100 year flood zone.

PROPOSED MANAGEMENT PLAN

Please see the enclosed Grading and Drainage Plan, C1.

The entire 2.12 acre site contributes 9.42 cfs for the 100 year, 6 hr storm event. Water from the site drains northward down Washington Avenue. Eventually, this water drains to the Alameda storm drain which is sized for the 10 year storm. As a result, the discharge from the Massey site must be less than the 10 year storm which is 6.05 cfs.

On site, most of the storm water (8.39 cfs) will drain to the center of the parking lot and then flow into the trench drain on the west side of the lot. Each side of the trench drain drains to an 18 inch pipe which goes to a detention pond. The remaining storm water (1.03 cfs) will drain behind the two westerly buildings and then directly into the detention ponds.

The storm water will be released at the northwest comer of the northern detention pond at a maximum rate of 6.05 cfs through a 0.7 foot opening in the wall of the detention pond. Thus, the site is discharging less than the 10 year storm.

ALBUQUERQUE NEW MEXICO

City of Albuquerque

February 22, 2000

Mark Goodwin, P.E.

Amy Driscoll

Mark Goodwin & Associates, PA

P.O. Box 90606

Albuquerque, NM 87199

RE: GRADING AND DRAINAGE PLAN FOR MASSEY WAREHOUSE SUBMITTED FOR BUILDING PERMIT APPROVAL (C-17/D003)

Dear Mr. Goodwin,

Based upon the information provided in your February 1, 2000, submittal, the project, referred to above, is approved for Building Permit. Please attach a copy of this approved plan to the construction sets prior to sign-off by Hydrology.

A separate permit is required for construction within the city right-of-way. A copy of this approval letter must be on hand when applying for the excavation permit.

Prior to release of the Certificate of Occupancy, an Engineer Certification, per the DPM checklist, will be required.

If you have any questions, please call me at 924-3988.

Sincerely,

Stuart Reeder, P.E. Hydrology Division

-100001 CECUAL

xc: Pam Lujan, Permits
Whitney Reierson
File

DRAINAGE REPORT for

MASSEY PROJECT

Prepared By

Mark Goodwin & Associates, PA P.O. Box 90606 Albuquerque, NM 87199

Prepared For

George Rainhart 2325 San Pedro NE, Suite 2B Albuquerque, NM 87110



February 2000



D. Mark Goodwin & Associates, P.A. Consulting Engineers

P.O. BOX 90606, ALBUQUERQUE, NM 87199 (505) 828-2200 FAX 797-9539

November 11, 2016

Mr. Abiel Carrillo, PE Principal Engineer, Hydrology Planning Dept. City of Albuquerque PO Box 1293 Albuquerque, NM 87103

Re: Ma

Massey Warehouse

Massey - Phase 2 - C17D003 - Stamp Date 10-10-2016

Dear Mr. Carrillo;

In response to your comment letter dated 11-3-16, your comments are addressed below:

1. The Hydrology Notes mention that the pond as the west end of the site will have enough volume to manage the first flush volume. The volume required needs to be shown on the plan, since the masterplan is dated prior to the date of the first flush ordinance.

The pond bottom will be dug out with a 2:1 side slope and will retain the volume needed for the first flush. The revised grading plan shows a detail of the pond along with notes for the first flush and its volume needed.

2. Place rip rap or other erosion control element upstream of the sidewalk piping along the southern swale to prevent clogging and conveyance to the adjacent property.

With this iteration of the grading plan the sidewalk piping has been removed and is no longer needed. — Plan 5511 5600 it

3. Will the site be graveled? Based on aerial photos it appears that the area between the Building E and the gate is a dirt lot used by a lot of trucks. A track pad (rip rapped pad) just inside of the gate should be considered to minimize sediment tracking onto the paved portion of the site (not a requirement, but may minimize maintenance of the ponds).

The portion of the site between the proposed building parking lot and the existing fence will be graveled to allow for truck movement and minimize sediment tracking. Notation of the graveled area is noted on the revised Grading & Drainage plan.

Please call me if you have any questions.

Sincerely,

MARK GOODWIN & ASSOCIATES, P.A.

Hiram L. Crook Staff Engineer

F:\1-Projects\2016\A16056 - Massey Warehouse\HYDRO LTR 11.21.016.docx



City of Albuquerque

P.O. BOX 1293 ALBUQUERQUE, NEW MEXICO 87103

Public Works Department Transportation Development Services Section

July 17, 2002

Bin Johnson for George Rainhart, Registered Architect George Rainhart & Associates 2325 San Pedro N.E., #2B Albuquerque, NM 87110

Re:

Certification Submittal for Final Building Certificate of Occupancy for

Massey Office/Warehouse, [C-17 / D003]

8410 & 8418 Washington N.E.

Architect's Stamp Dated 07/10/2002

Dear Mr. Johnson:

The TCL / Letter of Certification submitted on July 12, 2002 is sufficient for acceptance by this office for final Certificate of Occupancy (C.O.). Notification has been made to Building and Safety and final C.O. has been logged in by Vicki Chavez in the Building Safety Section downstairs.

Sincerely,

Mike Zamora, Commercial Plan Checker

Development and Building Services

Planning Department

c: Hydrology file Mike Zamora June 27, 2002



Mr. Mike Zamora
City of Albuquerque
Transportation Division
600 2nd Street NW
Albuquerque, NM 87102

RE: 8410 and 8418 Washington

Office Warehouse Albuquerque, NM Transportation Certification

Dear Mr. Zamora:


This letter hereby certifies that the site construction referenced above has been completed to the best of my knowledge. The site is constructed within substantial compliance with the approved Site Plan, as of the date of this certification. Please see the attached site plan which indicates the as-built conditions of the site.


Sincerely,

George Rainhart, Architect & Associates

George R. Rainhart, AIA

Cc: file





Mike Zamora Traffic Department City of Albuquerque 600 Second St. NW Albuquerque, NM 87103

Massey Office Warehouse C17/D003RE:

Ref Permit #: 0000916

8410 & 8418 Washington NE

Dear Mr. Zamora:

I have reviewed the completed project. To the best of my knowledge this site has been constructed per the approved Traffic control plan included in the building permit set.

Respectfully,

George Rainhart

George Rainhart, Architect & Associates

8918 of 3410 - Mare I 6/9/01-30t 155 Ref or 5/31/01 7/31/01-Calledin (GT) Final c.o. for Place I

GEORGE RAINHART, ARCHITECT & ASSOCIATES P.C.

2325 SAN PEDRO NE SUITE 2-B - ALBUQUERQUE, NEW MEXICO 87110

PHONE: 505-884-9110 ■ FAX: 505-837-9877 ■ Email: rainhart@worldnet.att.net

Visit Showed Phase I Not under coust. (weeds fully Grown) No Barricading Striping Not Per app'd Plan (infrant of O.H. Doors?), - large Truck & Parked / Stored in Ph II.

PURPOSE OF REPORT

The entire Massey Project is to construct 5 buildings with 3 offices each. At this time, only buildings A and B will be constructed. This report is being submitted for drainage approval. Please note, traffic circulation for this project was approved by Mike Zamora on January 24, 2000.

EXISTING CONDITIONS

The site is located on the enclosed Zone Atlas Map C-17 and is zoned SU-2, M-1. The property is bounded on the west by Washington Street, on the north and south by undeveloped land, and on the east by businesses on the west side of Jefferson.

A drainage swale runs from the north to the south at the midpoint between Washington Street and Jefferson Street. This swale is along the eastern edge of the property and prevents off-site flows from entering this property. This site has a uniform grade of 2.2% from east to west. The site is not within the 100 year flood zone.

PROPOSED MANAGEMENT PLAN

Please see the enclosed Grading and Drainage Plan, C1.

The entire 2.12 acre site contributes 9.42 cfs for the 100 year, 6 hr storm event. Water from the site drains northward down Washington Avenue. Eventually, this water drains to the Alameda storm drain which is sized for the 10 year storm. As a result, the discharge from the Massey site must be less than the 10 year storm which is 6.05 cfs.

On site, most of the storm water (8.39 cfs) will drain to the center of the parking lot and then flow into the trench drain on the west side of the lot. Each side of the trench drain drains to an 18 inch pipe which goes to a detention pond. The remaining storm water (1.03 cfs) will drain behind the two westerly buildings and then directly into the detention ponds.

The storm water will be released at the northwest corner of the northern detention pond at a maximum rate of 6.05 cfs through a 0.7 foot opening in the wall of the detention pond. Thus, the site is discharging less than the 10 year storm.

AHYMO SUMMARY TABLE (AHYMO194) - AMAFCA Hydrologic Model - January, 1994 RUN DATE (MON/DAY/YR) =02/01/2000 INPUT FILE = massey4.dat USER NO.= M_GOODWN.IO1

USER NO. = M_GOODWN.IO1

COMMAND		DROGRAPH	FROM ID NO.	TO ID NO.	AREA (SQ MI)	PEAK DISCHARGE (CFS)	RUNOFF VOLUME (AC-FT)	RUNOFF	TIME TO PEAK (HOURS)	CFS PER ACRE	PAGE =	
COMPUTE NM H	PE= 1 YD PE= 1	100.00	_	1	.00332	9.42	.347	1.96222	1.500	4.437		.00 2.400 85.00
COMPUTE NM H ROUTE RESERV FINISH		200.00 300.00	- 1	2 3	.00332	6.05 6.02	.214	1.20693 1.96214	1.500 1.633		RAIN6= PER IMP= AC-FT=	1.600 85.00 .088

START TIME=0.0

**** MASSEY WAREHOUSE

**** FILE: c:\AHYMO\MASSEY4.DAT JANUARY 2000 BY:AMY

**** 100-YEAR 6-HOUR STORM EVENT

RAINFALL TYPE=1 RAIN QUARTER=0.0 IN

> RAIN ONE=2.05 IN RAIN SIX=2.40 IN RAIN DAY=2.7 IN DT=0.033333 HR

**** DEVELOPED CONDITIONS

COMPUTE NM HYD ID=1 HYD NO=100.00 AREA=0.003317 SQ MI

PER A=0.00 PER B=0.15 PER C=0.00 PER D=0.85

TP=0.1333 HR MASS RAINFALL=-1

PRINT HYD ID=2 CODE=1

**** 10-YEAR, 6-HOUR STORM EVENT

RAINFALL TYPE=1 RAIN QUARTER=0.0 IN

> RAIN ONE=1.37 IN RAIN SIX=1.60 IN RAIN DAY=1.80 IN DT=0.033333 HR

**** DEVELOPED CONDITIONS

ID=2 HYD NO=200.00 AREA=0.003317 SQ MI COMPUTE NM HYD

PER A=0.00 PER B=0.15 PER C=0.00 PER D=0.85

TP=0.1333 HR MASS RAINFALL=-1

PRINT HYD ID=2 CODE=1

ROUTE RESERVOIR ID=3 HYD NO=300.00 INFLOW ID=1 CODE=5

> OUTFLOW (CFS) STORAGE (AC-FT) ELEVATION (FT)

0.0 0.0 0.0 6.05 0.0880 2.04

PRINT HYD ID=3 CODE=1

**** FINISH

AHYMO PROGRAM (AHYMO194) - AMAFCA Hydrologic Model - January, 1994 RUN DATE (MON/DAY/YR) = 02/01/2000START TIME (HR:MIN:SEC) = 10:00:46USER NO. = M GOODWN. 101 INPUT FILE = massey4.dat START TIME=0.0**** MASSEY WAREHOUSE **** FILE: c:\AHYMO\MASSEY4.DAT JANUARY 2000 BY:AMY * * * * * 100-YEAR 6-HOUR STORM EVENT **** **** RAINFALL TYPE=1 RAIN QUARTER=0.0 IN RAIN ONE=2.05 IN RAIN SIX=2.40 IN RAIN DAY=2.7 IN DT=0.033333 HR COMPUTED 6-HOUR RAINFALL DISTRIBUTION BASED ON NOAA ATLAS 2 - PEAK AT 1.40 HR. .033333 HOURS DT =5.999940 HOURS END TIME =.0000 .0017 .0034 .0051 .0069 .0087 .0106 .0145 .0125 .0165 .0185 .0206 .0228 .0250 .0273 .0297 .0321 .0346 .0372 .0399 .0427 .0485 .0455 .0517 .0549 .0583 .0618 .0656 .0736 .0695 .0780 .0837 .0897 .1101 .0962 .1892 .1413 .2580 .3520 .4755 .8289 .6329 1.0681 1.2893 1.3819 1.4601 1.5297 1.5929 1.6512 1.7558 1.7053 1.8032 1.8478 1.8898 1.9296 1.9672 2.0028 2.0366 2.0687 2.0991 2.1280 2.1346 2.1408 2.1467 2.1523 2.1576 2.1628 2.1677 2.1724 2.1770 2.1814 2.1857 2.1898 2.1938 2.1977 2.2052 2.2015 2.2088 2.2123 2.2157 2.2190 2.2223 2.2254 2.2286 2.2316 2.2346 2.2375 2.2404 2.2432 2.2460 2.2487 2.2514 2.2540 2.2566 2.2591 2.2616 2.2641 2.2665 2.2689 2.2712 2.2736 2.2758 2.2781 2.2803 2.2825 2.2847 2.2889 2.2868 2.2910 2.2931 2.2951 2.2971 2.2991 2.3011 2.3030 2.3049 2.3068 2.3087 2.3106 2.3160 2.3178 2.3142 2.3124 2.3196 2.3213 2.3231 2.3248 2.3265 2.3282 2.3299 2.3315 2.3331 2.3348 2.3364 2.3380 2.3396 2.3427 2.3411 2.3442 2.3458 2.3473 2.3488 2.3503 2.3518 2.3532 2.3547 2.3561 2.3590 2.3576 2.3604 2.3618 2.3632 2.3646 2.3660 2.3674 2.3687 2.3701 2.3714 2.3727 2.3741 2.3754 2.3767 2.3780 2.3793 2.3806 2.3818 2.3831 2.3843 2.3856 2.3868 2.3881 2.3893 2.3905 2.3917 2.3929 2.3941 2.3953 2.3965 2.3977 2.3988 2.4000 **** **** DEVELOPED CONDITIONS **** COMPUTE NM HYD ID=1 HYD NO=100.00 AREA=0.003317 SQ MI PER A=0.00 PER B=0.15 PER C=0.00 PER D=0.85 TP=0.1333 HR MASS RAINFALL=-1 K = .072649HR TP = .133300HR K/TP RATIO = .545000 SHAPE CONSTANT, N = 7.106420 UNIT PEAK = 11.131 CFS UNIT VOLUME = .9984 B = 526.28P60 = 2.0500.002819 SQ MI IA = .10000 INCHES INF = .04000 INCHES PER HOUR AREA =RUNOFF COMPUTED BY INITIAL ABSTRACTION/INFILTRATION NUMBER METHOD - DT = .033333 K = .132570HR TP = .133300HR K/TP RATIO = .994525 SHAPE CONSTANT, N = 3.549967 UNIT PEAK = 1.2092 CFS UNIT VOLUME = .9889 B = 323.96 P60 = 2.0500.000498 SQ MI IA = .50000 INCHES INF = 1.25000 INCHES PER HOURAREA =RUNOFF COMPUTED BY INITIAL ABSTRACTION/INFILTRATION NUMBER METHOD - DT = .033333 PRINT HYD ID=2 CODE=1 OUTFLOW HYDROGRAPH REACH .00 RUNOFF VOLUME = .00000 INCHES .0000 ACRE-FEET .00 CFS AT .000 HOURS BASIN AREA = PEAK DISCHARGE RATE = .0000 SQ. MI.

***** 10-YEAR, 6-HOUR STORM EVENT

TYPE=1 RAIN QUARTER=0.0 IN
RAIN ONE=1.37 IN RAIN SIX=1.60 IN
RAIN DAY=1.80 IN DT=0.033333 HR

```
COMPUTED 6-HOUR RAINFALL DISTRIBUTION BASED ON NOAA ATLAS 2 - PEAK AT 1.40 HR.
        .033333 HOURS
DT =
                            END TIME =
                                           5.999940 HOURS
   .0000
           .0011
                           .0033
                   .0022
                                   .0045
                                           .0056
                                                    .0068
           .0093
   .0081
                   .0106
                           .0120
                                   .0133
                                           .0147
                                                    .0162
   .0177
           .0192
                   .0208
                           .0224
                                   .0241
                                                    .0276
                                           .0258
   .0295
           .0314
                   .0334
                           .0355
                                   .0377
                                                    .0424
                                           .0400
           .0476
   .0450
                   .0505
                           .0543
                                   .0583
                                           .0626
                                                    .0720
   .0928
           .1248
                   .1708
                           .2336
                                   .3161
                                           .4213
                                                    .5523
   .7121
           .8600
                   .9219
                           .9741
                                  1.0206
                                          1.0629
                                                  1.1018
  1.1380
          1.1717
                  1.2034
                          1.2332
                                  1.2613
                                          1.2879
                                                  1.3130
  1.3368
          1.3594
                  1.3808
                          1.4011
                                  1.4205
                                          1.4248
                                                  1.4290
  1.4329
          1.4366
                  1.4401
                          1.4435
                                  1.4468
                                          1.4499
                                                  1.4530
          1.4587
                 1.4614
  1.4559
                          1.4641
                                  1.4667
                                          1.4692
                                                  1.4716
  1.4740
         1.4763 1.4785 1.4807
                                  1.4829
                                         1.4850
  1.4891
         1.4910
                  1.4930 1.4949
                                  1.4967
                                          1.4986 1.5004
                 1.5056 1.5072
  1.5021
         1.5039
                                  1.5089
                                          1.5105
                                                 1.5121
  1.5137
          1.5152
                 1.5168
                         1.5183
                                  1.5198
                                          1.5212
                                                  1.5227
  1.5241
         1.5255
                 1.5269 1.5283
                                  1.5296
                                          1.5310
                                                 1.5323
  1.5336
         1.5349
                 1.5362 1.5375
                                  1.5387
                                          1.5399
                                                  1.5412
         1.5436 1.5448 1.5459
  1.5424
                                  1.5471
                                          1.5483
                                                 1.5494
  1.5505
                  1.5528
          1.5517
                         1.5539
                                  1.5549
                                          1.5560
                                                 1.5571
  1.5582
         1.5592
                 1.5602 1.5613
                                  1.5623
                                          1.5633
                                                 1.5643
  1.5653
          1.5663
                  1.5673
                         1.5683
                                  1.5693
                                          1.5702
                                                 1.5712
          1.5731
  1.5721
                 1.5740 1.5749
                                  1.5758
                                          1.5767
                                                 1.5776
  1.5785
          1.5794
                  1.5803
                         1.5812
                                  1.5821
                                          1.5830
                                                  1.5838
  1.5847
          1.5855
                  1.5864 1.5872
                                  1.5881
                                          1.5889 1.5897
  1.5905
          1.5913
                  1.5922 1.5930
                                  1.5938
                                          1.5946 1.5953
  1.5961
         1.5969 1.5977 1.5985
                                  1.5992 1.6000
```

**** DEVELOPED CONDITIONS

COMPUTE NM HYD ID=2 HYD NO=200.00 AREA=0.003317 SQ MI PER A=0.00 PER B=0.15 PER C=0.00 PER D=0.85 TP=0.1333 HR MASS RAINFALL=-1

.072649HR K =TP =.133300HR K/TP RATIO = .545000SHAPE CONSTANT, N = 7.10642011.131 UNIT PEAK = CFS UNIT VOLUME = .9984 B =526.28 P60 = 1.3700.002819 SQ MI IA = .10000 INCHES INF = .04000 INCHES PER HOURAREA =RUNOFF COMPUTED BY INITIAL ABSTRACTION/INFILTRATION NUMBER METHOD - DT = .033333

K = .139790HR TP = .133300HR K/TP RATIO = 1.048685 SHAPE CONSTANT, N = 3.366619 UNIT PEAK = 1.1588 CFS UNIT VOLUME = .9883 B = 310.46 P60 = 1.3700 AREA = .000498 SQ MI IA = .50000 INCHES INF = 1.25000 INCHES PER PE

PRINT HYD

ID=2 CODE=1

PARTIAL HYDROGRAPH 200.00

RUNOFF VOLUME = 1.20693 INCHES = .2135 ACRE-FEET

PEAK DISCHARGE RATE = 6.05 CFS AT 1.500 HOURS BASIN AREA = .0033 SQ. MI.

ROUTE RESERVOIR ID=3 HYD NO=300

ID=3 HYD NO=300.00 INFLOW ID=1 CODE=5
OUTFLOW(CFS) STORAGE(AC-FT) ELEVATION(FT)
0.0 0.0 0.0
6.05 0.0880 2.04

* * * * * * * * * * * * *

TIME (HRS)	INFLOW (CFS)	ELEV (FEET)	VOLUME (AC-FT)	OUTFLOW (CFS)
.00	.00	.00	.000	.00
.17	.00	.00	.000	.00
.33	.00	.00	.000	.00

```
.50
                  .00
                            .00
                                       .000
                                                   .00
     .67
                  .00
                             .00
                                       .000
                                                   .00
     .83
                  .00
                             .00
                                       .000
                                                   .00
    1.00
                  .00
                                       .000
                             .00
                                                   .00
                  .04
    1.17
                            .00
                                       .000
                                                   .00
                2.72
    1.33
                             .25
                                       .011
                                                   .74
    1.50
                9.42
                           1.49
                                       .064
                                                  4.41
    1.67
                4.81
                           1.98
                                                  5.88
                                       .085
    1.83
                3.08
                           1.53
                                                  4.52
                                       .066
    2.00
                2.23
                           1.12
                                                  3.32
                                       .048
    2.17
                1.02
                                                  2.27
                                       .033
                            .77
    2.33
                  .48
                            .43
                                       .019
                                                  1.27
    2.50
                  .30
                                                   .72
                            .24
                                       .010
    2.67
                  .20
                                       .006
                                                   .43
                            .14
    2.83
                                       .004
                                                   .26
                  .14
                             .09
    3.00
                  .10
                             .06
                                       .003
                                                   .17
    3.17
                            .04
                  .08
                                       .002
    3.33
                  .07
                             .03
                                       .001
                                                   .09
    3.50
                  .06
                             .03
                                       .001
                                                   .08
    3.67
                  .06
                             .02
                                                   .07
                                       .001
    3.83
                  .06
                             .02
                                                   .06
                                       .001
                  .05
    4.00
                             .02
                                       .001
                                                   .06
    4.17
                  .05
                             .02
                                       .001
                                                   .05
                             .02
    4.33
                  .05
                                                   .05
                                       .001
    4.50
                  .05
                             .02
                                                   .05
                                       .001
    4.67
                  .05
                                       .001
                             .02
                                                   .05
    4.83
                  .05
                             .02
                                       .001
                                                   .05
    5.00
                  .05
                             .02
                                                   .05
                                        .001
    5.17
                             .02
                                                   .05
                  .05
                                        .001
    5.33
                             .02
                  .05
                                                   .05
                                        .001
    5.50
                  .06
                             .02
                                                   .05
                                       .001
    5.67
                  .06
                             .02
                                        .001
                                                   .06
    5.83
                            .02
                  .06
                                                   .06
                                       .001
    6.00
                  .06
                             .02
                                                   .06
                                       .001
    6.17
                            .02
                  .02
                                       .001
                                                   .05
                                       .000
    6.33
                  .01
                            .01
                                                   .03
    6.50
                  .00
                             .00
                                       .000
                                                   .01
    6.67
                  .00
                            .00
                                       .000
                                                   .01
    6.83
                  .00
                            .00
                                       .000
                                                   .00
PEAK DISCHARGE =
                          6.024 CFS - PEAK OCCURS AT HOUR
                                                                1.63
MAXIMUM WATER SURFACE ELEVATION =
                                            2.031
MAXIMUM STORAGE ==
                            .0876 AC-FT
                                               INCREMENTAL TIME=
                                                                       .033333HRS
```

PRINT HYD ID=3 CODE=1

HYDROGRAPH FROM AREA 300.00

RUNOFF VOLUME = 1.96214 INCHES = .3471 ACRE-FEET PEAK DISCHARGE RATE = 6.02 CFS AT 1.633 HOURS BASIN AREA = .0033 SQ. MI.

**** FINISH

NORMAL PROGRAM FINISH END TIME (HR:MIN:SEC) = 10:00:47