

CITY OF ALBUQUERQUE

PLANNING DEPARTMENT – Development Review Services



March 20, 2015

David Soule, P.E.
Rio Grande Engineering
P.O. Box 93924
Albuquerque, NM 87199

Richard J. Berry, Mayor

RE: American Toyota (File: C18D012)
Drainage Report, Engineer's Stamp Date 3-16-15
Grading and Drainage Plan, Engineer's Stamp Date 3-17-15

Dear Mr. Soule:

Based upon the information provided in your submittal received 3-18-15, the above referenced submittal is approved for action by the DRB on the Site Plan for for Building Permit with the following condition(s):


1. The proposed runoff to the Alameda Storm Drain is limited to 25 cfs. This is based on trying to reconcile the difference between the existing runoff of 33 cfs and the allowed runoff of 16 cfs from SAD #201(though this site is not a part of the hydrology report).
2. The "first flush" needs to be captured at Outfalls 2,3, and 4.
3. Details showing how the "first flush" mechanism will work need to be shown prior to approval for Building Permit.

If you have any questions, you can contact me at 924-3695.

Sincerely,

Rita Harmon, P.E.
Senior Engineer, Planning Dept.
Development Review Services

Orig: Drainage file
c.pdf: via Email: Recipient, Monica Ortiz



City of Albuquerque

Planning Department

Development & Building Services Division

DRAINAGE AND TRANSPORTATION INFORMATION SHEET

(REV 02/2013)

Project Title: American Toyota Building Permit #: _____ City Drainage #: C18d012
DRB#: _____ EPC#: _____ Work Order#: _____
Legal Description: Tracts A1 and B-1, American Toyota and lots 15-18 tract a unit b NAA
City Address: 5995 Alameda NE

Engineering Firm: RIO GRANDE ENGINEERING Contact: DAVID SOULE
Address: PO BOX 93924, ALBUQUERQUE, NM 87199
Phone#: 505.321.9099 Fax#: 505.872.0999 E-mail: DAVID@RIOGRANDEENGINEERING.COM

Owner: milller family group Contact: _____
Address: _____
Phone#: _____ Fax#: _____ E-mail: _____

Architect: john mahony Contact: _____
Address: _____
Phone#: _____ Fax#: _____ E-mail: _____

Surveyor: CONSTRUCTION SURVEY INCORPORATED Contact: JOHN GALLEGOS
Address: _____
Phone#: 917.8921 Fax#: _____ E-mail: _____

Contractor: _____ Contact: _____
Address: _____
Phone#: _____ Fax#: _____ E-mail: _____

TYPE OF SUBMITTAL:

☐ DRAINAGE REPORT
☐ DRAINAGE PLAN 1st SUBMITTAL
☒ DRAINAGE PLAN RESUBMITTAL
☐ CONCEPTUAL G & D PLAN
☐ GRADING PLAN
☐ EROSION & SEDIMENT CONTROL PLAN (ESC)
☐ ENGINEER'S CERT (HYDROLOGY)
☐ CLOMR/LOMR
☐ TRAFFIC CIRCULATION LAYOUT (TCL)
☐ ENGINEER'S CERT (TCL)
☐ ENGINEER'S CERT (DRB SITE PLAN)
☐ ENGINEER'S CERT (ESC)
☐ SO-19
☐ OTHER (SPECIFY) _____

CHECK TYPE OF APPROVAL/ACCEPTANCE SOUGHT:

☐ SIA/FINANCIAL GUARANTEE RELEASE
☐ PRELIMINARY PLAT APPROVAL
☐ S. DEV. PLAN FOR SUB'D APPROVAL
☒ S. DEV. FOR BLDG. PERMIT APPROVAL
☐ SECTOR PLAN APPROVAL
☐ FINAL PLAT APPROVAL
☐ CERTIFICATE OF OCCUPANCY (PERM)
☐ CERTIFICATE OF OCCUPANCY (TCL TEMP)
☐ FOUNDATION PERMIT APPROVAL
☒ BUILDING PERMIT APPROVAL
☒ GRADING PERMIT APPROVAL ☐ SO-19 APPROVAL
☐ PAVING PERMIT APPROVAL ☐ ESC PERMIT APPROVAL
☐ WORK ORDER APPROVAL ☐ ESC CERT. ACCEPTANCE
☐ GRADING CERTIFICATION ☐ OTHER (SPECIFY) _____

WAS A PRE-DESIGN CONFERENCE ATTENDED: _____ Yes ☒ No _____ Copy Provided _____

DATE SUBMITTED: 3/17/15 By: _____

Requests for approvals of Site Development Plans and/or Subdivision Plats shall be accompanied by a drainage submittal. The particular nature, location, and scope to the proposed development defines the degree of drainage detail. One or more of the following levels of submittal may be required based on the following:

1. **Conceptual Grading and Drainage Plan:** Required for approval of Site Development Plans greater than five (5) acres and Sector Plans
2. **Drainage Plans:** Required for building permits, grading permits, paving permits and site plans less than five (5) acres
3. **Drainage Report:** Required for subdivision containing more than ten (10) lots or constituting five (5) acres or more
4. **Erosion and Sediment Control Plan:** Required for any new development and redevelopment site with 1-acre or more of land disturbing area, including project less than 1-acre than are part of a larger common plan of development

REVISED
DRAINAGE REPORT


For

AMERICAN TOYOTA EXPANSION
Albuquerque, New Mexico

Prepared by

Rio Grande Engineering
PO Box 93924
Albuquerque, New Mexico 87199

MARCH 2015



David Soule P.E. No. 14522

TABLE OF CONTENTS

Purpose	3
Introduction.....	3
Existing Conditions.....	4
Exhibit A-Vicinity Map	5
Proposed Conditions	6
Summary	7

Appendix

Excerpt from original drainage report.....	A
NAADMP Excerpts and Map.....	B
EXISTING BASIN MAP.....	C
PROPOSED BASIN MAP	D
Pond Routing and AHYMO	E
Site Hydrology	F
Stormtech Details	G

Map

Site Grading and Drainage Plan

PURPOSE


The purpose of this report is to provide the Drainage Management Plan for the development of a 10acre parcel located at 5995 alameda. This plan was prepared in accordance with the City of Albuquerque design regulations, utilizing the City of Albuquerque's Development Process Manual drainage guidelines. This report will demonstrate that the grading does not adversely affect the surrounding properties, nor the upstream or downstream facilities.

INTRODUCTION

The subject of this report, as shown on the Exhibit A, is a 10-acre parcel of land located on the west side of San Pedro between Alameda and Eagle rock. The legal description of this site is Lots A and B land of American Toyota and lots 15-18, tract A, unit B North Albuquerque Aces. As shown on FIRM map35013C0137H, the majority of the site is located within Flood Zone X; a portion of the site is impacted by flood zone AO-1 foot. The site has had significant grading activities upon it over the past 10 years. The site is not in native condition and is currently developed. Due to the upstream construction of san Pedro, the site is not affected by any upland flow. The site free discharges to the west. The development of the site will require the site to discharge at a rate equal to or less than the fully developed conditions assumed for this site in the governing North Albuquerque Acres Master Drainage Plan (NAAMDP), which relevant excerpts can be found in appendix B.

EXISTING CONDITIONS


The site currently does have structures on it and has been impacted by human development over the years. The site is currently used as a car dealership and sales lot. The site was developed utilizing the approved drainage report in file C18d12, of which excerpts are found in appendix A. The file is old and significant portions were not found. The site is not impacted by any upland flows. As shown in appendix C, The site currently contains 4 basins. The three southern basins discharge to Alameda and existing storm drain in Alameda. The fourth basin discharges to the Eagle Rock Storm drain. As shown in appendix C, Basin Alameda B discharge 11.39 cfs to the Alameda roadway via surface flow thru the driveway. Basin Alameda A-1 discharges 7.78 cfs to the Alameda storm drain via a 12" RCP conduit, and Alameda A-2 discharges 13.87 cfs to an 24" storm drain that runs within the frontage road connecting to the Alameda storm drain. Basins Eagle C, the north portion of the site currently drains 13.20 cfs to a series of inlets which are connected to the Eagle rock storm drain. The adjacent site grading plan showed the inlets are designed for free discharge of the entire basin, which is significantly reduced due to the completion of San Mateo.



AGIS

Albuquerque Geographic Information System

Map amended through: 2/4/2010




**Note: Grey Shading
Represents Area Outside
of the City Limits**

Zone Atlas Page:

C-18-Z

Selected Symbols

- SECTOR PLANS**
- | | | | |
|---|----------------------|---|------------------------|
|  | Design Overlay Zones |  | Escarpment |
|  | City Historic Zones |  | 2 Mile Airport Zone |
|  | H-1 Buffer Zone |  | Airport Noise Contours |
|  | Petroglyph Mon. |  | Wall Overlay Zone |



PROPOSED CONDITIONS

The proposed improvements consist of demolishing the existing building and constructing a new 75,000 building. The general drainage patterns will remain, and increases in flows will be captured and harvested in accordance with new city policy. The amount of storage required was calculated by determining the allowed discharge rates for each identified basin within the North Albuquerque Acres Master drainage plan. Appendix B includes the developed conditions map of the NAA Drainage master plan and a map of the site with the allowed peak discharge rates allowed with the proposed land treatment assumptions of the NAADMP. The site is allowed to discharge 36.93 cfs to Alameda and 6.69 cfs to Eagle Rock. Based upon comments by the city and NMDOT, the plan will maintain the existing discharge points, reduce the flows to less than existing and less than allowed and capture the water generated from the activities associated with the use of the building as a vehicle service center. The proposed basin map shown in appendix D shows the basins captured by the underground catchment basins. Basin C2 Generates 6.03 cfs and 14,476 cubic feet of water during the 100-year, 10-day event. The entire basin is captured by infiltrator system 1. Basin B2 generates 3.26 and 9,154 cubic feet of water during the 100-year, 10-day event. Basin A2 generates 2.09 and 5,984 cubic feet of water during the 100-year, 10-day event. Each of these basins is retained onsite. The inlets act as emergency overflows. The remaining basins with the exception of C1 free discharge to the historical discharge points at rates less than existing and allowed. Basin C1 generates less than existing rates but 2.45 cfs greater than allowed, therefore the flow is throttled by the construction of a detention area located in the parking lot. The discharge rate is controlled by an 8" weir in the header curb. As shown in Appendix E, this pond was modeled using AYHMO and the resultant peak discharge is 6.5 cfs which is less than allowed. All proposed basins discharge water to existing discharge points at less than existing rates and less than the rates allowed in the NAADMP. A portion of the east driveway does enter the San Pedro right of way at a rate of .67 cfs. This is collected by the san

Pedro storm drain; near the bottom of the system therefore will not have an effect the drainage system.

The surrounding existing fully developed infrastructure was designed based upon the fully developed assumptions of the NAADMP. This site was designed to conform to the design assumptions within the plan. At all discharge points the discharge rates are less than allowed. Appendix F demonstrates all the inlets, pipes and rundowns have been sized to accommodate the 100-year design storms. In the event of clogging or rain events greater than the 100-year event the flows will overflow to the existing historical paths. The water retained onsite exceeds the volume required in a 100-year, 10-day storm. The retention basins were placed to capture the entire flow from the work areas of the buildings to eliminate nuisance flow that the NMDOT requested. No offsite improvements will be constructed.

SUMMARY AND RECOMMENDATIONS

This project is a redevelopment of an existing site. The development discharge will be consistent with and in all cases less than the land use assumptions of the North Albuquerque Acres Master drainage plan. The use of underground infiltration will be used to collect the excess discharge and the water quality volume required. The site has been designed in accordance with City of Albuquerque Drainage ordinance. This drainage plan and report conforms to the governing drainage regulations of the City. Since the effected area site encompasses more than 1 acre, a NPDES permit will be required prior to any construction activity. A letter of Map revision (LOMR) has been submitted to remove the floodplain. No insurable structures are located within the FEMA flood plain. Due to grading work in the area of the flood plain being removed a flood plain permit will be required.

Excerpts of Original drainage report

APPENDIX A

44-22-4



September, 1994

Robert Engstrom, Jr.
4425 Van Ness N. E. Suite 202
Albuquerque, New Mexico 87112

Forward by:

AMERICAN TOYOTA TRACT B
GRADING AND DRAINAGE PLAN

0000 0000 0000 1995

REALLY VIOLENT BORN



TO INTERSTATE 25

$\Delta = 89.43^\circ$
 $R = 25.00'$
 $L = 25.40'$
 $T = 12.95'$

TC 0+49.7


TC 0+49.7


FF @ 5221.00


FF @ 5209.00

SEE SHEET 2

CRUST. SURFACE
IN 1/4" VERTICAL
SCALE







Project Engineer

[Signature]

The above is a true and correct copy of the original as shown to me by the Project Engineer on the date of the above.

12 FEB 1961

Project Engineer

Project Engineer



Project Engineer

STATE HIGHWAY DEPARTMENT



NEWARK, N.J.

APPENDIX B
NAADMP EXCERPTS

CAUTION:
EXISTING UTILITIES ARE NOT SHOWN.
IT SHALL BE THE SOLE RESPONSIBILITY
OF THE CONTRACTOR TO CONDUCT ALL
NECESSARY FIELD INVESTIGATIONS PRIOR
TO ANY EXCAVATION TO DETERMINE THE
ACTUAL LOCATION OF UTILITIES & OTHER
IMPROVEMENTS.

EROSION CONTROL NOTES:

1. CONTRACTOR IS RESPONSIBLE FOR OBTAINING A TOPSOIL DISTURBANCE PERMIT PRIOR TO BEGINNING WORK.
2. CONTRACTOR IS RESPONSIBLE FOR MAINTAINING RUN-OFF ON SITE DURING CONSTRUCTION.
3. CONTRACTOR IS RESPONSIBLE FOR CLEANING ALL SEDIMENT THAT GETS INTO EXISTING RIGHT-OF-WAY.
4. REPAIR OF DAMAGED FACILITIES AND CLEANUP OF SEDIMENT ACCUMULATIONS ON ADJACENT PROPERTIES AND IN PUBLIC FACILITIES IS THE RESPONSIBILITY OF THE CONTRACTOR.
5. ALL EXPOSED EARTH SURFACES MUST BE PROTECTED FROM WIND AND WATER EROSION PRIOR TO FINAL ACCEPTANCE OF ANY PROJECT.



LEGAL DESCRIPTION:

NOTES:

1. ALL SPOT ELEVATIONS REPRESENT FLOWLINE ELEVATION UNLESS OTHERWISE NOTED.
2. ALL CURBS AND GUTTER TO 6" HEADER UNLESS OTHERWISE NOTED.
3. ALL RETAINING WALL DESIGN SHALL BE BY OTHERS.
4. ALL LANDSCAPE MEDIANE WILL BE DERESSED 6" FROM FLOW LINE AND 1' CURB OPENING PROVIDED ON THE HIGH SIDE, FOR WATER QUALITY.

LEGEND

---	EXISTING CONTOUR
---	EXISTING INDEX CONTOUR
---	PROPOSED CONTOUR
---	PROPOSED INDEX CONTOUR
---	SLOPE 1% S 548.25 X 4048.25
---	EXISTING SPOT ELEVATION
---	PROPOSED SPOT ELEVATION
---	BOUNDARY
---	CENTERLINE
---	RIGHT-OF-WAY
---	PROPOSED CURB AND GUTTER
---	EXISTING CURB AND GUTTER
---	PROPOSED SIDEWALK
---	PROPOSED SETBACK
---	PROPOSED LOT LINE
---	PROPOSED SCREEN WALL
---	PROPOSED RETAINING WALL
---	LIMITS OF FLOODPLAIN

ROUGH GRADING APPROVAL _____ DATE _____

ENGINEER'S SEAL	AMERICAN TOYOTA	DRAWN BY HCUH
		DATE 3-17-15
DAVID SCALE P.E. #14322	GRADING AND DRAINAGE PLAN	PROJECT NUMBER 15-00-14
	<i>Flo Grande Engineering</i> 1100 GARDEN AVENUE N.E. SUITE 200 ALBUQUERQUE, NM 87105 (505) 875-0875	SHEET # 21403



FINAL NORTH ALBUQUERQUE ACRES MASTER DRAINAGE PLAN

Prepared For:



City of Albuquerque

Prepared By:



ENGINEERS AND ENVIRONMENTAL SCIENTISTS
1720-B Randolph Road SE, Albuquerque, NM 87106
Telephone (505) 243-7300
Fax (505) 243-7400
rti@nmia.com

October 1998




TABLE A-2 (cont.)

LA CUEVA ARROYO SUB-BASIN CHARACTERISTICS

Basin ID	Hydrologic Condition	Basin Area (mi ²)	Land Treatment (%)				TP (hrs)
			A	B	C	D	
113*	Existing	.1136	80	0	15	5	.133
	Future	.1000	0	25	15	60	.133
115*	Existing	.1337	80	0	15	5	.133
	Future	.1202	0	26	12	62	.133
116*	Existing	.1309	80	0	5	15	.133
116.1	Future	.1000	0	25	15	50	.133
116.2	Future	.0719	0	25	15	60	.133
116.21	Future	.0344	0	40	20	40	.133
117.2*	Existing	.1391	73	0	7	20	.22
	Future	.0500	0	34	16	50	.133
117.21*	Existing	.0234	0	34	16	50	.133
117.22*	Future	.0156	0	20	10	70	.133
117.3*	Existing	.0863	65	5	15	15	.133
	Future	.1172	0	34	16	50	.133
117.31*	Existing	.0250	0	34	16	50	.133
117.32*	Existing	.0090	0	34	16	50	.133
117.4*	Existing	.0750	85	0	5	10	.133
	Future	.0512	0	25	15	60	.133
117.41*	Existing	.0550	0	10	20	70	.133
	Future	.0440	0	10	20	70	.133
118	Existing	.0649	0	20	10	70	.133
	Future	.0649	0	20	10	70	.133
118.1	Existing	.0306	75	5	10	10	.133
	Future	.0306	0	20	30	50	.133
119	Existing	.0549	0	20	10	70	.133
	Future	.0549	0	20	10	70	.133
120	Existing	.0268	50	0	0	50	.133
	Future	.0268	0	20	10	70	.133
121	Existing	.0489	80	0	15	5	.133
	Future	.0489	0	20	10	70	.133

*Modified for COA NAA MDP 9/97

A:\97-0809\MASTER.PLN

Weighted E Method

AMERICAN TOYOTA

NAAMDP Developed Basins

Basin	Area (sf)	Area (acres)	Treatment A		Treatment B		Treatment C		Treatment D		100-Year, 6-hr.			10-day
											Weighted E (ac-ft)	Volume (ac-ft)	Flow cfs	Volume (ac-ft)
			%	(acres)	%	(acres)	%	(acres)	%	(acres)				
EAGLEROCK(117.22)	66508	1.527	0%	0	20.0%	0.305	10.0%	0.15268	70%	1.069	1.965	0.250	6.69	0.393
ALAMEDA (117.5)	367341	8.433	0%	0	20.0%	1.687	10.0%	0.8433	70%	5.903	1.965	1.381	36.93	2.168

Equations:

Weighted E = $E_a \cdot A_a + E_b \cdot A_b + E_c \cdot A_c + E_d \cdot A_d$ / (Total Area)

Volume = Weighted D * Total Area

Flow = $Q_a \cdot A_a + Q_b \cdot A_b + Q_c \cdot A_c + Q_d \cdot A_d$

Where for 100-year, 6-hour storm (zone 3)

$E_a = 0.66$
 $E_b = 0.92$
 $E_c = 1.29$
 $E_d = 2.36$

$Q_a = 1.87$
 $Q_b = 2.6$
 $Q_c = 3.45$
 $Q_d = 5.02$

APPENDIX C
EXISTING HYDROLOGY

DISCHARGES TO
STORM DRAIN IN
EAGLE ROCK

LOT 14-A, BLOCK 10
TRACT A, UNIT B
NORTH ALBUQUERQUE ACRES
PL. 5/13/2004
BC. 2004C, PS. 101
OWNER: OMEGA AUTOMOTIVE
REAL ESTATE LTD

BASIN EAGLE

BASIN EAGLE

135,754 SF
Q=13.20 CFS

LOT 21-A, BLOCK 10
TRACT A, UNIT B
NORTH ALBUQUERQUE ACRES
PL. 5/13/2004
BC. 2004C, PS. 101
OWNER: OMEGA AUTOMOTIVE
REAL ESTATE LTD

DISCHARGES TO
STORM DRAIN IN
NMDOT R.O.W

BASIN ALAMEDA A-2

125,135 SF
Q=13.87 CFS

PAN AMERICAN FREEWAY
INTERSTATE 25 FRONTAGE ROAD
PUBLIC R.O.W.
WITH VARIES

BASIN ALAMEDA

170,138 SF
Q=7.78 CFS

DISCHARGES TO
STORM DRAIN IN
ALAMEDA

BASIN ALAMEDA-B

102,720 SF
Q=11.39 CFS

DISCHARGES TO
STORM DRAIN IN
ALAMEDA

SAN PEDRO DRIVE N.E.
77' PUBLIC R.O.W.

Weighted E Method

AMERICAN TOYOTA

EXISTING Developed Basins

Basin	Area (sf)	Area (acres)	Treatment A		Treatment B		Treatment C		Treatment D		100-Year, 6-hr.			10-day
			%	(acres)	%	(acres)	%	(acres)	%	(acres)	Weighted E (ac-ft)	Volume (ac-ft)	Flow cfs	Volume (ac-ft)
BASIN C- EAGLE	135754	3.116	0%	0	0.0%	0.000	50.0%	1.55824	50%	1.558	1.825	0.474	13.20	0.682
BASIN ALAMEDA B	102720	2.358	0%	0	4.0%	0.094	6.0%	0.14149	90%	2.122	2.238	0.440	11.39	0.723
BASIN ALAMEDA A1	70138	1.610	0%	0	4.0%	0.064	6.0%	0.09661	90%	1.449	2.238	0.300	7.78	0.494
BASIN ALAMEDA A2	125135	2.873	0%	0	4.0%	0.115	6.0%	0.17236	90%	2.585	2.238	0.536	13.87	0.881
WATER QUALITY	433747	9.957461												

Equations:

Weighted E = $E_a \cdot A_a + E_b \cdot A_b + E_c \cdot A_c + E_d \cdot A_d / (\text{Total Area})$

Volume = Weighted D * Total Area

Flow = $Q_a \cdot A_a + Q_b \cdot A_b + Q_c \cdot A_c + Q_d \cdot A_d$

Where for 100-year, 6-hour storm (zone 3)

$E_a = 0.66$

$E_b = 0.92$

$E_c = 1.29$

$E_d = 2.36$

$Q_a = 1.87$

$Q_b = 2.6$

$Q_c = 3.45$

$Q_d = 5.02$

APPENDIX D
PROPOSED HYDROLOGY

CAUTION:

EXISTING UTILITIES ARE NOT SHOWN.
IT SHALL BE THE SOLE RESPONSIBILITY
OF THE CONTRACTOR TO CONDUCT ALL
NECESSARY FIELD INVESTIGATIONS PRIOR
TO ANY EXCAVATION TO DETERMINE THE
ACTUAL LOCATION OF UTILITIES & OTHER
IMPROVEMENTS.

EROSION CONTROL NOTES:

1. CONTRACTOR IS RESPONSIBLE FOR OBTAINING A TOPSOIL DISTURBANCE PERMIT PRIOR TO BEGINNING WORK.
2. CONTRACTOR IS RESPONSIBLE FOR MAINTAINING RUN-OFF ON SITE DURING CONSTRUCTION.
3. CONTRACTOR IS RESPONSIBLE FOR CLEANING ALL SEDIMENT THAT GETS INTO EXISTING RIGHT-OF-WAY.
4. REPAIR OF DAMAGED FACILITIES AND CLEANUP OF SEDIMENT ACCUMULATIONS ON ADJACENT PROPERTIES AND IN PUBLIC FACILITIES IS THE RESPONSIBILITY OF THE CONTRACTOR.
5. ALL EXPOSED EARTH SURFACES MUST BE PROTECTED FROM WIND AND WATER EROSION PRIOR TO FINAL ACCEPTANCE OF ANY PROJECT.

EAGLE ROCK BASIN
EXISTING DISCHARGE=13.20 CFS
ALLOWED DISCHARGE=6.89 CFS
PROPOSED DISCHARGE=6.50 CFS

EXISTING OUTFALL-4
EXISTING INLET
EXISTING DISCHARGE=13.20 CFS
ALLOWED DISCHARGE=6.89 CFS
PROPOSED DISCHARGE=6.50 CFS

1" W/ER OPENING IN CURB
RW=5213.00
TOP=5215.75

LOT 14-A, BLOCK 10
NORTH ALAMEDA ACRES
P.L. 8/12/2004
CHERRY, JENNIFER
REAL ESTATE LTD

INSTALL STORMWATER
CHAMBER - SEE SHEET
FOR SPECIFICATIONS
REQ URED VOLUME=14500 CU. FT.

LOT 31-A, BLOCK 10
NORTH ALAMEDA ACRES
P.L. 8/12/2004
CHERRY, JENNIFER
REAL ESTATE LTD

1-TYPE C INLET
GRATE=5225.10
RW=5221.00

BASIN B2-28708 CF
PEAK FLOW=3.28CFS
VOLUME RETAINED=6,154CF

INSTALL STORMWATER
CHAMBER - SEE SHEET
FOR SPECIFICATIONS
VOLUME=9200 CU. FT.

BUILD 1-TYPE C SD MH
RW=5209.30
RW=5205.75

BASIN B1-62204SF
PEAK DISCHARGE=7.23CFS

1-SINGLE D INLET
GRATE=5209.35
RW=5206.00

EXISTING OUTFALL-3
24" RCP@8%
EXISTING DISCHARGE=13.87CFS
PROPOSED DISCHARGE=7.23 CFS

BASIN F-43056F
PEAK DISCHARGE=0.48 CFS

BASIN D-62562SF
PEAK DISCHARGE=8.94CFS

EXISTING OUTFALL-2
12" RCP@8%
EXISTING DISCHARGE=7.78 CFS
PROPOSED DISCHARGE=6.94 CFS

ALAMEDA BASIN
EXISTING DISCHARGE=33.09CFS
(13.87+7.78+11.39)
ALLOWED DISCHARGE=36.93
PROPOSED DISCHARGE=26.61 CFS
(7.72+6.84+10.85)

BASIN E-27176SF
PEAK DISCHARGE=2.57 CFS

EXISTING OUTFALL-1
SURFACE FLOW
EXISTING DISCHARGE=11.39F6
PROPOSED DISCHARGE=10.29 CFS

EAGLE ROCK AVE. N.E.
R.F. PUBLIC WORKS (2004) 150'

1-SINGLE D INLET
FOR TANK OVERFLOW
GRATE=5223.80
RW=5223.33

BASIN C1-62431 SF
PEAK FLOW
GENERATED=9.14CFS
PEAK DISCHARGE
=6.50 CFS


BASIN C2-62431 CF
PEAK FLOW=9.03CFS
VOLUME RETAINED=14477CF

EXISTING OUTFALLS
SURFACE FLOW
EXISTING DISCHARGE=0 CFS
PROPOSED DISCHARGE=0.87 CFS

BASIN F-59608F
PEAK
DISCHARGE=6.57
CFS

BASIN A2-15,136 CF
PEAK FLOW=2.36CFS
VOLUME RETAINED=5984CF

BASIN A1-59,622SF
PEAK DISCHARGE=7.72 CFS



LEGAL DESCRIPTION:

NOTES:

1. ALL SPOT ELEVATIONS REPRESENT FLOWLINE ELEVATION UNLESS OTHERWISE NOTED.
2. ALL CURB AND OUTER TO 6" HEADER UNLESS OTHERWISE
3. ALL RETAINING WALL DESIGN SHALL BE BY OTHERS.
4. ALL LANDSCAPE MEDIAN SHALL BE DEEPENED 6" FROM FLOW LINE AND 1' CURB OPENING PROVIDED ON THE HIGH SIDE, FOR WATER QUALITY.


LEGEND

- - - - - EXISTING CONTOUR
- - - - - EXISTING INDEX CONTOUR
- - - - - PROPOSED CONTOUR
- - - - - PROPOSED INDEX CONTOUR
- 1" 5048.25
5
X 4048.25
- - - - - EXISTING SPOT ELEVATION
- - - - - PROPOSED SPOT ELEVATION
- - - - - BOUNDARY
- - - - - CENTERLINE
- - - - - RIGHT-OF-WAY
- - - - - PROPOSED CURB AND OUTER
- - - - - EXISTING CURB AND OUTER
- - - - - PROPOSED SIDEWALK
- - - - - PROPOSED SETBACK
- - - - - PROPOSED LOT LINE
- - - - - PROPOSED SCREEN WALL
- - - - - PROPOSED RETAINING WALL
- - - - - LIMITS OF FLOODPLAIN

ROUGH GRADING APPROVAL

DATE

ENGINEER'S SEAL	AMERICAN TOYOTA	DRAWN BY HOWU
		DATE
		3-17-15
	PROPOSED BASIN MAP	PHOTO-INTERPRETATION
		SHEET #
		JOB #
		21403



Rio Grande Engineering
1400 COLUMBIA AVENUE, SUITE 200
ALBUQUERQUE, NEW MEXICO 87102-3885
(505) 875-0885

Weighted E Method

AMERICAN TOYOTA

PROPOSED Developed Basins

Basin	Area (sf)	Area (acres)	Treatment A		Treatment B		Treatment C		Treatment D		100-Year, 6-hr.		10-day
			%	(acres)	%	(acres)	%	(acres)	%	(acres)	Weighted E (ac-ft)	Volume (ac-ft)	Flow cfs
BASIN A1	69602	1.598	0%	0	4.0%	0.064	6.0%	0.09587	90%	1.438	2.238	0.298	7.72
BASIN A2	18136	0.416	0%	0	0.0%	0.000	0.0%	0	100%	0.416	2.360	0.082	2.09
BASIN B1	65204	1.497	0%	0	4.0%	0.060	6.0%	0.08981	90%	1.347	2.238	0.279	7.23
BASIN B2	28708	0.659	0%	0	0.0%	0.000	5.0%	0.03295	95%	0.626	2.307	0.127	3.26
BASIN C1	82431	1.892	0%	0	4.0%	0.076	6.0%	0.11354	90%	1.703	2.238	0.353	9.14
BASIN C2	52325	1.201	0%	0	0.0%	0.000	0.0%	0	100%	1.201	2.360	0.236	6.03
BASIN D	62562	1.436	0%	0	4.0%	0.057	6.0%	0.08617	90%	1.293	2.238	0.268	6.94
BASIN E	27176	0.624	0%	0	10.0%	0.062	42.0%	0.26203	48%	0.299	1.767	0.092	2.57
BASIN F	6395	0.147	0%	0	0.0%	0.000	15.0%	0.02202	85%	0.125	1.235	0.015	0.49
BASIN G	5985	0.137	0%	0	0.0%	0.000	10.0%	0.01374	90%	0.124	2.253	0.026	0.67
WATER QUALITY	418524	9.608									10580 cf		

Equations:

Weighted E = $E_a \cdot A_a + E_b \cdot A_b + E_c \cdot A_c + E_d \cdot A_d$ / (Total Area)

Volume = Weighted D * Total Area

Flow = $Q_a \cdot A_a + Q_b \cdot A_b + Q_c \cdot A_c + Q_d \cdot A_d$

Where for 100-year, 6-hour storm (zone 3)

$E_a = 0.66$

$E_b = 0.92$

$E_c = 1.29$

$E_d = 2.36$

$Q_a = 1.87$

$Q_b = 2.6$

$Q_c = 3.45$

$Q_d = 5.02$

Weighted E Method

AMERICAN TOYOTA

OUTFALL #1

PROPOSED Developed Basins

Basin	Area (sf)	Area (acres)	Treatment A		Treatment B		Treatment C		Treatment D		100-Year, 6-hr.			10-DAY
			%	(acres)	%	(acres)	%	(acres)	%	(acres)	Weighted E (ac-ft)	Volume (ac-ft)	Flow cfs	Volume (ac-ft)
BASIN A1	69602	1.598	0%	0	4.0%	0.064	6.0%	0.09587	90%	1.438	2.238	0.298	7.72	0.490
BASIN A2	18136	0.416	0%	0	0.0%	0.000	0.0%	0	100%	0.416	2.360	0.082	2.09	0.137
BASIN E	27176	0.624	0%	0	0.0%	0.000	0.0%	0	100%	0.624	2.360	0.123	3.13	0.206
WATER QUALITY		2288.704									RESULTANT DISCHARGE			10.85 CFS
<u>Equations:</u>											EXISTING			11.39 CFS

Weighted E = $E_a \cdot A_a + E_b \cdot A_b + E_c \cdot A_c + E_d \cdot A_d / (\text{Total Area})$

Volume = Weighted D * Total Area

Flow = $Q_a \cdot A_a + Q_b \cdot A_b + Q_c \cdot A_c + Q_d \cdot A_d$

Where for 100-year, 6-hour storm (zone 3)

$E_a = 0.66$

$E_b = 0.92$

$E_c = 1.29$

$E_d = 2.36$

$Q_a = 1.87$

$Q_b = 2.6$

$Q_c = 3.45$

$Q_d = 5.02$

STORAGE PROVIDED

6000 CF

0.137741047

STORAGE REQUIRED

5984.88

FIRST FLUSH

2288.704

Weighted E Method

AMERICAN TOYOTA

OUTFALL#2

PROPOSED Developed Basins

Basin	Area (sf)	Area (acres)	Treatment A		Treatment B		Treatment C		Treatment D		100-Year, 6-hr.		10-day
			%	(acres)	%	(acres)	%	(acres)	%	(acres)	Weighted E (ac-ft)	Volume (ac-ft)	Flow cfs
BASIN D	62562	1.436	0%	0	4.0%	0.057	6.0%	0.08617	90%	1.293	2.238	0.268	6.94
													0.440

Equations:

Weighted E = $E_a \cdot A_a + E_b \cdot A_b + E_c \cdot A_c + E_d \cdot A_d / (\text{Total Area})$

Volume = Weighted D * Total Area

Flow = $Q_a \cdot A_a + Q_b \cdot A_b + Q_c \cdot A_c + Q_d \cdot A_d$

Where for 100-year, 6-hour storm (zone 3)

$E_a = 0.66$

$E_b = 0.92$

$E_c = 1.29$

$E_d = 2.36$

$Q_a = 1.87$

$Q_b = 2.6$

$Q_c = 3.45$

$Q_d = 5.02$

RESULTANT DISCHARGE 6.94 CFS
EXISTING 7.78 CFS

FIRST FLUSH 1591.668624

STORAGE 1800 0.04132231

Weighted E Method

AMERICAN TOYOTA
OUTFALL 3

PROPOSED Developed Basins

Basin	Area (sf)	Area (acres)	Treatment A		Treatment B		Treatment C		Treatment D		100-Year, 6-hr.			10-day
			%	(acres)	%	(acres)	%	(acres)	%	(acres)	Weighted E (ac-ft)	Volume (ac-ft)	Flow cfs	Volume (ac-ft)
BASIN B1	65204	1.497	0%	0	4.0%	0.060	6.0%	0.08981	90%	1.347	2.238	0.279	7.23	0.459
BASIN B2	28708	0.659	0%	0	0.0%	0.000	5.0%	0.03295	95%	0.626	2.307	0.127	3.26	0.210

Equations:

Weighted E = $E_a \cdot A_a + E_b \cdot A_b + E_c \cdot A_c + E_d \cdot A_d / (\text{Total Area})$

Volume = Weighted D * Total Area

Flow = $Q_a \cdot A_a + Q_b \cdot A_b + Q_c \cdot A_c + Q_d \cdot A_d$

Where for 100-year, 6-hour storm (zone 3)

$E_a = 0.66$
 $E_b = 0.92$
 $E_c = 1.29$
 $E_d = 2.36$

$Q_a = 1.87$
 $Q_b = 2.6$
 $Q_c = 3.45$
 $Q_d = 5.02$

RESULTANT DISCHARGE
EXISTING

7.23 CFS
13.87 CFS

STORAGE PROVIDED
STORAGE REQUIRED
FIRST FLUSH

9200 CF
9154.2635 CF
2435.42567 CF

Weighted E Method

AMERICAN TOYOTA

OUTFALL 4

PROPOSED Developed Basins

Basin	Area (sf)	Area (acres)	Treatment A		Treatment B		Treatment C		Treatment D		100-Year, 6-hr.		24 hour
			%	(acres)	%	(acres)	%	(acres)	%	(acres)	Weighted E (ac-ft)	Volume (ac-ft)	Flow cfs
BASIN C1	82431	1.892	0%	0	4.0%	0.076	6.0%	0.11354	90%	1.703	2.238	0.353	9.14
BASIN C2	52325	1.201	0%	0	0.0%	0.000	0.0%	0	100%	1.201	2.360	0.236	6.03

WATER QUALITY 2101.9905 1.8923554

Equations:

Weighted E = $E_a \cdot A_a + E_b \cdot A_b + E_c \cdot A_c + E_d \cdot A_d$ / (Total Area)

Volume = Weighted D * Total Area

Flow = $Q_a \cdot A_a + Q_b \cdot A_b + Q_c \cdot A_c + Q_d \cdot A_d$

Where for 100-year, 6-hour storm (zone 3)

$E_a = 0.66$

$E_b = 0.92$

$E_c = 1.29$

$E_d = 2.36$

$Q_a = 1.87$

$Q_b = 2.6$

$Q_c = 3.45$

$Q_d = 5.02$

DIRECT DISCHARGE 9.14 CFS
EXISTING 13.22 CFS
ALLOWED 6.69
ROUTED DISCHARGE 6.5

STORAGE PROVIDED 14583 cf
STORAGE REQUIRED 14476.5833 CF
FIRST FLUSH 3584.53217 CF

Weighted E Method

AMERICAN TOYOTA

OUTFALL 5

PROPOSED Developed Basins

Basin	Area (sf)	Area (acres)	Treatment A		Treatment B		Treatment C		Treatment D		100-Year, 6-hr.		24 hour
			%		%		%		%		Weighted E (ac-ft)	Volume (ac-ft)	Flow cfs
			(acres)	(acres)	(acres)	(acres)	(acres)	(acres)	(acres)	(acres)			
BASIN G	5985	0.137	0%	0	0.0%	0.000	10.0%	0.01374	90%	0.124	2.253	0.026	0.67

WATER QUALITY 152.6175 0.1373967

Equations:

DIRECT DIS' DISCHARGE 0.67 CFS

EXISTING 0.00 CFS

Weighted E = $E_a \cdot A_a + E_b \cdot A_b + E_c \cdot A_c + E_d \cdot A_d$ / (Total Area)

Volume = Weighted D * Total Area

Flow = $Q_a \cdot A_a + Q_b \cdot A_b + Q_c \cdot A_c + Q_d \cdot A_d$

Where for 100-year, 6-hour storm (zone 3)

$E_a = 0.66$

$Q_a = 1.87$

$E_b = 0.92$

$Q_b = 2.6$

$E_c = 1.29$

$Q_c = 3.45$

$E_d = 2.36$

$Q_d = 5.02$

APPENDIX E
POND ROUTING AND AHYMO

VOLUME CALCULATIONS

PARKING LOT POND

POND BOTTOM

ACTUAL ELEV.	DEPTH (FT)	AREA SF	VOLUME (AC-FT)	Q (CFS)
13	0	1		
13.5	0.5	1277	0.00733471	0.69879828
14.00	1.00	4995.00	0.0359965	1.9765
14.50	1.50	7174.0000	0.06984128	3.63106236
15.00	2.00	10384.0000	0.10077066	5.59038621
15.50	2.50	12600.0000	0.13191232	7.81280224

Orifice Equation

$$Q = CLH^{1.5}$$

C = 2.95
 L(F) 0.67
 H (Ft) = VARIES

EAGLEROCK OUTFALL.txt

*S AHYMO - NORTH TRAMWAY ESTATES
 *S POND ROUTING

START TIME=0.0 PUNCH CODE=0

RAINFALL TYPE=2
 QUARTER=0.0 ONE= 2.14 IN
 SIX= 2.60 IN DAY= 3.10 IN DT = 0.05 HR

COMPUTE NM HYD ID=1 HYD NO=101 DA= .00296 SQ MI
 PER A=00 PER B=4 PER C=6 PER D=90
 TP=-.177 MASSRAIN=-1

PRINT HYD ID=1 CODE=24

* ROUTE THE TOTAL FLOW THROUGH THE PROPOSED RESERVOIR
 ROUTE RESERVOIR ID=2 HYD NO=102 INFLOW=1 CODE=24

OUTFLOW(CFS)	STORAGE(AC-FT)	ELEV(FT)
0.01	0.001	13.00
0.69	0.007	13.50
1.98	0.036	14.00
3.63	0.069	14.50
5.59	0.101	15.00
7.81	0.132	15.50

FINISH

AHYMO.OUT

AHYMO PROGRAM (AHYMO-S4) - Version: S4.01a - Rel: 01a
 RUN DATE (MON/DAY/YR) = 03/06/2015
 START TIME (HR:MIN:SEC) = 13:27:25 USER NO.=
 RioGrandeSingleA41963517
 INPUT FILE = ngs\Owner\Desktop\2013\13151-AMERICAN
 TOYOTA\Drainage\SUBMITTAL 030615\AHYMO.OUT

AHYMO PROGRAM (AHYMO-S4) - Version: S4.01a - Rel: 01a
 RUN DATE (MON/DAY/YR) = 03/06/2015
 START TIME (HR:MIN:SEC) = 13:02:52 USER NO.= RioGrandeSingleA41
 INPUT FILE = ents and Settings\Owner\Desktop\2013\13151-AMERICAN TO

*S AHYMO - NORTH TRAMWAY ESTATES
 *S POND ROUTING

START TIME=0.0 PUNCH CODE=0

RAINFALL TYPE=2
 QUARTER=0.0 ONE= 2.14 IN
 SIX= 2.60 IN DAY= 3.10 IN DT = 0.05 HR

24-HOUR RAINFALL DIST. - BASED ON NOAA ATLAS 14 FOR CONVECTIV
 DT = 0.050000 HOURS END TIME = 24.000002 HOURS

0.0000	0.0031	0.0062	0.0096	0.0133	0.0171	0.0214
0.0274	0.0368	0.0470	0.0575	0.0690	0.0807	0.0927
0.1052	0.1178	0.1320	0.1467	0.1627	0.1887	0.2196
0.2611	0.3081	0.3661	0.4435	0.5307	0.6811	0.9149
1.3155	1.5971	1.8192	1.9308	2.0287	2.0989	2.1549
2.2036	2.2393	2.2720	2.2991	2.3181	2.3331	2.3464
2.3590	2.3700	2.3804	2.3905	2.4002	2.4083	2.4129
2.4175	2.4219	2.4261	2.4303	2.4343	2.4383	2.4422
2.4459	2.4495	2.4531	2.4566	2.4601	2.4634	2.4667
2.4699	2.4731	2.4762	2.4792	2.4822	2.4851	2.4880
2.4909	2.4937	2.4965	2.4992	2.5019	2.5046	2.5072
2.5098	2.5124	2.5149	2.5175	2.5200	2.5224	2.5249
2.5273	2.5296	2.5320	2.5343	2.5366	2.5389	2.5412
2.5434	2.5456	2.5478	2.5500	2.5521	2.5542	2.5564
2.5584	2.5605	2.5626	2.5646	2.5666	2.5686	2.5706
2.5725	2.5745	2.5764	2.5783	2.5802	2.5821	2.5839
2.5858	2.5876	2.5894	2.5912	2.5930	2.5948	2.5965
2.5983	2.6000	2.6017	2.6035	2.6052	2.6069	2.6086
2.6104	2.6121	2.6138	2.6155	2.6172	2.6190	2.6207
2.6224	2.6241	2.6258	2.6275	2.6292	2.6309	2.6326
2.6343	2.6360	2.6377	2.6394	2.6411	2.6428	2.6445
2.6461	2.6478	2.6495	2.6512	2.6529	2.6545	2.6562
2.6579	2.6595	2.6612	2.6629	2.6645	2.6662	2.6679
2.6695	2.6712	2.6728	2.6745	2.6761	2.6778	2.6794
2.6811	2.6827	2.6844	2.6860	2.6876	2.6893	2.6909
2.6925	2.6942	2.6958	2.6974	2.6990	2.7007	2.7023
2.7039	2.7055	2.7071	2.7087	2.7104	2.7120	2.7136
2.7152	2.7168	2.7184	2.7200	2.7216	2.7232	2.7248
2.7264	2.7279	2.7295	2.7311	2.7327	2.7343	2.7359
2.7374	2.7390	2.7406	2.7422	2.7437	2.7453	2.7469
2.7484	2.7500	2.7516	2.7531	2.7547	2.7562	2.7578
2.7593	2.7609	2.7624	2.7640	2.7655	2.7671	2.7686

AHYMO.OUT

2.7701	2.7717	2.7732	2.7747	2.7763	2.7778	2.7793
2.7808	2.7824	2.7839	2.7854	2.7869	2.7884	2.7899
2.7915	2.7930	2.7945	2.7960	2.7975	2.7990	2.8005
2.8020	2.8035	2.8050	2.8065	2.8079	2.8094	2.8109
2.8124	2.8139	2.8154	2.8168	2.8183	2.8198	2.8213
2.8227	2.8242	2.8257	2.8271	2.8286	2.8301	2.8315
2.8330	2.8344	2.8359	2.8373	2.8388	2.8402	2.8417
2.8431	2.8446	2.8460	2.8474	2.8489	2.8503	2.8517
2.8532	2.8546	2.8560	2.8574	2.8589	2.8603	2.8617
2.8631	2.8645	2.8659	2.8674	2.8688	2.8702	2.8716
2.8730	2.8744	2.8758	2.8772	2.8786	2.8800	2.8813
2.8827	2.8841	2.8855	2.8869	2.8883	2.8897	2.8910
2.8924	2.8938	2.8952	2.8965	2.8979	2.8993	2.9006
2.9020	2.9033	2.9047	2.9061	2.9074	2.9088	2.9101
2.9115	2.9128	2.9141	2.9155	2.9168	2.9182	2.9195
2.9208	2.9222	2.9235	2.9248	2.9262	2.9275	2.9288
2.9301	2.9314	2.9328	2.9341	2.9354	2.9367	2.9380
2.9393	2.9406	2.9419	2.9432	2.9445	2.9458	2.9471
2.9484	2.9497	2.9510	2.9523	2.9536	2.9549	2.9561
2.9574	2.9587	2.9600	2.9612	2.9625	2.9638	2.9651
2.9663	2.9676	2.9689	2.9701	2.9714	2.9726	2.9739
2.9751	2.9764	2.9776	2.9789	2.9801	2.9814	2.9826
2.9839	2.9851	2.9863	2.9876	2.9888	2.9900	2.9912
2.9925	2.9937	2.9949	2.9961	2.9974	2.9986	2.9998
3.0010	3.0022	3.0034	3.0046	3.0058	3.0070	3.0082
3.0094	3.0106	3.0118	3.0130	3.0142	3.0154	3.0166
3.0178	3.0189	3.0201	3.0213	3.0225	3.0237	3.0248
3.0260	3.0272	3.0283	3.0295	3.0307	3.0318	3.0330
3.0341	3.0353	3.0364	3.0376	3.0387	3.0399	3.0410
3.0422	3.0433	3.0445	3.0456	3.0467	3.0479	3.0490
3.0501	3.0513	3.0524	3.0535	3.0546	3.0558	3.0569
3.0580	3.0591	3.0602	3.0613	3.0624	3.0635	3.0646
3.0658	3.0669	3.0680	3.0690	3.0701	3.0712	3.0723
3.0734	3.0745	3.0756	3.0767	3.0777	3.0788	3.0799
3.0810	3.0821	3.0831	3.0842	3.0853	3.0863	3.0874
3.0885	3.0895	3.0906	3.0916	3.0927	3.0937	3.0948
3.0958	3.0969	3.0979	3.0990	3.1000		

COMPUTE NM HYD ID=1 HYD NO=101 DA= .00296 SQ MI
 PER A=00 PER B=4 PER C=6 PER D=90
 TP=-.177 MASSRAIN=-1

K = 0.096465HR TP = 0.177000HR K/TP RATIO = 0.545000 SHAPE
 UNIT PEAK = 7.9209 CFS UNIT VOLUME = 0.9984 B = 526.28
 AREA = 0.002664 SQ MI IA = 0.10000 INCHES INF = 0.04000 I
 RUNOFF COMPUTED BY INITIAL ABSTRACTION/INFILTRATION NUMBER METHOD - DT

K = 0.157759HR TP = 0.177000HR K/TP RATIO = 0.891296 SHAPE
 UNIT PEAK = 0.59158 CFS UNIT VOLUME = 0.9789 B = 353.75
 AREA = 0.000296 SQ MI IA = 0.41000 INCHES INF = 0.99800 I
 RUNOFF COMPUTED BY INITIAL ABSTRACTION/INFILTRATION NUMBER METHOD - DT

PRINT HYD ID=1 CODE=24

PARTIAL HYDROGRAPH 101.00

TIME HRS	FLOW CFS	TIME HRS	FLOW CFS	TIME HRS	FLOW CFS
0.000	0.0	5.000	0.0	10.000	0.1
1.000	0.4	6.000	0.1	11.000	0.1

		AHYMO.OUT			
2.000	1.7	7.000	0.1	12.000	0.1
3.000	0.1	8.000	0.1	13.000	0.1
4.000	0.0	9.000	0.1	14.000	0.0

RUNOFF VOLUME = 2.68726 INCHES = 0.4242 ACRE-FeET
 PEAK DISCHARGE RATE = 8.46 CFS AT 1.550 HOURS BASIN AREA = 0

* ROUTE THE TOTAL FLOW THROUGH THE PROPOSED RESERVOIR
 ROUTE RESERVOIR ID=2 HYD NO=102 INFLOW=1 CODE=24
 OUTFLOW(CFS) STORAGE(AC-FT) ELEV(FT)
 0.01 0.001 13.00
 0.69 0.007 13.50
 1.98 0.036 14.00
 3.63 0.069 14.50
 5.59 0.101 15.00
 7.81 0.132 15.50

* * * * *

TIME (HRS)	INFLOW (CFS)	ELEV (FEET)	VOLUME (AC-FT)	OUTFLOW (CFS)
0.00	0.00	12.99	0.001	0.00
1.20	1.13	13.51	0.007	0.71
2.40	0.54	13.76	0.022	1.37
3.60	0.05	13.03	0.001	0.05
4.80	0.05	13.03	0.001	0.04
6.00	0.06	13.03	0.001	0.06
7.20	0.06	13.04	0.001	0.06
8.40	0.06	13.03	0.001	0.06
9.60	0.06	13.03	0.001	0.06
10.80	0.05	13.03	0.001	0.05
12.00	0.05	13.03	0.001	0.05
13.20	0.05	13.03	0.001	0.05
14.40	0.05	13.03	0.001	0.05
15.60	0.05	13.03	0.001	0.05
16.80	0.05	13.03	0.001	0.05
18.00	0.04	13.03	0.001	0.04
19.20	0.04	13.02	0.001	0.04
20.40	0.04	13.02	0.001	0.04
21.60	0.04	13.02	0.001	0.04
22.80	0.04	13.02	0.001	0.04
24.00	0.04	13.02	0.001	0.04
25.20	0.00	13.00	0.001	0.01
26.40	0.00	13.00	0.001	0.01
27.60	0.00	13.00	0.001	0.01
28.80	0.00	13.00	0.001	0.01
30.00	0.00	13.00	0.001	0.01
31.20	0.00	13.00	0.001	0.01
32.40	0.00	13.00	0.001	0.01
33.60	0.00	13.00	0.001	0.01
34.80	0.00	13.00	0.001	0.01
36.00	0.00	13.00	0.001	0.01

			AHYMO.OUT	
37.20	0.00	13.00	0.001	0.01
38.40	0.00	13.00	0.001	0.01
39.60	0.00	13.00	0.001	0.01
40.80	0.00	13.00	0.001	0.01
42.00	0.00	13.00	0.001	0.01
43.20	0.00	13.00	0.001	0.01
44.40	0.00	13.00	0.001	0.01
45.60	0.00	13.00	0.001	0.01
46.80	0.00	13.00	0.001	0.01
48.00	0.00	13.00	0.001	0.01
49.20	0.00	13.00	0.001	0.01
50.40	0.00	13.00	0.001	0.01
51.60	0.00	13.00	0.001	0.01
52.80	0.00	13.00	0.001	0.01
54.00	0.00	13.00	0.001	0.01
55.20	0.00	13.00	0.001	0.01
56.40	0.00	13.00	0.001	0.01
57.60	0.00	13.00	0.001	0.01
58.80	0.00	13.00	0.001	0.01
60.00	0.00	13.00	0.001	0.01
61.20	0.00	13.00	0.001	0.01
62.40	0.00	13.00	0.001	0.01
63.60	0.00	13.00	0.001	0.01
64.80	0.00	13.00	0.001	0.01
66.00	0.00	13.00	0.001	0.01

TIME (HRS)	INFLOW (CFS)	ELEV (FEET)	VOLUME (AC-FT)	OUTFLOW (CFS)
67.20	0.00	13.00	0.001	0.01
68.40	0.00	13.00	0.001	0.01
69.60	0.00	13.00	0.001	0.01
70.80	0.00	13.00	0.001	0.01
72.00	0.00	13.00	0.001	0.01
73.20	0.00	13.00	0.001	0.01
74.40	0.00	13.00	0.001	0.01
75.60	0.00	13.00	0.001	0.01
76.80	0.00	13.00	0.001	0.01
78.00	0.00	13.00	0.001	0.01
79.20	0.00	13.00	0.001	0.01
80.40	0.00	13.00	0.001	0.01
81.60	0.00	13.00	0.001	0.01
82.80	0.00	13.00	0.001	0.01
84.00	0.00	13.00	0.001	0.01
85.20	0.00	13.00	0.001	0.01
86.40	0.00	13.00	0.001	0.01
87.60	0.00	13.00	0.001	0.01
88.80	0.00	13.00	0.001	0.01
90.00	0.00	13.00	0.001	0.01
91.20	0.00	13.00	0.001	0.01
92.40	0.00	13.00	0.001	0.01
93.60	0.00	13.00	0.001	0.01
94.80	0.00	13.00	0.001	0.01
96.00	0.00	13.00	0.001	0.01
97.20	0.00	13.00	0.001	0.01
98.40	0.00	13.00	0.001	0.01
99.60	0.00	13.00	0.001	0.01
100.80	0.00	13.00	0.001	0.01
102.00	0.00	13.00	0.001	0.01
103.20	0.00	13.00	0.001	0.01
104.40	0.00	13.00	0.001	0.01
105.60	0.00	13.00	0.001	0.01
106.80	0.00	13.00	0.001	0.01

			AHYMO.OUT	
108.00	0.00	13.00	0.001	0.01
109.20	0.00	13.00	0.001	0.01
110.40	0.00	13.00	0.001	0.01
111.60	0.00	13.00	0.001	0.01
112.80	0.00	13.00	0.001	0.01
114.00	0.00	13.00	0.001	0.01
115.20	0.00	13.00	0.001	0.01
116.40	0.00	13.00	0.001	0.01
117.60	0.00	13.00	0.001	0.01
118.80	0.00	13.00	0.001	0.01
120.00	0.00	13.00	0.001	0.01
121.20	0.00	13.00	0.001	0.01
122.40	0.00	13.00	0.001	0.01
123.60	0.00	13.00	0.001	0.01
124.80	0.00	13.00	0.001	0.01
126.00	0.00	13.00	0.001	0.01
127.20	0.00	13.00	0.001	0.01
128.40	0.00	13.00	0.001	0.01
129.60	0.00	13.00	0.001	0.01
130.80	0.00	13.00	0.001	0.01
132.00	0.00	13.00	0.001	0.01
133.20	0.00	13.00	0.001	0.01

TIME (HRS)	INFLOW (CFS)	ELEV (FEET)	VOLUME (AC-FT)	OUTFLOW (CFS)
134.40	0.00	13.00	0.001	0.01
135.60	0.00	13.00	0.001	0.01
136.80	0.00	13.00	0.001	0.01
138.00	0.00	13.00	0.001	0.01
139.20	0.00	13.00	0.001	0.01
140.40	0.00	13.00	0.001	0.01
141.60	0.00	13.00	0.001	0.01
142.80	0.00	13.00	0.001	0.01
144.00	0.00	13.00	0.001	0.01
145.20	0.00	13.00	0.001	0.01
146.40	0.00	13.00	0.001	0.01
147.60	0.00	13.00	0.001	0.01
148.80	0.00	13.00	0.001	0.01
150.00	0.00	13.00	0.001	0.01
151.20	0.00	13.00	0.001	0.01
152.40	0.00	13.00	0.001	0.01
153.60	0.00	13.00	0.001	0.01
154.80	0.00	13.00	0.001	0.01
156.00	0.00	13.00	0.001	0.01
157.20	0.00	13.00	0.001	0.01
158.40	0.00	13.00	0.001	0.01
159.60	0.00	13.00	0.001	0.01
160.80	0.00	13.00	0.001	0.01
162.00	0.00	13.00	0.001	0.01
163.20	0.00	13.00	0.001	0.01
164.40	0.00	13.00	0.001	0.01
165.60	0.00	13.00	0.001	0.01
166.80	0.00	13.00	0.001	0.01
168.00	0.00	13.00	0.001	0.01
169.20	0.00	13.00	0.001	0.01
170.40	0.00	13.00	0.001	0.01
171.60	0.00	13.00	0.001	0.01
172.80	0.00	13.00	0.001	0.01
174.00	0.00	13.00	0.001	0.01
175.20	0.00	13.00	0.001	0.01
176.40	0.00	13.00	0.001	0.01
177.60	0.00	13.00	0.001	0.01

		AHYMO.OUT		
178.80	0.00	13.00	0.001	0.01
180.00	0.00	13.00	0.001	0.01
181.20	0.00	13.00	0.001	0.01
182.40	0.00	13.00	0.001	0.01
183.60	0.00	13.00	0.001	0.01
184.80	0.00	13.00	0.001	0.01
186.00	0.00	13.00	0.001	0.01
187.20	0.00	13.00	0.001	0.01
188.40	0.00	13.00	0.001	0.01
189.60	0.00	13.00	0.001	0.01
190.80	0.00	13.00	0.001	0.01
192.00	0.00	13.00	0.001	0.01
193.20	0.00	13.00	0.001	0.01
194.40	0.00	13.00	0.001	0.01
195.60	0.00	13.00	0.001	0.01
196.80	0.00	13.00	0.001	0.01
198.00	0.00	13.00	0.001	0.01
199.20	0.00	13.00	0.001	0.01
PEAK DISCHARGE =		5.575 CFS - PEAK OCCURS AT HOUR 1.70		
MAXIMUM WATER SURFACE ELEVATION =		14.996		
MAXIMUM STORAGE =		0.1008 AC-FT INCREMENTAL TIME= 0.050000HRS		

FINISH

NORMAL PROGRAM FINISH

END TIME (HR:MIN:SEC) = 13:02:52

APPENDIX F HYDRAULIC CALCULATIONS

Concrete Channel

Weir Equation:

$$Q = CLH^{3/2}$$

$$Q = 7.75 \text{ cfs}$$

$$C = 2.95$$


$$H = 0.5 \text{ ft}$$

L = Length of weir

$$L = \frac{7.75}{2.95(0.5)^{3/2}}$$

$$L = 7.43 \text{ ft}$$

Use 7.50 feet for length of weir



DROP INLET CALCULATIONS

POND	TYPE OF INLET	AREA (SF)	Q (CFS)	H (FT)	H ALLOW (FT)
1A	SINGLE	4.43	7.78	0.1330	0.5

ORIFICE EQUATION

$$Q = CA \sqrt{2gH} \quad H = (Q/CA)^2 / 2G$$

$$C = 0.6$$

$$g = 32.2$$

INLET GRATE=40"X25"

CALCULATE FOR BARS

$$40 - (11 \times .5) = 34.5"$$


$$25 - (13 \times .5) = 18.5"$$

OPENING IS 4.43 SF PER GRATE


GRATING CAPACITIES FOR TYPE 'A' , 'C' and 'D'



GRATING & GUTTER PLAN



TYPICAL HALF STREET SECTION
(ABOVE BASIN)



inlets on 5% slope
capacity 10cfs

Pipe Capacity

Pipe	D	Slope	Area	R	Q Provided	Q Required	Velocity
	(in)	(%)	(ft^2)		(cfs)	(cfs)	(ft/s)
18HDPE	18	1	1.77	0.375	9.13	6.03	3.41

Manning's Equation:

$$Q = 1.49/n * A * R^{2/3} * S^{1/2}$$

A = Area

R = D/4

S = Slope

n = 0.015

APPENDIX G
STORM TECH DETAILS

PROJECT INFORMATION	
ENGINEERED PRODUCT MANAGER:	PEGGY GRAHAM 720-982-6303 PEGGY.GRAHAM@ADS-PIPE.COM
ADS SALES REP:	PETER NICHOLS 505-301-5604 PETER.NICHOLS@ADS-PIPE.COM
PROJECT NO:	82394 REV2



ADVANCED DRAINAGE SYSTEMS, INC.



AMERICAN TOYOTA

ALBUQUERQUE, NM

STORMWATER CHAMBER SPECIFICATIONS

- CHAMBERS SHALL BE STORMTECH MC-4500 OR APPROVED EQUAL.
- CHAMBERS SHALL BE MANUFACTURED FROM VIRGIN, IMPACT-MODIFIED POLYPROPYLENE COPOLYMERS.
- CHAMBER ROWS SHALL PROVIDE CONTINUOUS, UNOBSTRUCTED INTERNAL SPACE WITH NO INTERNAL SUPPORT PANELS THAT WOULD IMPEDE FLOW OR LIMIT ACCESS FOR INSPECTION.
- THE STRUCTURAL DESIGN OF THE CHAMBERS, THE STRUCTURAL BACKFILL, AND THE INSTALLATION REQUIREMENTS SHALL ENSURE THAT THE LOAD FACTORS SPECIFIED IN THE AASHTO LRFD BRIDGE DESIGN SPECIFICATIONS, SECTION 12.12, ARE MET FOR: 1) LONG-DURATION DEAD LOADS AND 2) SHORT-DURATION LIVE LOADS, BASED ON THE AASHTO DESIGN TRUCK WITH CONSIDERATION FOR IMPACT AND MULTIPLE VEHICLE PRESENCES.
- CHAMBERS SHALL MEET THE REQUIREMENTS OF ASTM F2418, "STANDARD SPECIFICATION FOR POLYPROPYLENE (PP) CORRUGATED WALL STORMWATER COLLECTION CHAMBERS".
- CHAMBERS SHALL BE DESIGNED AND ALLOWABLE LOADS DETERMINED IN ACCORDANCE WITH ASTM F2787, "STANDARD PRACTICE FOR STRUCTURAL DESIGN OF THERMOPLASTIC CORRUGATED WALL STORMWATER COLLECTION CHAMBERS".
- ONLY CHAMBERS THAT ARE APPROVED BY THE SITE DESIGN ENGINEER WILL BE ALLOWED. THE CHAMBER MANUFACTURER SHALL SUBMIT THE FOLLOWING UPON REQUEST TO THE SITE DESIGN ENGINEER FOR APPROVAL BEFORE DELIVERING CHAMBERS TO THE PROJECT SITE:
 - A STRUCTURAL EVALUATION SEALED BY A REGISTERED PROFESSIONAL ENGINEER THAT DEMONSTRATES THAT THE SAFETY FACTORS ARE GREATER THAN OR EQUAL TO 1.95 FOR DEAD LOAD AND 1.75 FOR LIVE LOAD, THE MINIMUM REQUIRED BY ASTM F2787 AND BY AASHTO FOR THERMOPLASTIC PIPE.
 - A STRUCTURAL EVALUATION SEALED BY A REGISTERED PROFESSIONAL ENGINEER THAT DEMONSTRATES THAT THE LOAD FACTORS SPECIFIED IN THE AASHTO LRFD BRIDGE DESIGN SPECIFICATIONS, SECTION 12.12, ARE MET. THE 50 YEAR CREEP MODULUS DATA SPECIFIED IN ASTM F2418 MUST BE USED AS PART OF THE AASHTO STRUCTURAL EVALUATION TO VERIFY LONG-TERM PERFORMANCE.
 - STRUCTURAL CROSS SECTION DETAIL ON WHICH THE STRUCTURAL EVALUATION IS BASED.
- CHAMBERS AND END CAPS SHALL BE PRODUCED AT AN ISO 9001 CERTIFIED MANUFACTURING FACILITY.

IMPORTANT - NOTES FOR THE BIDDING AND INSTALLATION OF MC-4500 CHAMBER SYSTEM

- STORMTECH MC-4500 CHAMBERS SHALL NOT BE INSTALLED UNTIL THE MANUFACTURER'S REPRESENTATIVE HAS COMPLETED A PRE-CONSTRUCTION MEETING WITH THE INSTALLERS.
- STORMTECH MC-4500 CHAMBERS SHALL BE INSTALLED IN ACCORDANCE WITH THE "STORMTECH MC-3500/MC-4500 CONSTRUCTION GUIDE".
- CHAMBERS ARE NOT TO BE BACKFILLED WITH A DOZER OR EXCAVATOR SITUATED OVER THE CHAMBERS.
STORMTECH RECOMMENDS 3 BACKFILL METHODS:
 - STONESHOOTER LOCATED OFF THE CHAMBER BED.
 - BACKFILL AS ROWS ARE BUILT USING AN EXCAVATOR ON THE FOUNDATION STONE OR SUBGRADE.
 - BACKFILL FROM OUTSIDE THE EXCAVATION USING A LONG BOOM HOE OR EXCAVATOR.
- THE FOUNDATION STONE SHALL BE LEVELED AND COMPACTED PRIOR TO PLACING CHAMBERS.
- JOINTS BETWEEN CHAMBERS SHALL BE PROPERLY SEATED PRIOR TO PLACING STONE.
- MAINTAIN MINIMUM - 8" (230 mm) SPACING BETWEEN THE CHAMBER ROWS.
- INLET AND OUTLET MANIFOLDS MUST BE INSERTED A MINIMUM OF 12" (300 mm) INTO CHAMBER END CAPS.
- EMBEDMENT STONE SURROUNDING CHAMBERS MUST BE A CLEAN, CRUSHED, ANGULAR STONE 3/4-2" (20-50 mm) MEETING THE AASHTO M43 DESIGNATION OF #3 OR #4.
- STONE SHALL BE BROUGHT UP EVENLY AROUND CHAMBERS SO AS NOT TO DISTORT THE CHAMBER SHAPE. STONE DEPTHS SHOULD NEVER DIFFER BY MORE THAN 12" (300 mm) BETWEEN ADJACENT CHAMBER ROWS.
- STONE MUST BE PLACED ON THE TOP CENTER OF THE CHAMBER TO ANCHOR THE CHAMBERS IN PLACE AND PRESERVE ROW SPACING.
- ADS RECOMMENDS THE USE OF "FLEXSTORM CATCH IT" INSERTS DURING CONSTRUCTION FOR ALL INLETS TO PROTECT THE SUBSURFACE STORMWATER MANAGEMENT SYSTEM FROM CONSTRUCTION SITE RUNOFF.

NOTES FOR CONSTRUCTION EQUIPMENT

- STORMTECH MC-4500 CHAMBERS SHALL BE INSTALLED IN ACCORDANCE WITH THE "STORMTECH MC-3500/MC-4500 CONSTRUCTION GUIDE".
- THE USE OF EQUIPMENT OVER MC-4500 CHAMBERS IS LIMITED:
 - NO EQUIPMENT IS ALLOWED ON BARE CHAMBERS.
 - NO RUBBER TIRED LOADER, DUMP TRUCK, OR EXCAVATORS ARE ALLOWED UNTIL PROPER FILL DEPTHS ARE REACHED IN ACCORDANCE WITH THE "STORMTECH MC-3500/MC-4500 CONSTRUCTION GUIDE".
 - WEIGHT LIMITS FOR CONSTRUCTION EQUIPMENT CAN BE FOUND IN THE "STORMTECH MC-3500/MC-4500 CONSTRUCTION GUIDE".
- FULL 36" (900 mm) OF STABILIZED COVER MATERIALS OVER THE CHAMBERS IS REQUIRED FOR DUMP TRUCK TRAVEL OR DUMPING.

USE OF A DOZER TO PUSH EMBEDMENT STONE BETWEEN THE ROWS OF CHAMBERS MAY CAUSE DAMAGE TO CHAMBERS AND IS NOT AN ACCEPTABLE BACKFILL METHOD. ANY CHAMBERS DAMAGED BY USING THE "DUMP AND PUSH" METHOD ARE NOT COVERED UNDER THE STORMTECH STANDARD WARRANTY.

CONTACT STORMTECH AT 1-888-892-2694 WITH ANY QUESTIONS ON INSTALLATION REQUIREMENTS OR WEIGHT LIMITS FOR CONSTRUCTION EQUIPMENT.

PROPOSED LAYOUT (SYSTEM #1)


(90) STORMTECH MC-4500 CHAMBERS
(4) STORMTECH MC-4500 END CAPS
INSTALLED WITH 12" COVER STONE, 9" BASE STONE, 30% STONE VOID
INSTALLED SYSTEM VOLUME (PERIMETER STONE INCLUDED): 14,583 CF
AREA OF SYSTEM: 3,839 FT²
PERIMETER OF SYSTEM: 434 FT

PROPOSED ELEVATIONS (SYSTEM #1)

MAXIMUM ALLOWABLE GRADE (TOP OF PAVEMENT/UNPAVED):	5229.00
MINIMUM ALLOWABLE GRADE (UNPAVED WITH TRAFFIC):	5224.50
MINIMUM ALLOWABLE GRADE (BASE OF FLEXIBLE PAVEMENT):	5224.00
MINIMUM ALLOWABLE GRADE (TOP OF RIGID CONCRETE PAVEMENT):	5224.00
TOP OF STONE:	5223.00
TOP OF CHAMBER:	5222.00
24" TOP MANIFOLD INVERT:	5218.92
24" ISOLATOR ROW INVERT:	5217.19
BOTTOM OF CHAMBER:	5217.00
BOTTOM OF STONE:	5216.25

NOTES

- DUE TO THE ADAPTATION OF THIS CHAMBER SYSTEM TO SPECIFIC SITE AND DESIGN CONSTRAINTS, IT MAY BE NECESSARY TO CUT AND COUPLE ADDITIONAL PIPE TO STANDARD MANIFOLD COMPONENTS IN THE FIELD.
- THE SITE DESIGN ENGINEER MUST REVIEW ELEVATIONS AND IF NECESSARY ADJUST GRADING TO ENSURE THE CHAMBER COVER REQUIREMENTS ARE MET.



AMERICAN TOYOTA
ALBUQUERQUE, NM

DATE: 12/30/14
PROJECT #: 82394

DRAWN: WCM
CHECKED: GFI

REV	CHK	DESCRIPTION
1/28/15	WCM	NEW STORAGE VOLUMES AND STONE VOID
3/19/15	WCM	SYSTEM REMOVED

StormTech
Dedicated. Reliable. Water Quality.

70 INWOOD ROAD, SUITE 3 | ROCKY HILL, CT 06067
860-528-8188 | 1-800-887-0281 | WWW.STORMTECH.COM

ADS
ADVANCED DRAINAGE SYSTEMS, INC.

4640 TRUENMAN BLVD
HILLIARD, OH 43026
1-800-733-7473

20'
40'

SHEET
2 OF 8

THIS DRAWING HAS BEEN PREPARED BASED ON INFORMATION PROVIDED TO ADD UNDER THE DIRECTION OF THE SITE DESIGN ENGINEER OR OTHER PROJECT REPRESENTATIVE. THE SITE DESIGN ENGINEER SHALL REVIEW THIS DRAWING PRIOR TO CONSTRUCTION. IT IS THE ULTIMATE RESPONSIBILITY OF THE SITE DESIGN ENGINEER TO ENSURE THAT THE PRODUCTS(S) DEPICTED AND ALL ASSOCIATED DETAILS MEET ALL APPLICABLE LAWS, REGULATIONS, AND PROJECT REQUIREMENTS.

PROPOSED LAYOUT (SYSTEM #2)

(56) STORMTECH MC-4500 CHAMBERS
(4) STORMTECH MC-4500 END CAPS
INSTALLED WITH 12" COVER STONE, 9" BASE STONE, 30% STONE VOID
INSTALLED SYSTEM VOLUME (PERIMETER STONE INCLUDED): 9,290 CF
AREA OF SYSTEM: 2,477 FT²
PERIMETER OF SYSTEM: 384 FT

PROPOSED ELEVATIONS (SYSTEM #2)

MAXIMUM ALLOWABLE GRADE (TOP OF PAVEMENT/UNPAVED):	\$229.00
MINIMUM ALLOWABLE GRADE (UNPAVED WITH TRAFFIC):	\$224.50
MINIMUM ALLOWABLE GRADE (BASE OF FLEXIBLE PAVEMENT):	\$224.00
MINIMUM ALLOWABLE GRADE (TOP OF RIGID CONCRETE PAVEMENT):	\$224.00
TOP OF STONE:	\$223.00
TOP OF CHAMBER:	\$222.00
24" TOP MANIFOLD INVERT:	\$218.92
24" ISOLATOR ROW INVERT:	\$217.19
BOTTOM OF CHAMBER:	\$217.00
BOTTOM OF STONE:	\$216.25

NOTES

- DUE TO THE ADAPTATION OF THIS CHAMBER SYSTEM TO SPECIFIC SITE AND DESIGN CONSTRAINTS, IT MAY BE NECESSARY TO CUT AND COUPLE ADDITIONAL PIPE TO STANDARD MANIFOLD COMPONENTS IN THE FIELD.
- THE SITE DESIGN ENGINEER MUST REVIEW ELEVATIONS AND IF NECESSARY ADJUST GRADING TO ENSURE THE CHAMBER COVER REQUIREMENTS ARE MET.

AMERICAN TOYOTA
ALBUQUERQUE, NM


DATE: 12/30/14
PROJECT #: 82394
DRAWN: WCM
CHECKED: GFI

REV	DRW	CHK	DESCRIPTION
1/2/15	WCM	KAP	NEW STORAGE VOLUMES AND STONE VOID
3/16/15	WCM	KMS	SYSTEM REMOVED



4640 TRUEMAN BLVD
HILLIARD, OH 43026
1-800-733-7473


SHEET
3 OF 8



(38) STORMTECH MC-4500 CHAMBERS
(2) STORMTECH MC-4500 END CAPS
INSTALLED WITH 12" COVER STONE, 9" BASE STONE, 30% STONE VOID
INSTALLED SYSTEM VOLUME (PERIMETER STONE INCLUDED): 6,232 CF
AREA OF SYSTEM: 1,654 FT²
PERIMETER OF SYSTEM: 341 FT

MAXIMUM ALLOWABLE GRADE (TOP OF PAVEMENT/UNPAVED):	\$230.00
MINIMUM ALLOWABLE GRADE (UNPAVED WITH TRAFFIC):	\$225.50
MINIMUM ALLOWABLE GRADE (BASE OF FLEXIBLE PAVEMENT):	\$225.00
MINIMUM ALLOWABLE GRADE (TOP OF RIGID CONCRETE PAVEMENT):	\$225.00
TOP OF STONE:	\$224.00
TOP OF CHAMBER:	\$223.00
24" ISOLATOR ROW INVERT:	\$218.19
BOTTOM OF CHAMBER:	\$216.00
BOTTOM OF STONE:.....	\$217.25

- DUE TO THE ADAPTATION OF THIS CHAMBER SYSTEM TO SPECIFIC SITE AND DESIGN CONSTRAINTS, IT MAY BE NECESSARY TO CUT AND COUPLE ADDITIONAL PIPE TO STANDARD MANIFOLD COMPONENTS IN THE FIELD.
- THE SITE DESIGN ENGINEER MUST REVIEW ELEVATIONS AND IF NECESSARY ADJUST GRADING TO ENSURE THE CHAMBER COVER REQUIREMENTS ARE MET.




---	--

ACCEPTABLE FILL MATERIALS: STORMTECH MC-4500 CHAMBER SYSTEMS

MATERIAL LOCATION	DESCRIPTION	AASHTO MATERIAL CLASSIFICATIONS	COMPACTION / DENSITY REQUIREMENT
D	FINAL FILL: FILL MATERIAL FOR LAYER 'D' STARTS FROM THE TOP OF THE 'C' LAYER TO THE BOTTOM OF FLEXIBLE PAVEMENT OR UNPAVED FINISHED GRADE ABOVE. NOTE THAT PAVEMENT SUBBASE MAY BE PART OF THE 'D' LAYER.	N/A	PREPARE PER SITE DESIGN ENGINEER'S PLANS. PAVED INSTALLATIONS MAY HAVE STRINGENT MATERIAL AND PREPARATION REQUIREMENTS.
C	INITIAL FILL: FILL MATERIAL FOR LAYER 'C' STARTS FROM THE TOP OF THE EMBEDMENT STONE ('B' LAYER) TO 24" (600 mm) ABOVE THE TOP OF THE CHAMBER. NOTE THAT PAVEMENT SUBBASE MAY BE A PART OF THE 'C' LAYER.	AASHTO M145 ¹ A-1, A-2-4, A-3 OR AASHTO M43 ¹ 3, 357, 4, 467, 5, 56, 57, 6, 67, 68, 7, 78, 8, 89, 9, 10	BEGIN COMPACTIONS AFTER 24" (600 mm) OF MATERIAL OVER THE CHAMBERS IS REACHED. COMPACT ADDITIONAL LAYERS IN 12" (300 mm) MAX LIFTS TO A MIN. 95% PROCTOR DENSITY FOR WELL GRADED MATERIAL AND 95% RELATIVE DENSITY FOR PROCESSED AGGREGATE MATERIALS.
B	EMBEDMENT STONE: FILL SURROUNDING THE CHAMBERS FROM THE FOUNDATION STONE ('A' LAYER) TO THE 'C' LAYER ABOVE.	AASHTO M43 ¹ 3, 4	NO COMPACTION REQUIRED.
A	FOUNDATION STONE: FILL BELOW CHAMBERS FROM THE SUBGRADE UP TO THE FOOT (BOTTOM) OF THE CHAMBER.	AASHTO M43 ¹ 3, 4	PLATE COMPACT OR ROLL TO ACHIEVE A FLAT SURFACE. ^{1,2}

PLEASE NOTE:

- THE LISTED AASHTO DESIGNATIONS ARE FOR GRADATIONS ONLY. THE STONE MUST ALSO BE CLEAN, CRUSHED, ANGULAR. FOR EXAMPLE, A SPECIFICATION FOR #4 STONE WOULD STATE: "CLEAN, CRUSHED, ANGULAR NO. 4 (AASHTO M43) STONE".
- STORMTECH COMPACTION REQUIREMENTS ARE MET FOR 'A' LOCATION MATERIALS WHEN PLACED AND COMPACTED IN 9" (230 mm) (MAX) LIFTS USING TWO FULL COVERAGES WITH A VIBRATORY COMPACTOR.
- WHERE INFILTRATION SURFACES MAY BE COMPROMISED BY COMPACTION, FOR STANDARD DESIGN LOAD CONDITIONS, A FLAT SURFACE MAY BE ACHIEVED BY RAKING OR DRAGGING WITHOUT COMPACTION EQUIPMENT. FOR SPECIAL LOAD DESIGNS, CONTACT STORMTECH FOR COMPACTION REQUIREMENTS.



NOTES:

- MC-4500 CHAMBERS SHALL CONFORM TO THE REQUIREMENTS OF ASTM F2418 "STANDARD SPECIFICATION FOR POLYPROPYLENE (PP) CORRUGATED WALL STORMWATER COLLECTION CHAMBERS".
- MC-4500 CHAMBERS SHALL BE DESIGNED IN ACCORDANCE WITH ASTM F2787 "STANDARD PRACTICE FOR STRUCTURAL DESIGN OF THERMOPLASTIC CORRUGATED WALL STORMWATER COLLECTION CHAMBERS".
- "ACCEPTABLE FILL MATERIALS" TABLE ABOVE PROVIDES MATERIAL LOCATIONS, DESCRIPTIONS, GRADATIONS, AND COMPACTION REQUIREMENTS FOR FOUNDATION, EMBEDMENT, AND FILL MATERIALS.
- THE "SITE DESIGN ENGINEER" REFERS TO THE ENGINEER RESPONSIBLE FOR THE DESIGN AND LAYOUT OF THE STORMTECH CHAMBERS FOR THIS PROJECT.
- THE SITE DESIGN ENGINEER IS RESPONSIBLE FOR ASSESSING THE BEARING RESISTANCE (ALLOWABLE BEARING CAPACITY) OF THE SUBGRADE SOILS AND THE DEPTH OF FOUNDATION STONE WITH CONSIDERATION FOR THE RANGE OF EXPECTED SOIL MOISTURE CONDITIONS.
- PERIMETER STONE MUST BE EXTENDED HORIZONTALLY TO THE EXCAVATION WALL FOR BOTH VERTICAL AND SLOPED EXCAVATION WALLS.
- ONCE LAYER 'C' IS PLACED, ANY SOIL/MATERIAL CAN BE PLACED IN LAYER 'D' UP TO THE FINISHED GRADE. MOST PAVEMENT SUBBASE SOILS CAN BE USED TO REPLACE THE MATERIAL REQUIREMENTS OF LAYER 'C' OR 'D' AT THE SITE DESIGN ENGINEER'S DISCRETION.

AMERICAN TOYOTA
ALBUQUERQUE, NM


DATE: 12/30/14
PROJECT #: 82394
DRAWN: WCM
CHECKED: GFI

DESCRIPTION
NEW STORAGE VOLUMES AND STONE
SYSTEM REMOVED

StormTech
CORPORATION
170 INWOOD ROAD, SUITE 101, ROCKY HILL, CT 06067
860-528-4168 | 888-852-2884 | WWW.STORMTECH.COM

4640 TRUEMAN BLVD
HILLIARD, OH 43026
1-800-733-7473
ADVANCED DRAINAGE SYSTEMS, INC.

SHEET
5 OF 8




MC-4500 ISOLATOR ROW DETAIL
NTS

INSPECTION & MAINTENANCE

- STEP 1) INSPECT ISOLATOR ROW FOR SEDIMENT**
- A. INSPECTION PORTS (IF PRESENT)
 - A.1. REMOVE/OPEN LID ON NYLOPLAST INLINE DRAIN
 - A.2. REMOVE AND CLEAN FLEXSTORM FILTER IF INSTALLED
 - A.3. USING A FLASHLIGHT AND STADIA ROD, MEASURE DEPTH OF SEDIMENT AND RECORD ON MAINTENANCE LOG
 - A.4. LOWER A CAMERA INTO ISOLATOR ROW FOR VISUAL INSPECTION OF SEDIMENT LEVELS (OPTIONAL)
 - A.5. IF SEDIMENT IS AT, OR ABOVE, 3" (80 mm) PROCEED TO STEP 2. IF NOT, PROCEED TO STEP 3.
 - B. ALL ISOLATOR ROWS
 - B.1. REMOVE COVER FROM STRUCTURE AT UPSTREAM END OF ISOLATOR ROW
 - B.2. USING A FLASHLIGHT, INSPECT DOWN THE ISOLATOR ROW THROUGH OUTLET PIPE
 - i) MIRRORS ON POLES OR CAMERAS MAY BE USED TO AVOID A CONFINED SPACE ENTRY
 - ii) FOLLOW OSHA REGULATIONS FOR CONFINED SPACE ENTRY IF ENTERING MANHOLE
 - B.3. IF SEDIMENT IS AT, OR ABOVE, 3" (80 mm) PROCEED TO STEP 2. IF NOT, PROCEED TO STEP 3.
- STEP 2) CLEAN OUT ISOLATOR ROW USING THE JETVAC PROCESS**
- A. A FIXED CULVERT CLEANING NOZZLE WITH REAR FACING SPREAD OF 45° (1.1 m) OR MORE IS PREFERRED
 - B. APPLY MULTIPLE PASSES OF JETVAC UNTIL BACKFLUSH WATER IS CLEAN
 - C. VACUUM STRUCTURE SUMP AS REQUIRED
- STEP 3) REPLACE ALL COVERS, GRATES, FILTERS, AND LIDS; RECORD OBSERVATIONS AND ACTIONS.**
- STEP 4) INSPECT AND CLEAN BASINS AND MANHOLES UPSTREAM OF THE STORMTECH SYSTEM.**

NOTES

1. INSPECT EVERY 6 MONTHS DURING THE FIRST YEAR OF OPERATION. ADJUST THE INSPECTION INTERVAL BASED ON PREVIOUS OBSERVATIONS OF SEDIMENT ACCUMULATION AND HIGH WATER ELEVATIONS.
2. CONDUCT JETTING AND VACTORING ANNUALLY OR WHEN INSPECTION SHOWS THAT MAINTENANCE IS NECESSARY.



MC-4500 INSPECTION PORT DETAIL
NTS

AMERICAN TOYOTA
ALBUQUERQUE, NM

DATE: 12/30/14
PROJECT #: 92394

DRAWN: WCM

CHECKED: GFI

DESCRIPTION

NEW STORAGE VOLUMES AND STONE VOID SYSTEM REMOVED

REV

DRW

CHK

1/28/15

WCM

1/28/15

WCM

1/28/15

WCM

1/28/15

WCM

1/28/15

WCM

1/28/15

WCM

1/28/15

WCM

1/28/15

WCM

1/28/15

WCM

1/28/15

WCM

1/28/15

WCM

1/28/15

WCM

1/28/15

WCM

1/28/15

WCM

1/28/15

WCM

1/28/15

WCM

1/28/15

WCM

1/28/15

WCM

1/28/15

WCM

1/28/15

WCM

1/28/15

WCM

1/28/15

WCM

1/28/15

WCM

1/28/15

WCM

1/28/15

WCM

1/28/15

WCM

1/28/15

WCM

StormTech
CREATING PROTECTION. MAKING DRAINAGE.
70 INWOOD ROAD, SUITE 3 | ROCKY HILL, CT 06067
860.528.6158 | 1.888.862.2884 | WWW.STORMTECH.COM

4840 TRULEMAN BLVD
HULLAND, OH 43026
ADVANCED DRAINAGE SYSTEMS, INC.
1-800-733-7473



THIS DRAWING HAS BEEN PREPARED BASED ON INFORMATION PROVIDED TO ADVANCE THE DESIGN OF THE SITE DESIGN ENGINEER OR OTHER PROJECT REPRESENTATIVE. THE SITE DESIGN ENGINEER SHALL REVIEW THE DRAWING PRIOR TO CONSTRUCTION. IT IS THE ULTIMATE RESPONSIBILITY OF THE SITE DESIGN ENGINEER TO ENSURE THAT THE PRODUCTS DETECTED AND ALL ASSOCIATED DETAILS MEET ALL APPLICABLE LAWS, REGULATIONS, AND PROJECT REQUIREMENTS.

SHEET

6 OF 8

MC-4500 TECHNICAL SPECIFICATION

NTS



NOMINAL CHAMBER SPECIFICATIONS

SIZE (W X H X INSTALLED LENGTH)	100.0\" X 60.0\" X 48.3\"	(2540 mm X 1524 mm X 1227 mm)
CHAMBER STORAGE	106.5 CUBIC FEET	(3.01 m³)
MINIMUM INSTALLED STORAGE*	162.6 CUBIC FEET	(4.60 m³)
WEIGHT	130.0 lbs.	(59.0 kg)

NOMINAL END CAP SPECIFICATIONS

SIZE (W X H X INSTALLED LENGTH)	90.2\" X 59.4\" X 30.7\"	(2291 mm X 1509 mm X 781 mm)
END CAP STORAGE	35.7 CUBIC FEET	(1.01 m³)
MINIMUM INSTALLED STORAGE*	108.7 CUBIC FEET	(3.08 m³)
WEIGHT	135.0 lbs.	(61.2 kg)



*ASSUMES 12\" (305 mm) STONE ABOVE, 9\" (229 mm) STONE FOUNDATION AND BETWEEN CHAMBERS, 12\" (305 mm) STONE PERIMETER IN FRONT OF END CAPS AND 40% STONE POROSITY.

STUBS AT BOTTOM OF END CAP FOR PART NUMBERS ENDING WITH "B"
STUBS AT TOP OF END CAP FOR PART NUMBERS ENDING WITH "T"

PART #	STUB	B	C
MC4500REPE08T	6\" (150 mm)	42.54\" (1.081 m)	—
MC4500REPE08B	—	—	0.86\" (22 mm)
MC4500REPE08T	8\" (200 mm)	40.50\" (1.029 m)	—
MC4500REPE08B	—	—	1.01\" (26 mm)
MC4500REPE10T	10\" (250 mm)	38.37\" (975 mm)	—
MC4500REPE10B	—	—	1.33\" (34 mm)
MC4500REPE12T	12\" (300 mm)	35.69\" (907 mm)	—
MC4500REPE12B	—	—	1.55\" (39 mm)
MC4500REPE15T	15\" (375 mm)	32.72\" (831 mm)	—
MC4500REPE15B	—	—	1.70\" (43 mm)
MC4500REPE18TC	18\" (450 mm)	29.36\" (746 mm)	—
MC4500REPE18BC	—	—	1.97\" (50 mm)
MC4500REPE24TC	24\" (600 mm)	23.05\" (585 mm)	—
MC4500REPE24BC	—	—	2.26\" (57 mm)
MC4500REPE30BC	30\" (750 mm)	—	2.95\" (75 mm)
MC4500REPE36BC	36\" (900 mm)	—	3.25\" (83 mm)
MC4500REPE42BC	42\" (1050 mm)	—	3.55\" (90 mm)


NOTE: ALL DIMENSIONS ARE NOMINAL

CUSTOM PRECURED INVERTS ARE AVAILABLE UPON REQUEST. INVENTORIED MANIFOLDS INCLUDE 12-24\" (300-600 mm) SIZE ON SIZE AND 15-48\" (375-1200 mm) ECCENTRIC MANIFOLDS. CUSTOM INVERT LOCATIONS ON THE MC-4500 END CAP CUT IN THE FIELD ARE NOT RECOMMENDED FOR PIPE SIZES GREATER THAN 10\" (250 mm). THE INVERT LOCATION IN COLUMN 'B' ARE THE HIGHEST POSSIBLE FOR THE PIPE SIZE.



MC-SERIES END CAP INSERTION DETAIL

NTS



NOTE: MANIFOLD STUB MUST BE LAID HORIZONTAL FOR A PROPER FIT IN END CAP OPENING.

AMERICAN TOYOTA
ALBUQUERQUE, NM

DATE: 12/30/14
PROJECT #: 82394
DRAWN: WCM
CHECKED: GFI

DESCRIPTION
NEW STORAGE VOLUMES AND STONE VOID
SYSTEM REMOVED


StormTech
Dedicated. Proven. Near Quality.
70 INWOOD ROAD, SUITE 5 | ROCKY HILL, CT | 06067
860.528.4168 | 1.888.862.2884 | WWW.STORMTECH.COM

ADS
4640 TRUESMAN BLVD
HILLIARD, OH 43026
1-800-733-7473

SHEET
7 OF 8

NYLOPLAST DRAIN BASIN

NTS



NOTES

- 8-30" (200-750 mm) GRATES/SOLID COVERS SHALL BE DUCTILE IRON PER ASTM A536 GRADE 70-50-05
- 12-30" (300-750 mm) FRAMES SHALL BE DUCTILE IRON PER ASTM A536 GRADE 70-50-05
- DRAIN BASIN TO BE CUSTOM MANUFACTURED ACCORDING TO PLAN DETAILS
- DRAINAGE CONNECTION STUB JOINT TIGHTNESS SHALL CONFORM TO ASTM D3212 FOR CORRUGATED HDPE (ADS & HANCOR DUAL WALL) & SDR 35 PVC
- FOR COMPLETE DESIGN AND PRODUCT INFORMATION: WWW.NYLOPLAST-US.COM
- TO ORDER CALL: 800-821-6710

A	PART #	GRATE/SOLID COVER OPTIONS		
8" (200 mm)	2808AG	PEDESTRIAN LIGHT DUTY	STANDARD LIGHT DUTY	SOLID LIGHT DUTY
10" (250 mm)	2810AG	PEDESTRIAN LIGHT DUTY	STANDARD LIGHT DUTY	SOLID LIGHT DUTY
12" (300 mm)	2812AG	PEDESTRIAN AASHTO H-10	STANDARD AASHTO H-20	SOLID AASHTO H-20
15" (375 mm)	2815AG	PEDESTRIAN AASHTO H-10	STANDARD AASHTO H-20	SOLID AASHTO H-20
18" (450 mm)	2818AG	PEDESTRIAN AASHTO H-10	STANDARD AASHTO H-20	SOLID AASHTO H-20
24" (600 mm)	2824AG	PEDESTRIAN AASHTO H-10	STANDARD AASHTO H-20	SOLID AASHTO H-20
30" (750 mm)	2830AG	PEDESTRIAN AASHTO H-20	STANDARD AASHTO H-20	SOLID AASHTO H-20

AMERICAN TOYOTA
ALBUQUERQUE, NM

DESCRIPTION
NEW STORAGE VOLUMES AND STONE VOID SYSTEM REMOVED

REV
1/28/15
3/18/15

3110 VERONA AVE
BALFORD, GA 30818
PH: (770) 932-2443
FAX: (770) 932-2448
www.nyloplast-us.com

Nyloplast

4640 TRUMAN BLVD
HILLIARD, OH 43026
1-800-233-7473
ADS
ADVANCED DRAINAGE SYSTEMS, INC.

SHEET
8 OF 8

THIS DRAWING HAS BEEN PREPARED BASED ON INFORMATION PROVIDED TO ADS UNDER THE DIRECTION OF THE SITE DESIGN ENGINEER OR OTHER PROJECT REPRESENTATIVE. THE SITE DESIGN ENGINEER SHALL REVIEW THIS DRAWING PRIOR TO CONSTRUCTION. IT IS THE ULTIMATE RESPONSIBILITY OF THE SITE DESIGN ENGINEER TO ENSURE THAT THE PRODUCTS(S) DERIVED AND ALL ASSOCIATED DETAILS MEET ALL APPLICABLE LAWS, REGULATIONS, AND PROJECT REQUIREMENTS.

DATE: 12/30/14
PROJECT #: 82394
DRAWN: WCM
CHECKED: GFI

Project: 82394 - System #1 - REV2

Chamber Model -
Units -
Number of Chambers -
Number of End Caps -
Voids in the stone (porosity) -
Base of Stone Elevation -
Amount of Stone Above Chambers -
Amount of Stone Below Chambers -
Area of system -

%
ft
in
in
sf Min. Area - 3420 sf min. area

81	0.00	0.00	0.00	0.00	95.98	95.98	14583.88	5223.00
80	0.00	0.00	0.00	0.00	95.98	95.98	14487.90	5222.92
79	0.00	0.00	0.00	0.00	95.98	95.98	14391.93	5222.83
78	0.00	0.00	0.00	0.00	95.98	95.98	14295.95	5222.75
77	0.00	0.00	0.00	0.00	95.98	95.98	14199.98	5222.67
76	0.00	0.00	0.00	0.00	95.98	95.98	14104.00	5222.58
75	0.00	0.00	0.00	0.00	95.98	95.98	14008.03	5222.50
74	0.00	0.00	0.00	0.00	95.98	95.98	13912.05	5222.42
73	0.00	0.00	0.00	0.00	95.98	95.98	13816.08	5222.33
72	0.00	0.00	0.00	0.00	95.98	95.98	13720.10	5222.25
71	0.00	0.00	0.00	0.00	95.98	95.98	13624.13	5222.17
70	0.00	0.00	0.00	0.00	95.98	95.98	13528.15	5222.08
69	0.04	0.00	3.69	0.00	94.87	98.56	13432.18	5222.00
68	0.12	0.01	10.45	0.04	92.83	103.32	13333.62	5221.92
67	0.16	0.03	14.83	0.11	91.50	106.43	13230.30	5221.83
66	0.21	0.05	18.79	0.19	90.28	109.26	13123.88	5221.75
65	0.27	0.07	24.15	0.27	88.65	113.07	13014.62	5221.67
64	0.45	0.09	40.75	0.35	83.64	124.75	12901.55	5221.58
63	0.67	0.11	59.87	0.45	77.88	138.20	12776.80	5221.50
62	0.80	0.14	71.91	0.57	74.23	146.71	12638.60	5221.42
61	0.91	0.17	81.73	0.67	71.25	153.66	12491.89	5221.33
60	1.00	0.19	90.26	0.77	68.67	159.69	12338.23	5221.25
59	1.09	0.22	97.86	0.86	66.36	165.08	12178.54	5221.17
58	1.16	0.24	104.71	0.97	64.27	169.95	12013.46	5221.08
57	1.23	0.27	111.06	1.08	62.33	174.47	11843.51	5221.00
56	1.30	0.30	116.97	1.19	60.53	178.69	11669.03	5220.92
55	1.36	0.32	122.49	1.29	58.84	182.63	11490.35	5220.83
54	1.42	0.35	127.68	1.39	57.25	186.33	11307.72	5220.75
53	1.47	0.37	132.60	1.48	55.75	189.83	11121.39	5220.67
52	1.53	0.39	137.26	1.58	54.32	193.16	10931.56	5220.58
51	1.57	0.42	141.70	1.67	52.96	196.34	10738.40	5220.50
50	1.62	0.44	145.92	1.76	51.67	199.36	10542.06	5220.42
49	1.67	0.46	149.96	1.85	50.43	202.24	10342.70	5220.33
48	1.71	0.48	153.82	1.94	49.25	205.00	10140.46	5220.25
47	1.75	0.50	157.51	2.02	48.12	207.64	9935.46	5220.17
46	1.79	0.53	161.04	2.10	47.03	210.17	9727.81	5220.08
45	1.83	0.55	164.45	2.18	45.99	212.61	9517.64	5220.00
44	1.86	0.56	167.71	2.26	44.98	214.95	9305.03	5219.92
43	1.90	0.58	170.85	2.33	44.02	217.20	9090.08	5219.83
42	1.93	0.60	173.87	2.41	43.09	219.37	8872.87	5219.75
41	1.96	0.62	176.77	2.48	42.20	221.45	8653.51	5219.67
40	2.00	0.64	179.56	2.55	41.34	223.45	8432.06	5219.58
39	2.03	0.66	182.25	2.62	40.51	225.39	8208.61	5219.50
38	2.05	0.67	184.84	2.69	39.71	227.25	7983.22	5219.42
37	2.08	0.69	187.33	2.76	38.95	229.04	7755.97	5219.33
36	2.11	0.71	189.73	2.83	38.21	230.76	7526.93	5219.25
35	2.13	0.72	192.05	2.90	37.49	232.43	7296.16	5219.17
34	2.16	0.74	194.28	2.96	36.80	234.04	7063.73	5219.08
33	2.18	0.76	196.43	3.02	36.14	235.59	6829.69	5219.00
32	2.21	0.77	198.50	3.09	35.50	237.08	6594.09	5218.92
31	2.23	0.79	200.49	3.15	34.88	238.52	6357.01	5218.83
30	2.25	0.80	202.40	3.21	34.29	239.90	6118.49	5218.75
29	2.27	0.82	204.24	3.28	33.72	241.24	5878.59	5218.67
28	2.29	0.84	206.01	3.36	33.16	242.54	5637.35	5218.58
27	2.31	0.85	207.71	3.38	32.65	243.74	5394.81	5218.50
26	2.33	0.86	209.34	3.43	32.14	244.91	5151.08	5218.42
25	2.34	0.87	210.90	3.49	31.66	246.04	4906.16	5218.33
24	2.36	0.89	212.39	3.54	31.20	247.13	4660.12	5218.25
23	2.38	0.90	213.82	3.59	30.75	248.16	4412.99	5218.17
22	2.39	0.91	215.19	3.64	30.33	249.16	4164.83	5218.08
21	2.41	0.92	216.49	3.69	29.92	250.10	3915.67	5218.00
20	2.42	0.93	217.73	3.74	29.53	251.00	3665.57	5217.92
19	2.43	0.95	218.91	3.78	29.17	251.86	3414.56	5217.83
18	2.44	0.96	220.04	3.83	28.82	252.68	3162.70	5217.75
17	2.46	0.97	221.10	3.87	28.48	253.45	2910.02	5217.67
16	2.47	0.98	222.10	3.91	28.17	254.18	2656.57	5217.58

Project: 82394 - System #3 - REV2

Chamber Model -
 Units -
 Number of Chambers -
 Number of End Caps -
 Voids in the stone (porosity) -
 Base of Stone Elevation -
 Amount of Stone Above Chambers -
 Amount of Stone Below Chambers -
 Area of system -

%

ft

in

in

sf Min. Area - 1454 sf min. area

81	0.00	0.00	0.00	0.00	41.35	41.35	6232.42	5224.00
80	0.00	0.00	0.00	0.00	41.35	41.35	6191.07	5223.92
79	0.00	0.00	0.00	0.00	41.35	41.35	6149.72	5223.83
78	0.00	0.00	0.00	0.00	41.35	41.35	6108.37	5223.75
77	0.00	0.00	0.00	0.00	41.35	41.35	6067.02	5223.67
76	0.00	0.00	0.00	0.00	41.35	41.35	6025.67	5223.58
75	0.00	0.00	0.00	0.00	41.35	41.35	5984.32	5223.50
74	0.00	0.00	0.00	0.00	41.35	41.35	5942.97	5223.42
73	0.00	0.00	0.00	0.00	41.35	41.35	5901.62	5223.33
72	0.00	0.00	0.00	0.00	41.35	41.35	5860.27	5223.25
71	0.00	0.00	0.00	0.00	41.35	41.35	5818.92	5223.17
70	0.00	0.00	0.00	0.00	41.35	41.35	5777.57	5223.08
69	0.04	0.00	1.56	0.00	40.88	42.44	5736.22	5223.00
68	0.12	0.01	4.41	0.02	40.02	44.45	5693.78	5222.92
67	0.16	0.03	6.26	0.05	39.46	45.77	5649.33	5222.83
66	0.21	0.05	7.93	0.10	38.94	46.97	5603.56	5222.75
65	0.27	0.07	10.20	0.14	38.25	48.58	5556.59	5222.67
64	0.45	0.09	17.21	0.18	36.14	53.52	5508.01	5222.58
63	0.67	0.11	25.28	0.23	33.70	59.20	5454.49	5222.50
62	0.80	0.14	30.36	0.28	32.16	62.80	5395.28	5222.42
61	0.91	0.17	34.51	0.34	30.90	65.74	5332.48	5222.33
60	1.00	0.19	38.11	0.38	29.80	68.30	5266.74	5222.25
59	1.09	0.22	41.32	0.43	28.83	70.57	5198.45	5222.17
58	1.16	0.24	44.21	0.48	27.94	72.64	5127.87	5222.08
57	1.23	0.27	46.89	0.54	27.12	74.55	5055.24	5222.00
56	1.30	0.30	49.39	0.60	26.36	76.34	4980.68	5221.92
55	1.36	0.32	51.72	0.65	25.64	78.01	4904.34	5221.83
54	1.42	0.35	53.91	0.70	24.97	79.57	4826.34	5221.75
53	1.47	0.37	55.99	0.74	24.33	81.06	4746.76	5221.67
52	1.53	0.39	57.96	0.79	23.73	82.47	4665.70	5221.58
51	1.57	0.42	59.83	0.83	23.15	83.82	4583.23	5221.50
50	1.62	0.44	61.61	0.88	22.60	85.10	4499.42	5221.42
49	1.67	0.46	63.32	0.93	22.08	86.32	4414.32	5221.33
48	1.71	0.48	64.95	0.97	21.58	87.49	4328.00	5221.25
47	1.75	0.50	66.50	1.01	21.10	88.61	4240.51	5221.17
46	1.79	0.53	67.99	1.05	20.64	89.68	4151.90	5221.08
45	1.83	0.55	69.43	1.09	20.19	90.72	4062.22	5221.00
44	1.86	0.56	70.81	1.13	19.77	91.71	3971.51	5220.92
43	1.90	0.58	72.14	1.17	19.36	92.66	3879.80	5220.83
42	1.93	0.60	73.41	1.20	18.97	93.58	3787.14	5220.75
41	1.96	0.62	74.64	1.24	18.59	94.46	3693.56	5220.67
40	2.00	0.64	75.81	1.28	18.22	95.31	3599.09	5220.58
39	2.03	0.66	76.95	1.31	17.87	96.13	3503.78	5220.50
38	2.05	0.67	78.04	1.35	17.53	96.92	3407.65	5220.42
37	2.08	0.69	79.10	1.38	17.21	97.68	3310.72	5220.33
36	2.11	0.71	80.11	1.41	16.89	98.41	3213.04	5220.25
35	2.13	0.72	81.09	1.45	16.59	99.12	3114.63	5220.17
34	2.16	0.74	82.03	1.48	16.30	99.81	3015.50	5220.08
33	2.18	0.76	82.94	1.51	16.02	100.46	2915.70	5220.00
32	2.21	0.77	83.81	1.54	15.74	101.10	2815.23	5219.92
31	2.23	0.79	84.65	1.57	15.48	101.71	2714.13	5219.83
30	2.25	0.80	85.46	1.60	15.23	102.29	2612.43	5219.75
29	2.27	0.82	86.24	1.64	14.99	102.86	2510.13	5219.67
28	2.29	0.84	86.98	1.68	14.75	103.41	2407.27	5219.58
27	2.31	0.85	87.70	1.69	14.53	103.92	2303.86	5219.50
26	2.33	0.86	88.39	1.72	14.32	104.42	2199.93	5219.42
25	2.34	0.87	89.05	1.74	14.11	104.90	2095.51	5219.33
24	2.36	0.89	89.68	1.77	13.92	105.36	1990.61	5219.25
23	2.38	0.90	90.28	1.80	13.73	105.80	1885.25	5219.17
22	2.39	0.91	90.86	1.82	13.55	106.22	1779.44	5219.08
21	2.41	0.92	91.41	1.84	13.37	106.63	1673.22	5219.00
20	2.42	0.93	91.93	1.87	13.21	107.01	1566.59	5218.92
19	2.43	0.95	92.43	1.89	13.05	107.38	1459.58	5218.83
18	2.44	0.96	92.90	1.91	12.90	107.72	1352.21	5218.75
17	2.46	0.97	93.35	1.93	12.76	108.05	1244.48	5218.67
16	2.47	0.98	93.78	1.96	12.63	108.36	1136.43	5218.58

Project: 82394 - System #2 - REV2

Chamber Model -
Units -
Number of Chambers -
Number of End Caps -
Voids in the stone (porosity) -
Base of Stone Elevation -
Amount of Stone Above Chambers -
Amount of Stone Below Chambers -
Area of system -



%
ft
in
in
sf Min. Area - 2177 sf min. area

81	0.00	0.00	0.00	0.00	61.93	61.93	9290.97	5223.00
80	0.00	0.00	0.00	0.00	61.93	61.93	9229.04	5222.92
79	0.00	0.00	0.00	0.00	61.93	61.93	9167.12	5222.83
78	0.00	0.00	0.00	0.00	61.93	61.93	9105.19	5222.75
77	0.00	0.00	0.00	0.00	61.93	61.93	9043.27	5222.67
76	0.00	0.00	0.00	0.00	61.93	61.93	8981.34	5222.58
75	0.00	0.00	0.00	0.00	61.93	61.93	8919.42	5222.50
74	0.00	0.00	0.00	0.00	61.93	61.93	8857.49	5222.42
73	0.00	0.00	0.00	0.00	61.93	61.93	8795.57	5222.33
72	0.00	0.00	0.00	0.00	61.93	61.93	8733.64	5222.25
71	0.00	0.00	0.00	0.00	61.93	61.93	8671.72	5222.17
70	0.00	0.00	0.00	0.00	61.93	61.93	8609.79	5222.08
69	0.04	0.00	2.29	0.00	61.24	63.53	8547.87	5222.00
68	0.12	0.01	6.50	0.04	59.96	66.50	8484.34	5221.92
67	0.16	0.03	9.23	0.11	59.13	68.46	8417.83	5221.83
66	0.21	0.05	11.69	0.19	58.36	70.24	8349.38	5221.75
65	0.27	0.07	15.03	0.27	57.34	72.63	8279.14	5221.67
64	0.45	0.09	25.36	0.35	54.21	79.92	8206.50	5221.58
63	0.67	0.11	37.25	0.45	50.61	88.32	8126.58	5221.50
62	0.80	0.14	44.74	0.57	48.33	93.64	8038.26	5221.42
61	0.91	0.17	50.86	0.67	46.47	97.99	7944.62	5221.33
60	1.00	0.19	56.16	0.77	44.85	101.78	7846.63	5221.25
59	1.09	0.22	60.89	0.86	43.40	105.15	7744.85	5221.17
58	1.16	0.24	65.15	0.97	42.09	108.21	7639.70	5221.08
57	1.23	0.27	69.10	1.08	40.87	111.05	7531.49	5221.00
56	1.30	0.30	72.78	1.19	39.73	113.71	7420.44	5220.92
55	1.36	0.32	76.22	1.29	38.67	116.18	7306.73	5220.83
54	1.42	0.35	79.45	1.39	37.67	118.51	7190.55	5220.75
53	1.47	0.37	82.51	1.48	36.73	120.72	7072.04	5220.67
52	1.53	0.39	85.41	1.58	35.83	122.81	6951.32	5220.58
51	1.57	0.42	88.17	1.67	34.97	124.81	6828.50	5220.50
50	1.62	0.44	90.80	1.76	34.16	126.72	6703.69	5220.42
49	1.67	0.46	93.31	1.85	33.38	128.54	6576.97	5220.33
48	1.71	0.48	95.71	1.94	32.63	130.28	6448.44	5220.25
47	1.75	0.50	98.00	2.02	31.92	131.94	6318.16	5220.17
46	1.79	0.53	100.20	2.10	31.23	133.54	6186.22	5220.08
45	1.83	0.55	102.32	2.18	30.57	135.08	6052.68	5220.00
44	1.86	0.56	104.35	2.26	29.94	136.55	5917.60	5219.92
43	1.90	0.58	106.31	2.33	29.33	137.97	5781.05	5219.83
42	1.93	0.60	108.18	2.41	28.75	139.34	5643.08	5219.75
41	1.96	0.62	109.99	2.48	28.18	140.65	5503.74	5219.67
40	2.00	0.64	111.73	2.55	27.64	141.92	5363.09	5219.58
39	2.03	0.66	113.40	2.62	27.12	143.14	5221.17	5219.50
38	2.05	0.67	115.01	2.69	26.61	144.32	5078.03	5219.42
37	2.08	0.69	116.56	2.76	26.13	145.45	4933.71	5219.33
36	2.11	0.71	118.05	2.83	25.66	146.54	4788.26	5219.25
35	2.13	0.72	119.50	2.90	25.21	147.60	4641.71	5219.17
34	2.16	0.74	120.89	2.96	24.77	148.62	4494.12	5219.08
33	2.18	0.76	122.22	3.02	24.35	149.60	4345.50	5219.00
32	2.21	0.77	123.51	3.09	23.95	150.54	4195.90	5218.92
31	2.23	0.79	124.75	3.15	23.56	151.45	4045.36	5218.83
30	2.25	0.80	125.94	3.21	23.18	152.33	3893.91	5218.75
29	2.27	0.82	127.08	3.28	22.82	153.18	3741.58	5218.67
28	2.29	0.84	128.18	3.36	22.46	154.01	3588.40	5218.58
27	2.31	0.85	129.24	3.38	22.14	154.76	3434.39	5218.50
26	2.33	0.86	130.25	3.43	21.82	155.51	3279.63	5218.42
25	2.34	0.87	131.22	3.49	21.51	156.22	3124.12	5218.33
24	2.36	0.89	132.15	3.54	21.22	156.91	2967.90	5218.25
23	2.38	0.90	133.04	3.59	20.93	157.57	2810.99	5218.17
22	2.39	0.91	133.89	3.64	20.66	158.20	2653.42	5218.08
21	2.41	0.92	134.71	3.69	20.41	158.80	2495.22	5218.00
20	2.42	0.93	135.48	3.74	20.16	159.38	2336.42	5217.92
19	2.43	0.95	136.21	3.78	19.93	159.92	2177.04	5217.83
18	2.44	0.96	136.91	3.83	19.70	160.44	2017.12	5217.75
17	2.46	0.97	137.57	3.87	19.49	160.93	1856.68	5217.67
16	2.47	0.98	138.20	3.91	19.29	161.40	1695.74	5217.58

CAUTION:
EXISTING UTILITIES ARE NOT SHOWN.
IT SHALL BE THE SOLE RESPONSIBILITY
OF THE CONTRACTOR TO CONDUCT ALL
NECESSARY FIELD INVESTIGATIONS PRIOR
TO ANY EXCAVATION TO DETERMINE THE
ACTUAL LOCATION OF UTILITIES & OTHER
IMPROVEMENTS.

EROSION CONTROL NOTES:

1. CONTRACTOR IS RESPONSIBLE FOR OBTAINING A TOPSOIL DISTURBANCE PERMIT PRIOR TO BEGINNING WORK.
2. CONTRACTOR IS RESPONSIBLE FOR MAINTAINING RUN-OFF ON SITE DURING CONSTRUCTION.
3. CONTRACTOR IS RESPONSIBLE FOR CLEANING ALL SEDIMENT THAT GETS INTO EXISTING RIGHT-OF-WAY.
4. REPAIR OF DAMAGED FACILITIES AND CLEANUP OF SEDIMENT ACCUMULATIONS ON ADJACENT PROPERTIES AND IN PUBLIC FACILITIES IS THE RESPONSIBILITY OF THE CONTRACTOR.
5. ALL EXPOSED EARTH SURFACES MUST BE PROTECTED FROM WIND AND WATER EROSION PRIOR TO FINAL ACCEPTANCE OF ANY PROJECT.



LEGAL DESCRIPTION:

NOTES:

1. ALL SPOT ELEVATIONS REPRESENT FLOWLINE ELEVATION UNLESS OTHERWISE NOTED.
2. ALL CURB AND GUTTER TO 6" HEADER UNLESS OTHERWISE NOTED.
3. ALL RETAINING WALL DESIGN SHALL BE BY OTHERS.
4. ALL LANDSCAPE MEDANS WILL BE DEPRESSURED 8" FROM FLOW LINE AND 1' CURB OPENING PROVIDED ON THE 100' SIDE, FOR WATER QUALITY.

LEGEND

- 5410 --- EXISTING CONTOUR
- 5415 --- EXISTING INDEX CONTOUR
- 5416 --- PROPOSED CONTOUR
- 5416 --- PROPOSED INDEX CONTOUR
- 5416 --- SLOPE 1% TO
- 5416 --- EXISTING SPOT ELEVATION
- 5416 --- PROPOSED SPOT ELEVATION
- 5416 --- BOUNDARY
- 5416 --- CENTERLINE
- 5416 --- RIGHT-OF-WAY
- 5416 --- PROPOSED CURB AND GUTTER
- 5416 --- EXISTING CURB AND GUTTER
- 5416 --- PROPOSED SIDEWALK
- 5416 --- PROPOSED SETBACK
- 5416 --- PROPOSED LOT LINE
- 5416 --- PROPOSED SCREEN WALL
- 5416 --- PROPOSED RETAINING WALL
- 5416 --- LIMITS OF FLOODPLAIN



ROUGH GRADING APPROVAL

ENGINEER'S SEAL	AMERICAN TOYOTA	DRAWN BY: MCH
		DATE: 3-17-15
	GRADING AND DRAINAGE PLAN	PUB-1487-1-03-11
	Rio Grande Engineering	SHEET #
	1000 CENTRAL AVENUE SE SUITE 100 ALBUQUERQUE, NM 87104 (505) 275-0888	JOB #
DAVID SOULE P.E. #14522		21403