# CITY OF ALBUQUERQUE



June 2, 2015

David Soule, P.E. Rio Grande Engineering P.O. Box 93924 Albuquerque, NM 87199

Toyota Temporary Parking Lot, Grading and Drainage Plan Re: Certification dated –no date-Engineer's Stamp Date 4-13-15 (C18D083)

Dear Mr. Soule,

Based upon the information provided in your submittal received 4-28-15, the above referenced plan is acceptable for Site Plan for Building Permit and Building Permit approval for the Toyota project across the street.

PO Box 1293

This certification was not dated, the approved plan date in the certification language is incorrect (5-16-13 vs. 4-13-15) and the status of the Work Order was not provided as stated in the approval letter dated 4-21-15. The City does not wish to hold up progress on the Toyota site across the street due to administrative errors and the project manager explained the progress of the Work Order on 6-2-15 to the City's satisfaction.

Albuquerque

Therefore, after the drainage work in the City ROW and the site work that was not completed are complete; submit an engineer's certification on the plan dated 4-13-15. New Mexico 87103 Acceptance of the certification is required prior to obtaining Certificate of Occupancy on the Toyota building across the street.

If you have any questions, you can contact me at 924-3420.

www.cabq.gov

Sincerely,

Cuth a cheve

Curtis Cherne, P.E.

Principal Engineer, Stormwater Quality

For Hydrology

Planning Dept.

e-mail



# City of Albuquerque

# Planning Department

noche patrici

# Development & Building Services Division

# DRAINAGE AND TRANSPORTATION INFORMATION SHEET

(REV 02/2013)

| Project Title: AMERICAN TOYOTA                           | Building Permit #:     | City Drainage #: C18D083   |
|--|------------------------|--|
| DRB#: EPC#:  |                        | Work Order#:   |
| Legal Description: LOTS 1-3 &30-32 BLOCK 28, TRACT A, UI | NT B NORTH ALB ACES    |  |
| City Address: OAKLAND BETWEEN SAN PEDRO AND LOUIS        | SIANA                  |  |
| Engineering Firm: RIO GRANDE ENGINEERING                 |                        | Contact: DAVID SOULE   |
| Address: PO BOX 93924, ALBUQUERQUE, NM 87199             |                        |  |
| Phone#: 505.321.9099 Fax#: 5                             | 05.872.0999            | E-mail: DAVID@RIOGRANDEENGINEERING.COM   |
| Owner: VANDY INVESTMENTS,LLC                             |                        | Contact:   |
| Address: 6501 EAGLE ROCK                                 |                        |  |
| Phone#: Fax#:  |                        | E-mail:  |
| Architect: John Mahoney                                  |                        | Contact:   |
| Address:   |                        |  |
| Phone#: Fax#:  |                        | E-mail:  |
| Surveyor: CONSTRUCTION SURVEY TECHNOLOGIES               |                        | Contact: JOHN GALLEGOS   |
| Address:   |                        |  |
| Phone#: 917.8921 Fax#:                                   |                        | E-mail:  |
| Contractor:  |                        | Contact:   |
| Address:   |                        |  |
| Phone#:  |                        | E-mail:  |
| TYDE OF CUDATETAL.                                       | CHECK TYPE OF ADDROV   | AT /ACCEDTANCE COLICIET.   |
| TYPE OF SUBMITTAL:  DRAINAGE REPORT                      | SIA/FINANCIAL GUARAN   | TEE RELEASE AND LANGE  |
| DRAINAGE REFORT  DRAINAGE PLAN 1st SUBMITTAL             | PRELIMINARY PLAT APP   | POVAI  |
| DRAINAGE I LAN 130 SUBMITTAL  DRAINAGE PLAN RESUBMITTAL  | S. DEV. PLAN FOR SUB'D |  |
| CONCEPTUAL G & D PLAN                                    | S. DEV. FOR BLDG. PERM |  |
| GRADING PLAN   | SECTOR PLAN APPROVAL   | greeners control to the property of the proper |
| EROSION & SEDIMENT CONTROL PLAN (ESC                     |                        | In MAY 2 8 2015  |
| X ENGINEER'S CERT (HYDROLOGY)                            | CERTIFICATE OF OCCUPA  |  |
| CLOMR/LOMR   |                        | ANCY (TGL TEMP) OPMENT SECTION   |
| TRAFFIC CIRCULATION LAYOUT (TCL)                         | FOUNDATION PERMIT AF   | PROVAL.  |
| ENGINEER'S CERT (TCL)                                    | BUILDING PERMIT APPRO  |  |
| ENGINEER'S CERT (DRB SITE PLAN)                          | GRADING PERMIT APPRO   |  |
| ENGINEER'S CERT (ESC)                                    | PAVING PERMIT APPROV   |  |
| SO-19  | WORK ORDER APPROVAL    |  |
| OTHER (SPECIFY)  | GRADING CERTIFICATION  |  |
| WAS A PRE-DESIGN CONFERENCE ATTENDED:                    | Yes X No Co            | opy Provided   |
| DATE SUBMITTED: 5/29/                                    | By:                    |  |

Requests for approvals of Site Development Plans and/or Subdivision Plats shall be accompanied by a drainage submittal. The particular nature, location, and scope to the proposed development defines the degree of drainage detail. One or more of the following levels of submittal may be required based on the following

- 1. Conceptual Grading and Drainage Plan: Required for approval of Site Development Plans greater than five (5) acres and Sector Plans
- 2. Drainage Plans: Required for building permits, grading permits, paving permits and site plans less than five (5) acres
- 3. Drainage Report: Required for subdivision containing more than ten (10) lots or constituting five (5) acres or more
- 4. Erosion and Sediment Control Plan: Required for any new development and redevelopment site with 1-acre or more of land disturbing area, including project less than 1-acre than are part of a larger common plan of development

# CITY OF ALBUQUERQUE



April 21, 2015

David Soule, P.E.
Rio Grande Engineering
P.O. Box 93924
Albuquerque, NM 87199

Re: Toyota Temporary Parking Lot, Grading and Drainage Plan Engineer's Stamp Date 4-13-15 (C18D083)

Dear Mr. Soule,

Based upon the information provided in your submittal received 4-13-15, the above referenced plan is approved for Work Order and Paving Permit.

As mentioned at DRB, the work is to be complete and this plan certified prior to Hydrology signing the Site Plan for the American Toyota project across the street.

PO Box 1293

It may be difficult to certify the work in the ROW, as this process may take more time. However, please include the status, if not complete, of the Work Order in a separate letter, e.g. construction plans complete, Work Order approved, etc..., when submitting the certification.

Albuquerque

If you have any questions, you can contact me at 924-3420.


NM 87103

www.cabq.gov

Sincerely,

Curtis Cherne, P.E. Principal Engineer Planning Dept.

C: e-mail



# City of Albuquerque

# Planning Department

# Development & Building Services Division

## DRAINAGE AND TRANSPORTATION INFORMATION SHEET

(REV 02/2013)

| Project Title: AMERICAN TOYOTA                        | Building Permit #:                    | City Drainage #: C18D083                             |
|---|---------------------------------------|--|
| DRB#: EPC#  | •                                     | Work Order#:   |
| Legal Description: LOTS 1-3 &30-32 BLOCK 28, TRACT A, | UNT B NORTH ALB ACES                  |  |
| City Address: OAKLAND BETWEEN SAN PEDRO AND LOU       | JISIANA                               |  |
| Engineering Firm: RIO GRANDE ENGINEERING              |                                       | Contact: DAVID SOULE                                 |
| Address: PO BOX 93924, ALBUQUERQUE, NM 87199          |                                       | · · · · · · · · · · · · · · · · · · ·                |
| Phone#: 505.321.9099 Fax#:                            | 505.872.0999                          | E-mail: DAVID@RIOGRANDEENGINEERING.COM               |
| Owner: VANDY INVESTMENTS,LLC                          |                                       | Contact:   |
| Address: 6501 EAGLE ROCK                              |                                       |  |
| Phone#: Fax#:   |                                       | E-mail:  |
| Architect: John Mahoney                               |                                       | Contact:   |
| Address:  |                                       |  |
| Phone#: Fax#:   | ·<br>·                                | E-mail:  |
| Surveyor: CONSTRUCTION SURVEY TECHNOLOGIES            |                                       | Contact: JOHN GALLEGOS                               |
| Address:  | · · · · · · · · · · · · · · · · · · · |  |
| Phone#: 917.8921 Fax#:                                | ·<br>·                                | E-mail:  |
| Contractor:   |                                       | Contact:   |
| Address:  |                                       |  |
| Phone#: Fax#:   | · · · · · · · · · · · · · · · · · · · | E-mail:  |
| TYPE OF SUBMITTAL:                                    | CHECK TYPE OF APPROV                  | AL/ACCEPTANCE SOUGHT:                                |
| DRAINAGE REPORT                                       | SIA/FINANCIAL GUARAN                  | TEE RELEASE  |
| DRAINAGE PLAN 1st SUBMITTAL                           | PRELIMINARY PLAT APP                  |  |
| DRAINAGE PLAN RESUBMITTAL                             | S. DEV. PLAN FOR SUB'D                | APPROVAL IN E (당 돈 I V 토 I)                          |
| CONCEPTUAL G & D PLAN                                 | S. DEV. FOR BLDG. PERM                | [  |
| GRADING PLAN  | SECTOR PLAN APPROVA                   | L  |
| EROSION & SEDIMENT CONTROL PLAN (ES                   | SC) FINAL PLAT APPROVAL               |  |
| ENGINEER'S CERT (HYDROLOGY)                           | CERTIFICATE OF OCCUPA                 | ANCY (PERM) AND DEVISION SECTION                     |
| CLOMR/LOMR  | CERTIFICATE OF OCCUPA                 | ANCY (PERM) LAND DEVELOPMENT SECTION ANCY (TCL THMP) |
| TRAFFIC CIRCULATION LAYOUT (TCL)                      | FOUNDATION PERMIT A                   | PPROVAL  |
| ENGINEER'S CERT (TCL)                                 | BUILDING PERMIT APPRO                 | OVAL   |
| ENGINEER'S CERT (DRB SITE PLAN)                       | × GRADING PERMIT APPRO                | OVAL SO-19 APPROVAL                                  |
| ENGINEER'S CERT (ESC)                                 | PAVING PERMIT APPROV                  | AL ESC PERMIT APPROVAL                               |
| SO-19   | WORK ORDER APPROVA                    | ESC CERT. ACCEPTANCE                                 |
| OTHER (SPECIFY)                                       | GRADING CERTIFICATIO                  | OTHER (SPECIFY)                                      |
| WAS A PRE-DESIGN CONFERENCE ATTENDED:                 | Yes X No C                            | opy Provided   |
| DATE SUBMITTED: 4/11/15                               | By:                                   |  |

Requests for approvals of Site Development Plans and/or Subdivision Plats shall be accompanied by a drainage submittal. The particular nature, location, and scope to the proposed development defines the degree of drainage detail. One or more of the following levels of submittal may be required based on the following

- 1. Conceptual Grading and Drainage Plan: Required for approval of Site Development Plans greater than five (5) acres and Sector Plans
- 2. Drainage Plans: Required for building permits, grading permits, paving permits and site plans less than five (5) acres
- 3. Drainage Report: Required for subdivision containing more than ten (10) lots or constituting five (5) acres or more
- 4. Erosion and Sediment Control Plan: Required for any new development and redevelopment site with 1-acre or more of land disturbing area, including project less than 1-acre than are part of a larger common plan of development

Mr. Curtis Cherne, PE
Hydrology Department
Public Works Department
City of Albuquerque

RE: Grading Plan

**Toyota Temporary Lot** 

C18D083

Albuquerque, New Mexico

Dear Mr. Cherne:

The purpose of this letter is to accompany the enclosed grading plan. The grading plan has been modified to address your written comments dated April 7, 2015. The following is a summary of your comment and a response as to how we addressed the comment.

1. It appears an asphalt curb is needed to force the water into the first flush pond. In addition erosion protection is required where concentrated flows enter the ponds

We have added the curb and called for rip rap to be placed at the location concentrated flows enter the ponds.


2. Work within the right of way requires a work orderWe have added this note to the plan set.


Should you have any questions regarding this matter, please do not hesitate to call me.

Sincerely,

David Soule, PE RIO GRANDE ENGINEERING PO Box 93924 ALBUQUERQUE, NM 87199 321-9099

**Enclosures** 





# CITY OF ALBUQUERQUE



April 7, 2015

David Soule, P.E.
Rio Grande Engineering
P.O. Box 93924
Albuquerque, NM 87199

Re: Toyota Temporary Parking Lot, Grading and Drainage Plan Engineer's Stamp Date 2-24-15 (C18D083)

Dear Mr. Soule,

Based upon the information provided in your submittal received 2-25-15, the above referenced plan is approved for Work Order, however, it cannot be approved for Grading or Paving Permit until the following comments area addressed:

- 1. It appears a large portion of Onsite Basin A will drain to Oakland Ave ROW rather than to the northern onsite pond. Since the millings have already been laid, an asphalt curb could be constructed form the west edge of the millings east to the proposed 35 contour. Millings or similar should be laid where these concentrated flows will enter the pond to prevent erosion.
- 2. The work in the ROW will be built per the Work Order process, including the asphalt apron in Oakland Ave. Add a note to the existing build notes, that these times will be built per Work Order.

NM 87103 If you have any questions, you can contact me at 924-3420.

www.cabq.gov

PO Box 1293


Albuquerque

Curtis Cherne, P.E.
Principal Engineer

Planning Dept.


Sincerely,

C: e-mail



Albuquerosce - Making History 1 do 2006

# CITY OF ALBUQUERQUE



April 7, 2015

David Soule, P.E.
Rio Grande Engineering
P.O. Box 93924
Albuquerque, NM 87199

Re: Toyota Temporary Parking Lot, Grading and Drainage Plan Engineer's Stamp Date 2-24-15 (C18D083)

Dear Mr. Soule,

Based upon the information provided in your submittal received 2-25-15, the above referenced plan is approved for Work Order, however, it cannot be approved for Grading or Paving Permit until the following comments area addressed:

- 1. It appears a large portion of Onsite Basin A will drain to Oakland Ave ROW rather than to the northern onsite pond. Since the millings have already been laid, an asphalt curb could be constructed form the west edge of the millings east to the proposed 35 contour. Millings or similar should be laid where these concentrated flows will enter the pond to prevent erosion.
- 2. The work in the ROW will be built per the Work Order process, including the asphalt apron in Oakland Ave. Add a note to the existing build notes, that these times will be built per Work Order.

NM 87103 If you have any questions, you can contact me at 924-3420.

PO Box 1293


Albuquerque

www.cabq.gov

Curtis Cherne, P.E.
Principal Engineer
Planning Dept.

Sincerely,

C: e-mail



# City of Albuquerque

# Planning Department

# Development & Building Services Division DRAINAGE AND TRANSPORTATION INFORMATION SHEET

(REV 02/2013)

C18D083

| Project Title: AMERICAN TOYOTA -temp construction   | yard Building Permit #:               | City Drainage #: CTOGOT2                         |
|---|---------------------------------------|--|
| DRB#:   | EPC#:                                 | Work Order#:                                     |
| Legal Description: LOTS 1-3 &30-32 BLOCK 28, TRA  | CT A, UNT B NORTH ALB ACES            |  |
| City Address: OAKLAND BETWEEN SAN PEDRO AN  | D LOUISIANA                           | <u></u>  |
| Engineering Firm: RIO GRANDE ENGINEERING  |                                       | Contact: DAVID SOULE                             |
| Address: PO BOX 93924, ALBUQUERQUE, NM 8719   | 9                                     |  |
|   | Fax#: 505.872.0999                    | E-mail: DAVID@RIOGRANDEENGINEERING.COM           |
| T INCOLUMN TO THE TOTAL TO THE |                                       |  |
| Owner: VANDY INVESTMENTS,LLC  |                                       | Contact:   |
| Address: 6501 EAGLE ROCK  |                                       |  |
| Phone#:   | Fax#:                                 | E-mail:  |
| Architect: John Mahoney   |                                       | Contact:   |
| Address:  | · · · · · · · · · · · · · · · · · · · |  |
| ·   | Fax#:                                 | E-mail:  |
|   |                                       |  |
| Surveyor: CONSTRUCTION SURVEY TECHNOLOG   | BIES                                  | Contact: JOHN GALLEGOS                           |
| Address:  |                                       |  |
| Phone#: 917.8921  | Fax#:                                 | E-mail:  |
| Contractor:   |                                       | Contact:   |
| Address:  |                                       |  |
| <del></del>   | Fax#:                                 | E-mail:  |
|   |                                       | AL/ACCEPTANCE SOUGHT:                            |
| TYPE OF SUBMITTAL:  | SIA/FINANCIAL GUARAN                  |  |
| DRAINAGE REPORT DRAINAGE PLAN 1st SUBMITTAL   | PRELIMINARY PLAT APP                  |  |
| x DRAINAGE PLAN ISCOUDING TAL   | S. DEV. PLAN FOR SUB'D                |  |
| CONCEPTUAL G & D PLAN   | S. DEV. FOR BLDG. PERM                | TT ADDDONAT                                      |
| X GRADING PLAN  | SECTOR PLAN APPROVA                   |  |
| EROSION & SEDIMENT CONTROL PLA  | <del>(,, ', , ''' '''' ''''</del>     |  |
| ENGINEER'S CERT (HYDROLOGY)   | CERTIFICATE OF OCCUPA                 | ANCY (PERM) LAND DEVELOPMENT SEC                 |
| CLOMR/LOMR  | CERTIFICATE OF OCCUPA                 | ANCY (TCL TEMP)                                  |
| TRAFFIC CIRCULATION LAYOUT (TCI   | FOUNDATION PERMIT AI                  | PPROVAL  |
| ENGINEER'S CERT (TCL)   | BUILDING PERMIT APPRO                 | OVAL   |
| ENGINEER'S CERT (DRB SITE PLAN)   | × GRADING PERMIT APPRO                | <del></del>                                      |
| ENGINEER'S CERT (ESC)   | PAVING PERMIT APPROV                  |  |
| SO-19   | WORK ORDER APPROVA                    | <del>*************************************</del> |
| OTHER (SPECIFY)   | GRADING CERTIFICATIO                  | N OTHER (SPECIFY)                                |
| WAC A DOD DECICAL CONTENDENTATOR ATTENTATES   | ED. Voc Y No C                        | opy Provided                                     |
| WAS A PRE-DESIGN CONFERENCE ATTEND  |                                       | opy i tovided                                    |
| DATE SUBMITTED: 2/25/15   | By:                                   |  |

Requests for approvals of Site Development Plans and/or Subdivision Plats shall be accompanied by a drainage submittal. The particular nature, location, and scope to the proposed development defines the degree of drainage detail. One or more of the following levels of submittal may be required based on the followin

- Conceptual Grading and Drainage Plan: Required for approval of Site Development Plans greater than five (5) acres and Sector Plans
- Drainage Plans: Required for building permits, grading permits, paving permits and site plans less than five (5) acres
- Drainage Report: Required for subdivision containing more than ten (10) lots or constituting five (5) acres or more
- Erosion and Sediment Control Plan: Required for any new development and redevelopment site with 1-acre or more of land disturbing area, including project less than 1-acre than are part of a larger common plan of development

February 25, 2015

Ms. Rita Harmon
Senior Engineer
Hydrology Department
Public Works Department
City of Albuquerque

RE: Revised Grading Plan (C-18D012)

**American Toyota-Temporary Construction Lot** 

Albuquerque, New Mexico

Dear Ms. Harmon:

The purpose of this letter is to accompany the enclosed revised grading plan. The plan has been revised to accommodate your written comments dated 2/6/15. The following is a summary of your comment and the narrative as to how we addressed:

Determination of infrastructure required shall be required.
 I have enclosed letter of concurrence from the planning director, acknowledging the use is temporary so no permanent improvements required.

2. Upland flows were based upon developed due to master plan requirements of the future development, use existing conditions.

We have shown existing conditions, the entire area does not drain to this site. A portion of the upland basin goes out of an existing driveway to alameda. This shown on the upland basin map

3. Basin 1a needs to be modified to account for parked cars.

The land treatment is millings and gravel. Therefore land treatment C. We have increased the land treatment to 40% D, which accounts for cars and consolidation of drive isles, I am not sure it is appropriate to consider the land a car is parked on as 100% impervious. The site sheet flows and water flows under the cars and infiltration occurs. We feel our land treatment types are appropriate and conservative.

4. Some ponds may be needed due to increase in land treatment

We have provided a more detailed basin map and used conservative land treatment and the flow is less than allowed so pond is provided just for first flush, we have increased the pond sizes just to be more conservative.

5. Lot appears to have 2 basins; the pond connection pipe needs a slope.

We have added an onsite basin map and the site contains 4 basins. We have adjusted the grades such that the flow passing thru the pipe is less than its capacity. A pipe

FEB 2 5 2015

LAND DEVELOPMENT SECTION I

calculation has been added

- 6. Update sump calculations. How will emergency over flow be handled.
  We have updated the orifice calculation for the modified grates. We have a double grate with a 1.5' head. In the event of clogging the flow will continue to flow into San Pedro as it currently does.
- 7. Prove capacity of Oakland and san Pedro storm drain
  We have included excerpts from the drainage report used to construct the storm drain.
  We have also included the as built of the line. A 24" stub was added but not discussed in the report. The san Pedro storm drain anticipates a 45cfs addition at Oakland. The as built show 46 cfs, we are discharging 47.6 cfs between the Oakland stub and the onsite stub, Due to the large ponds, the true flow leaving site will be diminished but I have not completed a model to show how retention pond shave the peak. Due to the construction of the stub, additional flow was expected at this point and since our site is in accordance to the master drainage plan, we feel the 47.6 cfs is acceptable to the system.

Should you have any questions regarding this matter, please do not hesitate to call me.

Sincerely,


David Soule, PE

RIO GRANDE ENGINEERING

PO Box 93924

ALBUQUERQUE, NM 87199

321-9099



# CITY OF ALBUQUERQUE

## PLANNING DEPARTMENT - Development Review Services



Richard J. Berry, Mayor

February 6, 2015

David Soule, P.E.
Rio Grande Engineering
P.O. Box 93924
Albuquerque, NM 87199

RE: American Toyota – Temporary Lot (File: C18D012)
Conceptual Grading and Drainage Plan, Engineer's Stamp Date 1-9-15

Dear Mr. Soule:

Albuquerque

www.cabq.gov

Based upon the information provided in your submittal received 1-20-15, the above referenced submittal cannot be approved for action by the DRB on the Site Plan for Building Permit, nor Grading Permit, until the following comments are addressed:

- 1. Determination of whether or not infrastructure improvements are required for the temporary site plan is to be determined by City Legal, Zoning, and the Planning Director. Comments provided herein are cursory until such determination is made.
- PO Box 1293

  2. The upland flows are 38.4 cfs based on a fully developed condition, and based on 9.72
  Acres. However, Eagle Crest Subdivision is a 12.4 Acres subdivision and is not intended to drain across this lot in the fully developed condition (C18D064B).

  Therefore offsite drainage should be based on existing land treatments, and 12.4 Acres.
  - Basin A1 land treatments should be modified such that half the Treatment C is a Treatment D. The reason for the increase is that rows of vehicles will cause concentrated flows along the edge of the parking rows and to account for such, half the treatment C area should be treated as a D.
- New Mexico 8<sup>-103</sup> 4. With the increase in land treatments, some ponding may be required to maintain the allowable discharge.
  - Lot appears to be 2 basins, with the south side flowing into a pond and then through a 12' CMP at 0.0 %. Show pipe has capacity. Pipe should have a minimum slope.
     Sump inlet calculations should show how the area is calculated. As we discussed, it
  - would be helpful to have a full spreadsheet, similar to the street capacity calculations, that can be copied and used for similar type inlets. If the grate gets clogged how will emergency overflow be handled.
  - 7. Can the Storm Drain in Oakland and San Pedro support the proposed flows per the design assumptions? What were they designed for?

If you have any questions, you can contact me at 924-3695.

FEB 2 5 2015

LAND DEVELOPMENT SECTION


Sincerely,


Rita Harmon, P.E.

Senior Engineer, Planning Dept. Development Review Services

Orig: Drainage file

c.pdf: via Email: Recipient





February 18, 2015

Suzanne Lubar, Director Planning Department City of Albuquerque 600 Second Street NW Albuquerque, NM 87102

RE: Lots 30 through 32 and Lots 1 through 3, Tract A, Unit B of the North Albuquerque Acres

Dear Ms. Lubar:

The purpose of this letter is to explain and request concurrence with our request for a temporary construction storage yard on the subject property. I met with you and Brennon Williams, Zoning Manager on February 6, 2015 to discuss this request, which resulted in this approach.

Miller Family Real Estate would like to utilize the subject property for construction yard, which is a permissive use during the reconstruction of the American Toyota Facility to the west, located on the northwest corner of Alameda Boulevard NE and San Pedro Drive NE. The Site Plan for Building Permit for reconstruction of the American Toyota dealership has been approved by the EPC and is in the process of obtaining final sign-off from the DRB.

Miller Family Real Estate has leased the six lots to the east from Vandy investments LLC. The six lots are zoned SU-2 for HC or SU-2 for NC. According to the North I-25 Sector Development Plan, HC is the old zoning for the property, while NC is the new zoning as proposed by the Sector Plan. Permissive uses under the SU-2 for NC zone include C-1 permissive and conditional uses. Per §14-16-2-16(A)(13) of the Zoning Code, the following is a permissive use under the C-1 zone: "Storage structure or yard for equipment, material, or activity incidental to a specific construction project, provided it is of a temporary nature and is moved after the specific construction project is completed, or work on the project has been dormant for a period of six or more months, and further provided that it is limited to a period of one year unless the time is extended by the Planning Director."

As illustrated by the attached Site Plan, we have provided setbacks on the east and north sides for drainage. The surfacing of the temporary construction yard is proposed to be asphalt millings. The millings and all improvements will be removed once the construction is complete. Due to the temporary nature of the use, no landscaping or utilities are proposed. There will be a new security fence located inside the existing fence on the perimeter. The plan proposes to use the light fixtures during this interim condition that will be permanently installed at the new dealership to the west. All

AND DEVELOPMENT SECTION



activity on the site will be done by employees, so the public will not have access to this lot.

Landscape Architecture
Urban Design
Planning Services

This request shall follow all standard permitting requirements including the fence, inspection of light footings, and the preparation and approval of electrical and grading plans.

Please do not hesitate to contact me at 764-9801 with any questions or additional information you may need.

wow

302 Eighth St. NW . Albuquerque, NM 87102

(505) 764-9801 Fax 842-5495 co@consensusplanni

cp@consensusplanning.com

Sincerely,

James K. Strozier, AI2P

CONCURRENCE

Principal

Signature:

Date: 2/20


PRINCIPALS


James K. Strozier, AICP
Christopher J. Green, PLA,
ASLA, LEED AP
Jacqueline Fishman, AICP
Laurie Firor, PLA, ASLA

FEE 2 5 2015

LAND DEVELOPMENT SECTION

## NAADMP EXCERPTS






## TABLE A-2 (cont.)

## LA CUEVA ARROYO SUB-BASIN CHARACTERISTICS


| Besin ID                               | Hydrologic | Basin Area | Lau | d Trea | tment ( | (%)   | TP    |
|--|------------|------------|-----|--------|---------|-------|-------|
|  | Condition  | (mi²)      | A   | B      | C       | D     | (pra) |
| 113*                                   | Existing   | .1136      | 80  | 0      | 15      | 5     | .133  |
|  | Future     | 1000       | 0   | 25     | 15      | 60    | .133  |
| 115*                                   | Existing   | .1337      | 80  | O      | 15      | 5     | .133  |
| ************************************** | Future     | .1202      | 0   | 26     | 12      | 62    | .133  |
| 116*                                   | Existing   | .1309      | 80  | 0      | 5       | 15    | .133  |
| 116.1                                  | Future     | .1000      | 0   | 25     | 15      | 50    | .133  |
| 116.2                                  | Future     | .0719      | 0   | 25     | 15      | 60 50 | .133  |
| 116.21                                 | Future     | .0344      | 0   | 40     | 20      | 40    | .133  |
| 117.2*                                 | Existing   | .1391      | 73  | 0      | 7       | 20    | .22   |
|  | Future     | .0500      | 0   | 34     | 16      | 50    | .133  |
| 117.21*                                | Existing   | .0234      | 0   | 34     | 16      | 50    | .133  |
| 117.22*                                | Future     | .0156      | 0   | 20     | 10      | 70    | .133  |
| 117.3*                                 | Existing   | .0863      | 65  | . 5    | 15      | 15.   | .133  |
|  | Future     | .1172      | 0   | 34     | 16      | 50    | .133  |
| 117.31*                                | Existing   | .0250      | 0   | 34     | 16      | 50    | .133  |
| 117.32*                                | Existing   | .0090      | 0   | 34     | 16      | 50    | .133  |
| 117.4*                                 | Existing   | .0750      | 85  | 0      | 5       | 10    | .133  |
|  | Future     | .0512      | 0   | 25     | 15      | 60    | .133  |
| 117.5*                                 | Existing   | .0550      | 0   | 10     | 20      | 70    | .133  |
|  | Future     | .0550      | 0   | 10     | 20      | 70    | .133  |
| 118                                    | Existing   | .0649      | 0   | 20     | 10      | 70    | .133  |
|  | Future     | .0649      | 0   | 20     | 10      | 70    | .133  |
| 118.1                                  | Existing   | .0306      | 75  | 5      | 10      | 10    | .133  |
|  | Future     | .0306      | 0   | 20     | 30      | 50    | .133  |
| 119                                    | Existing   | .0549      | 0   | 20     | 10.     | 70    | .133  |
|  | Future     | .0549      | 0   | 20     | 10      | 70    | .133  |
| 120                                    | Existing   | .0268      | 50  | 0      | 0       | 50    | .133  |
|  | Future     | .0268      | 0   | 20     | 10      | 70    | .133  |
| 121                                    | Existing   | .0489      | 80  | 0      | 15      | 5     | .133  |
|  | Future     | .0489      | 0   | 20     | 10      | 70    | .133  |

<sup>\*</sup>Modified for COA NAA MDP 9/97

A:97-000MASTER.PLN



### SITE HYDROLOGY



## Weighted E Method

#### AMERICAN TOYOTA TEMPORARY YARD

|                        |        |         |             |         |           |         |        |         |           |         | 100-Year, 6-hr | •       |              | 10-day  |
|------------------------|--------|---------|-------------|---------|-----------|---------|--------|---------|-----------|---------|----------------|---------|--------------|---------|
| Basin                  | Area   | Area    | Treatment   | A       | Treatment | В       | Treatm | ent C   | Treatment | D       | Weighted E     | Volume  | Flow         | Volume  |
|                        | (sf)   | (acres) | %           | (acres) | %         | (acres) | %      | (acres) | %         | (acres) | (ac-ft)        | (ac-ft) | cfs          | (ac-ft) |
| ONSITE BASIN A         | 99964  | 2.295   | 0%          | 0       | 10.0%     | 0.229   | 50.0%  | 1.14743 | 40%       | 0.918   | 1.681          | 0.321   | 9.16         | 0.444   |
| ONSITE BASIN B         | 76597  | 1.758   | 0%          | 0       | 10.0%     | 0.176   | 50.0%  | 0.87921 | 40%       | 0.703   | 1.681          | 0.246   | 7.02         | 0.340   |
| ONSITE BASIN C         | 1964   | 0.045   | 0%          | 0       | 0.0%      | 0.000   | 50.0%  | 0.02254 | 50%       | 0.023   | 1.825          | 0.007   | 0.19         | 0.010   |
| ONSITE BASIN D         | 14497  | 0.333   | 0%          | 0       | 50.0%     | 0.166   | 40.0%  | 0.13312 | 10%       | 0.033   | 1.212          | 0.034   | 1.06         | 0.038   |
| ALLOWED IN NAAMDP      | 193022 | 4.431   | 0%          | 0       | 34.0%     | 1.507   | 16.0%  | 0.70899 | 50%       | 2.216   | 1.699          | 0.627   | 7 17.49      | 0.923   |
| UPLAND A(EX CONDITION) | 396342 | 9.099   | 0%          | 0       | 50.0%     | 4.549   | 40.0%  | 3.6395  | 10%       | 0.910   | 1.212          | 0.919   | <b>28.95</b> | - 1.040 |
| UPLAND B(EX CONDITION  | 26994  | 0.620   | 0%          | 0       | 34.0%     | 0.211   | 16.0%  | 0.09915 | 50%       | 0.310   | 0.816          | 0.042   | 1.22         | 0.083   |
| "ONSSITE SUMMARY       | 193022 |         | <del></del> |         |           |         | *      |         |           |         |                |         | 17.43        |         |

#### **Equations:**

Weighted E = Ea\*Aa + Eb\*Ab + Ec\*Ac + Ed\*Ad / (Total Area)

Volume = Weighted D \* Total Area

Flow = Qa \* Aa + Qb \* Ab + Qc \* Ac + Qd \* Ad

Where for 100-year, 6-hour storm (zone 3)


Ea= 0.66 Qa= 1.87 Eb= 0.92 Qb= 2.6 Ec= 1.29 Qc= 3.45 Ed= 2.36 Qd= 5.02


FIRST FLUSH= 1774.22 CF

#### DRAINAGE NARATIVE

Site is a temporary use. The site is located bains 117.2 and 117.3. The upland flow of 28.95 cfs will enter the site and drain to the swale along oakland. The flow will be captured by a double D inlet The upland flow of 1.22 cfs will enter the site and be captured by our harvest ponds and combine with the onsite flwo

The onite flow will be captured by a single D inlet connected to the wye stubed into the property. The land treatment of millings has been modied to account for parked cars and 40% has been treatment D The First flush volume of 1782 has been provided onsite







FEB 2 5 2015

I AND DEVELOPMENT SECTION

Onsite Basin



## SITE HYDRAULICS



# DROP INLET CALCULATIONS

| POND | TYPE OF | AREA | Q     | Н           | H ALLOW |
|------|---------|------|-------|-------------|---------|
|      | INLET   | (SF) | (CFS) | <u>(FT)</u> | (FT)    |
| 1    | DOUBLE  | 8.86 | 28.95 | 0.4605      | 1       |
| 1A   | SINGLE  | 4.43 | 17.49 | 0.6723      | 1       |

## ORIFICE EQUATION

Q = CA sqrt(2gH)  $H=(Q/CA)^2)/2G$ 

C = 0.6

g = 32.2

INLET GRATE=40"X25"
CALCULATE FOR BARS
40-(11\*.5) 34.5"
25-(13\*.5) 18.5"

OPENING IS 4.43 SF PER GRATE



# Pipe Capacity

| Pipe   | D    | Slope | Area   | R     | Q Provided | Q Required | Velocity |
|--------|------|-------|--------|-------|------------|------------|----------|
|        | (in) | (%)   | (ft^2) |       | (cfs)      | (cfs)      | (ft/s)   |
| 12HDPE | 18   | 1.5   | 1.77   | 0.375 | 11.18      | 7.02       | 3.97     |

ole

Manning's Equation:


 $Q = 1.49/n * A * R^{2/3} * S^{1/2}$ 

A = Area


R = D/4

S = Slope

n = 0.015




## SAN PEDRO STORM DRAIN DESIGN AND ASBUILTS



# DESIGN ANALYSIS REPORT FOR SAN PEDRO STORM DRAIN PROJECT CITY PROJECT NO. 5304.91

Prepared by:
Thompson Engineering Consultants, Inc.
P.O. Box 65760
Albuquerque, NM 87193

January 2010




| 1. Control   1.    |   | uci Keport (San Pearo Su - Final Singl       |                  |       |       |       |     |            |           |             |       |
|--|---|--|------------------|-------|-------|-------|-----|------------|-----------|-------------|-------|
| PAR & DEFENSE BOTH STANDARD SCHOOL         CHOLEN PRINTED SCHOOL   |   | -Node- Upstream Doffgstream                  |                  |       |       |       |     |            |           | A Cost earn |       |
| P. 4. 0 GEORGE NOT BIS SHIPPING A LAVERDA BLVD.   P. 4. 0 GEORGE NOT BIS SHIPPING A LAVERDA BLVD.   P. 4. 0 GEORGE NOT BIS SHIPPING A LAVERDA BLVD.   P. 4. 0 GEORGE NOT BIS SHIPPING A LAVERDA BLVD.   P. 4. 0 GEORGE NOT BIS SHIPPING A LAVERDA BLVD.   P. 4. 0 GEORGE NOT BIS SHIPPING A LAVERDA BLVD.   P. 4. 0 GEORGE NOT SHIPPING A LAVERDA BLVD   | ·l                                      | 4  | ular Phra - 66.0 |       | 532   | _     | 165 | 5.94       | 5230.42   | 222         |       |
| P. A. G. DEGENER WER, IN SAME PRIOR OF ALAMEDRA BLVD.         Cycles Prior B (2009)         520 0033         473 12.58         520 003           P. A. G. DEGENER WER, IN SAME PRIOR OF ALAMEDRA BLVD.         Cycles Prior B (2009)         130 0033         462 11.28         520 003           P. A. G. DEGENER WER, IN SAME PRIOR O. DALAMOD         Cycles Prior B (2009)         130 0033         462 11.28         520 003           P. A. G. DEGENER WER, IN SAME PRIOR O. DALAMOD         Cycles Prior B (2009)         130 0033         462 11.28         520 003           P. M. SALLER WER, IN SAME PRIOR O. DALAMOD         Cycles Prior B (2009)         130 0033         462 11.28         520 003           P. M. SALLER WER, IN SAME PRIOR O. DALAMOD         Cycles Prior B (2009)         130 0033         463 11.50         520 003           P. M. SALLER WER, IN SAME PRIOR O. DALAMOD         Cycles Prior B (2009)         130 0033         464 11.50         520 003           P. M. SALLER WER, IN SAME PRIOR O. DALAMOD RALAMODA PRIOR SALLAMODA PRIOR SAL  |   | R. 45 DEGREE WYE IN SAN PEDRO & ALAMEDA BLY  |                  |       |       |       |     |            | 5229.65   | 5219.8      |       |
| Pr. 45   GERGER WYEE IS SAN PERIOD & DANLAND  COUGH PRE-94 OF 16 OF 13 D 0.013   462   11.35   22.02.13     Pr. 45   GERGER WYEE IS SAN PERIOD & DANLAND  COUGH PRE-94 OF 16 OF 13 D 0.013   462   11.35   22.02.13     Pr. 16   GERGER WYEE IS SAN PERIOD & DANLAND  COUGH PRE-94 OF 16 OF 13 D 0.013   462   11.35   22.02.13     Pr. 16   GERGER WYEE IS SAN PERIOD & DANLAND COUGH PRE-94 OF 16 OF 13 D 0.013   462   11.35   22.02.13     Pr. 16   GERGE ROCK   | 84" RCP                                 | . 45 DEGREE WYE IN SAN PEDRO & ALAMEDA BLY   | Jiar Pipe - 84.0 | 0.005 | 525   | 0.013 | 417 | 12.96      | 5229.65   | 5219.8      |       |
| Process   Proc   |   | . 45 DEGREE WYE IN SAN PEDRO                 |                  |       |       |       |     |            | 5228      | 5217.29     |       |
| Print, INSTER WORTH OF SAM PERON & CORLAMO         CORLAM PERON & CORLAMO         CORLAM PERON & CORLAMO         CORLAM PERON & CORLAMO         STAGE TO THE SAM PERON & CORLAMO         CORLAM PERON & CORLAMO         STAGE TO THE SAM PERON & CORLAMO         CORLAM PERON & CORLAMOR & CORLA   | 84" RCP                                 | . 45 DEGREE WYE IN SAN PEDRO & DAKL          | Har Pipe - 84.0  | 0.005 | 136   | 0.013 | 462 | 3.6        | 5228      |             | 5223. |
| Principal Control of   |   | . INLET NORTH OF SAN PEDRO & CANAN           |                  |       |       |       |     |            | 5226.12   |             |       |
| Fig. Fig. Start Fig. Start Frozo A   | 84" RCP                                 | INLET NORTH OF SAN PEDRO & OAKLAN            | ular Pipe - 84.0 | 0.005 | 335   | 0.013 | 462 | ie.        | 5226.12   | 5216.57     |       |
| Pic. Het South Colored No.     | • | H SOUTH OF SAN PEDRO & EA                    |                  |       |       |       |     |            | 5224.23   |             |       |
| Activities (Comparison Comparison Comparis   | 84" RCP                                 | R. MH SOUTH OF SAN PEDRO & EAGLE ROCK        | ular Pipe - 84.0 | 0.00  | 31    | 0.013 | 462 | ļv.        | 5224.23   | 5214.89     |       |
| Presidence   Processes   Pro   | ••                                      | OPOSED J-BOX AT SAN PEDRO AND EAGLE          |                  |       |       |       |     |            | 7.        | 5210.5      |       |
| P. N. H. T. SAN PEDRO AND ALAMEDA PL.   CITCLING Pige - 78.0   F. O.   | 64* RCP                                 | KAT SAN PEDRO AND EAGLE                      | ular Pipe - 84.0 | 0.009 | 32    | 0.013 | 393 |            | 7         | 5210.5      | 52    |
| PR. NH. T. SAN PERDO AND ALAMERA PL.         CICCURF Pige - 78.0 in         0.0012         350         0.0013         17.577         522.1.4           R. N. H. T. SAN PERDO AND ALAMERA PL.         CICCURF Pige - 72.0 in         0.0013         257         0.0013         443         15.607         520.1.4           R. N. H. T. SAN PERDO AND ALAMERA PL. C. CICCURF Pige - 72.0 in         0.0013         257         0.0013         16.6         10.37         520.1.3           1. S. DEGREE END AND ALAMERA PL. C. T. BAR         CICCURF Pige - 54.0 in         0.0024         59         0.0013         16.6         8.4         523.0.4           1. S. DEGREE END AND ALAMERA PLO. STURGUT; QUID = 185 CFS         CICCURF Pige - 54.0 in         0.0024         59         0.0013         15.6         523.0.4           1. S. DEGREE END AND ALAMERA BLVD. STURGUT; QUID = 232 CFS         CICCURF Pige - 54.0 in         0.003         50         0.0013         252         15.84         523.0.1           5. DEGREE END AND ALAMERA BLVD. STURGUT; QUID = 45 CFS         CICCURF Pige - 54.0 in         0.003         50         0.0013         252         15.268           5. DEGREE END AND ALAMERA BLVD. STURGUT; QUID = 45 CFS         CICCURF Pige - 56.0 in         0.003         50         0.0013         523.0.1           6. DEGREE END AND ALAMERA BLAND AND ALAMERA BLAND AND ALAME  | *************************************** | TE TE  |                  |       |       |       |     |            | 5223.95   | 5210.22     |       |
| PR NH AT SAN PEDRO AND ALAMEDA PL   PR NH AT SAN PEDRO AND ALAMEDA PL   PR NH AT SAN PEDRO AND ALAMEDA PL   PR SAN PEDRO & STGGER BRICH MAY SAN PEDRO & ALAMEDA RAYOR   PR SAN PEDRO & STGGER BRICH MAY SAN PEDRO & ALAMEDA RAYOR   PR SAN PEDRO & ALAMEDA RAYOR & ATAMEDA RAYOR   PR SAN PEDRO & AND ALAMEDA RAYOR   PR SAN PEDRO & AND ALAMEDA RAYOR & ATAMEDA RAYOR & ATAMED   | 78* RCP                                 | PR MH  | ular Pine - 78.0 | 0.0   | 505   | 0,013 | 393 | N          | 50.572.05 | 12          |       |
| R. 45 DEGREE BEIND AND 76' X 72' BHR         CITCLIAN TO BE 72.0 In 0.012         50.013         440         15.67         5208.3           PR. SAM PERING S OUTFILL (1: 128 AND ALLANERA RALCE)         CITCLIAN TOPE - 54.0 In 0.025         59         0.013         165         6.4         5203.3           45 DEG BEIND G STGWAL STUROUT; Q100 = 165 CFS         CITCLIAN TOPE - 54.0 In 0.025         59         0.013         166         6.4         523.1.8           54 DEG BEIND G STGWAL STUROUT; Q100 = 165 CFS         CITCLIAN TOPE - 54.0 In 0.025         59         0.013         125         12.28         523.1.8           74 DEG BEIND G STUROUT; Q100 = 4.5 CFS         CITCLIAN TOPE - 54.0 In 0.025         59         0.013         222         11.283         523.0.1           65 DEG BEIND G STUROUT; Q100 = 4.5 CFS         CITCLIAN TOPE - 54.0 In 0.025         59         0.013         222         11.283         523.0.1           65 DEG BEIND G STUROUT; Q100 = 4.5 CFS         CITCLIAN TOPE - 36.0 In 0.025         50         0.013         222         11.283         523.0.1           65 DEG BEIND G STUROUT; Q100 = 4.5 CFS         CITCLIAN TOPE - 36.0 In 0.025         50         0.013         222         11.283         522.0.3           65 DEG BEIND G STUROUT; Q100 = 4.5 CFS         CITCLIAN TOPE - 36.0 In 0.025         50         0.013         3   |   | MH AT SAN PEDRO AND ALAM                     |                  |       |       |       |     | ::         | 5221.4    |             | 5212  |
| SAM PERRO SO QUITALL AT 1-25 AND ALAMEDA PLACE         Chrolar Pipe - 54.0 in         0.026         SQ 0.013         165         10.37         5233.2           FR. SAN PERRO S. SIGNAL, STUDGOTT: Q100 = 165 CFS         Chrolar Pipe - 54.0 in         0.026         SQ 0.013         165         8.4         5733.18           45 DEG BERNO         45 DEG BERNO         Chrolar Pipe - 50.0 in         0.036         SQ 0.013         252         15.84         5230.42           54 DEG BERNO         ALAMEDA RAVEDA RAVIO. 5TUBOUT: Q100 = 232 CFS         Chrolar Pipe - 50.0 in         0.034         SQ 0.013         252         15.84         5230.13           74 DEG BERNO         RALAMEDA RAVEDA RAVEDA RAVIO. 5TUBOUT: Q100 = 232 CFS         Chrolar Pipe - 50.0 in         0.034         SQ 0.013         4.5         6.17         5230.13           74 DEG BERNO         RALAMEDA RAVEDA RAVE  | 2" RCP                                  | 45 DEGREE BEND AND 78" X                     | utar Pipe - 72.0 | 0.012 | 257   | 0.013 | 43  | 160        | 5208.9    | 5 0015      |       |
| PR. SAN PEDRO & SIGNAL STUBEUT: Q100 = 165 CPS         Circular Pige - 54.0 in         0.026         50         0.013         165         10.37         5233.2           45 DEG BRID         45 DEG RRID         45 DEG RRID         0.0013         165         8 4         5230.42         5230.42           57 M. PEDRO & ALAMEDA BLVD.         Circular Pige - 60.0 in         0.003         55         0.013         252         1.5.84         5230.42           56 DEG BRID         FA S DEGREE BRID         Circular Pige - 60.0 in         0.034         50         0.013         252         1.2.83         5230.42           55 DEG BRID         45 DEGREE BRID         Circular Pige - 60.0 in         0.034         50         0.013         45         5230.42           45 DEG BRID         R. 45 DEGREE WITE IN SAN PEDRO & ALAMEDA BLVD.         Circular Pige - 56.0 in         0.036         50         0.013         45         5230.42           45 DEGREE WITE IN SAN PEDRO & CAKLAND         Circular Pige - 56.0 in         0.036         50         0.013         45         5220.43           45 DEGREE WITE IN SAN PEDRO & CAKLAND         Circular Pige - 72.0 in         0.036         50         0.013         43         5.22         5.22           45 DEGREE WITE BLOW         COKLAND         CIRCULAR PIGE   |   | AND ALAMEDA PLA                              |                  |       |       |       |     | i I        | 5203.5    | Š           | CUCS  |
| 45 DEG BEND   1650 BEND   1550 BEND   15   | K. RCP                                  | SIGNAL STUBOUT: Q100 = 165 CI                | ular Pipe - 54.0 | 0.026 | S     | 0.013 | 165 |            | 5233.2    | زانخ        |       |
| 45 DEG BEND IN SAM PEDRO & SIGNAL   CITCLIAN PIDE - 56.0 in   0.003   50 0.013   15.64   5230.42     52.04 PEDRO & ALAMEDA BLACIO, STUBOUT: Q100 = 45 CFS   CITCLIAN PIDE - 56.0 in   0.003   50 0.013   252   13.89   5230.3     45 DEG BEND   PEDRO & ALAMEDA BLVD. STUBOUT: Q100 = 45 CFS   CITCLIAN PIDE - 56.0 in   0.003   50 0.013   252   13.83   5230.3     45 DEG BEND   PEDRO & ALAMEDA BLVD. STUBOUT: Q100 = 45 CFS   CITCLIAN PIDE - 36.0 in   0.006   50 0.013   45   6.37   5230.3     45 DEG BEND   PEDRO & ALAMEDA BLVD. Q100 = 45 CFS   CITCLIAN PIDE - 36.0 in   0.006   50 0.013   45   6.37   5230.3     45 DEG BEND   PEDRO & ALAMEDA BLVD. Q100 = 45 CFS   CITCLIAN PIDE - 36.0 in   0.006   50 0.013   45   6.37   5230.3     45 DEG BEND   PEDRO & ALAMEDA BLVD. Q100 = 45 CFS   CITCLIAN PIDE - 36.0 in   0.006   50 0.013   45   6.37   5230.3     45 DEG BEND   PEDRO AND BAGLE ROCK   CITCLIAN PIDE - 78.0 in   0.001   30 0.013   325   6.37   5224.03     45 DEG BEND   PEDRO AND BAGLE ROCK   CITCLIAN PIDE - 78.0 in   0.017   30 0.013   325   5221.4     46 FA STORE BEND   PEDRO AND ALAMEDA PLANEDA PLA   |   | 45 DEG BEND                                  |                  |       |       |       |     |            | 5231.8    | 5224.36     | 523   |
| PR. 45 DEGREE BRIND IN SAM PEDRO & SIGNAL,   Chrolar Pipe - 54.0 in     | 50" RCP                                 |  | Har Pipe - 60.0  | 0.026 | 20    | 8     | 165 | • •        | 5231.8    |             |       |
| SAN PERPO & ALÁWEDA BLVD. 5TUBOUT: Q100 = 452 GTS   Grouler Pipe - 54.0 in   0.034   550   0.013   252   15.84   5230.1   15.84   5230.1   15.86   15.86   1   |   | BEND IN SAN PEDRO & SIGNAL                   |                  |       |       |       |     |            | 5230.42   | 5222.97     |       |
| 45 DEG BEND  PR. 45 DEG | 7- RCP                                  | 34 BLVD. STUBOUT: Q100 - 252                 | ula: Pipe - 54.0 | 0.034 | 20    | 0.013 | 252 | 15.84      | 5232.3    | ~           | 25    |
| 45 DEG BEND   Chrouler Pipe - 50.0 in   0.034   50   0.013   552   12.83   5230.1     PR. SAM PERDOR & ALAMEDA BLYD.   Chrouler Pipe - 36.0 in   0.026   50   0.013   45   5220.5     PR. SAM PERDOR & CARLAND STUBCUTT: Q100 = 45 CF5   Chrouler Pipe - 36.0 in   0.026   50   0.013   45   6.37   5229.3     45 DEG BEND   Chrouler Pipe   26.0 in   0.026   50   0.013   45   6.37   5229.3     45 DEG BEND   Chrouler Pipe   26.0 in   0.026   50   0.013   45   6.37   5229.3     45 DEG BEND   Chrouler Pipe   72.0 in   0.026   50   0.013   325   (W/A)   5224.03     45 DEG BEND   Chrouler Pipe   72.0 in   0.026   50   0.013   325   20.9   5224.03     45 DEG BEND   Chrouler Pipe   72.0 in   0.019   334   0.013   325   20.9   5224.03     45 DEG BEND   Chrouler Pipe   72.0 in   0.019   334   0.013   325   20.9   5224.03     45 DEG BEND   Chrouler Pipe   72.0 in   0.019   334   0.013   325   32.9   5224.03     46 DEGREE BEND   Chrouler Pipe   72.0 in   0.011   334   313.3   5224.03     47 DEGREE BEND   Chrouler Pipe   72.0 in   0.011   495.7   0.013   52.08     48 DEGREE BEND   Chrouler Pipe   72.0 in   0.011   50   0.013   50   10.44   52.08     49 DEGREE BEND   Chrouler Pipe   72.0 in   0.01   50   0.013   50   10.44   52.04     40 DEGREE BEND   Chrouler Pipe   72.0 in   0.01   50   0.013   50   10.44   52.04     40 DEGREE BEND   Chrouler Pipe   72.0 in   0.01   50   0.013   50   10.44   52.04     40 DEGREE BEND   Chrouler Pipe   72.0 in   0.01   50   0.013   50   10.44   52.04     40 DEGREE BEND   Chrouler Pipe   72.0 in   0.01   50   0.013   50   10.44   52.04     40 DEGREE BEND   Chrouler Pipe   72.0 in   0.01   50   0.01   50   10.01   50    |   | 45 DEG BEND                                  |                  |       |       |       |     |            | 5230.1    |             | 5229  |
| PR. 45 DEGREE WTE IN SAW PEDRO & ALÁWEDA BLVD.         Circular Pipe - 36.0 in         0.026         50         0.013         45         6.37         5229.65           PR. 50 DEGREE WTE IN SAW PEDRO & CAKLAND         Circular Pipe - 36.0 in         0.026         50         0.013         45         6.37         5229.33           45 DEG BEND         Circular Pipe - 72.0 in         0.026         5         0.013         325         5224.03           45 DEG REEW         PR. 45 DEGREE WTE IN SAW PEDRO AND EAGLE ROCK         Circular Pipe - 72.0 in         0.02         5         0.013         325         6.37         5224.03           PR. 45 DEGREE WTE IN SAW PEDRO AND EAGLE ROCK         Circular Pipe - 72.0 in         0.012         334         0.013         325         20.9         5224.03           PR. MH         SAN PEDRO AND ALAWEDA PL.         Circular Pipe - 78.0 in         0.017         30         0.013         443         13.35         5221.65           PR. 45 DEGREE BEND         CIRCULAR PIDE - 78.0 in         0.01         496.7         0.013         443         13.35         5220.6           PR. 45 DEGREE BEND         CIRCULAR PIDE - 78.0 in         0.01         50         0.013         50         10.14         522.0           PR. 64 DEGREE BEND OND ALAWEDA PL.   | 50" RCP                                 |  | ubr Pipe - 60.0  | 4     | 20    | 0.013 | 252 | 12.83      | 5230.1    | 5221.58     |       |
| PR. SAN PEDRO & CARLAND STUBGLIF: Q100 = 45 CFS   Chruler Pipe - 36.0 in pr. SAN PEDRO & CARLAND STUBGLIF: Q100 = 45 CFS   Chruler Pipe - 36.0 in pr. SAN PEDRO & CARLAND   Chruler Pipe - 36.0 in pr. SAN PEDRO & CARLAND   Chruler Pipe - 72.0 in pr. SAN PEDRO AND SAGLE ROCK   Chruler Pipe - 72.0 in pr. SAN PEDRO AND SAGLE ROCK   Chruler Pipe - 72.0 in pr. SAN PEDRO AND SAGLE ROCK   Chruler Pipe - 72.0 in pr. SAN PEDRO AND SAGLE ROCK   Chruler Pipe - 72.0 in pr. SAN PEDRO AND ALAMEDA PL.   Chruler Pipe - 73.0 in pr. SAN PEDRO AND ALAMEDA PL.   Chruler Pipe - 73.0 in pr. SAD EGREE BEND   Chruler Pipe - 73.0 in pr. SAD EGREE BEND   Chruler Pipe - 73.0 in pr. SAD EGREE BEND   Chruler Pipe - 73.0 in pr. SAD EGREE BEND   Chruler Pipe - 73.0 in pr. SAD EGREE BEND   Chruler Pipe - 73.0 in pr. SAD EGREE BEND   Chruler Pipe - 73.0 in pr. SAD EGREE BEND   Chruler Pipe - 73.0 in pr. SAD EGREE BEND   Chruler Pipe - 73.0 in pr. SAD EGREE BEND   Chruler Pipe - 73.0 in pr. SAD EGREE BEND   Chruler Pipe - 73.0 in pr. SAD EGREE BEND   Chruler Pipe - 73.0 in pr. SAD EGREE BEND   Chruler Pipe - 54.0 in pr. SAD EGREE BEND   C   |   | YE IN SAN PEDRO & ALAMEDA BLY                |                  |       |       |       |     |            | ·         | 5219.8      | 5     |
| 45 DEG BEND         Circular Pipe - 36.0 in         Circular Pipe - 72.0 in         Circular Pipe - 72.0 in         Circular Pipe - 72.0 in         Circular Pipe - 66.0 in         Circular Pipe - 66.0 in         Circular Pipe - 66.0 in         Circular Pipe - 78.0 in <td>36° RCP</td> <td>OAKLAND STUBOUT: Q100 = 45 CF</td> <td>siar Pipe - 36.0</td> <td>0.026</td> <td>20</td> <td>0.013</td> <td>45</td> <td>•</td> <td>5230.6</td> <td>5220.05</td> <td>522</td>   | 36° RCP                                 | OAKLAND STUBOUT: Q100 = 45 CF                | siar Pipe - 36.0 | 0.026 | 20    | 0.013 | 45  | •          | 5230.6    | 5220.05     | 522   |
| 45 DEG REE         BEND         Chrouler Pige - 36.0 in         0.0266         50         0.013         45         6.37         5229.3           PR. 45 DEGREE WYE IN SAW PEDRO AND EAGLE ROCK         Chrouler Pige - 72.0 in         0.02         5         0.013         325         (WA)         5224.03           PR. HH         PROPOSED 1-BOX AT SAN PEDRO AND EAGLE ROCK         Chrouler Pige - 66.0 in         0.012         334         0.013         325         20.9         5224           PR. HH         CHANNETTION TO EXISTING SD IN EAGLE ROCK         Chrouler Pige - 78.0 in         0.017         30         0.013         443         13.35         5212.65           PR. HH         CHANNETTION TO EXISTING SD IN EAGLE ROCK         Chrouler Pige - 78.0 in         0.017         30         0.013         443         13.35         5212.65           PR. HH         SEGREE BEND         Chrouler Pige - 78.0 in         0.01         496.7         0.013         443         13.35         5220.4           PR. 45 DEGREE BEND         Chrouler Pige - 78.0 in         0.01         50         0.013         50         10.77         5220           PR. 45 DEGREE BEND         Chrouler Pige - 78.0 in         0.01         50         0.013         50         10.77         5220  |   | 45 DEG BEND                                  |                  |       |       |       |     |            | 5229.3    | 5218.67     |       |
| PR. 45 DEGREE WITE IN SAM PEDRO & OAKLAND         Chruler Pipe - 72.0 in         0.013         325         (W/h)         5224.03           PROPOSED 3-80X AT SAN PEDRO AND EAGLE ROCK         Chruler Pipe - 66.0 in         0.019         334         0.013         325         (W/h)         5224.03           PR. MH         PR. NH         Chruler Pipe - 66.0 in         0.017         30         0.013         443         13.35         5224           PR. NH         CONNECTION TO EXISTING SD IN EAGLE ROCK         Chruler Pipe - 78.0 in         0.017         30         0.013         443         13.35         5224           PR. NH         FA SPEGREE BEND         Chruler Pipe - 78.0 in         0.01         496.7         0.013         443         17.77         5220           PR. 45 DEGREE BEND         Chruler Pipe - 78.0 in         0.01         496.7         0.013         443         17.77         5220           PR. 45 DEGREE BEND         Chruler Pipe - 78.0 in         0.01         496.7         0.013         443         17.77         5220           PR. 45 DEGREE BEND         Chruler Pipe - 78.0 in         0.01         50         0.013         50         10.44         5221.4           PR. 45 DEGREE BEND         Chruler Pipe - 78.0 in         0.01         50  | 36" RCP                                 | DEG BEND                                     | uar Pipe - 36.0  | 0.026 | 8     | 0.013 | \$  |            | * * *     | 5218,67     |       |
| PROPOSED 1-BOX AT SAN PEDRO AND EAGLE ROCK         Chruler Pipe - 72.0 in         0.019         334         0.013         325         (N/A)         5224.03           PR. MH         PR. MH         CONNECTION TO EXISTING SD IN EAGLE ROCK         Chruler Pipe - 66.0 in         0.019         334         0.013         325         20.9         5224           PR. MH         CONNECTION TO EXISTING SD IN EAGLE ROCK         Chruler Pipe - 78.0 in         0.017         30         0.013         443         13.35         5221.4           PR. MH AT SAN PEDRO AND ALAMEDA PL.         Chruler Pipe - 78.0 in         0.017         30         0.013         443         13.35         5221.4           PR. 45 DEGREE BEND         Chruler Pipe - 78.0 in         0.01         496.7         0.013         443         13.35         5220.6           PR. 45 DEGREE BEND         Chruler Pipe - 78.0 in         0.01         496.7         0.013         443         17.77         5220.6           PR. 45 DEGREE BEND         Chruler Pipe - 78.0 in         0.01         50         0.013         50         10.44         5222.6           PR. 45 DEGREE BEND         Chruler Pipe - 78.0 in         0.01         50         0.013         55         10.44         5222.4           PR. MH AT SAN PEDRO AND ALAMEDA  |   | . 45 DEGREE WYE IN SAN PEDRO & OAKLA         |                  |       |       |       |     |            | 5228      | 5217.29     |       |
| PR. MH         PR. MH         PR. MH         Chruler Pipe - 66.0 in         0.019         334         0.013         325         20.9         5224           PR. MH         CONNECTION TO EXISTING SD IN EAGLE ROCK         Chruler Pipe - 78.0 in         0.017         39         0.013         443         13.35         5221.45           PR. MH AT SAN PEDRO AND ALAMEDA PL.         Chruler Pipe - 78.0 in         0.01         496.7         0.013         443         13.35         5220           PR. 45 DEGREE BEND         PR. 45 DEGREE BEND         Chruler Pipe - 78.0 in         0.01         496.7         0.013         443         13.77         5220           PR. 45 DEGREE BEND         PR. 45 DEGREE BEND AND 78" X 72" BHR         Chruler Pipe - 78.0 in         0.01         496.7         0.013         443         13.77         5220           PR. 45 DEGREE BEND AND 78" X 72" BHR         PR. 45 DEGREE BEND AND 78" X 72" BHR         Chruler Pipe - 78.0 in         0.01         50         0.013         50         10.44         5220           PR. MH AT SAN PEDRO AND ALAMEDA PL.         Chruler Pipe - 78.0 in         0.02         50         0.013         256         16.1         5224.03           PROPOSED 3-BOX AT SAN PEDRO AND BAGLE ROCK         Chruler Pipe - 78.0 in         0.02         0.013         256<   | 72" RCP                                 | OPOSED 1-BOX AT SAN PEDRO AND EAGLE          | uter Prpe - 72.0 | 0.02  | 5     | 0.013 | 325 | (N/A)      | 5224.03   | 5210.5      |       |
| PR. MH         CONNECTION TO EXISTING SD IN EAGLE ROCK         Chruler Pipe - 66.0 in 0.019         334         0.013         325         20.9         5224           CONNECTION TO EXISTING SD IN EAGLE ROCK         Chruler Pipe - 78.0 in PR. 45 DEGREE BEND         Chruler Pipe - 78.0 in PR. 45 DEGREE BEND         443         13.35         5221.4           PR. 45 DEGREE BEND         Circular Pipe - 78.0 in PR. 45 DEGREE BEND         Chruler Pipe - 78.0 in PR. 496.7         0.013         443         17.77         5220           PR. 45 DEGREE BEND         Circular Pipe - 78.0 in PR. 45 DEGREE BEND AND 78" X 2" BHR         Circular Pipe - 42.0 in PR. 496.7         0.013         496.7         0.013         443         17.77         5220           PR. 45 DEGREE BEND AND AND ALAMEDA PL.         Circular Pipe - 42.0 in PR. 496.7         0.013         50         0.013         50         10.44         5221.4           PR. NH AT SAN PEDRO AND ALAMEDA PL.         Circular Pipe - 54.0 in PR. NH AT SAN PEDRO AND EAGLE ROCK         Circular Pipe - 54.0 in PR. 496.7         0.013         256         16.14         5224.03  |   | 32. MH                                       |                  |       |       |       |     |            | 5224      | 5210.4      | N)    |
| CONNECTION TO EXISTING SD IN EAGLE ROCK         CROUBE FROM         0.017         30         0.013         443         13.35         5221.4           PR. MH AT SAN PEDRO AND ALAMEDA PL.         Circular Pipe - 78.0 In         0.011         496.7         0.013         443         17.77         5220           PR. 45 DEGREE BEND         Circular Pipe - 78.0 In         0.01         496.7         0.013         443         17.77         5220           PR. 45 DEGREE BEND         AND 78" X 72" BHR         Circular Pipe - 42.0 In         0.01         50         0.013         50         10.44         5220           PR. A5 DEGREE BEND AND 78" X 72" BHR         Circular Pipe - 42.0 In         0.01         50         0.013         50         10.44         5220           PR. MH AT SAN PEDRO AND ALAMEDA PL.         Circular Pipe - 42.0 In         0.02         50         0.013         50         10.44         5221.4           PR. MH AT SAN PEDRO AND EAGLE ROCK         Circular Pipe - 54.0 In         0.02         50         0.013         256         16.1         5224.03  | 56" RCP                                 | R. MH  | utar Pipe - 66.0 | 0.019 | 334   | 0.013 | 325 | •          | 5224      | 5210.4      | 25    |
| PR. 45 DEGREE BEND         Chrouler Pipe - 78.0 in         0.017         30         0.013         443         13.35         5221.4           PR. 45 DEGREE BEND         Chrouler Pipe - 78.0 in         0.01         496.7         0.013         443         17.77         5220           PR. 45 DEGREE BEND         Chrouler Pipe - 78.0 in         0.01         496.7         0.013         443         17.77         5220           PR. 45 DEGREE BEND         Chrouler Pipe - 78.0 in         0.01         50         0.013         50         10.44         5222           PR. 45 DEGREE BEND         PR. 45 DEGREE BEND AND 78" X 72" BHR         Chrouler Pipe - 42.0 in         0.01         50         0.013         50         10.44         5222           PR. A5 DEGREE BEND AND 78" X 72" BHR         Chrouler Pipe - 42.0 in         0.01         50         0.013         50         10.44         5222           PR. MH AT SAN PEDRO AND ALAMEDA PL.         Chrouler Pipe - 54.0 in         0.00         50         0.013         256         16.1         5224.03           PROPOSED J-BOX AT SAN PEDRO AND EAGLE ROCK         Chrouler Pipe - 54.0 in         0.00         0.013         256         16.1         5224.03   |   | ONNECTION TO EXISTING SD IN EAGLE            |                  |       |       |       |     |            |           | 1 - I       | 2207  |
| PR. 45 DEGREE BEND         Circular Pipe - 78.0 in         0.01         496.7         0.013         443         17.77         5220           PR. 45 DEGREE BEND         AMEDIA         Circular Pipe - 78.0 in         0.01         496.7         0.013         443         17.77         5220           PR. 45 DEGREE BEND AND 78" X 72" BHR         Circular Pipe - 42.0 in         0.01         50         0.013         50         10.44         5222           PR. 45 DEGREE BEND AND 78" X 72" BHR         Circular Pipe - 42.0 in         0.01         50         0.013         50         10.44         5221.4           PR. MH AT SAN PEDRO AND FAGLE ROCK         Circular Pipe - 54.0 in         0.02         50         0.013         256         16.1         5224.03           PROPOSED 1-BOX AT SAN PEDRO AND EAGLE ROCK         CIRCUlar Pipe - 54.0 in         0.02         50         0.013         256         16.1         5224.03   | 78* RCP                                 | MH AT SAN PEDRO AND ALAM                     | udar Pipe - 78.0 | -4    | R     | 0.013 | 443 | m          | 3         | t 🗢         |       |
| PR. 45 DEGREE BEND         Circular Pipe - 75.0 in         0.01         496.7         0.013         443         17.77         5220           PR. 45 DEGREE BEND AND 78" X 72" BHR         Circular Pipe - 75.0 in         0.01         50         0.013         50         10.44         5222           PR. 45 DEGREE BEND AND 78" X 72" BHR         Circular Pipe - 42.0 in         0.01         50         0.013         50         10.44         5222           PR. MH AT SAN PEDRO AND ALAMEDA PL.         Circular Pipe - 54.0 in         0.02         50         0.013         256         16.1         5224.03           Q 100 = 256 INTERCEPTION AT EAGLE ROCK         Circular Pipe - 54.0 in         0.02         50         0.013         256         16.1         5224.03  |   | 45 DEGREE                                    |                  |       |       |       |     |            | 5220      | 5204.5      |       |
| PR. 45 DEGREE BEND AND 78" X 72" BHR         Storage of the control of the cont                                 | 78" RCP                                 | 45 DEGREE BEND                               | uter Pipe - 78.0 | 000   | 496.7 | 0.013 | \$  | <b>~</b> : | 5220      |             |       |
| PROPOSED INTERCEPTION OF Q 100 = 50 CFS AT ALAMEDA         Circular Pipe - 42.0 in         0.01         50         0.013         50         10.44         5222           PR. MH AT SAN PEDRO AND ALAMEDA PL.         Circular Pipe - 54.0 in         0.02         50         0.013         256         16.1         5224.03           PROPOSED 3-BOX AT SAN PEDRO AND EAGLE ROCK         PROPOSED 3-BOX AT SAN PEDRO AND EAGLE ROCK         5224.03         5224.03  | *************                           | 45 DEGREE BEND AND 78" X 72" BHR             |                  |       |       |       |     |            | 7 7 8     | 5199.5      |       |
| PR. MH AT SAN PEDRO AND ALAMEDA PL.         Circular Pipe - 54.0 in         0.02         50         0.013         256         16.1         5224.03           Q 100 = 256 INTERCEPTION AT EAGLE ROCK         Circular Pipe - 54.0 in         0.02         50         0.013         256         16.1         5226           PROPOSED 3-BOX AT SAN PEDRO AND EAGLE ROCK         5224.03         5224.03         5224.03   | 36. RC                                  | ROPOSED INTERCEPTION OF Q 100 - 50 CFS AT AL | uiar Pipe - 42.0 | 0.01  | 20    | 0.013 | 8   | 10.4       | 2225      | 5211.5      |       |
| 10 100 = 256 INTERCEPTION AT EAGLE ROCK  |   | R. MH AT SAN PEDRO AND ALAMEDA               |                  |       |       |       |     |            | 5221.4    | 2002        | 5212  |
| PROPOSED 3-BOX AT SAN PEDRO AND EAGLE ROCK 5224.03   | 2 3                                     | = 256 INTERCEPTION AT EAGLE ROCK             | utar Proe - 54.0 | 0.02  | 3     |       | 526 | ശ്         | 5226      | 5216        |       |
|  |   | -BOX AT SAN PEDRO AND EAGLE                  |                  |       |       |       | -   |            | 5224.03   | 5210.5      |       |


25 2015

LAND DEVELOPMENT SECTION

## San Pedro Storm Drain

# Proposed Single Pipe System





# CITY OF ALBUQUERQUE

PLANNING DEPARTMENT - Development Review Services



Richard J. Berry, Mayor

February 6, 2015

David Soule, P.E.
Rio Grande Engineering
P.O. Box 93924
Albuquerque, NM 87199

RE: American Toyota - Temporary Lot (File: C18D012)

Need to change

H grosert for:

Conceptual Grading and Drainage Plan, Engineer's Stamp Date 1-9-15

Dear Mr. Soule:

Based upon the information provided in your submittal received 1-20-15, the above referenced submittal cannot be approved for action by the DRB on the Site Plan for Building Permit, nor Grading Permit, until the following comments are addressed:

1. Determination of whether or not infrastructure improvements are required for the temporary site plan is to be determined by City Legal, Zoning, and the Planning Director. Comments provided herein are cursory until such determination is made.

PO Box 1293

The upland flows are 38.4 cfs based on a fully developed condition, and based on 9.72 Acres. However, Eagle Crest Subdivision is a 12.4 Acres subdivision and is not intended to drain across this lot in the fully developed condition (C18D064B). Therefore offsite drainage should be based on existing land treatments, and 12.4 Acres.

Albuquerque

3. Basin A1 land treatments should be modified such that half the Treatment C is a Treatment D. The reason for the increase is that rows of vehicles will cause concentrated flows along the edge of the parking rows and to account for such, half the treatment C area should be treated as a D.

New Mexico 87103 4

With the increase in land treatments, some ponding may be required to maintain the allowable discharge.

www.cabq.gov

Lot appears to be 2 basins, with the south side flowing into a pond and then through a 12' CMP at 0.0 %. Show pipe has capacity. Pipe should have a minimum slope.
Sump inlet calculations should show how the area is calculated. As we discussed, it

- 6. Sump inlet calculations should show how the area is calculated. As we discussed, it would be helpful to have a full spreadsheet, similar to the street capacity calculations, that can be copied and used for similar type inlets. If the grate gets clogged how will emergency overflow be handled.
- 7. Can the Storm Drain in Oakland and San Pedro support the proposed flows per the design assumptions? What were they designed for?

If you have any questions, you can contact me at 924-3695.

C18D012\_Temp Lot\_SPBP\_GP\_Cmmt.doc

1 of 2

Sincerely,

Rita Harmon, P.E.

Senior Engineer, Planning Dept.
Development Review Services

Orig: Drainage file

c.pdf: via Email: Recipient

# City of Albuquerque

# Planning Department


# Development & Building Services Division DRAINAGE AND TRANSPORTATION INFORMATION SHEET

(REV 02/2013)

| Project Title: AMERICAN TOYOTA                         | Building Permit #: City Drainage #: 1820/  |
|--|--|
| DRB#: EPC#   |  |
| Legal Description: LOTS 1-3 &30-32 BLOCK 28, TRACT A,  | UNT B NORTH ALB ACES   |
| City Address: OAKLAND BETWEEN SAN PEDRO AND LO         | JISIANA  |
| Engineering Firm: RIO GRANDE ENGINEERING               | Contact: DAVID SOULE   |
| Address: PO BOX 93924, ALBUQUERQUE, NM 87199           |  |
| Phone#: 505.321.9099 Fax#:                             | 505.872.0999 E-mail: DAVID@RIOGRANDEENGINEERING.COM                                      |
| Owner: VANDY INVESTMENTS,LLC                           | Contact:   |
| Address: 6501 EAGLE ROCK                               |  |
| Phone#: Fax#:  | E-mail:  |
| Architect: John Mahoney                                | Contact:   |
| Address:  Phone#:  Fax#:                               | E-mail:  |
| TAAT.  | D*IIIaii.  |
| Surveyor: CONSTRUCTION SURVEY TECHNOLOGIES             | Contact: JOHN GALLEGOS   |
| Address:   |  |
| Phone#: 917.8921 Fax#:                                 | E-mail:  |
| Contractor:  | Contact:   |
| Address:   |  |
| Phone#: Fax#:  | E-mail:  |
| TYPE OF SUBMITTAL:                                     | CHECK TYPE OF APPROVAL/ACCEPTANCE SOUGHT:  |
| X DRAINAGE REPORT                                      | SIA/FINANCIAL GUARANTEE RELEASE  |
| DRAINAGE PLAN 1st SUBMITTAL                            | PRELIMINARY PLAT APPROVAL  |
| DRAINAGE PLAN RESUBMITTAL                              | S. DEV. PLAN FOR SUB'D APPROVAL [ ] [ ] [ ] [ ] [ ] [ ] [ ] [ ] [ ] [                    |
| CONCEPTUAL G & D PLAN                                  | × S. DEV. FOR BLDG. PERMIT APPROVALLY  |
| X GRADING PLAN   | SECTOR PLAN APPROVAL III JAN 20 2015   |
| EROSION & SEDIMENT CONTROL PLAN (ES                    | FINAL PLAT APPROVAL  |
| ENGINEER'S CERT (HYDROLOGY)                            | CERTIFICATE OF OCCUPANCY (PERM)  LAND DEVELOPMENT SECTION                                |
| CLOMR/LOMR   | CERTIFICATE OF OCCUPANCY (PERM)  CERTIFICATE OF OCCUPANCY (TCL TEMP) DEVELOPMENT SECTION |
| TRAFFIC CIRCULATION LAYOUT (TCL)                       | FOUNDATION PERMIT APPROVAL 5509  |
| ENGINEER'S CERT (TCL)                                  | BUILDING PERMIT APPROVAL   |
| ENGINEER'S CERT (DRB SITE PLAN)  ENGINEER'S CERT (ESC) | X GRADING PERMIT APPROVAL SO-19 APPROVAL  DAVING DEDMIT APPROVAL  ECC. DEDMIT APPROVAL   |
| ENGINEER'S CERT (ESC) SO-19                            | PAVING PERMIT APPROVAL  ESC PERMIT APPROVAL  WORK ORDER APPROVAL  ESC CERT ACCEPTANCE    |
| OTHER (SPECIFY)  | WORK ORDER APPROVAL ESC CERT. ACCEPTANCE GRADING CERTIFICATION OTHER (SPECIFY)           |
|  |  |
| WAS A PRE-DESIGN CONFERENCE ATTENDED:                  | Yes X No Copy Provided   |
| DATE SUBMITTED: 1/18/15                                | By:  |

Requests for approvals of Site Development Plans and/or Subdivision Plats shall be accompanied by a drainage submittal. The particular nature, location, and scope to the proposed development defines the degree of drainage detail. One or more of the following levels of submittal may be required based on the following

- 1. Conceptual Grading and Drainage Plan: Required for approval of Site Development Plans greater than five (5) acres and Sector Plans
- 2. Drainage Plans: Required for building permits, grading permits, paving permits and site plans less than five (5) acres
- 3. Drainage Report: Required for subdivision containing more than ten (10) lots or constituting five (5) acres or more
- 4. Erosion and Sediment Control Plan: Required for any new development and redevelopment site with 1-acre or more of land disturbing area, including project less than 1-acre than are part of a larger common plan of development



# DROP INLET CALCULATIONS

| INLET | TYPE OF  | AREA  | Q ·   | Н      | H ALLOW |
|-------|----------|-------|-------|--------|---------|
|       | INLET    | (SF)  | (CFS) | (FT)   | (FT)    |
| 1     | SINGLE D | 5.92  | 18    | 0.3988 | 1       |
| 1     | DOUBLE D | 11.84 | 39    | 0.4680 | 1       |


# ORIFICE EQUATION

Q = CA sqrt(2gH)

0.6

g =

32.2



| Weighted E Metho  |        |               |                     |         |             |         |        |         |          | Del        | toutous        | A Hadi  | J. H. | JS CW   |
|---|--------|---------------|---------------------|---------|-------------|---------|--------|---------|----------|------------|----------------|---------|-------|---------|
|   | A      |               | //<br>  <del></del> |         | T           |         |        |         |          |            | 100-Year, 6-hr |         |       | 10-day  |
| Basin   | Area   | Area          | Treatment           | * *     | Treatment E |         | Treatm |         | Treatmen | t\D        | Weighted E     | Volume  | Flow  | Volume  |
|   | (sf)   | (acres        | <b>%</b>            | (acres) | <u> </u>    | (acres) |        | (acres) | <b>%</b> | ;∻(acres)  | (ac-ft)        | (ac-ft) | cfs   | (ac-ft) |
| BASIN A1  | 193022 | 4.431         | 0%                  | 0       | 12.0%       | 0.532   | 50.0%  | 2.21559 | 38%      | 1.684      | 1.652          | 0.610   | 17.48 | 0.835   |
| ALLOWED IN NAAMDP   | 193022 | 4.431         | 0%                  | 0       | 34.0%       | 1.507   | 18.0%  | 0.70899 | 50%      | 2.216      | 1.699          | 0.627   | 17.49 | 0.923   |
| UPLAND  | 423336 | 9.718         | 0%                  | 0       | 34.0%       | 3.304   | 16.0%  | 1.55495 | 50%      | 4.859      | 1.699          | 1.376   | 38.35 | 2.024   |
| equations:  Veighted E = Ea*Aa + Eb*Ab  Volume = Weighted D * Total |        | d*Ad / (Total | Area)               |         |             |         |        |         | bas      | ر م<br>الا | ris            |         |       |         |

## DRAINAGE NARATIVE

Flow = Qa \* Aa + Qb \* Ab + Qc \* Ac + Qd \* Ad

Ea= 0.66

Eb = 0.92

Ec= 1.29

Ed = 2.36

Where for 100-year, 6-hour storm (zone 3)

Site is a temporary use. The site is located bains 117.2 and 117.3. The upland flow of 38.35 cfs will enter the site and drain to the swale along oakland. The flow will be captured by a double D inlet The onite flow will be captured by a single D inlet connected to the wye stubed into the property. The land treatment of millings was approximated by assigning 50%d and 50%C. The First flush volume of 2078 has been provided onsite

FIRST FLUSH=

1781.317 CF

Qa= 1.87

Qb=2.6

Qc = 3.45

Qd = 5.02

