RESOURCE TECH INC

C/9/D049

File

December 19, 2006

Michael Smith, P.E. 5003 Dream Dancer Dr NE Rio Rancho, NM 87144 505-771-8677

Post-It® Fax Note 7671	Date # of pages /c+4
To Brad Binghan	From MICHAEL SM. 114
Co./Dept.	Co.
Phone #	Phone # 771-8677
Fax II	Fax #

Re: New Covenant Church Grading Plan Comments for Site Development Plan and

Preliminary/Final Plat

Site: 7200 Holly NE (C19/D49)

Dear Mr. Cheme,

Thank you for your comments dated December 11, 2006. This letter will endeavor to address all of your concerns regarding the Site Development Plan and Preliminary/ Final plat for this project. Additional information will be sent to address the comments for Building Permit. If you still have remaining concerns or additional questions, feel free to contact me or Elizabeth Smith, P.E. at the above phone number.

The drainage in Holly Avenue is partitioned into three parts. The eastern reach adjacent to Wyoming Boulevard and east of our site drains to a low point in Holly and flows overland into the AMAFCA pond and dam. The ultimate plan, according to the North Albuquerque Acres Master Drainage Plan, is for the existing storm drain in Holly Avenue to be extended to this low point and for additional inlets to be installed. This reach of street does not contribute flow to Holly Avenue adjacent to our property, nor does our property contribute flow to this overland flow. The majority of the flow in Holly that enters the AMAFCA pond, all but 25 cfs, originates in this reach. Since there is a low point in the street at this point, all of the flow generated in this reach will enter the AMAFCA pond.

The central portion of Holly in which our site resides, drains into two existing type 'C' inlets and an existing 30" storm drain that discharges to the AMAFCA pond and dam. The existing storm drain was designed to convey the ultimate flow of 119 cfs into the pond (see North Albuquerque Acres table 5e page 33 excerpt in report). The fully developed Holly Avenue is capable of conveying 171 cfs, however, this reach will only need to convey 25 cfs to the inlets. The remaining flow is captured by the low point to the east. The two inlets are within a street sloped at 2.75%. Therefore, since they are not in a sump, it is not possible for these inlets to capture all of the flow in the street. There will be some bypass flow that will enter the two double 'A' inlets further west in Holly or the three existing inlets in Paseo del Norte at the Louisiana Boulevard intersection. These inlets drain into the Paseo del Norte storm drain. The existing inlets in Holly that discharge to the pond will capture 14 cfs and will allow 11 cfs to bypass. Therefore, of the 119 cfs generated, the pond will receive 103 cfs. The North Albuquerque Acres Master Drainage Plan does not suggest installing additional inlets within this reach.

To conclude, Holly Avenue adjacent to our property has sufficient capacity to convey the contributing flow to the existing inlets. The storm drain and inlets to serve this reach of Holly Avenue have been constructed. However, storm drain facilities are not in place to accommodate

drainage from properties east of our site on Holly Avenue. Holly Avenue is currently only developed on the south side of the street in the eastern reach. The properties on the north side of the street could construct a storm drain to serve them when they construct the north curb and gutter and complete the street paving.

Responses by comment:


- 1) The capacity of the inlets in Holly are 7 cfs each. The capacity of the 30" storm drain is 119 cfs.
- 2) The storm drain from the pond east has only been constructed to accommodate the central reach of Holly Avenue. The storm drain has not been constructed to the existing local low point east of our site. Our site does not contribute flow to this low point.
- 3) Holly Street Capacity = 171 cfs
- 4) The total developed runoff contributing to the AMAFCA pond per the North Albuquerque Acres Master Drainage Plan assumptions will be 119 cfs.

Engineer's Stamp

Michael D. Smith, P.E.

19 1 Ant 15

December 19, 2006



Worksheet Worksheet for Irregular Channel


		Andrian and in Camber and in
Project Description	חכ	
Worksheet	Irregular	
	Channel - I	
Flow Element	Irregular	
	Channel	
Method	Manning's	
	Formula	
Solve For	Discharge	
Input Data	******	
Slope	2.7500 %	
Water Surface	0.67 ft	
Elevation		
Options		
Current Roughnes	ss Method	Improved Lotter's Method
Open Channel We	eighting Method	Improved Lotter's Method
Closed Channel V	Veighting Method	Horton's Method
Results		
Mannings Coeffic	ient	0.016
Elevation Range		0.00 to 0.67
Discharge		171.20
Flow Area		18.8
Wetted Perimeter	•	41.35
Top Width		40.00
Actual Depth		0.67
Critical Elevation		1.03
Critical Slope		0.4247
Velocity		9.11
Velocity Head		1.29
Specific Energy		1.96
Froude Number		2.34
Flow Type		Supercritical

Roug	ghness Seg	ments
Start Station	End Station	Mannings Coefficie nt
0+00	0+40	0.016

	Channel ints
Station	Elevation
(ft)	(ft)
0+00	0.67
0+00	0.00
0420	0.40
0+40	0.00
0+40	0.67

Cross Section Cross Section for Irregular Channel

Project Description	רא		
Worksheet	Irregular Channel - 1		
Flow Element	Irregular Channel		
Method	Manning's Formula		
Solve For	Discharge		
Section Data		······································	······································
Mannings Coeffic	ient	0.016	
Slope		2.7500	%
Water Surface El	evation	0.67	ft
Elevation Range		0.00 to 0.67	
Discharge		171.20	cts



V:10,0\\\H:1 NTS



December 16, 2008

Michael D. Smith, P.E. 5003 Dream Dancer Dr Rio Rancho, NM 87144

Re: New Covenant Church, 7200 Holly Ave NE, Grading Plan

Engineer's Stamp dated 12-12-08 (C19/D049)

Dear Mr. Smith,

Based upon the information provided in your submittal received 12-15-08, the above referenced plan is approved for Building Permit and SO 19 Permit. Please attach a copy of this approved plan to the construction sets prior to sign-off by Hydrology.

To obtain a temporary or permanent CO, Engineer Certification of the Grading Plan per the DPM is required and the sidewalk culverts in the City ROW must be inspected and accepted. Please contact Duane Schmitz, 235-8016, to schedule an inspection.

PO Box 1293

If you have any questions, you can contact me at 924-3695.

Albuquerque

Sincerely,

NM 87103

Curtis A. Cherne, P.E.
Senior Engineer, Planning Dept.

Development and Building Services

www.cabq.gov

Copy: file

Duane Schmitz, Street/Storm Drain Maintenance Antoinette Baldonado, Excavation and Barricading



December 22, 2008

Michael D. Smith, P.E. 5003 Dream Dancer Dr Rio Rancho, NM 87144

Re: New Covenant Church, 7200 Holly Ave NE

Permanent Certificate of Occupancy Approved

Engineer's Stamp dated 12/12/08 (C19/D049)

Certification dated 12/18/08

Based upon the information provided in your submittal received 12/22/2008, the above referenced certification is approved for release of Permanent Certificate of Occupancy by Hydrology.

If you have any questions, you can contact me at 924-3695.

PO Box 129-3

Albuquerque

Sincerely,

Curtis A. Cherne, P.E.

Senior Engineer


Development and Building Services

NM 87103

C: File

Katrina Sigala- CO Clerk

www.cabq.gov



August 22, 2008

Michael D. Smith, P.E. 5003 Dream Catcher Dr Rio Rancho, NM 87144

Re: New Covenant Church, 7200 Holly Ave NE, Grading Plan Engineer's Stamp dated 8-5-08 (C19/D049)

Dear Mr. Smith,

Based upon the information provided in your submittal received 8-5-08, the above referenced plan is approved for Building Permit and SO 19 Permit. Please attach a copy of this approved plan to the construction sets prior to sign-off by Hydrology.

It is not apparent that you intend to build standard curb and gutter along Holly Ave. Standard curb and gutter is required to build a sidewalk culvert per COA STD DWG 2236.

PO Box 1293

To obtain a temporary or permanent CO, Engineer Certification of the Grading Plan per the DPM is required and the storm drain work in the City ROW must be inspected and accepted. Please contact Duane Schmitz, 235-8016, to schedule an inspection.

Albuquerque

If you have any questions, you can contact me at 924-3695.

NM 87103

Curtis A. Cherne, P.E.

Sincerely

www.cabq.gov

Senior Engineer, Planning Dept.
Development and Building Services


Copy: file

Antoinette Baldonado, Excavation and Barricading Duane Schmitz, Street/Storm Drain Maintenance

NEW COVENANT CHURCH DRAINAGE PLAN

DECEMBER 5, 2006

Engineer's Seal



I. INTRODUCTION

A. Purpose and Scope of Report

The purpose of this drainage plan is to analyze and assess the impacts of the proposed New Covenant Church development. This report has been submitted for Preliminary and Final Plat review and Site Development Plan for Building Permit. This report includes graphical description of the onsite drainage area, estimates quantities of water discharged from the site before and after development, and presents a graphic description of the direction of water flow and points of discharge from the site after development. In addition, a discussion of the impact of the development on downstream properties is provided including capacity analysis of current facilities to handle the design flow.

B. Site Location

The New Covenant Church property is located in North Albuquerque Acres within the City of Albuquerque, Bernalillo County, New Mexico. The property is located west of Wyoming Boulevard and north of Paseo del Norte on Holly Avenue. The address is 7200 Holly Avenue and is legally lot 7A, block 10 of North Albuquerque Acres Tract 2, Unit 3. See the attached Zone Atlas map for more detail.

C. Development Concept

This property will be developed as a new church facility for New Covenant Church. The facility has been designed in three phases. The first phase is a 13,000 square foot worship center. The second phase is a 6000 square foot single story classroom wing to the north of the worship center. Finally, phase three is a 6000 square foot office wing to the east of the worship center. This building will be located on a 2.8 acre parcel of land. The property is zoned SU-2.

D. Drainage Concept

The drainage from this property has been accounted for in the North Albuquerque Acres Master Drainage Plan prepared by Resource Technology Inc. The runoff from the site will enter Holly Avenue and flow west to the AMAFCA pond to the north of Holly and then to

the Lower North Domingo Baca Dam. The flow from this site was included in the design of this pond and dam.

The Flood Insurance Rate Map indicates that the property is in unshaded Zone X.

II. EXISTING CONDITIONS

The New Covenant site is currently undeveloped and drains from south-east to north-west at a slope of approximately 4%. The property to the east has been developed with a metal building and a parking lot. Flow from this neighboring site enters Holly Avenue and diverts all offsite flow away from the site. The property to the west is currently undeveloped.

The existing flow from the New Covenant Site enters Holly Avenue to the west of the property and is captured by existing storm drain inlets in Holly Avenue east of Louisiana Boulevard. These inlets deposit the flow into the AMAFCA pond and subsequently into the Lower North Domingo Baca Dam. These facilities were designed to accommodate developed flow from this site. Please refer to the Basin Map drawings.

III. DEVELOPED CONDITIONS

The runoff from this site will flow within the paved parking lot and enter Holly Avenue at the two entrances. It will then flow west on Holly Avenue to the existing storm drain inlets and into the AMAFCA pond. Please refer to the attached grading plan for detailed grading.

The proposed developed conditions were analyzed for the 100-year, 6 hour storm event in accordance with the revised Section 22.2, Hydrology, of the Development Process Manual (DPM) for the City of Albuquerque, January, 1993 and were compared with the original design for the AMAFCA pond that accepts the flow. Since this site is less than 2 acres, the 40 Acre and Smaller Basins method was employed.

The AMAFCA pond was originally designed to accept 112.5 cfs from 28.9 acres of land and convey the flow into the Lower North Domingo Baca Dam. A storm drain system, including inlets, was designed and constructed within Holly Avenue that will accommodate 119 cfs. (See excerpts from the North Albuquerque Acres Master Drainage Plan in Appendix C.) The contributing land was assumed to have 60% impervious area when these facilities

were designed. Therefore, the New Covenant site was expected to produce 11.5 cfs of runoff. In actuality, this site will produce 13.0 cfs during the 100-year event due to an increased impervious percentage of 82%. (See spreadsheets in Appendix B.) This modification will increase the expected runoff by 1.5 cfs. This minimal increase in runoff will not adversely affect the downstream system because the storm drain system was designed with an excess of 6.5 cfs and the pond discharges directly into the Dam. It is not likely that all of the basins contributing to the Dam will receive the 100-year flow at the same time. This extra flow is well within the safety capacity that was built into the system.

IV. CONCLUSIONS

The primary purpose of this report is to evaluate impacts to the downstream system due to the proposed development. The development of the New Covenant Church Facility does not adversely impact the downstream system. The existing storm drain, pond, and dam were designed to accommodate the flow from this development.

V. REFERENCES

<u>Development Process Manual</u>, City of Albuquerque, Planning Development and Public Works Department, January, 1993.

North Albuquerque Acres Master Drainage Plan, Resource Technology Inc., October 1998.

Title

NCC

BASIN:

Description


NW corner of ex. Property


CONDITION:

Description

Input	zone 1 2 3 4	(x) ×	area (acres) 1.0900	land treatment (AB 0.0 CD 100.0	0	
Output Volume	2-YR	6-hr 24-hr 4-day 10-day	(ac-ft) 0.081 0.126 0.158 0.167	Q-Peak	2-YR 10-YR 100-YR	(cfs) 2.224 3.695 5.472
	10-YR	6-hr 24-hr 4-day 10-day	0.136 0.182 0.213 0.223			
•	100-YR	6-hr 24-hr 4-day 10-day	0.214 0.260 0.337 0.423			

^{*} City of Albuquerque Development Process Manual, Volume 1, 1997 Revision, pages 22-7 to 22-16.





NEW COVENANI CHURCH OFFSITE BASINS COA# 664482 C19/D49

Title

NCC

BASIN:

Description


South offsite flow east of Existing church property

CONDITION:

Description

Input	zone 1 2 3 4		area (acres) 0.2800	land treatment (AB 100.0 CD 0.0	0	
Output Volume	2-YR	6-hr 24-hr 4-day 10-day	(ac-ft) 0.001 0.001 0.001 0.001	Q-Peak	2-YR 10-YR 100-YR	(cfs) 0.059 0.333 0.728
	10-YR	6-hr 24-hr 4-day 10-day	0.008 0.008 0.008			
	100-YR	6-hr 24-hr 4-day 10-day	0.021 0.021 0.021 0.021		•	

^{*} City of Albuquerque Development Process Manual, Volume 1, 1997 Revision, pages 22-7 to 22-16.



Title

NCC

BASIN:

Description

Existing church property going to cross-access


CONDITION:

Description

nput			
	zone (x)	area (acres)	land treatment (%)
	1	0.6850	A
	2		B 0.00
	3 ×		C
	4		D 100.00
	 		

Output			(ac-ft)			(cfs)
Volume	2-YR	6-hr	0.051	Q-Peak	2-YR	1.397
		24-hr	0.079		10-YR	2.322
		4-day	0.099		100-YR	3.439
		10-day	0.105			
	10-YR	6-hr	0.086			
		24-hr	0.114			
		4-day	0.134			
		10-day	0.140			
	100-YR	6-hr	0.135			
		24-hr	0.163			
		4-day	0.212			
		10-day	0.266			

^{*} City of Albuquerque Development Process Manual, Volume 1, 1997 Revision, pages 22-7 to 22-16.



New Covenant Church

BASIN:

Church and parking lot

CONDITION:

As designed NAA

Part A -- Procedure for 40 Acre and Smaller Basins*

Input

zone (x)	area (acres)	land trea	tment (%)
1	2.7500	Α	0.00
2		В	25.00
3 x		C	15.00
4		D	60.00

Output			(ac-ft)			(cfs)
Volume	2-YR	6-hr	0.133	Q-Peak	2-YR	3.832
		24-hr	0.201		10-YR	7.237
		4-day	0.250		100-YR	11.494
		10-day	0.263			
	10-YR	6-hr	0.248			
		24-hr	0.317			
		4-day	0.365			
		10-day	0.379			
	100-YR	6-hr	0.422			
		24-hr	0.490			
		4-day	0.607			
		10-day	0.738			

^{*} City of Albuquerque Development Process Manual, Volume 1, 1997 Revision, pages 22-7 to 22-16.

PROJECT: New Covenant Church

BASIN: Church and parking lot

CONDITION: Final buildout

Input				
	zone (x)	area (acres)	land trea	tment (%)
	1	2.7500	A	0.00
	2		В	0.00
	3 x		C	18.00
	4		D	82.00

Output			(ac-ft)			(cfs)
Volume	2-YR	6-hr	0.175	Q-Peak	2-YR	4.986
		24-hr	0.269		10-YR	8.634
		4-day	0.335		100-YR	13.028
		10-day	0.354			
	10-YR	6-hr	0.307			
		24-hr	0.401			
		4-day	0.467			
		10-day	0.486			
	100-YR	6-hr	0.497			
		24-hr	0.591			
		4-day	0.750			
		10-day	0.929			

^{*} City of Albuquerque Development Process Manual, Volume 1, 1997 Revision, pages 22-7 to 22-16.



Planning Department Transportation Development Services Section

January 13, 2008

Joe Slagle, Registered Architect, Slagle Herr Architects 1600 Rio Grande NW Albuquerque, NM 87104

Re: Approval of Permanent (Final) Certificate of Occupancy (C.O.) for

New Convenant Church, [C-19 / D049]

7200 Holly NE

Architect's Stamp Dated 01/08/00

Dear Mr. Slagle:

Sincerely,

The TCL/Letter of Certification submitted on January 13, 2009 is sufficient for acceptance by this office for Permanent, Final, Certificate of Occupancy (C.O.). Notification has been made to the Building and Safety Section.

PO Box 1293

Albuquerque

NM 87103

Senior Traffic Engineer

Development and Building Services

Nilo E. Salgado-Fernandez, P.E.

Planning Department

www.cabq.gov

c: Engineer
Hydrology file

CO Clerk

January 8, 2009

Mr. Nilo Salgado-Fernandez, P.E. City of Albuquerque Transportation Development Department 600 2nd Street SW Albuquerque, NM 87102

RE: NEW COVENANT CHURCH - WEST DRIVEWAY 7200 Holly NE

Nilo,

Per our phone conversation, this letter shall serve to clarify our position regarding the west driveway serving the property listed above from Holly Ave. NE.

The driveway was installed at a steeper grade than originally intended because of some unforeseen grading and accessibility issues. However, the existing condition has been reviewed by the civil engineer for the project as well as the ownership and our office and we are all in agreement that the condition is acceptable.

If you are in agreement that this is consistent with our conversation, please

issue a letter of approval for permanent C.O.

Thank you for your attention to this matter.

Sincerely,

Joe L. Slagle

President

SlagleHERR Architects Inc.

JAN 13 :303 HYDROLOGY SECTION SINIE OF NEW

O

1600 rio grande nw 5 o 5 2 4 6 o 8 7 o fax 505 246 0437 new mexico 87104

January 8, 2009

Mr. Nilo Salgado-Fernandez, P.E.
City of Albuquerque
Transportation Development Department
600 2nd Street SW
Albuquerque, NM 87102

RE: NEW COVENANT CHURCH - WEST DRIVEWAY 7200 Holly NE

Nilo,

Per our phone conversation, this letter shall serve to clarify our position regarding the west driveway serving the property listed above from Holly Ave. NE.

The driveway was installed at a steeper grade than originally intended because of some unforeseen grading and accessibility issues. However, the existing condition has been reviewed by the civil engineer for the project as well as the ownership and our office and we are all in agreement that the condition is acceptable.

If you are in agreement that this is consistent with our conversation, please issue a letter of approval for permanent C.O.

Thank you for your attention to this matter.

Sincerely,

Joe 4. Slagle

President

SlagfeHERR Architects Inc.



l a G

Ð

1600 rio grande nw 1600 rio grande nw 505 fax 505 246 0437 new mexico 87104

5 o 5 2 4 6 o 8 7 o