CITY OF ALBUQUERQUE

Planning Department Alan Varela, Director



Mayor Timothy M. Keller

June 20, 2024

Mark H. Burak, P.E. 1512 Sagebrush Trail SE Albuquerque, NM 87123

RE:

Carmel – Ventura Subdivision Grading and Drainage Plans

Engineer's Stamp Date: 04/14/2024

Hydrology File: C20D090

Dear Mr. Burak:

Based upon the information provided in your submittal received 05/06/2024, the Grading & Drainage Plan is approved for Building Permit and Grading Permit. Please attach a copy of this approved plan in the construction sets for Building Permit processing along with a copy of this letter.

PO Box 1293

PRIOR TO CERTIFICATE OF OCCUPANCY:

Albuquerque

1. Engineer's Certification, per the DPM Part 6-14 (G): *Engineer's Certification Checklist For Subdivisions* is required.

NM 87103

As a reminder, if the project total area of disturbance (including the staging area and any work within the adjacent Right-of-Way) is 1 acre or more, then an Erosion and Sediment Control (ESC) Plan and Owner's certified Notice of Intent (NOI) is required to be submitted to the Stormwater Quality Engineer (Doug Hughes, PE, jhughes@cabq.gov, 924-3420) 14 days prior to any earth disturbance.

www.cabq.gov

If you have any questions, please contact me at 924-3314 or amontoya@cabq.gov.

Sincerely,

Anthony Montoya, Jr., P.E.

and Mars

Senior Engineer, Hydrology

Planning Department, Development Review Services

GRADING & DRAINTAGE PLAN CARMEL-VENTURA SUBDIVISION

APRIL 2024

NOTES

Site Location - As shown by the Vicinity Map, the 0.726-acre site is located on the north side of Carmel Avenue NE, on the east side of Ventura Street just north of Paseo del Norte Boulevard. At present, the site is undeveloped and drains roughly from west to east to an existing drop inlet located in Ventura Street. The purpose of this project is to develop the property to construct four separate residential structures with a 150-foot long private roadway.

Legal Description - Carmel Avenue NE. Lot 32, Block 18, Unit 3, Tract 3 North Albuquerque Acres, New Mexico. UPC 102006427312040301

Flood Zone - As shown by Panel 141G of 825 of the National Flood Insurance Program Flood Insurance Rate Maps (FIRM) for Bernalillo County, New Mexico, dated September 26, 2008, this site does not lie within a designated flood hazard zone.

Existing Conditions – Currently, the site is undeveloped. Previous grading has been conducted on the property and it is sloped westward with little to no native vegetation. Runoff from upstream impacts Carmel from the east and is partially captured in the existing drop inlet located near the Ventura intersection. The drop inlet is part of the North Domingo Baca arroyo storm drain system and is located directly west of Carmel Avenue on the west side of Ventura Street. This storm drain has been designed to intercept the entire offsite discharge from Carmel Avenue and Ventura Street Additional runoff impacts Ventura from the north which is also intercepted within an existing drop inlet on the west and east sides of Ventura Street. Currently, Ventura Street is only partially completed with the east side of the roadway being about six feet narrower than fully developed conditions. Also, there is no sidewalk on the east side of Ventura Street adjacent to the subject property.

Hydrologic Methods - The drainage calculations estimate the potential runoff from the project to assess the peak flow rate at the outfall of the project site culminating at the southeastern property boundary at Carmel Avenue. The calculations which appear hereon analyze both the existing and fully developed conditions for the 100-year, 6-hour rainfall event. Four offsite basins and eight on-site basins were assessed. The on-site basins were established to reflect the rear and front portions of each proposed parcel along with the new roadway. See attached spreadsheet for calculations.

First Flush / Water Quality Management - The first flush has been mitigated based on 18,000 sf of the project site to be impervious. This equates to an area of 9,300*0.61/12 or 904 cubic feet. This storage has been provided on the plan by implementing a shallow retention basin into the rear area of each proposed lot. Basins L, K, L, and M all drain into a retention area in the rear yards of Lots 1-4 with a total available retention volume of 939 cubic feet. Any excess runoff is to be directed to the Ventura Street right-of-way through single turned blocks in the westerly garden walls.

Proposed Conditions – All four residences are to be constructed with finished floor elevations of 5,551.5 to 5,553.0feet. To provide adequate pad sites that will drain to the retention areas and/or Meiomi Court and Carmel Avenue, between one to four feet of fill material will be required for the four proposed lots. This will allow for a one percent slope for the west gutter of the proposed roadway to ensure adequate drainage capacity.

The existing homes adjacent to the east are about two to three feet higher than the ground of the subject property. A retaining wall is located along the eastern property boundary. To retain additional material along the western side of the property, a new six-foot high retaining wall will need to be constructed adjacent to the new Ventura Street right-of-way. Since the proposed sidewalk, and curb and gutter for Meiomi Court is adjacent to the existing east retaining wall, the curb return radius to Carmel Avenue will need to be reduced to only 12-feet. This will allow adequate room for the sidewalk and handicap ramps at the intersection.


Carmel Avenue is currently completed including the property frontage. This reach adjacent to the subject property will require a new curb cut for the proposed roadway along with associated handicap ramps. Carmel Avenue is currently sloped at three percent from east to west. The proposed sidewalk slope was decreased to two percent to allow for a flatter handicap ramp at the east side of the new intersection. The handicap ramp is located at the vertical juncture between the one percent north/south curb and gutter and the new Carmel curb and gutter. The bottom of the handicap ramp is level at the curb return. The western portion of the new roadway will transition from one percent to two percent towards the south. To obtain a flat handicap ramp access from the roadway, the new road slope will need to increase to three percent for a short reach.

The rear yard areas between the proposed houses and retaining wall will be depressed about one foot to obtain a maximum retention capacity for each lot between 400-550 cubic feet. These depressed areas will be landscaped and a portion of the roof drainage will discharge into these areas. The ponding areas will overflow through turned blocks in the wall onto the Ventura Street drop inlet. The overflow runoff from the front portions of the lots will continue south along the new roadway and will discharge into Carmel Avenue where it will be intercepted by the same storm drainage system.


The rear and side yards are to be graded away from the houses to discharge into one of the water quality basins. The rear yards within the garden wall may be sodded since the retention areas are limited to only one foot of depth. The side yard areas are to be graveled and landscaped with native plantings. All graded and disturbed areas within the property are to be reseeded and revegetated in accordance with City of Albuquerque Guidelines for Sustainability.

The concept of this development is to blend harmoniously into the existing environment. The area within the garden walls will be graded to a minimum slope to ensure that any runoff impacting the area will be spread into sheet flow to minimize discharge, depths and velocities associated with the design rainfall event.






VICINITY MAP



FEMA MAP





Subdivisio


OTS 31-32, BLOCK 6, TRACT 2, U NORTH ALBUQUERQUE ACRES,

DRAWING NUMBER

1 OF 6








SUMP CONDITION Double "A" Curb Ope		
Lateral Width, W. 2.00 feet	Weir flow	7.12 cfs
Orifice height, h 0.50 feet	Orifice flow	8.20 cfs

Type Double "A" Inlet 2'x3' Standard		
Flow depth, y 0.75 feet Grate open area, F 24.00 sq.ft. Grate Perimeter, P 16.00 feet Clogging percenta; 50 %	Weir flow 15.59 cfs Orifice flow 55.84 cfs	

EXIST. DROP INLET CAPACITY



4'-6' RETAINING WALL DETAIL


LEGEND Sanitary Sewer Manhole Storm Sewer Manhole SAS Sanitary Sewer Line ____ST___ Storm Drain Line ——UGE— Underground Electric line ——OHE— Overhead Electric line ——COM — Underground Communications L Sanitary Sewer Clean-out Water Valve Hydrant Cable Pedstal Electric Pedstal Electric Transformer Light Pole Concrete Symbol ■ Power Pole Telephone Pedestal

P.

Subdivision LOTS 31-32, BLOCK 6, TRACT 2, UNIT NORTH ALBUQUERQUE ACRES, NM

DRAWING NUMBER

2 OF 3



3 OF 3