

City of Albuquerque

P.O. BOX 1293 ALBUQUERQUE, NEW MEXICO 87103

November 19, 2001

Kim Kemper, PE Kemper – Vaughan Construction Engineers 5610 San Francisco NE Albuquerque, NM 87199

Re: Lorraine Ct. Warehouse Grading and Drainage Plan

Engineer's Stamp dated 2-22-01, (D17/D67)

Engineering Certification dated 11-06-01

Dear Mr. Kemper,

Based upon the information provided in your submittal dated 11-13-01 and 11-19-01, Engineering Certification for Certificate of Occupancy for the above referenced site is approved.

If I can be of further assistance, please contact me at 924-3986.

Sincerely, Budle L. Bushum

Bradley L. Bingham, PE

Senior Engineer,

Building and Development Services

C: Vickie Chavez, CoA file



City of Albuquerque

P.O. BOX 1293 ALBUQUERQUE, NEW MEXICO 87103

768-2804

February 22, 2001

Kim R. Kemper, P.E. Kemper-Vaughan Consulting Engineers 5610 San Francisco NE Albuquerque, NM 87109

Re: Drainage Plan & Grading Plan Submittal for Building Permit Approval and SO-19, Lorraine Court Warehouse, Engineer's stamp dated 01-22-01 (D17/D067F)

Dear Mr. Kemper:

Based on the information provided in your submittal dated Feb. 22, 2001, the above referenced project is approved for Building Permit. Please attach a copy of this approved plan to the construction sets prior to sign-off by Hydrology.

In addition, the submittal is approved for an SO 19 permit, which is required for construction of the drainage improvements within the city right-of-way.

Prior to release of the Certificate of Occupancy, an Engineer Certification per the DPM checklist will be required. If you have any questions or if I may be of further assistance to you, please call me at 924-3988.

Sincerely,

Many Mus and

Nancy Musinski, P.E.

Hydrology/Utility Development

City of Albuquerque Public Works

cc: Pamela Lujan, PWD - Permits

file

LORRAINE COURT WAREHOUSE

GRADING PLAN & DRAINAGE PLAN

January 17, 2001

Prepared for:

JLS Architecture

• ;

1600 Rio Grande Blvd. NW


Albuquerque, New Mexico 87104

Prepared by:

KEMPER-VAUGHAN CONSULTING ENGINEERS

3700 Coors Road NW

Albuquerque, New Mexico 87120



PROJECT OVERVIEW

The site is located in the newly developed Paseo Del Norte Industrial Park Subdivision just west of Jefferson and south of Paseo Del Norte. As shown on panel 136 of the 1996 FIRM (attached), this site does not lie within a designated flood hazard area. The site is 1.94 acres in total and is currently vacant. There exists a 50-foot railroad spur easement along the eastern property line. Due to the topography within this easement approximately 0.13 acres of this site drains to the north and does not impact the subject site. As such all the data presented herein includes a total site area of 1.81 acres. The proposed project includes the construction of a new office/warehouse and related parking and landscaping.

DRAINAGE PLAN

As stated above, this site is within the Paseo Del Norte Industrial Park Subdivision that has just recently been completed. The drainage plan for this subdivision can be found it City file D17/D67. In that subdivision plan limited downstream capacities were identified. As such, each parcel in the subdivision was assigned a maximum allowable peak rate of discharge. The subject site, parcel H, has an allowable discharge of 3.2 cfs. This limitation requires onsite detention of developed storm water runoff.

The site is configured and graded into two separate sub-basins. There is a grade break in the southeast corner of the site. The east and north drive isles and parking represent one sub-basin identified in the calculations as the north drainage area. The new building, storage yards and south drive isle represent the sub-basin identified as the south drainage area. Two detention areas, two controlled outlets and two new sidewalk culverts were required to complete this plan. Each detention area is drained with a small diameter pipe. In a storm larger than the design event each detention area will breach through the proposed driveways into public right-of-way. The water blocks in the new drive isles were set at an elevation to provide the required detention volume and to provide a maximum head water (h) on the proposed pipe outlets. Using this maximum (h) a maximum peak rate of discharge for the controlled release can be calculated. Calculations for these culverts (controlled release) are attached.

Calculations are provided for the total site as well as the north area and the south area individually. To determine the required detention volumes it was identified that these ponds will drain in less than 6-hours; therefore, the 6-hour volumes were used. Hydrographs were calculated for the total site and each sub-basin. The volume of storm water released during the design event was determined and the required storage could then be calculated. The results of this exercise is as follows:

Total Site:

$$V_{100} = 11,375 \text{ cf}$$
 $Q_{100} = 7.28 \text{ cfs}$
$$T_b = (2.107)(1.73)(1.81/7.28) - (0.25)(1.23/1.81) = 0.736 \text{ hrs}$$

$$T_p = (0.7)(0.2) + ((1.6-1.23/1.81)/12) = 0.217 \text{ hrs}$$

Duration of Peak = (0.25)(1.23/1.81) = 0.170 hrs

North Area:

$$V_{100} = 4{,}479 \text{ cf}$$
 $Q_{100} = 2.87 \text{ cfs}$

$$T_b = (2.107)(1.67)(0.74/2.87)-(0.25)(0.49/0.74) = 0.742 \text{ hrs}$$


$$T_p = (0.7)(0.2) + ((1.6-0.49/0.74)/12) = 0.218 \text{ hrs}$$

Duration of Peak = (0.25)(0.49/0.74) = 0.166 hrs

8" culvert discharge pipe @ h = 1.27' max. $Q_{max} = 1.4$ cfs

Volume of water released during the storm event = 3,031 cf

Required storage = 4,479 - 3,031 = 1,448 cf



Storage provided per the proposed grading plan at water surface elevation equal to 5092.0 is approximately 2,400 cf

South Area:

$$V_{100} = 6,896$$
 cf $Q_{100} = 4.41$ cfs

$$T_b = (2.107)(1.67)(1.07/4.41)-(0.25)(0.74/1.07) = 0.737 \text{ hrs}$$

$$T_p = (0.7)(0.2) + ((1.6-0.74/1.07)/12) = 0.216 \text{ hrs}$$

Duration of Peak =
$$(0.25)(0.74/1.07) = 0.173$$
 hrs

10" culvert discharge pipe @
$$h = 1.00$$
' max. $Q_{max} = 1.7$ cfs $u = 1.1$

Volume of water released during the storm event = 3,846 cf

$$8186$$
 4340
Required storage = $65896 - 3,846 = 3,050$ cf

Storage provided per the proposed grading plan at water surface elevation equal to 5092.5 is approximately 3,300 ct year 1040 nume on ft. fine waterblock to 92,60 The maximum peak rate of discharge from this site as proposed is 1.4 + 1.7 = 3.1 cfs.

PIPE CULVERT ANALYSIS COMPUTATION OF CULVERT PERFORMANCE CURVE

January 17, 2001 LORRAINE CT. WAREHOUSE CONTROL OUTLET 8" CMP

DESCRIPT:	INPUT DATA: ION	•					VA 			
Culvert Diameter (feet)										
FHWA Char	rt Number ((1,2 or 3)	3)				1			
Scale Nur	mber on Cha	art (Type	e of Culv	zert Ent	crance)		3			
	s Roughness						0.0			
	Loss Coeff				_		0.5			
	Length (fee						10.0			
Culvert S	Slope (feet	: per foo	ot)				0.0			
======:	=======	=======	=======================================	======	=======	======	=====			
PROGRAM I Flow Rate (cfs)	Tailwater Depth	Headwat Inlet Control	Outlet	Normal Depth (ft)	Critical Depth (ft)	Depth at Outlet (ft)	Out Veloc			
Flow	Tailwater Depth	Inlet	Outlet	Depth	Depth	Outlet	Veloc			
Flow Rate (cfs)	Tailwater Depth (ft)	Inlet Control	Outlet Control	Depth (ft)	Depth (ft)	Outlet (ft)	Veloc (f 3			
Flow Rate (cfs)	Tailwater Depth (ft)0.00	Inlet Control 0.73	Outlet Control 0.89	Depth (ft) 0.67	Depth (ft) 0.48	Outlet (ft) 0.48	Veloc (f 3			
Flow Rate (cfs) 1.0 1.1	Tailwater Depth (ft)0.00 0.00	Inlet Control 0.73 0.79	Outlet Control 0.89 0.98	Depth (ft) 0.67 0.67	Depth (ft) 0.48 0.50	Outlet (ft) 0.48 0.50	Veloc (f 3			
Flow Rate (cfs)1.0 1.1 1.2	Tailwater Depth (ft) 0.00 0.00 0.00	Inlet Control 0.73 0.79 0.83	Outlet Control 0.89 0.98 1.09	Depth (ft) 0.67 0.67 0.67	Depth (ft) 0.48 0.50 0.52	Outlet (ft) 0.48 0.50 0.52	Veloc (f 3 4			

PIPE CULVERT ANALYSIS COMPUTER PROGRAM Version 1.7 Copyright (c) 1986 Dodson & Associates, Inc., 7015 W. Tidwell, #107, Houston, TX 77092 (713) 895-8322. All Rights Reserved.

PIPE CULVERT ANALYSIS COMPUTATION OF CULVERT PERFORMANCE CURVE

January 17, 2001 LORRAINE CT. WAREHOUSE CONTROL OUTLET 10" CMP

PROGRAM INPUDESCRIPTION							VALUE
Culvert Diam FHWA Chart I Scale Number Manning`s Ro Entrance Los Culvert Leng Culvert Slop	Number r on Cha oughness ss Coeff gth (fee	(1,2 or 3 art (Type s Coefficent of the coeffice	of Culverse Culvers	vert Ent -value) rt Open:	rance)		10.0
========	=======	=======	======	=	=======	=======	======
Rate	ilwater Depth	Inlet	Outlet	Depth	Depth	Depth at Outlet (ft)	Outlet Velocity (fps)
1.5	0.00	0.83	0.93	0.83	0.55	0.55	3.95

0.60 0.83 1.8 0.95 1.11 0.00 PIPE CULVERT ANALYSIS COMPUTER PROGRAM Version 1.7 Copyright (c) 1986 Dodson & Associates, Inc., 7015 W. Tidwell, #107, Houston, TX 77092

1.05

0.99 ~ 0.83

0.83

0.86

0.90

0.00

0.00

(713) 895-8322. All Rights Reserved.

1.6

1.7

4.06

4.17

4.28

0.57

0.59

0.60

0.57

0.59

DRAINAGE ZONE 2	AREA =	1.81 ac.		LORRAII TOTAL S		Γ OFFICE-W	VAREHOU	ISE	
PRECIPITATION:	360 = 1140 = 10day =	2.35 in. 2.75 in. 3.95 in.							
EXCE	SS PRECIP	ITATION:		PEAK DI	SCHARGE				
TREATMENT A TREATMENT B TREATMENT C TREATMENT D	0.53 in. 0.78 in. 1.13 in. 2.12 in.			1.56 2.28 3.14 4.70	cfs/ac. cfs/ac. cfs/ac. cfs/ac.				
EXISTING CONDITIO	NS: AREA		PROPOSI AREA	ED CONDI	ITIONS:				
TREATMENT A TREATMENT B TREATMENT C TREATMENT D	1.81 ac. 0 ac. 0 ac. 0 ac.		0.00 ac. 0.37 ac. 0.21 ac. 1.23 ac.						
EXISTING EXCESS P	RECIPITATI	<u>ON:</u>							
Weighted E = 0.53	•	1.81)+(0.78)x(0.00)+(1.13)x(0.00)+(2.12)x(0.00)/	1.81 ac.
V100-360 =	(0.53)x(1.81)/ 1	2 =	0.079942	ac-ft =	3482	of		
EXISTING PEAK DISC	CHARGE:								
Q100 =	(1.56)x(1.81)+(2.28)x(0.00)+(3.14)x(0.00)+(4.70)x(0.00)=	2.82 cfs
PROPOSED EXCESS	PRECIPITA	TION:				•			
Weighted E = 1.73	•	0.00)+(0.78)x(0.37)+(1.13)x(0.21)+(2.12)x(1.23)/	1.81 ac.
V100-360 =		1.81)/	12.0 =	0.261125	ac-ft =	11375 c	:f		
V100-1440 =	(0.26)+(1.23)x(2.75 -	2.35)/	12 =	0.302125 a	ic-ft =	13161	of
V100-10day =	(0.26)+(1.23)x(3.95 -	2.35)/	12 =	0.425125 a	ic-ft =	18518	cf
PROPOSED PEAK DI	SCHARGE:								
Q100 =	(1.56)x(0.00)+(2.28)x(0.37)+(3.14)x(0.21)+(4.70)x(1.23)=	7.28 cfs
RESULTS					•				

7.28 - 2.82 = 4.46 cfs Increase in peak discharge 11375 - 3482 = 7892 cf Increase in runoff volume

	AREA =	0.74 ac.		LORRAINE COURT OFFICE-WAREHOUSE NORTH DRAINAGE AREA							
DRAINAGE ZONE 2 PRECIPITATION:		2.35 in. 2.75 in. 3.95 in.									
EXC	ESS PRECIF	PITATION:		PEAK DIS	SCHARGE	•					
TREATMENT A TREATMENT B TREATMENT C TREATMENT D	0.53 in. 0.78 in. 1.13 in. 2.12 in.			1.56 2.28 3.14 4.70	cfs/ac. cfs/ac. cfs/ac. cfs/ac.						
EXISTING CONDITIO				ED CONDI	TIONS:						
TREATMENT A TREATMENT B TREATMENT C TREATMENT D	AREA 0.74 ac. 0 ac. 0 ac. 0 ac.		REA 0.00 ac. 0.25 ac. 0.00 ac. 0.49 ac.				•				
EXISTING EXCESS F	PRECIPITAT	<u>ION:</u>			*						
Weighted E =		0.74)+(0.78)x(0.00)+(1.13)x(0.00)+(2.12)x(0.00)/	0.74 ac.		
= 0.53 V100-360 =	m. (0.53)x(0.74)/ 12	2 =	0.032683	ac-ft =	1424	cf				
EXISTING PEAK DIS	CHARGE:										
Q100 =	(1.56)x(0.74)+(2.28)x(0.00)+(3.14)x(0.00)+(4.70)x(0.00)=	1.15 cfs		
PROPOSED EXCESS	S PRECIPITA	TION:					**				
Weighted E =	•	0.00)+(0.78)x(0.25)+(1.13)x(0.00)+(2.12)x(0.49)/	0.74 ac.		
= 1.67 V100-360 =		0.74)/	12.0 =	0.102817	ac-ft =	4479	cf				
V100-1440 =	(0.10)+(0.49)x(2.75 -	2.35)/	12 =	0.119150	ac-ft =	5190	cf		
V100-10day =	(0.10)+(0.49)x(3.95 -	2.35)/	12 =	0.168150	ac-ft =	7325	cf		
PROPOSED PEAK D	SCHARGE:										
Q100 =	(1.56)x(0.00)+(2.28)x(0.25)+(3.14)x(0.00)+(4.70)x(0.49)=	2.87 cfs		
RESULTS					•						
	2.87 -	1.15 =			•	ak dischar	-				

4479 - 1424 = 3055 cf

Increase in runoff volume

		AREA =	1.07 ac.	•	-			T OFFICE	-WAR	EHO	USE	
DRAINAGE ZONE 2	1				SOUTH	DKAIN	IAG	EAREA				
PRECIPITATION:	•	360 =	2.35 in.									
		1140 =	2.75 in.									
	1	10day =	3.95 in.									
EXC	ESS	S PRECIP	ITATION:		PEAK D	SCHA	RGF	-				
					1 1447 (1)		1102					
TREATMENT A		0.53 in.			1.56	cfs/a	C.					
TREATMENT B		0.78 in.			2.28	cfs/a	C.					
TREATMENT C		1.13 in.			3.14	cfs/a	C.					
TREATMENT D		2.12 in.			4.70	cfs/a	C.					
EXISTING CONDITION	ONS	•		PROPOS	ED COND	ITION	S:					
	A	AREA		AREA			-					
TREATMENT A		1.07 ac.		0.00 ac	•						•	
TREATMENT B		0 ac.		0.12 ac	•							
TREATMENT C		0 ac.		0.21 ac	•							
TREATMENT D		0 ac.		0.74 ac	•							
EXISTING EXCESS	PRE	CIPITATI	<u>ON:</u>									
Weighted E = 0.53		0.53)x(1.07)+(0.78)x((0.00)+	(1.13	3)x(0.00)+(2.12	2)x(0.00)/	1.07 ac.
V100-360 =		0.53)x(1.07)/	12 =	0.047258	ac-ft	=	2059	cf			
EXISTING PEAK DIS	SCH/	RGE:										
Q100 =	(1.56)x(1.07)+(2.28)x(0.00)+	(3.14)x(0.00)+(4.70))x(0.00)=	1.67 cfs
PROPOSED EXCES	S PF	RECIPITA	TION:								 ±	
								0			95	
Weighted E = 2.11			0.00)+(0.78)x(0.12)+(1.13)x(0.21)+(2.12	2)x(0.74)	1.07 ac.
= -1.78 V100-360 =	in.	1.78)x(1.07)/	12.0 =	رو 18 79 0.158308	ac-ft	=	ප (පිර 6896	cf			
V100-1440 =	(0.16)+(0.74)x(2.75 -	2.35)/	12	=	0.182975	ac-ft	=	7970	cf
V100-10day =	(0.16)+(0.74)x(3.95 -	2.35)/	12	=	0.256975	ac-ft	=	11194 (of
			, ,		•							
PROPOSED PEAK D	ISCI	HARGE:									o./	16.74
Q100 =	(1.56)x(0.00)+(2.28)x(0.12)+(3.14)x(0 .2 4)+(4.70)x(.95 0.74()=	4.41 cfs
RESULTS							•					
	L	1-74		3,07								
		1 ~ 1 · · · · · · · · · · · · · · · · ·	167 -	9-71 ofc	ina	rooco i	in na	ak dicahar	~~			

-4.41 - 1.67 = 2.74 cfs

6896~ - 2059 = 4837 cf

6127

8186

Increase in peak discharge

Increase in runoff volume



City of Albuquerque

P.O. BOX 1293 ALBUQUERQUE, NEW MEXICO 87103

Public Works Department Transportation Development Services Section

November 19, 2001

Fred Robinson for Joe Slagel, Registered Architect JLS Architects
1600 Rio Grande Blvd. N.W.
Albuquerque, NM 87106

Re:

Certification Submittal for Final Building Certificate of Occupancy for

Lorraine Court Warehouse, [D17 / D067F]

7900 Lorraine Ct. N.E. No Architect's Stamp

Dear Mr. Robinson:

The TCL / Letter of Certification submitted is sufficient for acceptance by this office for final Certificate of Occupancy (C.O.). Notification has been made to Building and Safety and final C.O. has been logged in by Vicki Chavez in the Building Safety Section downstairs.

For future submittals, TCL or letter of certification must be stamped with designer's seal, signed, and dated(date of submittal). The address of the site, development name and Hydrology file number need to be included in letter or on TCL.

<u>All</u> staff members of the design company must be made aware of these revisions to the procedure toward finalization of each commercial building project for Transportation/Hydrology.

Sincerely,

Mike Zamora

Commercial Plan Checker


Development and Building Services

Public Works Department

c: Engineer Terri Martin, Hydrology Office File

DRAINAGE INFORMATION SHEET

(REV. 11/01/2001)




PROJECT TITLE: LORDAINE COURT WAREHOUSE DRB #:EPC#:	ZONE MAP/DRG. FILE #: D-17-2 WORK ORDER#:
LEGAL DESCRIPTION: TRACTH PASED DEL HORTO CITY ADDRESS: 7700 LORRAINE CT. NE	E BUSINESS PARK
ENGINEERING FIRM: HUITT - ZOLLARS ADDRESS: 6501 AMERICAS PHUY CITY, STATE: AUSUQUERQUE, HM	CONTACT: KIM KEMPER PHONE: 885-8114 ZIP CODE: 87110
OWNER: LOS MOCHOS REALTY/DIVERSIFIED REALES ADDRESS: 1510 WYOMING TSLVD. NE CITY, STATE: ALBUQUELQUE, NM	PHONE: ZIP CODE:
ARCHITECT: JLS ARCHITECTS ADDRESS: 1600 RIO GRAHDE HW CITY, STATE: AUSUQUER QUE, HM	CONTACT: FRED ROBINSON PHONE: 246-0870 ZIP CODE: \$7106
SURVEYOR: REX VOBEL-RIO GRANDE SURV ADDRESS	PHONE: 265-8940 ZIP CODE:
CONTRACTOR: THE CONSTruction, Inc. ADDRESS: 2 Fine Rd. CITY, STATE: Flacitar, NM 87043	CONTACT: Frant Thomas PHONE: 867 0323 ZIP CODE: 97047
CHECK TYPE OF SUBMITTAL: DRAINAGE REPORT DRAINAGE PLAN CONCEPTUAL GRADING & DRAINAGE PLAN GRADING PLAN EROSION CONTROL PLAN ENGINEER'S CERTIFICATION (HYDROLOGY) CLOMR/LOMR TRAFFIC CIRCULATION LAYOUT (TCL) ENGINEERS CERTIFICATION (TCL) ENGINEERS CERTIFICATION (DRB APPR. SITE PLAN) OTHER	HECK TYPE OF APPROVAL SOUGHT: SIA / FINANCIAL GUARANTEE RELEASE PRELIMINARY PLAT APPROVAL S. DEV. PLAN FOR SUB'D. APPROVAL S. DEV. PLAN FOR BLDG. PERMIT APPROVAL SECTOR PLAN APPROVAL FINAL PLAT APPROVAL FOUNDATION PERMIT APPROVAL BUILDING PERMIT APPROVAL CERTIFICATE OF OCCUPANCY (PERM.) CERTIFICATE OF OCCUPANCY (TEMP.) GRADING PERMIT APPROVAL PAVING PERMIT APPROVAL WORK ORDER APPROVAL OTHER (SPECIFY)
WAS A PRE-DESIGN CONFERENCE ATTENDED: YES NO COPY PROVIDED	NOV 1 9 2001 HYDROLOGY SECTION
DATE SUBMITTED: 11/19/01 BY: 52	ROSINSON

Requests for approvals of Site Development Plans and/or Subdivision Plats shall be accompanied by a drainage submittal. The particular nature, location and scope of the proposed development defines the degree of drainage detail. One or more of the following levels of submittal may be required based on the following:

- 1. Conceptual Grading and Drainage Plan: Required for approval of Site Development Plans greater than five
- 2. Drainage Plans: Required for building permits, grading permits, paving permits and site plans less than five (5)
- 3. Drainage Report: Required for subdivisions containing more than ten (10) lots or constituting five (5) acres or

Heyfied Down States; 4/19/01 - ctain GT; Sent letter dated 11/19/01; loggedin to T.m.

November 12, 2000



Mr. Mike Zamora
City of Albuquerque
Transportation Development Department
600 2nd Street SW
Albuquerque, NM 87102

RE: Lorraine Court warehouse; 7900 Lorraine Court NE

Mr. Zamora:

This letter is to certify that the traffic circulation for the above referenced project has been constructed substantially in accordance with the City approved construction. Minor as-built revisions are clouded on the attached site plan.

Please contact me if you have any questions.

Sincerely,

Joe L. Slagle
JOS Architects

ARCHITE (T.S.

4/9/01 = Ctim GT; = Soutlefor Dufed it/19/01; - Ligation

