

CITY OF ALBUQUERQUE

Planning Department
Brennon Williams, Director



Mayor Timothy M. Keller

December 31, 2019

Genny Donart, P.E.
Isaacson & Arfman, P.A.
128 Monroe St. N.E
Albuquerque, NM 87108

**RE: Masthead Street Extension
Masthead St, West of Bartlett
Grading Plan Stamp Date: 12/18/19
Drainage Report Stamp Date: 12/18/19
Hydrology File: D17D109**

Dear Ms. Donart:

PO Box 1293
Based on the submittal received on 12/19/19 the above-referenced submittal is approved for Work Order.

Albuquerque
If you have any questions, please contact me at 924-3695 or dpeterson@cabq.gov.

NM 87103

Sincerely,

www.cabq.gov

Dana Peterson, P.E.
Senior Engineer, Planning Dept.
Development Review Services

DECEMBER 2019

DRAINAGE REPORT

FOR

MASTHEAD ST. EXTENSION

BUILDERS TRUST OF NEW MEXICO

BY

 **Isaacson &**
EST 1980
Arfman, Inc.
Civil Engineering Consultants
128 Monroe Street NE
Albuquerque, New Mexico | 505-268-8828 | www.iacivil.com



Genevieve L. Donat
12/18/19

TABLE OF CONTENTS

INTRODUCTION	1
EXISTING CONDITIONS	2
PROPOSED CONDITIONS	3

APPENDIX A

BASIN MAP
GRADING & DRAINAGE PLAN

APPENDIX B

100 YEAR-6 HOUR HYDROLOGY CALCULATIONS PER DPM
STORM DRAIN CAPACITY CALCULATIONS

- STORM DRAIN A & B
- STORM DRAIN C

APPENDIX C -REFERENCES

BHI BASIN MAP
AS-BUILT DRAWINGS OF EXISTING STORM DRAIN
NORTH PINO ARROYO HEC-RAS ANALYSIS PROVIDED BY CITY OF
ALBUQUERQUE



The extension of Masthead St will bring the road about 384 ft west of where it currently ends at Bartlett St. Dedicated right-of-way for this new road crosses AMAFCA-owned land where water from the North Pino Arroyo eddies, and where an existing storm drain south of the road discharges into the arroyo. The new street needs to be built high enough to allow the storm drain to extend under the road, and to lift it above the 100-year water surface elevation in the arroyo.

In the future, the City of Albuquerque has plans to connect Masthead to a new road along the north diversion channel. As part of the preliminary design T.Y. Lin International prepared "Channel Rd Phase 2: Hawkins Street NE to El Pueblo Rd NE, Preliminary Hydrology and Hydraulics Report" dated April 19, 2016. This report was never stamped or approved, but the general concepts were used as a basis for this study.

There was a basin map "Journal Center-Phase 2, Unit II: Drainage Plan & Basin Map" generated by Bruce Stidworthy of Bohannon-Huston, Inc. dated November 8, 2002 which can be found in Appendix C. This map analyzed the drainage basins that contribute to the existing storm drain. Conditions in the field are somewhat different from that proposed design, so a new Basin Map that references the same basin IDs for similar areas is provided in this report to show the proposed basins. The Basin Map can be found in Appendix A.

A HEC-RAS analysis for the North Pino Arroyo was provided to Isaacson & Arfman, Inc. by the City of Albuquerque to detail flow characteristics within the area. This analysis is referenced in this report in Appendix C.

This report calculates the proposed 100-year, 6-hour peak flow quantities using the new basin map; the capacity of the existing storm drain with the new extension using proposed flow quantities; and the capacity of the new storm drain that captures storm water at the proposed low point of Masthead St.



The existing site extends west from the end of Masthead St at Bartlett St, between undeveloped Lots 4-A-1, 6-A, and 7-A of Journal Center Phase 2, Unit 2, and crosses over a drainage discharge path from an existing storm drain south of Masthead St. The North Pino Arroyo is to the north.

Portions of the road have been partially graded for development, while areas to the west have drainage infrastructure that includes a rip-rap lined berm with an earthen bottom. Both the berm and channel bottom have native shrubs and grasses. A maintenance access road runs along the top of the berm, with a branch that runs down the berm for access to the bottom of the arroyo.

To the east and south, existing office buildings within the Journal Center generate storm water that is captured an existing storm drain system (EX SD A & B) with inlets in Bartlett St and Rutledge Rd.

The North Pino Arroyo is an AMAFCA-owned drainage channel that discharges to the North Diversion Channel east of the site.



See Appendix A for the proposed Basin Map, and Grading & Drainage Plan.

See Appendix B for calculations.

See Appendix C for referenced materials, including the City of Albuquerque provided HEC-RAS analysis results.

The proposed extension of the road as shown in the Grading & Drainage Plan will pass between Lots 4-A-1, 6-A, and 7-A and continue west. Once adjacent to AMAFCA-owned land, the road will be elevated both for driveability and to raise it above the 100-year water surface elevation of the North Pino Arroyo. Areas south of the right-of-way will be filled to cover the new pipe. The filled portion will direct storm water either towards new inlets in the road or to the existing inlet west of Lot 8-A.

The existing storm drain will be extended north (SD A), and pass under the proposed portion of the road. Calculations show that a 60" pipe will carry the 100-year flows without affecting the existing capacity of the pipe. Recycled riprap is placed at the outlet of the pipe.

A separate storm drain (SD C) will capture storm water generated within the Road basin at inlets in the sag. This will discharge to the North Pino Arroyo, onto the same riprap as the 60" pipe.



An embankment extends west of the proposed paving, to tie into the existing maintenance road at the top of the berm. A new ramp is designed from the north side of the road that allows maintenance access to the bottom of the arroyo.

.



BASIN MAP
GRADING & DRAINAGE PLAN







ISAACSON & ARFMAN, P.A.
Consulting Engineering Associates
128 Monroe Street N.E.
Albuquerque, New Mexico 87108
Ph. 505-268-8828 www.iacivil.com
2108 C-701-BASIN EXHIBIT.dwg Dec 17, 2019

CITY OF ALBUQUERQUE PUBLIC WORKS DEPARTMENT ENGINEERING DEVELOPMENT GROUP			
MASTHEAD STREET BASIN EXHIBIT			
DESIGN REVIEW COMMITTEE	CITY ENGINEER APPROVAL	Mo./DAY/YR.	
		LAST DESIGN UPDATE	
City Project No.	Zone Map No.	Sheet	Of
651785	D-17		9

ENGINEER'S SEAL		SURVEY INFORMATION		BENCH MARKS		AS-BUILT INFORMATION	
			FIELD NOTES		Albuquerque Control Survey Monument "13-D16"	CONTRACTOR	
					New Mexico State Plane Coordinates	WORK SPACED BY	DATE
					(Central Zone - NAD 83)	REVISION	DATE
					North= 1,518,996.001 feet	BY	DATE
					East= 1,534,181.325 feet	REVISION	DATE
					Elevation= 5073.471 feet (NAVD 1988)	BY	DATE
					Delta Alpha= -0012'17.26"	REVISION	DATE
					Ground To Grid Factor= 0.99967357	BY	DATE
						NO.	

REVISIONS	
NO.	DATE
	REMARKS
	BY
	DESIGN
DESIGNED BY	FCA
DRAWN BY	IA
CHECKED BY	FCA
	DATE 06/18
	DATE 06/18
	DATE 06/18

GRADING GENERAL NOTES


- ALL TRASH, DEBRIS, & SURFACE VEGETATION SHALL BE CLEARED AND LEGALLY DISPOSED OF OFFSITE.
- ALL SUBGRADE, OVEREXCAVATION, AND FILL SHALL BE PLACED AND / OR COMPACTED PER THE GEOTECHNICAL REPORT AND CITY OF ALBUQUERQUE SPECIFICATIONS.
- EXCAVATION IS UNCLASSIFIED AND INCLUDES EXCAVATION TO SUBGRADE ELEVATIONS INDICATED BY GEOTECHNICAL REPORT, REGARDLESS OF CHARACTER OF MATERIALS ENCOUNTERED.
- PROPOSED SPOT AND CONTOUR ELEVATIONS SHOWN REPRESENT TOP OF FINISH MATERIAL (I.E. TOP OF CONCRETE, TOP OF PAVEMENT MATERIAL, TOP OF LANDSCAPING MATERIAL, ETC.). CONTRACTOR SHALL GRADE, COMPACT SUBGRADE AND DETERMINE EARTHWORK ESTIMATES BASED ON ELEVATIONS SHOWN MINUS MATERIAL THICKNESSES.
- GRADING SHALL BE PERFORMED AT THE ELEVATIONS AND IN ACCORDANCE WITH THE DETAILS SHOWN ON THIS PLAN.
- UNIFORMLY GRADE AREAS WITHIN LIMITS OF GRADING AS SHOWN ON PLAN. SMOOTH FINISHED SURFACE WITHIN SPECIFIED TOLERANCE, COMPACT WITH UNIFORM SLOPES BETWEEN POINTS WHERE ELEVATIONS ARE INDICATED.
- SIDESLOPES STEEPER THAN 3:1 BUT LESS THAN 2:1 MUST HAVE PERMANENT EROSION PROTECTION INSTALLED. TYPICAL. NO SLOPE SHALL BE STEEPER THAN 2:1. MINIMUM SLOPES SHALL BE 1% UNLESS OTHERWISE NOTED.
- FIVE (5) WORKING DAYS PRIOR TO ANY EXCAVATION, CONTRACTOR MUST CONTACT NM811 FOR LOCATION OF EXISTING UTILITIES.
- IF ANY UTILITY LINES, PIPELINES, OR UNDERGROUND UTILITY LINES ARE SHOWN ON THESE DRAWINGS, THEY ARE SHOWN IN AN APPROXIMATE MANNER ONLY, AND SUCH LINES MAY EXIST WHERE NONE ARE SHOWN. IF ANY SUCH EXISTING LINES ARE SHOWN, THE LOCATION IS BASED UPON INFORMATION PROVIDED BY THE OWNER OF SAID UTILITY, AND THE INFORMATION MAY BE INCOMPLETE, OR MAY BE OBSOLETE BY THE TIME CONSTRUCTION COMMENCES. THE ENGINEER HAS CONDUCTED ONLY PRELIMINARY INVESTIGATION OF THE LOCATION, DEPTH, SIZE OR TYPE OF EXISTING UTILITY LINES, PIPELINES, OR UNDERGROUND UTILITY LINES. THIS INVESTIGATIONS

- IS NOT CONCLUSIVE, AND MAY NOT BE COMPLETE. THEREFORE, MAKES NO REPRESENTATION PERTAINING THERETO, AND ASSUMES NO RESPONSIBILITY OR LIABILITY THEREFORE. THE CONTRACTOR SHALL CONTACT NM811 FOR LOCATIONS OF ANY UTILITY LINE, PIPELINE, OR UNDERGROUND UTILITY LINE IN OR NEAR THE AREA OF THE WORK IN ADVANCE OF AND DURING EXCAVATION WORK. THE CONTRACTOR IS FULLY RESPONSIBLE FOR ANY AND ALL DAMAGE CAUSED BY ITS FAILURE TO CONTACT NM811 AND PROTECT LOCATED UTILITIES. IN PLANNING AND CONDUCTING EXCAVATION, THE CONTRACTOR SHALL COMPLY WITH STATE STATUTES, MUNICIPAL AND LOCAL ORDINANCES, RULES AND REGULATIONS, IF ANY, PERTAINING TO THE LOCATION OF THESE LINES AND FACILITIES.
- OWNER WILL PROVIDE SOIL TESTING AND INSPECTION SERVICES DURING EARTHWORK OPERATIONS. CONTRACTOR SHALL ALLOW TESTING LABS TO INSPECT AND APPROVE COMPACTED SUBGRADES AND FILL LAYERS BEFORE FURTHER CONSTRUCTION WORK IS DONE. SHOULD COMPACTION TESTS INDICATE INADEQUATE DENSITY, CONTRACTOR SHALL PROVIDE ADDITIONAL COMPACTION AND TESTING AT THE CONTRACTOR'S SOLE EXPENSE.
 - CONTRACTOR SHALL PROVIDE ALL OTHER CONSTRUCTION STAKING INCLUDING TRACT CORNERS. CONTRACTOR SHALL LOCATE AND PRESERVE ALL BOUNDARY CORNERS AND REPLACE ANY LOST OR DISTURBED CORNERS AT THE CONTRACTOR'S SOLE EXPENSE.
 - THE ENVIRONMENTAL PROTECTION AGENCY (EPA) AND THE CITY OF ALBUQUERQUE REQUIRE A STORM WATER POLLUTION PREVENTION PLAN (SWPPP), AN NPDES PERMIT, AND AN EROSION AND SEDIMENT CONTROL (ESC) PERMIT FOR PROJECTS WHERE CONSTRUCTION ACTIVITIES MEET THE EPA THRESHOLD. (SWPPP, NPDES PERMIT, AND ESC PLAN BY OTHERS.) A CURRENT CITY-APPROVED ESC PERMIT MUST BE INCLUDED WITH THE CONTRACTOR'S SUBMITTAL FOR A ROUGH GRADING, GRADING, PAVING, BUILDING, OR WORK ORDER PERMIT. CONTRACTOR SHALL COORDINATE WITH OWNER TO DETERMINE WHO WILL PREPARE SWPPP AND INSPECT REQUIRED ELEMENTS..
 - IF THE SITE IS SMALL ENOUGH NOT TO REQUIRE A SWPPP/NPDES PERMIT (LESS THAN ONE ACRE), THE CONTRACTOR SHALL STILL BE

- RESPONSIBLE FOR USING EROSION AND SEDIMENT CONTROL BEST MANAGEMENT PRACTICES (BMP'S) TO ENSURE THAT NO SOIL ERODES FROM THE SITE ONTO ADJACENT PUBLIC RIGHT-OF-WAY.
- MEASURES REQUIRED FOR EROSION AND SEDIMENT CONTROL SHALL BE INCIDENTAL TO THE PROJECT COST.
 - IT IS THE CONTRACTOR'S RESPONSIBILITY TO FIELD VERIFY EXISTING CONDITIONS PRIOR TO CONSTRUCTION. REPORT ALL DISCREPANCIES TO THE ENGINEER AND VERIFY THE ENGINEER'S INTENT BEFORE PROCEEDING.
 - IF FIELD GRADE ADJUSTMENTS ARE REQUIRED, THE CONTRACTOR SHALL NOTIFY THE ENGINEER.
 - ALL NEW PAVEMENT GRADES ARE SHOWN AS 'MATCH' OR '±', TRANSITIONS SHALL BE SMOOTH AND LEVEL. ANY NEW PAVING SURFACE HOLDING WATER (BIRDBATH) SHALL BE REMOVED AND REPLACED AT THE CONTRACTOR'S SOLE EXPENSE.
 - SIDESLOPES STEEPER THAN 3:1 BUT LESS THAN 2:1 MUST HAVE PERMANENT EROSION CONTROL (FRACTURED FACE ROCK [F.F. ROCK] OR LANDLOK TRM 450 O.E.) INSTALLED, TYPICAL. NO SLOPE SHALL BE STEEPER THAN 2:1.
 - ALL AREAS DISTURBED BY CONSTRUCTION (OUTSIDE PROPOSED TURF AREA) SHALL BE RESEED WITH NATIVE GRASS PER C.O.A. SPECIFICATIONS SECTION 1012 (FOR SANDY SOILS) OR AS SPECIFIED ON THE LANDSCAPE PLAN.
 - OWNER SHALL MAINTAIN EROSION PROTECTION ELEMENTS. OWNER SHALL INSPECT SITE YEARLY AND AFTER EACH RAINFALL TO IDENTIFY NEW AREAS OF EROSION AND INSTALL ADDITIONAL EROSION PROTECTION AS NEEDED BASED ON ACTUAL OCCURANCES.
 - ALL NEW PAVEMENT SURFACES SHALL BE CONSTRUCTED WITH POSITIVE SLOPE AWAY FROM BUILDINGS AND POSITIVE SLOPE TOWARD EXISTING AND/OR PROPOSED DRAINAGE PATHS. PAVING AND ROADWAY GRADES SHALL BE ±0.1' FROM PLAN ELEVATIONS.
 - WHERE GRADES BETWEEN NEW AND EXISTING ARE SHOWN AS 'MATCH' OR '±', TRANSITIONS SHALL BE SMOOTH.


- FOR ALL ACCESSIBLE ROUTES, MAXIMUM ALLOWABLE CROSS SLOPE IS 2.0% AND MAXIMUM LONGITUDINAL SLOPE WITHOUT RAMP IS 5.0% FOLLOW ALL ADA ACCESSIBILITY GUIDELINES OR CITY CODES, WHICHEVER IS MORE STRINGENT.
- FOR ENGINEER'S CERTIFICATION OF SUBSTANTIAL COMPLIANCE (FOR CERTIFICATE OF OCCUPANCY) CONTRACTOR SHALL PROVIDE AN AUTOCAD FORMAT AS-BUILT SURVEY PREPARED BY A LICENSED SURVEYOR WHICH INCLUDES:
 - AS-BUILT SPOT ELEVATIONS AT EACH DESIGN SPOT ELEVATION SHOWN ON THE APPROVED PLAN;
 - ALL CONSTRUCTION, INCLUDING DRAIN INLETS, PIPES AND PONDS SHOWN ON THIS PLAN MUST BE CONSTRUCTED IN SUBSTANTIAL COMPLIANCE WITH THE APPROVED PLAN IN ORDER TO RECEIVE ENGINEER'S CERTIFICATION.

VICINITY MAP



LEGEND

- EXISTING CONTOUR
- PROPOSED CONTOUR
- PROPOSED SPOT ELEVATION
- FLOW ARROW
- FLOWLINE ELEVATION
- INVERT ELEVATION
- STORM DRAIN MANHOLE




ISAACSON & ARFMAN, P.A.
Consulting Engineering Associates
128 Monroe Street N.E.
Albuquerque, New Mexico 87108
Ph. 505-268-8828 www.iacivil.com
2108 CG-101.dwg Dec 18, 2019

CITY OF ALBUQUERQUE
PUBLIC WORKS DEPARTMENT
ENGINEERING DEVELOPMENT GROUP

MASTHEAD STREET
GRADING PLAN

DESIGN REVIEW COMMITTEE	CITY ENGINEER APPROVAL	Mo./DAY/YR.	Mo./DAY/YR.
City Project No.	Zone Map No.	Sheet	Of
651785	D-17	5	10

AS-BUILT INFORMATION		BENCH MARKS		SURVEY INFORMATION		ENGINEER'S SEAL		REVISIONS		DESIGNED BY		DRAWN BY		CHECKED BY	
CONTRACTOR	DATE	WORK SPACED BY	DATE	ALBUQUERQUE Control Survey Monument "13-016"	FIELD NOTES	NEW MEXICO PROFESSIONAL ENGINEER	BY	NO.	DATE	FCA	DATE	IA	DATE	FCA	DATE
		STAMPED BY	DATE	New Mexico State Plane Coordinates							06/18		06/18		06/18
		ACCEPTANCE BY	DATE	(Central Zone - NAD 83)											
		REVISION BY	DATE	North= 1,518,996.001 feet											
		DRAWING CORRECTED BY	DATE	East= 1,534,181.325 feet											
				Elevation= 5073.471 feet (NAVD 1988)											
				Delta Alpha= -001°12'17.26"											
				Ground To Grid Factor= 0.99967357											



100 YEAR-6 HOUR HYDROLOGY CALCULATIONS PER DPM

STORM DRAIN CAPACITY CALCULATIONS

- STORM DRAIN A & B
- STORM DRAIN C

NORTH PINO ARROYO HEC-RAS ANALYSIS PROVIDED BY CITY OF
ALBUQUERQUE FOR REFERENCE



CALCULATIONS: 2108 MASTHEAD :

Based on Drainage Design Criteria for City of Albuquerque Section 22.2, DPM, Vol 2, dated Jan., 1993

100-YEAR, 6-HOUR CALCULATIONS

AREA OF SITE: 1271966 SF = 29.20 ACRE

100-year, 6-hour

HISTORIC FLOWS:**DEVELOPED FLOWS:****EXCESS PRECIP:**

	Treatment SF	%		Treatment SF	%	Precip. Zone	2
Area A =	1271966	100%	Area A =	0	0%	$E_A = 0.53$	
Area B =	0	0%	Area B =	63598	5%	$E_B = 0.78$	
Area C =	0	0%	Area C =	127197	10%	$E_C = 1.13$	
Area D =	0	0%	Area D =	1081171	85%	$E_D = 2.12$	
Total Area =	1271966	100%	Total Area =	1271966	100%		

On-Site Weighted Excess Precipitation (100-Year, 6-Hour Storm)

$$\text{Weighted E} = \frac{E_A A_A + E_B A_B + E_C A_C + E_D A_D}{A_A + A_B + A_C + A_D}$$

Historic E =	0.53 in.	Developed E =	1.95 in.
--------------	----------	---------------	----------

On-Site Volume of Runoff: $V_{360} = E * A / 12$

Historic V_{360} =	56178 CF	Developed V_{360} =	207118 CF
----------------------	----------	-----------------------	-----------

On-Site Peak Discharge Rate: $Q_p = Q_{pA} A_A + Q_{pB} A_B + Q_{pC} A_C + Q_{pD} A_D / 43,560$

For Precipitation Zone 2

$Q_{pA} =$	1.56	$Q_{pC} =$	3.14
$Q_{pB} =$	2.28	$Q_{pD} =$	4.70

Historic Q_p =	45.6 CFS	Developed Q_p =	129.2 CFS
------------------	----------	-------------------	-----------

BASIN NO.	B1	DESCRIPTION		Sheriff's Dept and adjacent road
Area of basin flows =	643867	SF	=	14.78 Ac.
The following calculations are based on Treatment %'s as shown in table to the right				LAND TREATMENT
Sub-basin Weighted Excess Precipitation:				A = 0%
Weighted E = 1.95 in.				B = 5%
Sub-basin Volume of Runoff:				C = 10%
V ₃₆₀ = 104843 CF				D = 85%
Sub-basin Peak Discharge Rate:				FIRST FLUSH VOL.
Q _P = 65.4 cfs				15506 CF

BASIN NO.	C1	DESCRIPTION		
Area of basin flows =	381065	SF	=	8.7 Ac.
The following calculations are based on Treatment %'s as shown in table to the right				LAND TREATMENT
Sub-basin Weighted Excess Precipitation:				A = 0%
Weighted E = 1.95 in.				B = 5%
Sub-basin Volume of Runoff:				C = 10%
V ₃₆₀ = 62050 CF				D = 85%
Sub-basin Peak Discharge Rate:				FIRST FLUSH VOL.
Q _P = 38.7 cfs				9177 CF

BASIN NO.	D2	DESCRIPTION		
Area of basin flows =	174827	SF	=	4.0 Ac.
The following calculations are based on Treatment %'s as shown in table to the right				LAND TREATMENT
Sub-basin Weighted Excess Precipitation:				A = 0%
Weighted E = 1.95 in.				B = 5%
Sub-basin Volume of Runoff:				C = 10%
V ₃₆₀ = 28468 CF				D = 85%
Sub-basin Peak Discharge Rate:				FIRST FLUSH VOL.
Q _P = 17.8 cfs				4210 CF

BASIN NO.	ROAD	DESCRIPTION		
Area of basin flows =	72207	SF	=	1.7 Ac.
The following calculation S				LAND TREATMENT
Sub-basin Weighted Excess Precipitation:				A = 0%
Weighted E = 1.95 in.				B = 5%
Sub-basin Volume of Runoff:				C = 10%
V ₃₆₀ = 11758 CF				D = 85%
Sub-basin Peak Discharge Rate:				FIRST FLUSH VOL.
Q _P = 7.3 cfs				1739 CF

Plan View

Stormwater Studio 2019 v 3.0.0.15

Project Name: Enter Project Name...

12-18-2019



GLD Report

Stormwater Studio 2019 v 3.0.0.15

Project Name: Enter Project Name...

12-18-2019


Line No.	Line No.	Line ID	Line Size (in)	Defl. Angle (Deg)	Known Q (cfs)	Flow Rate (cfs)	Vel Ave (ft/s)	n-value Pipe	Line Length (ft)	Invert Dn (ft)	Invert Up (ft)	Line Slope (ft/ft)	HGL Dn (ft)	HGL Up (ft)	Grnd/Rim Elev Dn (ft)	Grnd/Rim Elev Up (ft)	EGL Dn (ft)	
1	1	24in SD C	24	30.35	3.70	7.40	3.65	0.013	93.28	5078.60	5080.30	0.0182	5080.60	5081.26	5080.60	5088.31	5080.69	
2	2	18in SD C	18	56.60	3.70	3.70	4.61	0.013	38.17	5080.80	5081.18	0.01	5081.46	5081.92	5088.31	5088.31	5081.82	
Notes:																		
Project File: 2108 SD-C.sws																		

Line 1 - 24in SD C

Stormwater Studio 2019 v 3.0.0.15

Project Name: Enter Project Name...

12-18-2019




Line 2 - 18in SD C

Stormwater Studio 2019 v 3.0.0.15

Project Name: Enter Project Name...

12-18-2019




Plan View

Stormwater Studio 2019 v 3.0.0.15

Project Name: Enter Project Name...

11-18-2019



GLD Report

Stormwater Studio 2019 v 3.0.0.15

Project Name: Enter Project Name...

11-18-2019

Line No.	Line No.	Line ID	Line Size (in)	Defl. Angle (Deg)	Known Q (cfs)	Flow Rate (cfs)	Vel Ave (ft/s)	n-value Pipe	Line Length (ft)	Invert Dn (ft)	Invert Up (ft)	Line Slope (ft/ft)	HGL Dn (ft)	HGL Up (ft)	Grnd/Rim Elev Dn (ft)	Grnd/Rim Elev Up (ft)	EGL Dn (ft)	
1	1	NEW SD	60	79.25	0.00	121.90	7.71	0.013	165.77	5078.71	5079.41	0.0042	5082.75	5082.93	5088.00	5088.00	5083.55	
2	2	EX 54-IN	54	0.52	0.00	121.90	8.35	0.013	75.83	5079.66	5080.11	0.0059	5083.72	5083.84	5088.00	5086.61	5084.74	
3	3	EX 42-IN SD A	42	10.80	32.70	65.40	6.80	0.013	405.24	5080.21	5082.74	0.0062	5085.58	5087.30	5086.61	5088.04	5086.30	
4	4	EX INLETS SD A	24	0.00	32.70	32.70	10.41	0.013	53.16	5082.84	5084.37	0.0288	5087.15	5088.26	5088.04	5088.07	5088.83	
5	5	EX 42-IN SD B	42	-79.42	0.00	38.70	4.02	0.013	318.15	5080.21	5082.14	0.0061	5085.86	5086.33	5086.61	5089.22	5086.11	
6	6	EX INLET 1 SD B	30	-10.70	12.90	25.80	5.26	0.013	12.90	5082.24	5082.78	0.0414	5086.43	5086.48	5089.22	5089.13	5086.86	
7	7	EX INLET 2 SD B	24	31.92	12.90	12.90	4.11	0.013	35.81	5082.87	5083.60	0.0204	5086.89	5087.01	5089.13	5089.06	5087.16	
8	8	EX INLET 3 SD B	24	61.11	12.90	12.90	4.11	0.013	25.80	5082.24	5083.77	0.0593	5086.53	5086.62	5089.22	5089.14	5086.79	
9	9	EX LOT 8 INLET	18	-27.05	17.80	17.80	10.07	0.013	13.38	5080.21	5080.48	0.0202	5085.07	5085.45	5086.61	5084.40	5086.64	

Notes:


Project File: 2108 SD.sws

Line 1 - NEW SD

Stormwater Studio 2019 v 3.0.0.15

Project Name: Enter Project Name...

11-18-2019




Line 2 - EX 54-IN

Stormwater Studio 2019 v 3.0.0.15

Project Name: Enter Project Name...

11-18-2019




Line 3 - EX 42-IN SD A

Stormwater Studio 2019 v 3.0.0.15

Project Name: Enter Project Name...

11-18-2019




Line 4 - EX INLETS SD A

Stormwater Studio 2019 v 3.0.0.15

Project Name: Enter Project Name...

11-18-2019




Line 5 - EX 42-IN SD B

Stormwater Studio 2019 v 3.0.0.15

Project Name: Enter Project Name...

11-18-2019




Line 6 - EX INLET 1 SD B

Stormwater Studio 2019 v 3.0.0.15

Project Name: Enter Project Name...

11-18-2019




Line 7 - EX INLET 2 SD B

Stormwater Studio 2019 v 3.0.0.15

Project Name: Enter Project Name...

11-18-2019




Line 8 - EX INLET 3 SD B

Stormwater Studio 2019 v 3.0.0.15

Project Name: Enter Project Name...

11-18-2019




Line 9 - EX LOT 8 INLET

Stormwater Studio 2019 v 3.0.0.15

Project Name: Enter Project Name...

11-18-2019




BHI BASIN MAP

AS-BUILT DRAWINGS OF EXISTING STORM DRAIN

NORTH PINO ARROYO HEC-RAS ANALYSIS PROVIDED BY CITY OF
ALBUQUERQUE FOR REFERENCE





Journal Center Phase - 2 Unit - 2
Drainage Management Plan

Purpose

The purpose of this plan is to amend the approved drainage report for Journal Center Phase 2 Units 1&2 (ref. hydrology file # D17/D3AA). Unit 1 has been constructed and this plan amends Unit 2, for the purpose of obtaining preliminary plat approval of Unit 2.

Site Location and Background Information

Journal Center Phase - 2 Unit - 2 is located southwest of Journal Center Phase 1, west of the intersection of Masthead and Jefferson in northeast Albuquerque. This site is bounded on the east by Washington, on the north by the North Pino Arroyo, on the west by the AMAFCA North Diversion Channel and on the south by commercial development along Hawkins St. The site is in precipitation zone 2 as defined by Figure A-1 of the DPM section 22.2.A.1. The existing legal description of the site is Tract 8A-1 Journal Center Phase - 2. Please see the vicinity map on this sheet for a graphic depiction of the site location.

The most recent drainage report to address drainage of this site and the surrounding area is entitled "Drainage Report for Journal Center - Phase 2", dated August 25, 2000, and prepared by Bohannan Huston. This drainage report has been approved (see letter dated 10/3/00 from Brad Bingham to Kerry Davis) and can be found in hydrology file # D17/D3AA. This submission is in full compliance with the guidance and recommendations set forth in that report.

Existing Conditions

The existing conditions of this site are substantially unchanged from the description in the approved drainage report. Some earthwork/borrow was performed for the construction of Unit 1, however existing drainage patterns remain essentially unchanged.

Proposed Conditions

Under proposed conditions the site is 85% land treatment D, with 5% and 10% land treatment B and C respectively. The following changes to basins in the approved drainage report have been made. Please reference the Proposed Basin Map in the approved drainage report:

Basin F1 in Unit 1 is now Basin F1 where the lots on the west side of Washington are now included in Unit 2 Basin C1. The flow has been decreased from Q=109.1 cfs to Q=98.3 cfs. The sump condition proposed in Unit 1 to capture the flow from Basin F1 has been modified in this plan. Inlets are proposed west of the existing inlets in Masthead, this portion of the street would be considered "on grade" and the residual flow passing from basin F1 to basin C1 is 19.0 cfs. Basin E in Unit 1 is now Basin E1 where the lots on the west side of Washington are now included in Unit 2, Basin B1. The flow has been decreased from Q=12.8 cfs to Q=11.1 cfs. All of the previously approved basins in Unit 2 have been modified to accommodate earthwork and grading, see this sheet.

Flows from Basins D1 & D2 flow into the North Pino Arroyo (and/or the AMAFCA de-silting basin) and Basin A1 flows to the AMAFCA North Diversion Channel. These flows do not impact flows in any streets.

The residual flow from Basin F1 of 19.0 cfs combines with Basin C1 (Q=57.1 cfs) which flows in the street to inlets in sump condition (AP2) for a total flow of 76.1 cfs. The hydraulic capacity of the street, inlets and pipes are shown in tables on this sheet.

Basins E1 and Offsite 2 (total Q= 11.1 cfs) in Unit 1 flow in Washington to existing inlets in sump. A proposed 24" storm drain will tie to the existing 24" storm drain in Rutledge, and convey the 11.1 cfs to the 48" SD at the low point in Rutledge (AP1).


Basin B1 (Q=65.36 cfs) flows in the street to inlets in sump condition (AP1). In the storm drain this flow combines with the 11.1 cfs in the 24" SD for a total flow in the 48" SD of 76.4 cfs. Flows at AP1 and AP2 combine (Q= 152.5 cfs) and outfall from the 54" SD to the AMAFCA distillation basin west of basin D2.

Hydraulic capacity calculations for the streets, inlets and pipes are provided on this sheet. The storm drains are designed to operate as gravity systems, without pressure flow.

Conclusions

This drainage submission has been prepared in accordance with City of Albuquerque requirements, and complies with the previously approved drainage report for the area. This plan clearly demonstrates the proposed grading and drainage concepts. The implementation of these concepts will result in the safe passage of the 100 year storm event.

With this submission we request hydrology department approval of this Grading and Drainage Plan for preliminary plat approval.



VICINITY MAP
ZONE ATLAS ZONE INDEX MAP NO. D-17-Z

LEGAL DESCRIPTION
TRACT 8A-1, JOURNAL CENTER PHASE 2

JOURNAL CENTER - PHASE 2
Ultimate Development Conditions Basin Data Table


This table is based on the DPM Section 22.2, Zone: 2										
BASIN	Area	Area	Land Treatment Percentages				Q(100)	Q(100)	WT E	V(100) ₃₆₀
ID	(SQ. FT)	(AC.)	A	B	C	D	(cfs/ac.)	(csf)	(inches)	(CF)
UNIT1										
F1	967907	22.22	0.0%	5.0%	10.0%	85.0%	4.42	98.28	1.95	157608
E1	91622	2.10	0.0%	5.0%	10.0%	85.0%	4.42	9.30	1.95	14919
UNIT2										
C1	562195	12.91	0.0%	5.0%	10.0%	85.0%	4.42	57.08	1.95	91544
B1	643724	14.78	0.0%	5.0%	10.0%	85.0%	4.42	65.36	1.95	104820
D1	123807	2.84	0.0%	5.0%	10.0%	85.0%	4.42	12.57	1.95	20160
D2	306295	7.03	0.0%	5.0%	10.0%	85.0%	4.42	31.10	1.95	49875
A1	667021	15.31	0.0%	5.0%	10.0%	85.0%	4.42	67.73	1.95	108613

INLET TABLE										
INLET #	CONTRIBUTING BASIN	INLET TYPE	INLET CONDITION	ACTUAL FLOW cfs	AVAIL HEAD ft	CAPACITY	Notes			
I1	1/3 C1 & BYPASS FROM F1	DBL A, DBL WING	sump	25.36	0.85	37.57	INCLUDES A 50% CLOGGING FACTOR			
I2	1/3 C1 & BYPASS FROM F1	DBL A, DBL WING	sump	25.36	0.85	37.57	INCLUDES A 50% CLOGGING FACTOR			
I3	1/3 C1 & BYPASS FROM F1	DBL A, DBL WING	sump	25.36	0.85	37.57	INCLUDES A 50% CLOGGING FACTOR			
I4	1/2 B1	DBL A, DBL WING	sump	32.68	1.00	47.94	INCLUDES A 50% CLOGGING FACTOR			
I5	1/2 B1	DBL A, DBL WING	sump	32.68	1.00	47.94	INCLUDES A 50% CLOGGING FACTOR			
I6	BASIN F1	EXISTING, DBL A, S WING	on grade	FROM NOMOGRAPH d=1.0', s=0.2%	17.5	17.5	FLOW AT INLET = 38.75 CFS			
I7	BASIN F1	EXISTING, DBL A, S WING	on grade	FROM NOMOGRAPH d=1.0', s=0.2%	17.5	17.5	FLOW AT INLET = 38.75 CFS			
I8	BASIN F1	DBL C	on grade	FROM NOMOGRAPH d=.79', s=0.2%	11.75	11.75	BYPASS FLOW FROM BASIN F1 = 9.50			
I9	BASIN F1	DBL C	on grade	FROM NOMOGRAPH d=.79', s=0.2%	11.75	11.75	BYPASS FLOW FROM BASIN F1 = 9.50			

Street Capacity Table					
ASSUMES 36" F-F, 2% CROSS-SLOPE, AND STD. CURB AND GUTTER					
	ANALYSIS POINT	FLOW IN STREET	STREET SLOPE	EGL	DEPTH ABOVE FL
Rutledge	AP1	65.2	1.10%	0.98	0.65
Bartlett	AP2	76.1	1.00%	1.04	0.71
Masthead	AP3	42.5	0.20%	0.85	0.79

STORM DRAIN PIPE TABLE							
PIPE #	Size in.	Slope	PIPE Capacity	ACTUAL FLOW	LENGTH	INVERT IN	INVERT OUT
P6	24	0.0100	22.62	11.08	357.00	92.30	88.73
P5	24	0.0100	22.62	11.08	400.00	88.63	84.63
P4	24	0.0100	22.62	11.08	383.00	84.53	80.70
P3B	24	0.0100	22.62	11.08	20.00	80.60	80.40
P3A	24	0.0210	32.78	32.68	32.00	81.07	80.40
P3	42	0.0060	77.93	76.44	450.00	80.40	77.70
P2C	24	0.0130	25.79	25.36	18.00	80.05	79.81
P2B	24	0.0150	27.71	25.36	46.00	80.50	79.81
P2A	24	0.0130	25.79	25.36	18.00	80.05	79.81
P2	42	0.0060	77.93	76.08	336.00	79.71	77.70
P1	54	0.0065	158.54	152.53	92.00	77.60	77.00

PIPE CAPACITIES ARE BASED ON GRAVITY FLOW USING MANNING'S EQN. WHERE n=0.013



Bohannan Huston

Courtyard I 7500 Jefferson St. NE Albuquerque, NM 87109-4335

ENGINEERING • SPATIAL DATA • ADVANCED TECHNOLOGIES

CITY OF ALBUQUERQUE

PUBLIC WORKS DEPARTMENT

ENGINEERING DEVELOPMENT GROUP

JOURNAL CENTER-PHASE 2

UNIT II: DRAINAGE PLAN & BASIN MAP

Design Review Committee City Engineer Approval

City Project No. _____ Zone Map No. **D-17** Sheet _____ Of _____

Mo./Day/Yr. _____

Mo./Day/Yr. _____

Mo./Day/Yr. _____

Mo./Day/Yr. _____

DRB# _____

City Project No. _____

Design By: BUS

Drawn By: KJM

Checked By: BUS

Date: 10/2002

Date: 10/2002

Date: 10/2002


REVISIONS

No.	Date	By
1	11/8/02	By

CONSTRUCTION PLANS FOR JOURNAL CENTER PHASE 2, UNIT 2 ALBUQUERQUE, NEW MEXICO

CERTIFICATE OF SUBSTANTIAL COMPLIANCE ON PLANS

I, **William L. Vreeke, P.E.**, of the firm of **Bohannon Huston, Inc.**, a Registered Professional Engineer in the State of New Mexico, do hereby certify, to the best of my knowledge and belief, that the infrastructure installed as part of this project (Journal Center Phase 2, Unit 2 - City Project No. 651783) has been inspected by me or by a qualified person under my direct supervision and has been constructed in accordance with the plans and specifications approved by the City Engineer and that the original design intent of the approved plans has been met, except as noted by me on the as-built construction drawings. This Certification is based on site inspections by me or personnel under my direction and survey information provided by the contractor, **Franklins Earthmoving Co., Inc.** and their surveyor, **Tim Aldrich**, NMPS 7719.



INDEX


SHEET NUMBER

DESCRIPTION

1	TITLE SHEET
2A-2B	PLAT
3	GRADING PLAN
4	OVERALL PAVING PLAN
5	PAVING & STORM DRAIN PLAN AND PROFILES
6	BARTLETT STREET STA. 1+48 - 9+10
7	MASTHEAD STREET STA. 9+10 - 18+00
8	RUTLEDGE ROAD STA. 6+20 - 18+00
9	RUTLEDGE ROAD STA. 18+00-21+50 & WASHINGTON/WOLCOTT INTERSECTION DETAILS
10	SNAPROLL & HAWKINS INTERSECTION DETAILS
11	SNAPROLL STREET STA. 0+00 - 7+07
12	STORM DRAIN "A" LINE
	STORM DRAIN "B" LINE
13	OVERALL UTILITY PLAN
14	UTILITY PLAN AND PROFILES
15	BARTLETT STREET STA. 1+48 - 9+10
16-17	MASTHEAD STREET STA. 9+10 - 18+00
18	RUTLEDGE ROAD STA. 6+20 - 21+42
19	SNAPROLL STREET STA. 0+00 - 7+07
	SANITARY SEWER "A" LINE
20-21	AMAFCA DRAINAGE SWALE
22	MISCELLANEOUS DETAILS
23	SIGNING AND CONSTRUCTION TRAFFIC CONTROL STANDARDS
24	TYPICAL TRAFFIC CONTROL & SIGNING EXAMPLES (REF. M.U.T.C.D.)

CONSTRUCTION NOTES:

1. THE CONTRACTOR SHALL ABIDE BY ALL LOCAL, STATE, AND FEDERAL LAWS, RULES AND REGULATIONS WHICH APPLY TO THE CONSTRUCTION OF THESE IMPROVEMENTS.
2. PRIOR TO CONSTRUCTION CONTRACTOR SHALL EXCAVATE AND VERIFY THE HORIZONTAL AND VERTICAL LOCATIONS OF ALL POTENTIAL OBSTRUCTIONS. SHOULD A CONFLICT EXIST, THE CONTRACTOR SHALL NOTIFY THE ENGINEER OR CONSTRUCTION OBSERVER SO THAT THE CONFLICT CAN BE RESOLVED WITH A MINIMUM AMOUNT OF DELAY.
3. ALL ELECTRICAL, TELEPHONE, CABLE TV, GAS AND OTHER UTILITY LINES, CABLES AND APPURTENANCES ENCOUNTERED DURING CONSTRUCTION THAT REQUIRE RELOCATION, SHALL BE COORDINATED WITH THAT UTILITY. THE CONTRACTOR SHALL BE RESPONSIBLE FOR COORDINATION OF ALL NECESSARY UTILITY ADJUSTMENTS. NO ADDITIONAL COMPENSATION WILL BE ALLOWED FOR DELAYS OR INCONVENIENCES CAUSED BY UTILITY COMPANY WORK CREWS. THE CONTRACTOR MAY BE REQUIRED TO RESCHEDULE HIS ACTIVITIES TO ALLOW UTILITY CREWS TO PERFORM THEIR REQUIRED WORK.
4. DISPOSAL SITE FOR ALL EXCESS EXCAVATION MATERIAL, AND UNSUITABLE MATERIAL SHALL BE OBTAINED BY THE CONTRACTOR IN COMPLIANCE WITH APPLICABLE ENVIRONMENTAL REGULATIONS AND APPROVED BY THE CONSTRUCTION OBSERVER. ALL COSTS INCURRED IN OBTAINING A DISPOSAL SITE AND HAUL THERE TO SHALL BE CONSIDERED INCIDENTAL TO THE PROJECT AND NO SEPARATE MEASUREMENT OR PAYMENT SHALL BE MADE.
5. THE CONTRACTOR IS RESPONSIBLE FOR PROTECTING THE EXISTING UTILITY LINES WITHIN THE CONSTRUCTION AREA. ANY DAMAGE TO EXISTING FACILITIES CAUSED BY CONSTRUCTION ACTIVITY SHALL BE REPAIRED OR REPLACED AT THE CONTRACTOR'S EXPENSE AND APPROVED BY THE CONSTRUCTION OBSERVER.
6. CONSTRUCTION ACTIVITY SHALL BE LIMITED TO THE PROPERTY AND/OR PROJECT LIMITS. ANY DAMAGE TO ADJACENT PROPERTIES RESULTING FROM THE CONSTRUCTION PROCESS IS THE RESPONSIBILITY OF THE CONTRACTOR. ANY COSTS INCURRED FOR REPAIRS SHALL BE THE COST OF THE CONTRACTOR.
7. OVERNIGHT PARKING OF CONSTRUCTION EQUIPMENT SHALL NOT OBSTRUCT DRIVEWAYS OR DESIGNATED TRAFFIC LANES. THE CONTRACTOR SHALL NOT STORE ANY EQUIPMENT OR MATERIAL WITHIN THE PUBLIC RIGHT-OF-WAY.
8. THE CONTRACTOR SHALL OBTAIN ALL THE NECESSARY PERMITS FOR THE PROJECT PRIOR TO COMMENCING CONSTRUCTION (I.E. BARRICADING, SURFACE DISTURBANCE)
9. THE CONTRACTOR SHALL BE RESPONSIBLE TO REPLACE AT HIS EXPENSE ANY AND ALL PROPERTY CORNERS DESTROYED DURING CONSTRUCTION. ALL PROPERTY CORNERS MUST BE RESET BY A REGISTERED LAND SURVEYOR.
10. ALL PERMANENT PAVEMENT MARKING AND TRAFFIC SIGNING SHALL BE FURNISHED BY THE CONTRACTOR PER PLAN.
11. THE CONTRACTOR SHALL FOLLOW THE CONSTRUCTION TRAFFIC CONTROL AND SIGNING PLAN PROVIDED HEREIN. THE CONTRACTOR SHALL COORDINATE WITH THE CITY OF ALBUQUERQUE, TRAFFIC ENGINEERING DEPARTMENT, PRIOR TO BEGINNING ANY CONSTRUCTION WORK ON ADJACENT TO EXISTING STREETS.
12. ALL BARRICADES AND CONSTRUCTION SIGNING SHALL CONFORM TO APPLICABLE SECTIONS OF THE "MANUAL OF UNIFORM TRAFFIC CONTROL DEVICES" (MUTCD), U.S. DEPARTMENT OF TRANSPORTATION, LATEST EDITION.
13. THE CONTRACTOR SHALL MAINTAIN ALL CONSTRUCTION BARRICADES AND SIGNING AT ALL TIMES. THE CONTRACTOR SHALL VERIFY THE PROPER LOCATION OF ALL BARRICADING AT THE END AND BEGINNING OF EACH DAY.
14. ALL SAW CUT PAVEMENT SHALL HAVE A UNIFORM EDGE AND BE SPRAYED WITH TACK.
15. WHEN ABUTTING NEW CURB AND GUTTER TO EXISTING PAVEMENT, A 1' WIDE SECTION OF EXISTING PAVEMENT ADJACENT TO THE CURB AND GUTTER SHALL BE SAW CUT, REMOVED, AND REPLACED AS PER THE STANDARD SPECIFICATIONS.
16. THE CONTRACTOR SHALL ASSUME RESPONSIBILITY FOR ANY DAMAGE TO EXISTING PAVEMENTS, PAVEMENT MARKINGS, CURB & GUTTER, DRIVE PADS, WHEELCHAIR RAMPS, AND SIDEWALK DURING CONSTRUCTION, APART FROM THOSE SECTIONS INDICATED FOR REMOVAL ON THE PLANS AND SHALL REPAIR OR REPLACE PER COA STANDARDS, AT HIS OWN EXPENSE.



VICINITY MAP
ZONE MAP NO. D-17

NOTICE TO CONTRACTORS

1. AN EXCAVATION/CONSTRUCTION PERMIT WILL BE REQUIRED BEFORE BEGINNING ANY WORK WITHIN THE CITY RIGHT-OF-WAY.
2. ALL WORK DETAILED ON THESE PLANS TO BE PERFORMED UNDER CONTRACT SHALL, EXCEPT AS OTHERWISE STATED OR PROVIDED FOR HEREON, BE CONSTRUCTED IN ACCORDANCE WITH THE CITY OF ALBUQUERQUE STANDARD SPECIFICATIONS FOR PUBLIC WORKS CONSTRUCTION, 1986 EDITION AS REVISED THROUGH UPDATE #6.
3. TWO WORKING DAYS PRIOR TO ANY EXCAVATION, THE CONTRACTOR MUST CONTACT NEW MEXICO ONE CALL SYSTEM (260-1990) FOR LOCATION OF EXISTING UTILITIES.
4. PRIOR TO CONSTRUCTION, THE CONTRACTOR SHALL EXCAVATE AND VERIFY THE HORIZONTAL AND VERTICAL LOCATIONS OF ALL OBSTRUCTIONS, SHOULD A CONFLICT EXIST, THE CONTRACTOR SHALL NOTIFY THE ENGINEER IMMEDIATELY SO THAT THE CONFLICT CAN BE RESOLVED WITH A MINIMUM AMOUNT OF DELAY.
5. FIVE (5) WORKING DAYS PRIOR TO BEGINNING CONSTRUCTION, THE CONTRACTOR SHALL SUBMIT TO CONSTRUCTION COORDINATION DIVISION A DETAILED CONSTRUCTION SCHEDULED. TWO (2) WORKING DAYS PRIOR TO THE START OF CONSTRUCTION, THE CONTRACTOR SHALL OBTAIN A BARRICADING PERMIT FROM THE CONSTRUCTION COORDINATION DIVISION, CONTRACTOR SHALL NOTIFY THE CONSTRUCTION COORDINATION ENGINEER (924-3400) PRIOR TO OCCUPANCY AN INTERSECTION. REFER TO SECTION 19 OF THE GENERAL CONDITIONS OF THE STANDARD SPECIFICATIONS.
6. ALL WORK EFFECTING ARTERIAL ROADWAYS REQUIRES TWENTY-FOUR HOUR CONSTRUCTION.
7. ALL STREET STRIPING ALTERED OR DESTROYED SHALL BE REPLACED WITH PLASTIC REFLECTORIZED PAVEMENT MARKING BY CONTRACTOR TO THE SAME LOCATION AS WAS EXISTING, OR AS INDICATED BY THIS PLAN SET.
8. CONTRACTOR SHALL NOTIFY THE ENGINEER NOT LESS THAN SEVEN (7) DAYS PRIOR TO STARTING WORK IN ORDER THAT THE CITY SURVEYOR MAY TAKE NECESSARY MEASURES TO INSURE THE PRESERVATION OF SURVEY MONUMENTS. CONTRACTOR SHALL NOT DISTURB PERMANENT SURVEY MONUMENTS WITHOUT THE CONSENT OF THE CITY SURVEYOR AND SHALL NOTIFY THE CITY SURVEYOR AND BEAR THE EXPENSE OF REPLACING ANY THAT MAY BE DISTURBED WITHOUT PERMISSION. REPLACEMENT SHALL BE DONE ONLY BY THE CITY SURVEYOR. WHEN A CHANGE IS MADE IN THE FINISHED ELEVATIONS OF THE PAVEMENT OF ANY ROADWAY IN WHICH A PERMANENT SURVEY MONUMENT IS LOCATED, CONTRACTOR SHALL, AT HIS OWN EXPENSE, ADJUST THE MONUMENT COVER TO THE NEW GRADE UNLESS OTHERWISE SPECIFIED. REFER TO SECTION 4.4 OF THE GENERAL CONDITIONS OF THE STANDARD SPECIFICATIONS.
9. CONTRACTOR SHALL RECORD DATA ON ALL UTILITY LINES AND ACCESSORIES AS REQUIRED BY THE CITY OF ALBUQUERQUE FOR THE PREPARATION OF "AS CONSTRUCTED" DRAWINGS. CONTRACTOR SHALL NOT COVER UTILITY LINES AND ACCESSORIES UNTIL ALL DATA HAS BEEN RECORDED.
10. CONTRACTOR SHALL MAINTAIN A GRAFFITI-FREE WORK SITE. CONTRACTOR SHALL PROMPTLY REMOVE ANY GRAFFITI FROM ALL EQUIPMENT, WHETHER PERMANENT OR TEMPORARY.
11. CONTRACTOR SHALL COORDINATE WITH THE CITY OF ALBUQUERQUE WATER SYSTEMS DIVISION (857-8200) SEVEN (7) WORKING DAYS IN ADVANCE OF ANY WORK THAT MAY AFFECT EXISTING PUBLIC WATER OR SEWER UTILITIES. EXISTING VALVES TO BE OPERATED BY CITY PERSONNEL ONLY. CONTRACTOR SHALL CONTACT THE WATER SYSTEMS DIVISION SEVEN (7) WORKING DAYS PRIOR TO NEEDING VALVES TURNED ON OR OFF.


THE FOLLOWING NOTES ALSO APPLY WHEN CHECKED

- ☐ ALL UTILITIES AND UTILITY SERVICE LINES SHALL BE INSTALLED PRIOR TO PAVING.
- ☒ BACKFILL COMPACTION SHALL BE ACCORDING TO SPECIFIED STREET USE.
- ☒ TACK COAT REQUIREMENTS SHALL BE DETERMINED BY THE ENGINEER.
- ☒ SIDEWALKS AND WHEELCHAIR RAMPS WITHIN THE CURB RETURNS SHALL BE CONSTRUCTED WHEREVER A NEW CURB RETURN IS CONSTRUCTED.
- ☐ IF CURB IS DEPRESSED FOR A DRIVE PAD, THE DRIVE PAD SHALL BE CONSTRUCTED PRIOR TO ACCEPTANCE OF CURB AND GUTTER.
- ☐ ALL STORM DRAINAGE FACILITIES SHALL BE COMPLETED PRIOR TO FINAL ACCEPTANCE.
- ☒ THE REQUESTER OR DEVELOPER SHALL BE RESPONSIBLE FOR REPAIR OR REPLACEMENT OF ALL CURB AND GUTTER OR SIDEWALK DAMAGED AFTER APPROVAL BY THE CITY ENGINEER OF WORK COMPLETED BY THE CONTRACTOR.

APPROVED AS RECORD DRAWINGS
DESIGN REVIEW SECTION
CITY ENGINEER
[Signature]
10-13-03

SURVEYOR'S CERTIFICATION

"I, Timothy Aldrich, a duly qualified Registered Professional Land Surveyor under the laws of the State of New Mexico, do hereby certify that the 'as-built' information shown on these drawings was obtained from field construction and 'as-built' surveys performed by me or under my supervision, that the 'as-built' information shown on these drawings was added by me or under my supervision, and that this 'as-built' information is true and correct to the best of my knowledge and belief." Aldrich Land Surveying is not responsible for any of the design concepts, calculations, engineering or intent of the record drawings.




S. No. 7719

10-13-03 Date


1 2 3 4 5 6 7 8 9 10 11 12 13 14 15
26 65 17 83 04

DRB # 1002321


Bohannon Huston
Court yard | 7500 Jefferson St. NE Albuquerque, NM 87109-4335
ENGINEERING • SPATIAL DATA • ADVANCED TECHNOLOGIES



REV.	SHEETS	CITY ENGINEER	DATE	USER DEPARTMENT	DATE	USER DEPARTMENT	DATE
ENGINEERS STAMP & SIGNATURE	APPROVALS	ENGINEER	DATE	*****	APPROVED FOR CONSTRUCTION		
	DRC Chairman	<i>[Signature]</i>	4-22-03				
	Transportation	<i>[Signature]</i>	3/27/03				
	Water/Wastewater	<i>[Signature]</i>	3/27/03				
	Hydrology	<i>[Signature]</i>	4-15-03				
	Parks	<i>[Signature]</i>	4-22-03				
	Const. Management	<i>[Signature]</i>	4/13/03				
	AMAFCA	<i>[Signature]</i>					
City Project No.							
	651783						
Sheet	Of						
1	24						



SNAPROLL STREET



PAVEMENT DESIGN PER
PAVEMENT SECTION ON SHEET 4.


- 


3/17/03

Bohannon  **Huston** 

Courtyard I 7500 Jefferson St. NE Albuquerque, NM 87109-4335

ENGINEERING  **SPATIAL DATA**  **ADVANCED TECHNOLOGIES**

					
CITY OF ALBUQUERQUE PUBLIC WORKS DEPARTMENT ENGINEERING DEVELOPMENT GROUP					
JOURNAL CENTER PHASE 2, UNIT2 PAVING PLAN & PROFILE SNAPROLL STREET					
Revision/Description	Approved/Date	Civil Engineer	Checked/Date	Reviewed/Date	

SNAPROLL STREET		Mo./Day/Yr.	Mo./Day/Yr.
 <p>DESIGN REVIEW COMMITTEE</p>	City Engineer Approval		

City Project No.	651783	Zone Map No.	D-17	Sheet	10	Of	24
------------------	--------	--------------	------	-------	----	----	----




BHI JOB NO. 020075 Date: FEBRUARY, 2003
Copyright Bohannon Huston 2003


P: \020075\cdp\pnp\020075Ppnp05.dwg

BHI JOB NO. 020075

Date: FEBRUARY, 2003


Copyright Bohannon Huston 200





SCALE 1:100



CITY OF ALBUQUERQUE DEPARTMENT OF MUNICIPAL DEVELOPMENT ENGINEERING DIVISION			
TITLE: North Pino Cross Sections			
NOT FOR CONSTRUCTION	DESIGNED BY:	LAST DESIGN UPDATE	
	REVIEWED BY:		
City Project No.	Zone Map No. X-XXX	Sheet 1	Of 1

HEC-RAS Plan: Proposed River: NPino Reach: Site 1

Reach	River Sta	Profile	Q Total	Min Ch El	W.S. Elev	Crit W.S.	E.G. Elev	E.G. Slope	Vel Chnl	Flow Area	Top Width	Froude # Chl
			(cfs)	(ft)	(ft)	(ft)	(ft)	(ft/ft)	(ft/s)	(sq ft)	(ft)	
Site 1	1298.65	636 cfs	636.00	5083.45	5086.00	5087.68	5092.10	0.015009	19.82	32.09	17.89	2.61
Site 1	1298.65	2700 cfs	2700.00	5083.45	5088.61	5091.96	5101.23	0.015023	28.49	94.76	30.44	2.85
Site 1	1194.3	636 cfs	636.00	5081.53	5082.68	5084.00	5089.56	0.042140	21.03	30.24	33.98	3.93
Site 1	1194.3	2700 cfs	2700.00	5081.53	5084.38	5087.59	5099.05	0.024480	30.73	87.87	34.05	3.37
Site 1	1106.48	636 cfs	636.00	5078.42	5082.72	5080.23	5082.80	0.000769	2.33	273.48	79.47	0.22
Site 1	1106.48	2700 cfs	2700.00	5078.42	5088.15	5082.55	5088.32	0.000679	3.33	810.94	243.92	0.23
Site 1	1010.32	636 cfs	636.00	5078.16	5082.75		5082.76	0.000090	0.87	728.45	185.59	0.08
Site 1	1010.32	2700 cfs	2700.00	5078.16	5088.23		5088.26	0.000093	1.47	1840.62	440.69	0.09
Site 1	950.3	636 cfs	636.00	5078.09	5082.73		5082.75	0.000151	1.16	548.08	133.72	0.10
Site 1	950.3	2700 cfs	2700.00	5078.09	5088.19		5088.25	0.000174	2.01	1341.29	255.83	0.12
Site 1	894.93	636 cfs	636.00	5077.64	5082.70		5082.74	0.000292	1.63	390.14	92.86	0.14
Site 1	894.93	2700 cfs	2700.00	5077.64	5088.12		5088.23	0.000338	2.70	1009.94	131.53	0.17
Site 1	851.32	636 cfs	636.00	5077.34	5082.67		5082.72	0.000387	1.79	354.77	91.03	0.16
Site 1	851.32	2700 cfs	2700.00	5077.34	5088.08		5088.21	0.000417	2.97	908.68	127.05	0.19
Site 1	798.56	636 cfs	636.00	5077.45	5082.57		5082.69	0.001096	2.68	237.45	83.22	0.26
Site 1	798.56	2700 cfs	2700.00	5077.45	5087.94		5088.17	0.000842	3.91	690.39	122.74	0.26
Site 1	748.96	636 cfs	636.00	5076.99	5082.40		5082.61	0.001927	3.62	175.68	86.19	0.35
Site 1	748.96	2700 cfs	2700.00	5076.99	5087.64		5088.09	0.001736	5.41	499.24	186.53	0.36
Site 1	697.25	636 cfs	636.00	5077.08	5082.16		5082.48	0.002790	4.48	141.96	38.91	0.41
Site 1	697.25	2700 cfs	2700.00	5077.08	5087.19		5087.95	0.003170	6.96	387.70	113.04	0.48
Site 1	644.46	636 cfs	636.00	5076.72	5080.70	5080.70	5082.06	0.018666	9.36	67.92	25.25	1.01
Site 1	644.46	2700 cfs	2700.00	5076.72	5084.97	5084.97	5087.46	0.015344	12.65	213.48	43.05	1.00
Site 1	596.99	636 cfs	636.00	5076.31	5079.57	5080.12	5081.66	0.003609	11.60	54.83	23.43	1.34
Site 1	596.99	2700 cfs	2700.00	5076.31	5083.44	5084.33	5087.09	0.002696	15.32	176.29	39.17	1.27
Site 1	547.57	636 cfs	636.00	5075.45	5078.29	5079.26	5081.34	0.006015	14.01	45.41	21.48	1.70
Site 1	547.57	2700 cfs	2700.00	5075.45	5082.07	5083.52	5086.83	0.003818	17.50	154.29	36.37	1.50

HEC-RAS Plan: Proposed River: NPino Reach: Site 1 (Continued)

Reach	River Sta	Profile	Q Total	Min Ch El	W.S. Elev	Crit W.S.	E.G. Elev	E.G. Slope	Vel Chnl	Flow Area	Top Width	Froude # Chl
			(cfs)	(ft)	(ft)	(ft)	(ft)	(ft/ft)	(ft/s)	(sq ft)	(ft)	
Site 1	497.99	636 cfs	636.00	5075.07	5077.84	5078.85	5081.02	0.006497	14.30	44.48	21.71	1.76
Site 1	497.99	2700 cfs	2700.00	5075.07	5081.41	5083.04	5086.59	0.004336	18.26	147.87	36.18	1.59
Site 1	444.75	636 cfs	636.00	5074.19	5076.91	5078.07	5080.59	0.007845	15.39	41.33	20.79	1.92
Site 1	444.75	2700 cfs	2700.00	5074.19	5080.40	5082.29	5086.26	0.005129	19.43	138.99	35.15	1.72
Site 1	399.87	636 cfs	636.00	5073.51	5076.13	5077.39	5080.18	0.008919	16.15	39.39	20.27	2.04
Site 1	399.87	2700 cfs	2700.00	5073.51	5079.59	5081.64	5085.97	0.005700	20.26	133.29	34.17	1.81
Site 1	362.32	636 cfs	636.00	5072.60	5073.48	5074.68	5079.39	0.036661	19.50	32.61	37.00	3.66
Site 1	362.32	2700 cfs	2700.00	5072.60	5075.51	5078.08	5085.31	0.014142	25.11	107.51	37.00	2.60
Site 1	262		Culvert									
Site 1	261.24	636 cfs	636.00	5071.60	5075.47		5075.77	0.000321	4.44	143.09	37.00	0.40
Site 1	261.24	2700 cfs	2700.00	5071.60	5080.11		5081.25	0.000537	8.58	314.79	37.00	0.52
Site 1	167.31	636 cfs	636.00	5070.30	5074.21	5074.24	5075.61	0.002040	9.50	66.97	25.00	1.02
Site 1	167.31	2700 cfs	2700.00	5070.30	5078.47	5078.51	5081.03	0.001675	12.85	210.19	42.36	1.02

MastheadJDH Plan: Proposed 12/6/2019

NPino Site 1

