

ONTROL NOTES	GENERAL NOTES
ONSIBLE FOR EACH CONTROL MEASURE JCTION SITE ENTRANCE, AND SEDIMENT ION CONTROL MEASURES BEFORE ANY IBLE MEASURES SHALL BE INSTALLED	1. THE CONTRACTOR SHALL BE RESPONSIBLE FOR EXECUTING ALL APPLICABLE NATIONAL POLLUTANT DISCHARE ELIMINATION SYSTEM (NPDES) REQUIREMENTS. THOSE REQUIREMENTS SHALL INCLUDE, BUT NOT BE LIMITED TO, OBTAINING AN NPDES PERMIT PRIOR TO ANY CONSTRUCTION, FILING THE NOTICE OF INTENT (NOI) AND THE NOTICE OF TERMINATION (NOT) APPLICATIONS. THE CONTRACTOR SHALL ALSO BE RESPONSIBLE FOR THE IMPLEMENTATION AND INSPECTION OF THE STORM WATER POLLUTION PREVENTION PLAN (SWPPP) INCLUDING THE FILING OF THE INSPECTION REPORTS.
PLY WATER TO DISTURBED AREAS FOR	2. THE CONTRACTOR SHALL MAINTAIN A COPY OF THE APPROVED SWPPP ON-SITE AT ALL TIMES.
TALLATION PHASE ENTIRE PHASE. APPLY WATER TO AS NECESSARY.	3. THE CONTRACTOR SHALL CONFORM TO ALL LOCAL, STATE AND FEDERAL DUST AND EROSION CONTROL REGULATIONS. THE CONTRACTOR PREPARE APPLICATIONS FOR AND OBTAIN ANY NECESSARY DUST OR EROSION CONTROL PERMITS FROM THE
TION CONTROLS PER APPROVED SITE ICED BY SWPPP).	APPLICABLE REGULATORY AGENCIES. 4. THE CONTRACTOR SHALL COMPLY WITH ALL APPLICABLE LOCAL, STATE AND FEDERAL REGULATIONS CONCERNING SURFACE AND SUBSURFACE WATER. CONTACT WITH SURFACE AND SUBSURFACE WATER BY CONSTRUCTION EQUIPMENT AND
OL NOTES	PERSONNEL SHALL BE MINIMIZED. EQUIPMENT MAINTENANCE AND REFUELING OPERATIONS SHALL BE PERFORMED IN AN ENVIRONMENTALLY SAFE MANNER IN COMPLIANCE WITH GOVERNMENT REGULATIONS.
RANCE REQUIRED BETWEEN	5. WHERE PRIVATE STORM DRAIN INLETS ARE SUSCEPTIBLE TO INFLOW OF SILT OR DEBRIS FROM, OR DUE TO, CONSTRUCTION ACTIVITIES, PROTECTION FROM SAID INFLOW SHALL BE PROVIDED UTILIZING BEST MANAGEMENT PRACTICES (BMPS) IDENTIFIED IN THE APPROVED SWPPP.
NG FOR TEMPORARY EROSION CONTROL. RUCTION SECURITY FENCING FOR	NO OFFSITE STORM DRAIN INLETS SHALL BE BLOCKED. ONLY ONSITE/PROPOSED STORM DRAIN INLETS CAN BE BLOCKED DURING CONSTRUCTION.
BE WATERED AS NECESSARY FOR TROL.	6. IF SEDIMENT ESCAPES THE CONSTRUCTION SITE IT SHALL BE REMOVED FROM THE ADJACENT PROPERTY OR RIGHT-OF-WAY AT THE TIME OF OCCURRENCE. IN ADDITION, THE CONTRACTOR SHALL MAINTAIN A REGIMEN OF STREET SWEEPING AND GENERAL CLEAN-UP MEASURES.
STAGING AREAS MAY BE RELOCATED CHANGING CONDITIONS ON THE JOB ND CONCRETE WASH-OUT PITS TO BE TECTED COPY OF SAME SHALL BE	7. ANY AREAS DISTURBED BY CONSTRUCTION AND NOT TO BE COVERED BY DESIGNED LANDSCAPING OR IMPERVIOUS SURFACES SHALL BE REVEGETATED WITH NATIVE GRASS SEEDING. UNLESS INDICATED OTHERWISE ON THESE PLANS OR ON THE LANDSCAPING PLAN, NATIVE GRASS SEEDING SHALL BE CLASS 'A SEEDING PER SECTION 1012 OF THE NEW MEXICO STANDARD SPECIFICATIONS FOR PUBLIC
NING SWPPP INFORMATION. THIS SITE TO WATERS OF THE U.S. OR RROWED FROM AN OFFSITE LOCATION.	WORKS CONSTRUCTION, APWA NM CHAPTER, LATEST EDITION. WHEN CONSTRUCTION ACTIVITIES CEASE AND EARTH DISTURBING ACTIVITIES WILL NOT RESUME WITHIN 14 DAYS, SURFACE STABILIZATION MEASURES, AS DEFINED ON THE SWPPP, MUST BE INITIATED.
DRAWINGS FOR FINAL STRUCTURAL AYS, PARKING AREAS, RUNDOWNS, RAWINGS FOR FINAL STABILIZATION OF	8. ALL WASTE PRODUCTS FROM THE CONSTRUCTION SITE, INCLUDING, BUT NOT LIMITED TO, ITEMS RESULTING FROM DEMOLITION, CONSTRUCTION WASTE, CONSTRUCTION EQUIPMENT WASTE PRODUCTS (OIL, GAS, DIESEL, TIRES, ETC.), GARBAGE, DEBRIS FROM GRUBBING AND EXCESS CUT MATERIAL SHALL BE APPROPRIATELY DISPOSED OF OFF-SITE. IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO OBTAIN THE PROPER PERMITS TO HAUL AND DISPOSE OF WASTE PRODUCTS. IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO ENSURE THAT THE WASTE DISPOSAL SITE IS PROPERLY PERMITTED PER LOCAL, STATE AND FEDERAL REGULATIONS TO ACCEPT THE WASTE BEING DISPOSED OF.
CTION ENTRANCE	9. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE REPORTING AND CLEAN-UP OF SPILLS OF HAZARDOUS MATERIALS ASSOCIATED WITH THE CONSTRUCTION SITE. HAZARDOUS MATERIALS ARE THOSE WHICH MAY BE A
10' MIN.	THREAT TO THE ENVIRONMENT, INCLUDING, BUT NOT LIMITED TO, GASOLINE, DIESEL FUEL, MOTOR OIL, SOLVENTS, CHEMICALS AND PAINTS. THE CONTRACTOR SHALL REPORT THE DISCOVERY OF PAST OR PRESENT SPILLS TO THE NEW MEXICO ENVIRONMENT DEPARTMENT EMERGENCY RESPONSE TEAM AT 505-827-9329.
	BMP LEGEND
5' MIN. EXISTING PAVEMENT	SILT FENCE STABILIZED CONSTRUCTION ENTRANCE
	CATCH BASIN PROTECTION
5:1 SLOPE TOP OF BERM SHALL BE AT LEAST 6" ABOVE ADJACENT ASPHALT.	
PROFILE 8	
FACILITY	
NANTONIO SAN ANTONIO	
SU-1 SU-1 508 1007 44 SU-1 5	
CENTER CONTER	
	no. date remarks by REVISIONS
	PROFESSIONS PROFESSION PROFE
	sheet title EROSION & SEDIMENT CONTROL
	UnderstandUnderstandUnderstanddrawn bydrawn bydesign by02/17/18METOJJB1715
	Bordenave designs sheet P.O. BOX 91194, ALBUQUERQUE, NM 87199 C1.3 Office (505)823-1344 Cell (505)480-6812 C1.3
	Email JakeBordenave@comcast.net