

ROUGH GRADING APPROVAL

DATE:

BENCHMARK

ACS "NM47-13"
CENTRAL STATION DATA
NM STATE PLANE COORDINATES
CENTRAL ZONE
X=382262.47
Y=1495830.34
G=0.99997825
A=-0°13'35"
ELEV=4968.392
LOCATED AT THE CENTER OF
2ND ST. AND MANUEL BLVD.

KEY NOTES

1. INSTALL GUTTER SYSTEM FROM NE CORNER TO NW CORNER OF THE BUILDING.
2. INSTALL GUTTER SYSTEM FROM SE CORNER TO SW CORNER OF THE BUILDING.

Location

The site is the existing Tortilla Company and it is located on the east side of 5th street and approximately 200' north of Menaul Boulevard. See vicinity map for location.

Purpose

The purpose of this plan is to present a grading and drainage plan for building permit approval for the proposed addition.

Existing Drainage Conditions

The proposed addition will be over an existing unpaved area. The runoff from the entire site, at a flow rate of 2.23 cfs, drains east (+/- 50%) and west (+/- 50%) to 4th and 5th street. No offsite runoff enters this site. According to FIRM map number 35001C0332 D the site does not fall within a 100-year flood plain. The site falls within a 500-year flood plain.

Proposed Conditions and On-Site Drainage Management Plan


The drainage pattern will remain the same. The finished floor elevation of the new addition will be set as the building to the south. The proposed flow rate is 2.55 cfs. The increase in flow rate is only 0.32 cfs. This increase in the flow rate is very minimal and will not have any impact on the storm sewer structures down stream.

Calculations

City of Albuquerque, Development Process Manual, Section 22.2, Hydrology Section, revised January, 1993, was used for the runoff calculations. A treatment of B=10.00% cfs, D=90.00% was used for on site proposed conditions. A treatment of B=10.00% cfs, D=90.00% was used for on site existing conditions. The site falls under Zone 2 according to figure A page 2.

EROSION CONTROL PLAN AND POLLUTION PREVENTION NOTES

1. CONTRACTOR IS RESPONSIBLE FOR OBTAINING A TOPSOIL DISTURBANCE PERMIT PRIOR TO BEGINNING WORK.
2. CONTRACTOR IS RESPONSIBLE FOR CLEANING ALL SEDIMENT OUT OF EXISTING RIGHT-OF-WAY.
3. CONTRACTOR IS RESPONSIBLE FOR MAINTAINING ALL STORM RUN OFF ON SITE.
4. REPAIR OF DAMAGED FACILITIES AND CLEAN-UP OF SEDIMENT ACCUMULATION ON ADJACENT PROPERTIES AND IN PUBLIC FACILITIES IS THE RESPONSIBILITY OF THE CONTRACTOR.
5. ALL EXPOSED EARTH SURFACES MUST BE PROTECTED FROM WIND AND WATER EROSION PRIOR TO FINAL ACCEPTANCE OF ANY PROJECT.



LEGAL DESCRIPTION:

LOTS 7, 8, 23, 24, 25, 26, BLOCK 4, UNIT 2, WHITE CITY ADDITION

NOTES:


1. ALL SPOT ELEVATIONS PRESENT THE FLOWLINE ELEVATION UNLESS OTHERWISE NOTED.
2. ADD 4900 TO ALL THE PROPOSED SPOT ELEVATIONS.
3. THE OWNER OF THIS PROPERTY IS IN PROCESS OF REPLACING THE LOTS INTO ONE LOT TO PREVENT THE CROSS LOT DRAINAGE PROBLEM.

PROJECT DATA:


PROJECT DESCRIPTION:
NEW BUILDING ADDITION TO ALBUQUERQUE TORTILLA COMPANY.
PROJECT ADDRESS:
2701 4TH STREET, NW
TOTAL ADDITION:
3,200 S.F.

LEGEND

- X—X—X— EXISTING FENCE
- - - - - EXISTING POWER LINES
- - - - - EXISTING CURB & GUTTER
- - - - - BOUNDARY LINE
- - - - - EASEMENT
- - - - - PROPOSED SIDEWALK
- x 4963.70 PROPOSED GRADE
- x 5095.52 EXISTING GRADE
- x 64.33 EXISTING MANHOLE
- 65.08 AS-BUILD GRADE



GRAPHIC SCALE




ALBUQUERQUE TORTILLA COMPANY GRADING AND DRAINAGE PLAN


ENGINEER'S SEAL		DRAWN BY SH.B
		DATE 7-2-98
		9815GRR1.DWG
		SHEET # 1
		JOB # 9815

10209 SNOWFLAKE CT., NW
ALBUQUERQUE, NEW MEXICO 87114
(505) 899-5570

SHAHAB BIAZAR
P.E. #13479



I certify that the grades shown on the plans have been built in substantial compliance with approved grading and drainage plan dated 10-14-98. Survey information was supplied by Sandia surveying, Leonard G. Martinez, in accordance with normal surveying practices.



AHYMO INPUT FILE

```
*
* ZONE 2
* (100-YEAR, 6 HOUR, STORM)

START TIME=0.0
RAINFALL TYPE=1 RAIN QUARTER=0.0 IN
RAIN ONE=2.01 IN RAIN SIX=2.35 IN
RAIN DAY=2.75 IN DT=0.03333 HR

* UNDER EXISTING CONDITIONS
COMPUTE NM HYD ID=1 HYD NO=101.0 AREA=0.000888 SQ MI
PER A=0.00 PER B=18.00 PER C=23.00 PER D=59.00
TP=0.1333 HR MASS RAINFALL=-1

* PROPOSED CONDITIONS
COMPUTE NM HYD ID=1 HYD NO=101.0 AREA=0.000888 SQ MI
PER A=0.00 PER B=10.00 PER C=0.00 PER D=90.00
TP=0.1333 HR MASS RAINFALL=-1

* FINISH
```

AHYMO SUMMARY OUTPUT FILE

AHYMO SUMMARY TABLE (AHYMO194)-AMAFCA Hydrologic Model-January,1994 RUN DATE (MON/DAY/YR) =06/10/1998
INPUT FILE = BURRITO

COMMAND	HYDROGRAPH IDENTIFICATION	FROM NO.	TO NO.	AREA (SQ MI)	PEAK DISCHARGE (CFS)	RUNOFF VOLUME (AC-FT)	TIME TO RUNOFF (INCHES)	CFS PER ACRE	PAGE = 1
START	RAINFALL TYPE= 1								
COMPUTE NM HYD	101.00	-	1	0.00089	2.23	0.078	1.64085	1.500	3.929
COMPUTE NM HYD	101.00	-	1	0.00089	2.55	0.094	1.98165	1.500	4.490
FINISH									

NOTICE TO CONTRACTORS

1. AN EXCAVATION/CONSTRUCTION PERMIT WILL BE REQUIRED BEFORE BEGINNING ANY WORK WITHIN CITY RIGHT-OF-WAY. AN APPROVED COPY OF THESE PLANS MUST BE SUBMITTED AT THE TIME OF APPLICATION FOR THIS PERMIT.
2. ALL WORK DETAILED ON THESE PLANS TO BE PERFORMED, EXCEPT AS OTHERWISE STATED OR PROVIDED HEREON, SHALL BE CONSTRUCTED IN ACCORDANCE WITH CITY OF ALBUQUERQUE INTERIM STANDARD SPECIFICATIONS FOR PUBLIC WORKS CONSTRUCTION, 1985.
3. TWO WORKING DAYS PRIOR TO ANY EXCAVATION, CONTRACTOR MUST CONTACT LINE LOCATING SERVICE, 765-1234, FOR LOCATION OF EXISTING UTILITIES.
4. PRIOR TO CONSTRUCTION, THE CONTRACTOR SHALL EXCAVATE AND VERIFY THE HORIZONTAL AND VERTICAL LOCATIONS OF ALL CONSTRUCTIONS. SHOULD A CONFLICT EXIST, THE CONTRACTOR SHALL NOTIFY THE ENGINEER SO THAT THE CONFLICT CAN BE RESOLVED WITH A MINIMUM AMOUNT OF DELAY.
5. BACKFILL COMPACTION SHALL BE ACCORDING TO RESIDENTIAL STREET USE.
6. MAINTENANCE OF THESE FACILITIES SHALL BE THE RESPONSIBILITY OF THE OWNER OF THE PROPERTY SERVED.
7. WORK ON ARTERIAL STREETS SHALL BE PERFORMED ON A 24-HOUR BASIS.



LEGAL DESCRIPTION:
LOTS 7, 8, 23, 24, 25, 26, BLOCK 4, UNIT 2, WHITE CITY ADDITION

- NOTES:
1. ALL SPOT ELEVATIONS PRESENT THE FLOWLINE ELEVATION UNLESS OTHERWISE NOTED.
 2. ADD 4900 TO ALL THE PROPOSED SPOT ELEVATIONS.
 3. THE OWNER OF THIS PROPERTY IS IN PROCESS OF REPLACING THE LOTS INTO ONE LOT TO PREVENT THE CROSS LOT DRAINAGE PROBLEM.


PROJECT DATA:

PROJECT DESCRIPTION:
NEW BUILDING ADDITION TO ALBUQUERQUE TORTILLA COMPANY.


PROJECT ADDRESS:
2701 4TH STREET, NW

TOTAL ADDITION:
3,200 S.F.

- LEGEND
- EXISTING FENCE
 - EXISTING POWER LINES
 - EXISTING CURB & GUTTER
 - BOUNDARY LINE
 - EASEMENT
 - PROPOSED SIDEWALK
 - PROPOSED GRADE
 - EXISTING GRADE
 - EXISTING MANHOLE





GRAPHIC SCALE



RECEIVED
OCT 14 1998
HYDROLOGY SECTION

ALBUQUERQUE TORTILLA COMPANY
GRADING AND DRAINAGE PLAN



10209 SNOWFLAKE CT., NW
ALBUQUERQUE, NEW MEXICO 87114
(505)899-5570

DRAWN BY SH.B
DATE 7-2-98
9815GRR1.DWG
SHEET # 1
JOB # 9815

ROUGH GRADING APPROVAL DATE

BENCHMARK

ACS "NM47-13"
CENTRAL STATION DATA
NM STATE PLANE COORDINATES
CENTRAL ZONE
X=382262.47
Y=1495630.34
G=0.99967825
A=-0013'35"
ELEV=4968.392
LOCATED AT THE CENTER OF
2ND ST. AND MENAUL BLVD.

KEY NOTES

1. INSTALL GUTTER SYSTEM FROM NE CORNER TO NW CORNER OF THE BUILDING.
2. INSTALL GUTTER SYSTEM FROM SE CORNER TO SW CORNER OF THE BUILDING.

Location

The site is the existing Tortilla Company and it is located on the east side of 5th street and approximately 200' north of Menaul Boulevard. See vicinity map for location.

Purpose

The purpose of this plan is to present a grading and drainage plan for building permit approval for the proposed addition.

Existing Drainage Conditions

The proposed addition will be over an existing unpaved area. The runoff from the entire site, at a flow rate of 2.23 cfs, drains east (+/- 50%) and west (+/- 50%) to 4th and 5th street. No offsite runoff enters this site. According FIRM map number 35001C0332 D the site does not fall within a 100-year flood plain. The site falls within a 500-year flood plain.

Proposed Conditions and On-Site Drainage Management Plan


The drainage pattern will remain the same. The finished floor elevation of the new addition will be set as the building to the south. The proposed flow rate is 2.55 cfs. The increase in flow rate is only 0.32 cfs. This increase in the flow rate is very minimal and will not have any impact on the storm sewer structures down stream.

Calculations

City of Albuquerque, Development Process Manual, Section 22.2, Hydrology Section, revised January, 1993, was used for the runoff calculations. A treatment of B=10.00% cfs, D=90.00% was used for on site proposed conditions. A treatment of B=10.00% cfs, D=90.00% was used for on site existing conditions. The site falls under Zone 2 according to figure A page 2.

EROSION CONTROL PLAN
AND POLLUTION PREVENTION NOTES

1. CONTRACTOR IS RESPONSIBLE FOR OBTAINING A TOPSOIL DISTURBANCE PERMIT PRIOR TO BEGINNING WORK.
2. CONTRACTOR IS RESPONSIBLE FOR CLEANING ALL SEDIMENT OUT OF EXISTING RIGHT-OF-WAY.
3. CONTRACTOR IS RESPONSIBLE FOR MAINTAINING ALL STORM RUN OFF ON SITE.
4. REPAIR OF DAMAGED FACILITIES AND CLEAN-UP OF SEDIMENT ACCUMULATION ON ADJACENT PROPERTIES AND IN PUBLIC FACILITIES IS THE RESPONSIBILITY OF THE CONTRACTOR.
5. ALL EXPOSED EARTH SURFACES MUST BE PROTECTED FROM WIND AND WATER EROSION PRIOR TO FINAL ACCEPTANCE OF ANY PROJECT.



AHYMO INPUT FILE

*
* ZONE 2
* (100-YEAR, 6 HOUR, STORM)

START TIME=0.0
RAINFALL TYPE=1 RAIN QUARTER=0.0 IN
RAIN ONE=2.01 IN RAIN SIX=2.35 IN
RAIN DAY=2.75 IN DT=0.03333 HR

* UNDER EXISTING CONDITIONS
COMPUTE NM HYD ID=1 HYD NO=101.0 AREA=0.000888 SQ MI
PER A=0.00 PER B=18.00 PER C=23.00 PER D=59.00
TP=0.1333 HR MASS RAINFALL=-1

* PROPOSED CONDITIONS
COMPUTE NM HYD ID=1 HYD NO=101.0 AREA=0.000888 SQ MI
PER A=0.00 PER B=10.00 PER C=0.00 PER D=90.00
TP=0.1333 HR MASS RAINFALL=-1

*
FINISH

AHYMO SUMMARY OUTPUT FILE

AHYMO SUMMARY TABLE (AHYMO194)-AMAFCA Hydrologic Model-January,1994 RUN DATE (MON/DAY/YR) =06/10/1998
INPUT FILE = BURRITO

COMMAND	HYDROGRAPH ID	FROM ID NO.	TO ID NO.	AREA (SQ MI)	PEAK DISCHARGE (CFS)	RUNOFF VOLUME (AC-FT)	TIME TO RUNOFF (INCHES)	CFS PER ACRE	PAGE
START	TYPE= 1								11
RAINFALL									
COMPUTE NM HYD	101.00	-	1	0.00089	2.23	0.078	1.64085	1.500	3.929
COMPUTE NM HYD	101.00	-	1	0.00089	2.55	0.094	1.98165	1.500	4.490
FINISH									
									NOTATION
									TIME= .00
									RAIN= 2.350
									PER IMP= 59.00
									PER IMP= 90.00

NOTICE TO CONTRACTORS

1. AN EXCAVATION/CONSTRUCTION PERMIT WILL BE REQUIRED BEFORE BEGINNING ANY WORK WITHIN CITY RIGHT-OF-WAY. AN APPROVED COPY OF THESE PLANS MUST BE SUBMITTED AT THE TIME OF APPLICATION FOR THIS PERMIT.
2. ALL WORK DETAILED ON THESE PLANS TO BE PERFORMED, EXCEPT AS OTHERWISE STATED OR PROVIDED HEREON, SHALL BE CONSTRUCTED IN ACCORDANCE WITH CITY OF ALBUQUERQUE INTERIM STANDARD SPECIFICATIONS FOR PUBLIC WORKS CONSTRUCTION, 1985.
3. TWO WORKING DAYS PRIOR TO ANY EXCAVATION, CONTRACTOR MUST CONTACT LINE LOCATING SERVICE, 765-1234, FOR LOCATION OF EXISTING UTILITIES.
4. PRIOR TO CONSTRUCTION, THE CONTRACTOR SHALL EXCAVATE AND VERIFY THE HORIZONTAL AND VERTICAL LOCATIONS OF ALL CONSTRUCTIONS. SHOULD A CONFLICT EXIST, THE CONTRACTOR SHALL NOTIFY THE ENGINEER SO THAT THE CONFLICT CAN BE RESOLVED WITH A MINIMUM AMOUNT OF DELAY.
5. BACKFILL COMPACTION SHALL BE ACCORDING TO RESIDENTIAL STREET USE.
6. MAINTENANCE OF THESE FACILITIES SHALL BE THE RESPONSIBILITY OF THE OWNER OF THE PROPERTY SERVED.
7. WORK ON ARTERIAL STREETS SHALL BE PERFORMED ON A 24-HOUR BASIS.

ROUGH GRADING APPROVAL

DATE

BENCHMARK

ACS "NM47-13"
CENTRAL STATION DATA
NM STATE PLANE COORDINATES
CENTRAL ZONE
X=382282.47
Y=1495630.34
G=0.99967825
A=-0013'35"
ELEV=4968.392
LOCATED AT THE CENTER OF
2ND ST. AND MENAUL BLVD.

KEY NOTES

1. INSTALL GUTTER SYSTEM FROM NE CORNER TO NW CORNER OF THE BUILDING.
2. INSTALL GUTTER SYSTEM FROM SE CORNER TO SW CORNER OF THE BUILDING.

Location

The site is the existing Tortilla Company and it is located on the east side of 5th street and approximately 200' north of Menaul Boulevard. See vicinity map for location.

Purpose

The purpose of this plan is to present a grading and drainage plan for building permit approval for the proposed addition.

Existing Drainage Conditions

The proposed addition will be over an existing unpaved area. The runoff from the entire site, at a flow rate of 2.23 cfs, drains east (+/- 50%) and west (+/- 50%) to 4th and 5th street. No offsite runoff enters this site. According FIRM map number 35001C0332 D the site does not fall within a 100-year flood plain. The site falls within a 500-year flood plain.

Proposed Conditions and On-Site Drainage Management Plan


The drainage pattern will remain the same. The finished floor elevation of the new addition will be set as the building to the south. The proposed flow rate is 2.55 cfs. The increase in flow rate is only 0.32 cfs. This increase in the flow rate is very minimal and will not have any impact on the storm sewer structures down stream.

Calculations

City of Albuquerque, Development Process Manual, Section 22.2, Hydrology Section, revised January, 1993, was used for the runoff calculations. A treatment of B=10.00% cfs, D=90.00% was used for on site proposed conditions. A treatment of B=10.00% cfs, D=90.00% was used for on site existing conditions. The site falls under under Zone 2 according to figure A page 2.

EROSION CONTROL PLAN
AND POLLUTION PREVENTION NOTES

1. CONTRACTOR IS RESPONSIBLE FOR OBTAINING A TOPSOIL DISTURBANCE PERMIT PRIOR TO BEGINNING WORK.
2. CONTRACTOR IS RESPONSIBLE FOR CLEANING ALL SEDIMENT OUT OF EXISTING RIGHT-OF-WAY.
3. CONTRACTOR IS RESPONSIBLE FOR MAINTAINING ALL STORM RUN OFF ON SITE.
4. REPAIR OF DAMAGED FACILITIES AND CLEAN-UP OF SEDIMENT ACCUMULATION ON ADJACENT PROPERTIES AND IN PUBLIC FACILITIES IS THE RESPONSIBILITY OF THE CONTRACTOR.
5. ALL EXPOSED EARTH SURFACES MUST BE PROTECTED FROM WIND AND WATER EROSION PRIOR TO FINAL ACCEPTANCE OF ANY PROJECT.



LEGAL DESCRIPTION

LOTS 7, 8, 23, 24, 25, 26, BLOCK 4, UNIT 2, WHITE CITY ADDITION

NOTES

1. ALL SPOT ELEVATIONS PRESENT THE FLOWLINE ELEVATION UNLESS OTHERWISE NOTED.
2. ADD 4900 TO ALL THE PROPOSED SPOT ELEVATIONS.
3. THE OWNER OF THIS PROPERTY IS IN PROCESS OF REPLATING THE LOTS INTO ONE LOT TO PREVENT THE CROSS LOT DRAINAGE PROBLEM.


PROJECT DATA

PROJECT DESCRIPTION:
NEW BUILDING ADDITION TO ALBUQUERQUE TORTILLA COMPANY.
PROJECT ADDRESS:
2701 4TH. STREET, NW
TOTAL ADDITION:
3,200 S.F.

LEGEND

- EXISTING FENCE
- EXISTING POWER LINES
- EXISTING CURB & GUTTER
- BOUNDARY LINE
- EASEMENT
- PROPOSED SIDEWALK
- PROPOSED GRADE
- EXISTING GRADE
- EXISTING MANHOLE

GRAPHIC SCALE




SCALE: 1"=20'

ALBUQUERQUE TORTILLA COMPANY
GRADING AND DRAINAGE PLAN

ENGINEER'S SEAL
SHAHAB BIAZAR
REGISTERED PROFESSIONAL ENGINEER
P.E. #13479

ADVANCED
ENGINEERING
and CONSULTING
10209 SNOWFLAKE CT., NW
ALBUQUERQUE, NEW MEXICO 87114
(505)899-5570

DRAWN BY SH.B
DATE 7-2-98
9815GR.DWG
SHEET # 1
JOB # 9841



NOTICE TO CONTRACTORS

1. AN EXCAVATION/CONSTRUCTION PERMIT WILL BE REQUIRED BEFORE BEGINNING ANY WORK WITHIN CITY RIGHT-OF-WAY. AN APPROVED COPY OF THESE PLANS MUST BE SUBMITTED AT THE TIME OF APPLICATION FOR THIS PERMIT.
2. ALL WORK DETAILED ON THESE PLANS TO BE PERFORMED, EXCEPT AS OTHERWISE STATED OR PROVIDED HEREON, SHALL BE CONSTRUCTED IN ACCORDANCE WITH CITY OF ALBUQUERQUE INTERIM STANDARD SPECIFICATIONS FOR PUBLIC WORKS CONSTRUCTION, 1985.
3. TWO WORKING DAYS PRIOR TO ANY EXCAVATION, CONTRACTOR MUST CONTACT LINE LOCATING SERVICE, 785-1234, FOR LOCATION OF EXISTING UTILITIES.
4. PRIOR TO CONSTRUCTION, THE CONTRACTOR SHALL EXCAVATE AND VERIFY THE HORIZONTAL AND VERTICAL LOCATIONS OF ALL CONSTRUCTIONS. SHOULD A CONFLICT EXIST, THE CONTRACTOR SHALL NOTIFY THE ENGINEER SO THAT THE CONFLICT CAN BE RESOLVED WITH A MINIMUM AMOUNT OF DELAY.
5. BACKFILL COMPACTION SHALL BE ACCORDING TO RESIDENTIAL STREET USE.
6. MAINTENANCE OF THESE FACILITIES SHALL BE THE RESPONSIBILITY OF THE OWNER OF THE PROPERTY SERVED.
7. WORK ON ARTERIAL STREETS SHALL BE PERFORMED ON A 24-HOUR BASIS.

AHYMO INPUT FILE

*
* ZONE 2
* (100-YEAR, 6 HOUR, STORM)
START TIME=0.0
RAINFALL TYPE=1 RAIN QUARTER=0.0 IN
RAIN ONE=2.01 IN RAIN SIX=2.35 IN
RAIN DAY=2.75 IN DT=0.03333 HR
* UNDER EXISTING CONDITIONS
COMPUTE NM HYD ID=1 HYD NO=101.0 AREA=0.000888 SQ MI
PER A=0.00 PER B=18.00 PER C=23.00 PER D=59.00
TP=0.1333 HR MASS RAINFALL=-1
* PROPOSED CONDITIONS
COMPUTE NM HYD ID=1 HYD NO=101.0 AREA=0.000888 SQ MI
PER A=0.00 PER B=10.00 PER C=0.00 PER D=90.00
TP=0.1333 HR MASS RAINFALL=-1
*
FINISH

AHYMO SUMMARY OUTPUT FILE

AHYMO SUMMARY TABLE (AHYMO194)-AMAFCA Hydrologic Model-January,1994 RUN DATE (MON/DAY/YR) =06/10/1998
INPUT FILE = BURRITO
COMMAND HYDROGRAPH ID ID AREA DISCHARGE PEAK RUNOFF TIME TO CFS PER PAGE = 1
IDENTIFICATION NO. NO. (SQ MI) (CFS) (AC-FT) (INCHES) (HOURS) ACRE NOTATION
START RAINFALL TYPE= 1 TIME= .00
COMPUTE NM HYD 101.00 - 1 0.00089 2.23 0.078 1.64085 1.500 3.929 RAIN= 2.350
COMPUTE NM HYD 101.00 - 1 0.00089 2.55 0.094 1.98165 1.500 4.490 PER IMP= 59.00
FINISH PER IMP= 90.00