# CITY OF ALBUQUER



June 2, 2015

Graeme Means, PE High Mesa Consulting Group, Inc. 6010-B Midway Park Blvd. NE Albuquerque, NM 87109

RE:

Aztec Elementary School, 2611 Eubank Blvd. NE

Grading and Drainage Plan

Engineer's Stamp Date 5-01-2015 (File: H20-D033)

Dear Mr. Means:

Based upon the information provided in your submittal received 5-05-15, the above referenced Grading and Drainage Plan cannot be approved for Building Permit until the following comments are addressed:

PO Box 1293

1) Provide the AHYMO input and output files and inlet capacity calculations.

Albuquerque

2) Show roof drain locations on the grading plan.

If you have any questions, you can contact me at 924-3924.

New Mexico 87103

www.cabq.gov

Sincerely,

Jeanne Wolfenbarger, P.E. Senior Engineer, Planning Dept.

Development Review Services

Orig: Drainage file

c.pdf Addressee via Email



# City of Albuquerque

#### Planning Department

#### Development & Building Services Division

#### DRAINAGE AND TRANSPORTATION INFORMATION SHEET

(REV 02/2013)

	ACILITY Building Permit #: City Drainage #: H20 D033
DRB#: EPC#:	
Legal Description: TRACTS E AND F, LANDS OF	F BOARD OF EDUCATION, AZTEC ELEM. SCHOOL
City Address: 2611 EUBANK BLVD NE, ALBUC	QUERQUE NM 8/110
Engineering Firm: High Mesa Consulting Group  Address: 6010-B Midway Park Blvd NE, Albuq	Contact: Graeme Means #13676
Phone#: 505-345-4250 Fax#: 505-	345-4254 E-mail: gmeans@highmesacg.com
Phone#: 303-343-4230 Pax#. 303-	
Owner: Albuquerque Public Schools	Contact: Annelle Darby
Address: 915 Oak Street SE, 87106	
Phone#: 848-8829 Fax#:	E-mail: <u>annelle.darby@aps.edu</u>
Architect: Westwork Architects	Contact: Mark DePree
Address: PO Box 10921, Albuquerque NM 8718	84
Phone#: 884-5252 Fax#: 884-	E-mail: westwork@swcp.com
Surveyor: High Mesa Consulting Group	Contact: Chuck Cala NMPS#11184
Address: 6010-B Midway Park Blvd NE, Albuq	uerque NM 87109
Phone#: 505-345-4250 Fax#: 505-	E-mail: ccala@highmesacg.com
Contractor: To be selected	Contact:
Address:	
Phone#: Fax#:	E-mail:
TYPE OF SUBMITTAL:	CHECK TYPE OF APPROVAL/ACCEPTANCE SOUGHT:
DRAINAGE REPORT (DMP)	SIA/FINANCIAL GUARANTEE RELEASE A varified
X DRAINAGE PLAN 1st SUBMITTAL	
DRAINAGE PLAN RESUBMITTAL	PRELIMINARY PLAT APPROVAL  S. DEV. PLAN FOR SUB'D APPROVAL  E  E  E  E  E  E  E  E  E  E  E  E  E
CONCEPTUAL G & D PLAN	S. DEV. FOR BLDG. PERMIT APPROVAL MAY 0 5 2015
X GRADING PLAN	SECTOR PLAN APPROVAL
EROSION & SEDIMENT CONTROL PLAN (ESC)	
ENGINEER'S CERT (HYDROLOGY)	CERTIFICATE OF OCCUPANCY (PERMI) DEVELOPMENT SECTION
CLOMR/LOMR	CERTIFICATE OF OCCUPANCY (TCL TEMP) Durch \$5000 (
TRAFFIC CIRCULATION LAYOUT (TCL)	FOUNDATION PERMIT APPROVAL
ENGINEER'S CERT (TCL)	X BUILDING PERMIT APPROVAL
ENGINEER'S CERT (DRB SITE PLAN)	X GRADING PERMIT APPROVAL SO-19 APPROVAL
ENGINEER'S CERT (ESC)	X PAVING PERMIT APPROVAL ESC PERMIT APPROVAL
SO-19	WORK ORDER APPROVAL ESC CERT. ACCEPTANCE
OTHER (SPECIFY)	GRADING CERTIFICATION OTHER (DMP)
WAS A PRE-DESIGN CONFERENCE ATTENDED:	Yes X No Copy Provided
DATE SUBMITTED: 05-05-2015	By: Justin Schara
DATE GODINITIES. 05 05 2015	

Requests for approvals of Site Development Plans and/or Subdivision Plats shall be accompanied by a drainage submittal. The particular nature, location, and scope to the proposed development defines the degree of drainage detail. One or more of the following levels of submittal may be required based on the following Conceptual Grading and Drainage Plan: Required for approval of Site Development Plans greater than five (5) acres and Sector Plans

- Drainage Plans: Required for building permits, grading permits, paving permits and site plans less than five (5) acres
- Drainage Report: Required for subdivision containing more than ten (10) lots or constituting five (5) acres or more
- Erosion and Sediment Control Plan: Required for any new development and redevelopment site with 1-acre or more of land disturbing area, including project less than 1-acre than are part of a larger common plan of development

THIS PROJECT, LOCATED IN THE NORTHEAST HEIGHTS OF THE ALBUQUERQUE METROPOLITAN AREA, REPRESENTS A MODIFICATION T AN EXISTING APS SITE WITHIN AN INFILL AREA. THE PROPOSED DEVELOPMENT IS COMPRISED OF THE CONSTRUCTION OF A NEW PERMANENT BUILDING TO REPLACE EXISTING PORTABLE CLASSROOM BUILDINGS AND OLDER PERMANENT BUILDINGS. THE PROPOSED DEVELOPMENT WILL BE LOCATED AT THE CENTRAL AND SOUTHWEST PORTIONS OF THE CAMPUS. THE PROPOSED IMPROVEMENTS REFERENCED HEREIN ARE THE FIRST PHASE OF A MULTI-PHASE PROJECT THAT WILL ULTIMATELY ELIMINATE THE EXISTING PERMANENT BUILDINGS AND INCLUDE A NEW PAVED PARKING LOT; THE REMOVAL OF THE EXISTING PERMANENT BUILDINGS AND NEW PARKING LOT CONSTRUCTION WILL BE BY SEPARATE SUBMITTAL.

THE DRAINAGE CONCEPT FOR THIS PROJECT WILL BE THE CONTINUED DISCHARGE OF DEVELOPED RUNOFF TO AN EXISTING ONSITE DETENTION POND AT THE SOUTHWEST CORNER OF THE COMPLEX SITE, WITH CONTROLLED DISCHARGE TO AN EXISTING DOWNSTREAM DRAINAGE EASEMENT.

#### II. PROJECT DESCRIPTION

AS SHOWN BY THE VICINITY MAP, THE AZTEC COMPLEX IS LOCATED AT THE SOUTHWEST CORNER OF THE INTERSECTION OF EUBANA BLVD NE AND LEXINGTON AVENUE NE. THE CURRENT LEGAL DESCRIPTION IS TRACTS E, AZTEC ELEMENTARY SCHOOL. AS SHOWN BY PANEL 356 OF 825 OF THE NATIONAL FLOOD INSURANCE PROGRAM FLOOD INSURANCE RATE MAPS PUBLISHED BY FEMA FOR BERNALILLO COUNTY, NEW MEXICO, THIS SITE DOES NOT LIE WITHIN A DESIGNATED FLOOD HAZARD ZONE. PRIOR SITE DEVELOPMENT HAS ESTABLISHED A PRECEDENT FOR ONSITE DETENTION PONDING. INASMUCH AS THIS IS A REDEVELOPMENT PROJECT OF AN EXISTING FULLY DEVELOPED SITE, THE EXISTING DRAINAGE PATTERNS AND CONCEPTS SHALL BE MAINTAINED.

#### III. BACKGROUND DOCUMENTS

- THE PREPARATION OF THIS PLAN RELIED UPON THE FOLLOWING DOCUMENTS:
- DRAINAGE SUBMITTAL FOR SIERRA ALTERNATIVE SCHOOL PREPARED BY WILSON & COMPANY, NMPE 11955, DATED 8-12-98. THIS REFERENCED PLAN ESTABLISHED THE CONCEPT FOR THE ONSITE DETENTION OF STORM WATER RUNOFF WITH CONTROLLE DISCHARGE VIA 18" STORM DRAIN OUTLET OF 7.67 CFS TO A DOWNSTREAM DRAINAGE EASEMENT.
- GRADING AND DRAINAGE PLAN FOR DIAGNOSTICIAN CONSOLIDATION AT AZTEC COMPLEX, PREPARED BY HIGH MESA CONSULTING GROUP, NMPE 8547, DATED 08-28-2010 AND CERTIFIED 12-30-2010. THIS 2010 SUBMITTAL INCLUDED THE RENOVATION OF AN EXISTING PORTABLE CLASSROOM PARK TO SERVE DIAGNOSTICIANS; THESE PORTABLE CLASSROOMS WILL BE REMOVED AND REPLACED WITH PERMANENT BUILDING AS PART OF THE DEVELOPMENT OF THE SITE.
- TOPOGRAPHIC SURVEY PREPARED BY HIGH MESA CONSULTING GROUP, NMPS 11184, DATED 11-18-2013. THIS REFERENCED SURVY PROVIDES THE BASIS FOR THE EXISTING CONDITIONS OF THE PROJECT SITE.

#### IV. EXISTING CONDITIONS

THE PROJECT SITE PRESENTLY CONSISTS OF SEVERAL EXISTING PERMANENT AND PORTABLE CLASSROOM BUILDINGS. THE SITE IS SERVED BY TWO ASPHALT PAVED PARKING LOTS AT THE NORTHWEST AND NORTHEAST CORNERS OF THE SITE. THE DRAINAGE PATTERN FOR THE SITE ESTABLISHED BY PREVIOUS SUBMITTALS IS SHEETFLOW FROM NORTHEAST TO SOUTHWEST WITH DISCHARGE TO AN EXISTING DETENTION POND LOCATED AT THE SOUTHWEST CORNER OF THE SITE, AND CONTROLLED DISCHARGE FROM THE POND TO AN EXISTING DOWNSTREAM DRAINAGE EASEMENT.

THERE ARE NO APPARENT OFFSITE FLOWS IMPACTING THIS SITE. LEXINGTON AVE NE AND EUBANK BLVD NE, FULLY DEVELOPED CITY STREETS, LIE TO THE NORTH AND EAST WITH FLOWS APPARANTLY CONFINED TO THE CONSTRUCTED STREETS. EXISTING RESIDENTIAL LOTS TO THE SOUTH AND WEST ARE TOPOGRAPHICALLY LOWER AND APPEAR TO DISCHARGE DEVELOPED RUNOFF TO THE FRONTING CITY STREETS

#### DEVELOPED CONDITIONS

THE PROPOSED CONSTRUCTION CONSISTS OF A NEW PERMANENT BUILDING AND PAVED ACCESS AND PARKING IMPROVEMENTS TO REPLACE EXISTING PERMANENT BUILDINGS AND PORTABLE CLASSROOM BUILDINGS. THE DEVELOPED CONDITIONS DEPICTED HEREIN ARE PART OF A MULTI-PHASE PROJECT, WHEREIN THE PORTABLE CLASSROOM BUILDINGS WILL BE REMOVED PRIOR TO CONSTRUCTION OF THE NEW BUILDING, AND REMOVAL OF THE EXISTING PERMANENT BUILDINGS WILL OCCUR IN A FUTURE PHASE BY SEPARATE SUBMITTAL. RUNOFF FROM THE SITE WILL CONTINUE TO GENERALLY SHEETFLOW FROM EAST TO WEST AND NEW PRIVATE STORM DRAIN IMPROVEMENTS WILL BE CONSTRUCTED TO COLLECT AND CONVEY RUNOFF DIRECTLY TO THE ONSITE PRIVATE DETENTION POND AT THE SOUTHWEST CORNER OF THE SITE. THE PROPOSED IMPROVEMENTS WILL RESULT IN A MINOR DECREASE IN PEAK DISCHARGE AND VOLUME OF RUNOFF GENERATED BY THE SITE.

THE EXISTING RETENTION POND WILL BE REGRADED TO INCREASE PONDING CAPACITY. IN ADDITION, THE BOTTOM OF THE POND WILL BE LOWERED BELOW THE EXISTING STORM DRAIN OUTLET, RESULTING IN A RETENTION CAPACITY OF 29,460 CF. AS A RESULT, THE 2 YEAR, 24 HOUR DEVELOPED RUNOFF (20,870 CF) GENERATED BY THE SITE WILL BE RETAINED ONSITE, WHICH WILL ALSO MEET THE CONDITION OF MANAGING AND CONTROLLING THE FIRST FLUSH OF DEVELOPED RUNOFF DUE TO THE NEW IMPERVIOUS AREAS, AS WELL AS LEED REQUIREMENTS FOR STORMWATER QUANTITY AND QUALITY. THE EXISTING 18" STORM DRAIN OUTLET PIPE WILL NOT BE MODIFIED, AND WILL CONTINUE TO CONTROL DISCHARGE TO THE DOWNSTREAM DRAINAGE EASEMENT. AS DETERMINED BY AHYMO RESERVOIR ROUTING, THE 100-YEAR RELEASE RATE WILL BE 2.2 CFS WHICH IS MUCH LESS THAN THE PREVIOUSLY APPROVED 7.67 CFS RATE ESTABLISHED IN THE 1998 DRAINAGE PLAN REFERENCED ABOVE.

THERE WILL CONTINUE TO BE NO APPARENT OFFSITE FLOWS IMPACTING THE SITE AS A RESULT OF THESE DEVELOPED CONDITIONS. VI. GRADING PLAN

THE GRADING PLAN SHOWS 1.) EXISTING AND PROPOSED GRADES INDICATED BY SPOT ELEVATIONS AND CONTOURS AT 1'-0" INTERVALS, 2.) THE LIMIT AND CHARACTER OF THE EXISTING AND PROPOSED IMPROVEMENTS, AND 3.) CONTINUITY BETWEEN EXISTING AND PROPOSED GRADES. AS SHOWN BY THIS PLAN, THE ROPOSED GRADING WILL DIRECT DEVELOPED RUNOFF TO THE EXISTING ONSITE PRIVATE DETENTION POND.

#### VII. CALCULATIONS

THE CALCULATIONS CONTAINED HEREON ANALYZE THE EXISTING AND DEVELOPED CONDITIONS FOR THE 100-YEAR, 6-HOUR AND THE 2-YEAR, 24-HOUR RAINFALL EVENTS. THE PROCEDURE FOR 40 ACRE AND SMALLER BASINS, AS SET FORTH IN THE REVISION OF SECTION 22.2, HYDROLOGY OF THE DEVELOPMENT PROCESS MANUAL, VOLUME 2, DESIGN CRITERIA, DATED JANUARY 1993, HAS BEEN USED TO QUANTIFY THE PEAK RATE OF DISCHARGE AND VOLUME OF RUNOFF GENERATED. AS DEMONSTRATED BY THESE CALCULATIONS, THE PROPOSED DEVELOPMENT WILL RESULT IN A MINOR DECREASE IN THE DEVELOPED RUNOFF GENERATED BY THI AZTEC COMPLEX SITE. IN ADDITION THE AVERAGE END AREA METHOD WAS USED TO QUANTIFY THE CAPACITY OF THE REGRADED PRIVATE DETENTION POND, AND MANNING'S EQUATION WAS USED TO CALCULATE THE CAPACITY OF THE PROPOSED PRIVATE STORM DRAIN SYSTEM. AHYMO CALCULATIONS ROUTING THE SITE RUNOFF THROUGH THE DETENTION POND WERE RUN TO DEMONSTRATE THAT THE A PEAK DISCHARGE OF 2.2 CFS WILL DISCHARGE THROUGH THE EXISTING 18" STORM DRAIN OUTLET DURING A 100-YEAR STORM EVENT, WELL BELOW THE 7.67 CFS ALLOWABLE DISCHARGE RATE ESTABLISHED BY PRIOR SUBMITTAL.

#### VIII.CONCLUSIONS THE FOLLOWING CONCLUSIONS HAVE BEEN ESTABLISHED AS A RESULT OF THE EVAULATIONS CONTAINED HEREIN:

- THE PROPOSED IMPROVEMENTS ARE CONSISTENT WITH THE CONCEPT FOR DETENTION PONDING ESTABLISHED BY PRIOR
- THE PROPOSED IMPROVEMENTS WILL RESULT IN A MINOR DECREASE IN DEVELOPED PEAK DISCHARGE AND VOLUME OF RUNOFF GENERATED BY THE SITE THE REGRADED POND WILL RETAIN THE 2-YEAR, 24 HOUR RAINFALL EVENT, THEREFORE THE CONDITION OF MANAGING AND
- CONTROLLING THE FIRST FLUSH OF DEVELOPED RUNOFF FROM NEW IMPERVIOUS AREAS WILL BE MET THE EXISTING 18" STORM DRAIN OUTLET FOR THE SITE WILL NOT BE MODIFIED BY THE SITE DEVELOPMENT, MAINTAINING THE CONTROLLED DISCHARGE FROM THE SITE TO THE DOWNSTREAM DRAINAGE EASEMENT

7	STORM DRAIN HYDRAULICS						
	PIPE ID	Mannings Coefficient	Slope (ft/ft)	Diameter (in)	Maximum Discharge (cfs)	Discharge Full (cfs)	
	Α	0.013	0.0234	24	37.2	34.6	
	В	0.013	0.0200	24	34.4	32.0	
	С	0.013	0.0105	24	24.9	23.2	
	D	0.013	0.0112	30	46.7	43.4	
	Е	0.013	0.0054	30	32.4	30.1	
	F	0.013	0.0142	30	52.6	48.9	
	G	0.013	0.0142	12	4.6	4.3	
	Η	0.013	0.0085	30	40.7	37.8	
	I	0.013	0.0111	30	46.5	43.2	

	I	0.013	0.0111	30	46.5
A		POND V	OLUME by	ELEVATION	
1	ELEV FT	AREA SF	VOL CF	Σ VOL CF	Σ VOL AC-FT
	81.20	12070	0	0	0.00
	82.00	21490	13420	13420	0.31
	82.70	24350	16040	29460	0.68
	83.00	25870	7530	36990	0.85
	84.00	30500	23180	60170	1.38
	85.00	37300	33900	94070	2.16

### CALCULATIONS

#### SITE CHARACTERISTICS

A. PRECIPITATION ZONE = 2.6 IN B.  $P_{100.6 HR} = P_{360} =$ 1.3 IN  $P_{2, 24 HR} = P_{1440-2} =$ 442.510 SF TOTAL PROJECT AREA (A<sub>T</sub>) =

#### D. LAND TREATMENTS EXISTING LAND TREATMENT

١.	EXISTING LAND TREATMENT				
	TREATMENT	AREA (SF/AC)		%	
	Α				
	В	22,250		5	
	B	0.51	AC	5	
		217,890	SF	49	
	С	5.00	AC	49	
	D	202,370		46	
	b	4.65	AC	40	

10.16 AC

2.	DEVELOPED LAND TREATMENT				
	TREATMENT	AREA (SF/AC)		%	
	٨				
	^				
	B	123,506	SF	28	
	Б	2.84	AC	20	
	C	123,506	SF	28	
	C	2.84	AC	20	
	0	195,498	SF	44	
	Б	4.49	AC	74	

#### II. HYDROLOGY

#### A. EXISTING CONDITION 100 YEAR

100-YR STORM a. VOLUME 100-YR, 6- HR

 $E_W = (E_A A_A + E_B A_B + E_C A_C + E_D A_D)/A_T$ 

1.76 IN  $E_W = (0.66*0.00) + (0.92*0.51) + (1.29*5.00) + (2.36*4.65)/10.16 =$ 1.4899 AC-FT = **64,900 CF**  $V_{100.6 \text{ HR}} = (E_W/12)A_T = (1.76/12)10.16 =$ 

1.6835 AC-FT = **73,330 CF** 

0.5158 AC-FT = **22,470 CF** 

1.5923 AC-FT = **69,360 CF** 

39.7 CFS

12.0 CFS

b. VOLUME 100- YR, 24- HR  $V_{100,24 \text{ HR}} = V_{6HR} + A_D*(P_{24HR} - P_{6HR})/12 \text{ in/ft}$ 

= 1.49+4.65\*(3.10-2.60)/12 in/ft=

c. PEAK DISCHARGE  $Q_{P} = Q_{PA}A_{A} + Q_{PB}A_{B} + Q_{PC}A_{C} + Q_{PD}A_{D}$ 

 $Q_P = (1.87 * 0.00) + (2.60 * 0.51) + (3.45 * 5.00) + (5.02 * 4.65) =$ 41.9 CFS

#### 2. 2-YR STORM

a. VOLUME  $E_W = (E_A A_A + E_B A_B + E_C A_C + E_D A_D)/A_T$ 

 $E_W = (0.00*0.00) + (0.06*0.51) + (0.20*5.00) + (0.89*4.65)/10.16 =$ 0.51 IN  $V_{2,6 HR} = (E_W/12)A_T = (0.51/12)10.16 =$ 0.4317 AC-FT = 18,810 CF

b. VOLUME 2- YR, 24- HR

 $V_{2,24 \text{ HR}} = V_{2,6HR} + A_D*(P_{2,24HR} - P_{2,6HR})/12 \text{ in/ft}$ 

= 0.43+4.65\*(1.35-1.13)/12 in/ft=

c. PEAK DISCHARGE

 $Q_P = Q_{PA}A_A + Q_{PB}A_B + Q_{PC}A_C + Q_{PD}A_D$  $Q_P = (0.00 * 0.00) + (0.21 * 0.51) + (0.78 * 5.00) + (2.04 * 4.65) =$ 13.5 CFS

#### **B. DEVELOPED CONDITION**

 1. 100-YR STORM a. VOLUME

 $E_{W} = (E_{A}A_{A} + E_{B}A_{B} + E_{C}A_{C} + E_{D}A_{D})/A_{T}$ 

 $E_W = (0.66*0.00) + (0.92*2.84) + (1.29*2.84) + (2.36*4.49)/10.16 =$  $V_{100,6 \text{ HR}} = (E_W/12)A_T = (1.66/12)10.16 =$ 1.4053 AC-FT = 61.210 CF

b. VOLUME 100- YR. 24- HR  $V_{100,24 \text{ HR}} = V_{6HR} + A_D*(P_{24HR} - P_{6HR})/12 \text{ in/ft}$ 

= 1.41+4.49\*(3.10-2.60)/12 in/ft=

c. PEAK DISCHARGE

 $Q_{P} = Q_{PA}A_{A} + Q_{PB}A_{B} + Q_{PC}A_{C} + Q_{PD}A_{D}$ 

 $Q_P = (1.87 * 0.00) + (2.60 * 2.84) + (3.45 * 2.84) + (5.02 * 4.49) =$ 

#### 2. 2-YR STORM a. VOLUME

 $E_W = (E_A A_A + E_B A_B + E_C A_C + E_D A_D)/A_T$  $E_W = (0.00*0.00) + (0.06*2.84) + (0.20*2.84) + (0.89*4.49)/10.16 =$  $V_{2.6 \text{ HR}} = (E_W/12)A_T = (0.47/12)10.16 =$ 0.3979 AC-FT = 17,330 CF

b. VOLUME 2- YR, 24- HR

 $V_{2,24 \text{ HR}} = V_{2,6HR} + A_D*(P_{2,24HR} - P_{2,6HR})/12 \text{ in/ft}$ 0.4790 AC-FT = **20,870 CF** = 0.40+4.49\*(1.35-1.13)/12 in/ft=

c. PEAK DISCHARGE

 $Q_{P} = Q_{PA}A_{A} + Q_{PB}A_{B} + Q_{PC}A_{C} + Q_{PD}A_{D}$  $Q_P = (0.00 * 0.00) + (0.21 * 2.84) + (0.78 * 2.84) + (2.04 * 4.49) =$ 

#### C. COMPARISON 100 YEAR

1. 100-YR STORM

a. VOLUME 100-YR, 6-HR			
$\Delta V_{100, 6 HR} =$	61210 - 64900 =	-3,690 CF	(DECREASE)
b. VOLUME 100-YR, 24-Hr			_
$\Delta V_{100, 24 HR} =$	69360 - 73330 =	-3,970 CF	(DECREASE)
c. PEAK DISCHARGE			
$\Delta Q_{100} =$	39.7 - 41.9 =	-2.2 CFS	(DECREASE)
2 VD STORM			
2. 2-YR STORM			

# a. VOLUME 2-YR, 6-HR

$\Delta V_{2, 6 HR} =$	17330 - 18810 =	-1,480 CF	(DECREASE)	
b. VOLUME 2-YR, 24- Hr				
$\Delta V_{2, 24 HR} =$	20870 - 22470 =	-1,600 CF	(DECREASE)	
c. PEAK DISCHARGE				
$\Delta Q_2 =$	12.0 - 13.5 =	-1.5 CFS	(DECREASE)	

# CONSTRUCTION NOTES:

ALBUQUERQUE STANDARDS AND PROCEDURES.

- 1. ALL WORK DETAILED ON THESE PLANS TO BE PERFORMED UNDER CONTRACT SHALL. EXCEPT AS OTHERWISE STATED OR PROVIDED FOR HEREON, BE CONSTRUCTED IN ACCORDANCE WITH THE NEW MEXICO STANDARD SPECIFICATIONS FOR PUBLIC WORKS
- CONSTRUCTION 1987, PUBLISHED BY THE NEW MEXICO CHAPTER AMERICAN PUBLIC WORKS ASSOCIATION. (REVISED 12/06) 2. TWO (2) WORKING DAYS PRIOR TO ANY EXCAVATION, CONTRACTOR MUST CONTACT NEW MEXICO ONE CALL SYSTEM (NM 811) FOR DESIGNATION (LINE-SPOTTING) OF EXISTING PUBLIC UTILITIES AND EXISTING PRIVATE UTILITIES OWNED AND OPERATED BY ALBUQUERQUE PUBLIC
- 5. PRIOR TO CONSTRUCTION, THE CONTRACTOR SHALL EXCAVATE AND VERIFY THE HORIZONTAL AND VERTICAL LOCATION OF ALL POTENTIAL OBSTRUCTIONS. SHOULD A CONFLICT EXIST, THE CONTRACTOR SHALL NOTIFY THE ENGINEER IN WRITING SO THAT THE CONFLICT CAN BE RESOLVED WITH A MINIMUM AMOUNT OF DELAY. THE CONTRACTOR SHALL BE RESPONSIBLE FOR ALL INTERPRETATIONS IT MAKES WITHOUT FIRST CONTACTING THE ENGINEER AS REQUIRED ABOVE
- 4. ALL WORK ON THIS PROJECT SHALL BE PERFORMED IN ACCORDANCE WITH APPLICABLE FEDERAL, STATE AND LOCAL LAWS, RULES
- AND REGULATIONS CONCERNING CONSTRUCTION SAFETY AND HEALTH. 5. ALL CONSTRUCTION WITHIN PUBLIC RIGHT-OF-WAY SHALL BE PERFORMED IN ACCORDANCE WITH APPLICABLE CITY OF
- 6. IF ANY UTILITY LINES, PIPELINES, OR UNDERGROUND UTILITY LINES ARE SHOWN ON THESE DRAWINGS, THEY ARE SHOWN IN AN APPROXIMATE MANNER ONLY, AND SUCH LINES MAY EXIST WHERE NONE ARE SHOWN. IF ANY SUCH EXISTING LINES ARE SHOWN, THE LOCATION IS BASED UPON INFORMATION PROVIDED BY THE OWNER OF SAID UTILITY, AND THE INFORMATION MAY BE INCOMPLETE, OR MAY BE OBSOLETE BY THE TIME CONSTRUCTION COMMENCES. THE ENGINEER HAS CONDUCTED ONLY PRELIMINARY INVESTIGATION OF THE LOCATION, DEPTH, SIZE, OR TYPE OF EXISTING UTILITY LINES, PIPELINES, OR UNDERGROUND UTILITY LINES. THIS INVESTIGATION IS NOT CONCLUSIVE, AND MAY NOT BE COMPLETE, THEREFORE, MAKES NO REPRESENTATION PERTAINING THERETO, AND ASSUMES NO RESPONSIBILITY OR LIABILITY THEREFOR. THE CONTRACTOR SHALL INFORM ITSELF OF THE LOCATION OF ANY UTILITY LINE, PIPELINE, OR UNDERGROUND UTILITY LINE IN OR NEAR THE AREA OF THE WORK IN ADVANCE OF AND DURING EXCAVATION WORK. THE CONTRACTOR IS FULLY RESPONSIBLE FOR ANY AND ALL DAMAGE CAUSED BY ITS FAILURE TO

LOCATE, IDENTIFY AND PRESERVE ANY AND ALL EXISTING UTILITIES, PIPELINES, AND UNDERGROUND UTILITY LINES, IN PLANNING

AND CONDUCTING EXCAVATION, THE CONTRACTOR SHALL COMPLY WITH STATE STATUTES, MUNICIPAL AND LOCAL ORDINANCES,

RULES AND REGULATIONS, IF ANY, PERTAINING TO THE LOCATION OF THESE LINES AND FACILITIES 7. THE DESIGN OF PLANTERS AND LANDSCAPED AREAS IS NOT PART OF THIS PLAN. ALL PLANTERS AND LANDSCAPED AREAS ADJACENT TO THE BUILDING(S) SHALL BE PROVIDED WITH POSITIVE DRAINAGE TO AVOID ANY PONDING ADJACENT TO THE STRUCTURE. FOR CONSTRUCTIÓN DETAILS, REFER TO LANDSCAPING PLANS.

#### **EROSION CONTROL MEASURES:**

- 1. THE CONTRACTOR SHALL ENSURE THAT NO SOIL ERODES FROM THE SITE INTO PUBLIC RIGHT-OF-WAY OR ONTO PRIVATE
- 2. THE CONTRACTOR SHALL PROMPTLY CLEAN UP ANY MATERIAL EXCAVATED WITHIN THE PUBLIC RIGHT-OF-WAY SO THAT THE EXCAVATED MATERIAL IS NOT SUSCEPTIBLE TO BEING WASHED DOWN THE STREET.
- 3. CONTRACTOR SHALL SECURE "TOPSOIL DISTURBANCE PERMIT" FROM THE CITY PREPARE A SWPPP, AND FILE A NOTICE OF INTENT (N.O.I.) ON BEHALF OF THEMSELVES AND THE OWNER WITH THE EPA PRIOR TO BEGINNING CONSTRUCTION.

IRRIGATION CONTROL BOX

METAL BUILDING COLUMN

METER CAN WITH HOSE BIB

SHEET

IRRIGATION VALVE BOX

PIPE INVERT

MANHOLE

MLN

METAL BENCH

METAL HAND RAIL

METAL LANDING METAL LIGHT POLE

METAL RAMP

METAL SIGN OHC(1) OVERHEAD COMMUNICATION

OHE(1) OVERHEAD ELECTRIC

(# OF LINES)

(# OF LINES)

METAL POWER POLE

METAL TRASH CAN

LE	GEND				
AAAAABBBBBBCC CCCCCCCCCCCCCCCCCCCCCCCCC	BASKETBALL GOAL BUILDING OVERHANG BOLLARD BRICK PLANTER WALL BIKE RACK BRICK WALL CURB AND GUTTER COMMUNICATION LINE BY PAINT MARK SECURITY CAMERA IRON PIPE, CAPPED CONCRETE CURB COMMUNICATION CABINET COMMUNICATION CONDUIT CONCRETE DRIVE PAD LANDSCAPING CRUSHER FINES CAST IRON PIPE CENTERLINE DOOR CENTERLINE DOUBLE DOOR CHAIN LINK FENCE COMMUNICATION MANHOLE COMMUNICATION MISER CONCRETE MOW STRIP CONCRETE BLOCK WALL ELECTRIC CONDUIT CLEANOUT CONCRETE PLANTER WALL CONCRETE PLANTER WALL CONCRETE STEP CONCRETE CONCRETE CONCRETE CONCRETE CONCRETE WALL COVERED CONCRETE CONCRETE WALL COVERED CONCRETE WALKWAY DOUBLE CLEANOUT DOUBLE GATE DOUBLE PIPE GATE LECTRIC LINE BY PAINT MARK EDGE OF ASPHALT ELECTRIC BREAKER BOX ELECTRIC BREAKER ELECTRIC PANEL ELECTRIC PANEL ELECTRIC PANEL ELECTRIC PANEL ELECTRIC PANEL ELECTRIC PULLBOX BUILDING EXHAUST UNIT	WHB WL WLN WLP WMB WPP	OVERHEAD UTILITY MAST CONCRETE WHEEL STOP PLAYGROUND EQUIPMENT PAINTED PARKING LOT ISLAND PLANTER PAINTED PARKING STRIPE PICNIC TABLE ROOF DRAIN ROW OF CONCRETE WHEEL STOPS LANDSCAPING RAILROAD TIES SANITARY SEWER LINE BY PAINT MARK SIGN BASE STORM DRAIN STORM DRAIN STORM DRAIN INLET SERVICE DROP POLE ASPHALT SPEED HUMP STANDARD CONCRETE SIDEWALK SIDEWALK SIDEWALK CONCRETE SIDEWALK SIDEWALK CONCRETE TOP OF ASPHALT TOP OF ASPHALT TOP OF CONCRETE TOP OF GRATE ELECTRIC TRANSFORMER TRAFFIC SIGN TOP OF WALL TYPICAL VITRIFIED CLAY PIPE VENT PIPE WATER LINE BY PAINT MARK CONCRETE WHEELCHAIR RAMP WOOD FENCE WOOD STEPS WATER FAUCET WATER HOT BOX WATER LINE WOOD LANDING WOOD LIGHT POLE WATER METER BOX WOOD POWER POLE WOOD POWER POLE WOOD SHED WATER VALUT WATER VALVE BOX PAINTED UTILITY MARKER TREE TRUNK DIAMETER	INV TA TC TG + 488.70	INVERT TOP OF ASPHALT PAVEMENT TOP OF CURB TOP OF GRATE EXISTING SPOT ELEVATION PROPOSED SPOT ELEVATION EXISTING FLOWLINE PROPOSED FLOWLINE EXISTING CONTOUR PROPOSED CONTOUR EXISTING DIRECTION OF FLOW PROPOSED DIRECTION OF FLOW RIGHT OF WAY LINE PUBLIC EASEMENT LINE PROPOSED STORM DRAIN PROPOSED STORM DRAIN PROPOSED STORM INLET PROPOSED STORM DRAIN MANHOLE EXISTING STORM DRAIN MANHOLE EXISTING FIRE HYDRANT PROPOSED FIRE HYDRANT FIRE DEPARTMENT CONNECTION EXISTING SAS MANHOLE EXISTING VALVE BOX PROPOSED SAS MANHOLE EXISTING VALVE BOX PROPOSED VALVE BOX PROPOSED DOUBLE CLEANOUT PROPOSED DOUBLE CLEANOUT PROPOSED SINGLE CLEANOUT EXISTING SINGLE CLEANOUT EXISTING WATER SERVICE PROPOSED WATER SERVICE EXISTING WATER LINE PROPOSED WATER LINE PROPOSED SANITARY SEWER LINE EXISTING FIRE LINE PROPOSED FIRE LINE PROPOSED POST INDICATOR VALVE
FH FL FP	FIRE HYDRANT FLOWLINE FLAG POLE A CAS LINE BY DAINT MARK	*	SMALL DECIDUOUS TREE		PROPOSED CONCRETE
G/PN GA GLR GM GPR	GUY WIRE ANCHOR GAS LINE TO ROOF GAS METER GAS PRESSURE	WWW.W	CONIFEROUS TREE		PROPOSED ASPHALT PAVING
GRV GS	RELIEF VALVE GRAVEL GAS SERVICE		SMALL GROUP OF TREES		STABILIZED CRUSHER FINES
GT GTS	GATE GATE STOP POST	$\bigcirc$	SHRUB		
GVB HCP	GAS VALVE BOX HANDICAPPED PARKING SIGN	o Ġ	SMALL SHRUB HANDICAPPED PARKING SPACE		
HDPE HT	HIGH-DENSITY POLYETHYLENE HEATER IPPICATION CONTROL BOY		THE PROPERTY OF ACE		

INDEX OF DRAWINGS

DESCRIPTION

LEGEND AND INDEX OF DRAWINGS

CG-101 OVERALL GRADING (IF BID LOT 4 IS TAKEN)

CU-100 OVERALL WATER AND SANITARY SITE PLAN

CG-501 GRADING AND DRAINAGE SECTIONS AND DETAILS

CG-502 GRADING AND DRAINAGE SECTIONS AND DETAILS

CG-100 OVERALL GRADING PLAN - BASE BID

CP-501 PAVING SECTIONS AND DETAILS

CP-502 PAVING SECTIONS AND DETAILS

VICINITY MAP, DRAINAGE PLAN & CALCULATIONS,

WATER AND SANITARY SEWER SECTIONS AND DETAILS

CU-502 WATER AND SANITARY SEWER SECTIONS AND DETAILS

# VICINITY MAP ' SCALE: 1" = 750'

LEGAL DESCRIPTION TRACTS E AND F, LANDS OF THE BOARD OF EDUCATION. AZTEC ELEMENTARY SCHOOL, ALBUQUERQUE, NEW MEXICO

# BENCHMARKS

PROJECT BENCHMARK

AGRS 3 1/4" ALUMINUM DISC STAMPED "13-H21 1989", SET FLUSH IN THE TOP OF CURB, AT THE NORTH END OF A TRAFFIC ISLAND IN THE NORTHEAST QUADRANT OF THE INTERSECTION OF EUBANK BOULEVARD N.E. AND CLAREMONT AVENUE N.E. ELEVATION = 5499.574 FEET (NAVD 1988)

A MAG NAIL WITH WASHER SET IN ASPHALT AT THE NORTHEASTERN PORTION OF THE CAMPUS. AS SHOWN ON SHEETS CG-100 AND

ELEVATION = 5501.63 FEET (NAVD 1988)TEMPORARY BENCHMARK #2 (T.B.M.)

A MAG NAIL WITH WASHER SET IN ASPHALT AT THE NORTHWESTERN ELEVATION = 5489.20 FEET (NAVD 1988)

HIGH

101/2015 PHONE: 505.345.4250 FAX: 505.345.4254

Consulting Group

6010-B MIDWAY PARK BLVD. NE

ALBUQUERQUE, NEW MEXICO 87109

2014.037.1

PO Box 10921 ALBUQUERQUE, NEW MEXICO 87184-0921

#### CONSULTANTS

CIVIL: HIGH MESA CONSULTING GROUP 6010-B MIDWAY PARK BLVD. NE Albuquerque, NM 87109

Phone: (505)345-4250 Fax (505) 345-4254 STRUCTURAL: Chavez-Grieves Consulting Engineers, Inc. 4700 Lincoln Road NE. Suite 102

Albuquerque, NM 87109 O: 505-344-4080 C: 505-259-7486 MECHANICAL/PLUMBING/ELECTRICAL

 $\overline{\phantom{a}}$ 

 $\infty$ 

T & D Services 6001 Indian School Rd. NE Albuquerque, NM 87110 - 4183

(505) 314-7508 Direct

(505) 314-7500 Office

(505) 314-7501 FAX

DATE 08-16-2012

TEMPORARY BENCHMARK #1 (T.B.M.)

PORTION OF THE CAMPUS, AS SHOWN ON SHEETS CG-100 AND CU-100

# exic O $\overline{A}$ 0 Ω

N DRAWING SUBMITTAL 9/04/14 50% CONSTRUCTION DOCUMENT REVIEW

PROJECT NO: 2014.037.1 CAD DWG FILE: DRAWN BY: CHK'D BY: COPYRIGHT: WESTWORK ARCHITECTS 2015 SHEET TITLE **DRAINAGE PLAN** 

04 4/15/15 100% C.O.A. PERMIT DOCUMENTS

<u>I</u> 5/1/15 ADDENDUM I

7/15 95% CONSTRUCTION DOCUMENT REVIEW

**CALCULATIONS** 

C-001







