

City of Albuquerque

P.O. BOX 1293 ALBUQUERQUE, NEW MEXICO 87103

March 20, 1990

Jeff Mortensen, P.E. Jeff Mortensen & Associates, Inc. 811 Dallas, NE Albuquerque, New Mexico 87110

RE: DRAINAGE PLAN FOR AN ADDITION TO C.E.C. BUILDING TRADES (J-15/D1A) ENGINEER'S STAMP DATED MARCH 9, 1990

Dear Mr. Mortensen:

Based on the information provided on your submittal of March 12, 1990, the above referenced plan is approved for Building Permit.

Please attach a copy of this plan to the construction sets prior to sign-off by Hydrology.

If I can be of further assistance, please feel free to call me at 768-2650.

Cordially,


Fred J. Aguirre, P.E

Hydrologist

BJM:FJA/bsj (WP+1730)

DRAINAGE INFORMATION SHEET

PROJECT TITLE: C.E.C. BULDING TRADES ZONE	E ATLAS/DRNG. FILE # T-15/Dla
LEGAL DESCRIPTION: A PORTION OF ALBURUERO	EUF HIGH STUDY SITE
CITY ADDRESS: 800 ODELIA RD.	N.E.
ENGINEERING FIRM: JEFF MORTENSEN & ASSOC	
"ADDRESS: 811 DALLAS N.E.	PHONE: 265-5611
OWNER: ALBUQUERQUE PUBLIC SCHOOLS	CONTACT: MYRON JOHNSON
ADDRESS: 915 OAK ST. S.E.	PHONE: 242-5865
ARCHITECT: MARK HARBERTS ARCHITECT	CONTACT: MARK HARBERTS
ADDRESS: 2001 CARLISLE N.E.	PHONE: _268-1234
SURVEYOR: JEFF MORTENSENY ASSOC.	CONTACT: LEONARD P. UTTER
ADDRESS: 811 DALLAS N.E.	PHONE: 265-5611
	CONTACT: OWNER
ADDRESS:	PHONE:
PRE-DESIGN MEETING:	
YES DRB	ND
ND .	NO
COPY OF CONFERENCE RECAP PRO	J. NO.
SHEET PROVIDED	
TYPE OF SUBMITTAL: CHECK	TYPE OF APPROVAL SOUGHT:
DRAINAGE PERAPT	KETCH PLAT APPROVAL
I DROTNOGE DLON	RELIMINARY PLAT APPROVAL
CONCEPTUAL GRADING & DRAINAGE PLAN SITE DEVELOPMENT PLAN APPROVAL	
GRODING DLON	INAL PLAT APPROVAL
EDUCTON CONTROL OF DA	
ENGINEEDIC CERTIFICATION	UILDING PERMIT APPROVAL
	OUNDATION PERMIT APPROVAL
11 1 L (5) L 1 W 12 (1)	ERTIFICATE OF OCCUPANCY APPROVAL
20 Marie 1 Mar	OUGH GRADING PERMIT APPROVAL
	RADING/PAVING PERMIT APPROVAL
HYDROLOGY DIVISION	THER(SPECIFY)
DATE SUBMITTED: 03-09-90	
By: P. 14H	•



EXIST. BUILDINGS TO BE REMOVED BY APS PRIOR TO OCCUPANCY OF NEW BUILDING

INSTALL RAIN GUTTER

UNPLATTED

GUTTER ROOF RUNOFE -TO FRONT OF BUILDING W/ DOWNSHOUT BOWN TO CONCRETE

JEFF MORTENSEN & ASSOCIATES, INC.

811 DALLAS, N.E. DALBUQUERQUE, NM 87110

□ ENGINEERS □ TELEPHONE (505) 265-5611 □

BLOCKWALL

EXPST 4 SIDEWALK

SCALE : 1" = 800

LEGAL DESCRIPTION A PORTION OF ALBUQUERQUE

AS SHOWN BELOW.

N.M.S.H.C. STATION I-25-25, A STANDARD

GET IN TOP OF A CONC. POST FLUGH WITH

LOM AS BLVD. @ THE I-25 OVER PAGE, APPROX.

100' UP THE OVERPASS EMBANKMENT, AT THE

TEMPORARY BENCHMARK

ELEVATION = 5022.00 FEET (M.S.L.D.)

T.BM. = FINISHED FLOOR OF EXISTING BLOG

EXISTING

PORT. BLOG. F.F.=5024.23

ELEVATION = 5068.41 FEET (M.S.L.O.)

THE GROUND. STATION IS LOCATED NORTH OF

NMSHC BRAGG TABLET STAMPED "STA I-25-25"

LEGEND +23.3 EXISTING SPOT ELEVATION ____ EXIST. SUALE / FLOUILINE

TC/FL TOP OF CURB / FLOWLINE TC/TA TOP OF CURB / TOP OF ASPHALT

TOP OF SLOPE TOE OF SLOPE

PROPOSED CONCRETE ♦19.00 PROPOSED SPOT ELEVATION

--- PROPOSED CONTOUR

+ CONSTRUCT INVERT

- NEW DRIVERAD

FL 18.04± DIRT AREA

EXIST, 570.

CURB & GUTTER TO 15.12.

FL 14.46

FL 18.77±

CONSTRUCTION NOTES:

1. TWO (2) WORKING DAYS PRIOR TO ANY EXCAVATION, CONTRACTOR MUST CONTACT LINE LOCATING SERVICE 765-1234, FOR LOCATION OF EXISTING UTILITIES.

2. PRIOR TO CONSTRUCTION, THE CONTRACTOR SHALL EXCAVATE AND VERIFY THE HORIZONTAL AND VERTICAL LOCATION OF ALL POTENTIAL OBSTRUCTIONS. SHOULD A CONFLICT EXIST, THE CONTRACTOR SHALL NOTIFY THE ENGINEER IN WRITING SO THAT THE CONFLICT CAN BE RESOLVED WITH A MINIMUM AMOUNT OF DELAY.

3. ALL WORK ON THIS PROJECT SHALL BE PERFORMED IN ACCORDANCE WITH APPLICABLE FEDERAL, STATE AND LOCAL LAWS, RULES AND REGULATIONS CONCERNING CONSTRUCTION SAFETY AND HEALTH.

4. ALL CONSTRUCTION WITHIN PUBLIC RIGHT-OF-WAY SHALL BE PERFORMED IN ACCORDANCE WITH APPLICABLE CITY OF ALBUQUERQUE STANDARDS AND PROCEDURES.

5. IF ANY UTILITY LINES, PIPELINES, OR UNDERGROUND UTILITY LINES ARE SHOWN ON THESE DRAWINGS, THEY ARE SHOWN IN AN APPROXIMATE MANNER ONLY, AND SUCH LINES MAY EXIST WHERE NONE ARE SHOWN. IF ANY SUCH EXISTING LINES ARE SHOWN, THE LOCATION IS BASED UPON INFORMATION PROVIDED BY THE OWNER OF SAID UTILITY, AND THE INFORMATION MAY BE INCOMPLETE, OR MAY BE OBSOLETE BY THE TIME CONSTRUCTION COMMENCES. THE ENGINEER HAS CONDUCTED ONLY PRELIMINARY INVESTIGATION OF THE LOCATION, DEPTH, SIZE, OR TYPE OF EXISTING UTILITY LINES, PIPELINES, OR UNDERGROUND UTILITY LINES. THIS INVESTIGATION IS NOT CONCLUSIVE, AND MAY NOT BE COMPLETE, THEREFORE, MAKES NO REPRESENTATION PERTAINING THERETO, AND ASSUMES NO RESPONSIBILITY OR LIABILITY THEREFOR. THE CONTRACTOR SHALL INFORM ITSELF OF THE LOCATION OF ANY UTILITY LINE, PIPELINE, OR UNDERGROUND UTILITY LINE IN OR NEAR THE AREA OF THE WORK IN ADVANCE OF AND DURING EXCAVATION WORK. THE CONTRACTOR IS FULLY RESPONSIBLE FOR ANY AND ALL DAMAGE CAUSED BY ITS FAILURE TO LOCATE, IDENTIFY AND PRESERVE ANY AND ALL EXISTING UTILITIES, PIPELINES. AND UNDERGROUND UTILITY LINES. IN PLANNING AND CONDUCTING EXCAVATION. THE CONTRACTOR SHALL COMPLY WITH STATE STATUTES, MUNICIPAL AND LOCAL ORDINANCES, RULES AND REGULATIONS, IF ANY, PERTAINING TO THE LOCATION OF THESE LINES AND FACILITIES.

6. THE DESIGN OF PLANTERS AND LANDSCAPED AREAS IS NOT PART OF THIS PLAN. ALL PLANTERS AND LANDSCAPED AREAS ADJACENT TO THE BUILDING(S) SHALL BE PROVIDED WITH POSITIVE DRAINAGE TO AVOID ANY PONDING ADJACENT TO THE STRUCTURE. FOR CONSTRUCTION DETAILS, REFER TO LANDSCAPING PLAN.

TC24.03 TC25.29
FC24.61

ROAD

EROSION CONTROL MEASURES

1. THE CONTRACTOR SHALL ENSURE THAT NO SOIL ERODES FROM THE SITE INTO PUBLIC RIGHT-OF-WAY OR ONTO PRIVATE PROPERTY. THIS CAN BE ACHIEVED BY CONSTRUCTING TEMPORARY BERMS AT THE PROPERTY LINES AND WETTING THE SOIL TO KEEP IT FROM BLOWING.

THE CONTRACTOR SHALL PROMPTLY CLEAN UP ANY MATERIAL EXCAVATED WITHIN THE PUBLIC RIGHT-OF-WAY SO THAT THE EXCAVATED MATERIAL IS NOT SUSCEPTIBLE TO BEING WASHED DOWN THE STREET.

3. THE CONTRACTOR SHALL SECURE "TOPSOIL DISTURBANCE PERMIT" PRIOR TO BEGINNING CONSTRUCTION.

4 == == == n

·======

EXIST. ASPHALT

PLANTER, TYP.

CURB CONC

7c 30.50

N.E.

7A 30.00 TE 31.20

7C 32.00 TA31.42

TA 32.45

DRAINAGE PLAN

The following items concerning the C.E.C. Building Trades Grading and Drainage Plan are contained hereon:

> 1. Vicinity Map 2. Grading Plan

3. Calculations

As shown by the Vicinity Map, the site is located on the north side of Mountain Road N.E. between Stone Street N.E. and Interstate 25. At present, the site is developed. Much of the surrounding area is currently developed, making this a modification to an existing site within an infill area. As shown by Panel 29 of the National Flood Insurance Program Flood Boundary and Floodway Maps for the City of Albuquerque, New Mexico, this site does not lie within a designated flood hazard zone. Downstream flooding is not shown and therefore does not appear to be a problem. At present, the majority of runoff generated by the site flows from northwest to southeast onto the paved private drive. From that point, runoff flows south to Mountain Road N.E. Mountain Road N.E. drains to the west and contains a public storm drain facility which discharges to the Broadway Pump Station. This represents the outfall for this site. No offsite flows affect this project because it is located at the extreme west side of the already developed school site. The land to the west and south are topographically lower, hence do not contribute any runoff to this project.

The Grading Plan shows 1) existing grades indicated by spot elevations, 2) proposed grades indicated by spot elevations and contours at 1'0" intervals, 3) the limit and character of the existing improvements, 4) the limit and character of the proposed improvements, and 5) continuity between existing and proposed grades. As shown by this plan, the proposed improvements consist of the removal of two existing buildings and paving and the construction of a new building along with adjacent paving. Runoff generated by the proposed improvements will be routed from west to east onto the private drive. From that point, runoff will flow south to Mountain Road N.E. From that point, runoff will flow west to Broadway Boulevard N.E. as discussed above. Based upon the fact that this site is currently developed, the project is relatively small in size, and a decrease in runoff generated by the proposed improvements, the free discharge of runoff from this site is appropriate.

The Calculations which appear hereon analyze both the existing and developed conditions for the 100-year, 6-hour rainfall event. The Rational Method has been used to quantify the peak rate of discharge and the SCS Method has been used to quantify the volume of runoff. Both Methods have been used in accordance with the City of Albuquerque Development Process Manual, Volume II, and the Mayor's Emergency Rule adopted January 14, 1986. As shown by these calculations, the proposed improvements will decrease the peak discharge by approximately 0.1 cfs.

CALCULATIONS

Dirt area)

Ground Cover Information

From SCS Bernalillo County Soil Survey, Plate 31: BkD - Bluepoint - Kokan association, Cu - Cut and fill land Hydrologic Soil Group: A Existing Pervious CN = 72 (DPM Plate 22.2 C-2 Dirt area) Developed Pervious CN = 72 (DPM Plate 22.2 C-2

Time of Concentration/Time to Peak

 $T_C = 0.0078 L^{0.77}/S^{0.385}$ (Kirpich Equation)

 $T_D = T_C = 10 \text{ min.}$

Point Rainfall $P_6 = 2.22$ in. (DPM Plate 22.2 D-1)

Rational Method

Discharge: Q = CiA

where C varies

 $i = P_6$ (6.84) T_C $^{-0.51} = 4.69$ in/hr $P_6 = 2.22$ in (DPM Plate 22.2D-1) $T_C = 10 \text{ min (minimum)}$ A = area, acres

SCS Method

Volume: V = 3630(DRO) A

Where DRO = Direct runoff in inches

A = area, acres

Existing Condition

 $A_{total} = 17,100 \text{ sf} = 0.39 \text{ Ac}$ Roof area = 2,160 sf (0.13)Paved area = 3,480 sf (0.20)Dirt area = 11,460 sf (0.67)C = 0.58 (Weighted average per Emergency Rule, 1/14/86) $Q_{100} = CiA = 0.58(4.69)(0.39) = 1.1 cfs$


 $A_{imp} = 5,640 \text{ sf}$; % impervious = 33 % Composite CN = 81 (DPM Plate 22.2 C-2) DRO = 0.8 in (DPM Plate 22.2 C-4) $V_{100} = 3630 (DRO)A = 1,133 cf$

Developed Condition

 $A_{total} = 17,100 \text{ sf} = 0.39 \text{ Ac}$ Roof area = 2,800 sf (0.16)Paved area = 1,750 sf (0.10) Dirt area = 12,550 sf (0.73)C = 0.54 (Weighted average per Emergency Rule, 1/14/86) $Q_{100} = CiA = 0.54(4.69)(0.39) = 1.0 cfs$ Aimp = 4,550 sf; % impervious = 26 % Composite CN = 79 (DPM Plate 22.2 C-2) DRO = 0.65 in (DPM Plate 22.2 C-4) $V_{100} = 3630 (DRO)A = 920 cf$

Comparison

 $\triangle Q_{100} = 1.1 - 1.0 = 0.1$ (decrease) $\Delta V_{100} = 1,133 - 920 = 213$ cf (decrease)



GRADING AND DRAINAGE PLAN

C. E. C. BUILDING TRADES

76.24.83 FC 24.77

EL 24.10 FE 24.22 PC 24.48

EXISTING BUILDING

CONC. SIDEMALK

F.F. = 5026.00

- EXIST. GRADES IN THIS AREA SUBJECT TO CHANGE (DATE OF SURVEY 1984)

CAREER

CENTER

ENRICHMENT

. OXIST. ABPHALT - # 26.10

MOUNTAIN

REVISIONS NO. DATE BY 41663 DESIGNED BY L.P.U. 2 - 1990 DRAWN BY _____. M. A. APPROVED BY J.G.M.