

INFORMATION SHEET

PROJECT TITLE Brownstone Project TYPE OF SUBMITTAL Pre-Prelim.
 ZONE ATLAS PAGE NO. 1-15-00 CITY ADDRESS _____
 LEGAL DESCRIPTION 5.774 Acres in NE 1/4 of NE 1/4 Sec. 16 T. 10N., R. 3E.
 ENGINEERING FIRM William Matetan & Assoc. CONTACT Red Referson
 ADDRESS 230 Truman St. NE, Alb. N.M. PHONE 265-8467
 OWNER Brownstone Group CONTACT Richard Rushing
 ADDRESS 3130 Southwest Freeway PHONE 713-520-7272
Suite 204, Houston, Texas
 ARCHITECT _____ CONTACT Richard Rushing
 ADDRESS _____ PHONE _____
 SURVEYOR William Matetan & Assoc. CONTACT Red Referson
 ADDRESS _____ PHONE _____
 CONTRACTOR _____ CONTACT _____
 ADDRESS _____ PHONE _____

DATE SUBMITTED 23 Sept. 1983
 BY William Matetan & Associates, Inc.

Use this Information Sheet when submitting the following:

Drainage report or plan, conceptual grading and drainage plan, engineer's certification plan, erosion plan and grading plan. Provide the information applicable to your submittal.

INFORMATION SHEET

PROJECT TITLE CASA SANDIA APARTMENTS TYPE OF SUBMITTAL Drainage Report
 ZONE ATLAS PAGE NO. J-15 CITY ADDRESS 1642 Indian School Road, N. E.
 LEGAL DESCRIPTION Brownstone Tract in the NE 1/4, NE 1/4, Sec. 16, T. 10N., R. 3E., N.M.P.M.
 ENGINEERING FIRM William Matotan & Assoc., Inc. CONTACT William I. Matotan
 ADDRESS 230 Truman St., N.E., Alb., N.M. 87108 PHONE (505) 265-8467
 OWNER Brownstone Group CONTACT Gale Hunsinger
 ADDRESS 230 Truman St., N.E., Alb., N.M. 87108 PHONE (505) 266-7955
 ARCHITECT Miguel Trujillo & Assoc. CONTACT Miguel Trujillo
 ADDRESS 8210 La Mirada Rd., N.E., Alb. N.M. 87109 PHONE (505) 298-7543
 SURVEYOR William Matotan & Assoc., Inc. CONTACT William I. Matotan
 ADDRESS 230 Truman St., N.E., Alb., N.M. 87108 PHONE (505) 265-8467
 CONTRACTOR _____ CONTACT _____
 ADDRESS _____ PHONE _____

PRE-DESIGN MEETING:

☒ YES
☐ NO
☒ COPY OF CONFERENCE RECAP SHEET PROVIDED

PLEASE CHECK TYPE OF APPROVAL EXPECTED WITH THIS SUBMITTAL:

☐ SKETCH PLAT APPROVAL
☐ PRELIMINARY PLAT APPROVAL
☐ SITE DEVELOPMENT PLAN APPROVAL
☐ FINAL PLAT APPROVAL
☒ BUILDING PERMIT APPROVAL
☐ CERTIFICATE OF OCCUPANCY APPROVAL
☐ ROUGH GRADING PERMIT APPROVAL
☐ GRADING/PAVING PERMIT APPROVAL
☒ OTHER DRAINAGE REPORT (SPECIFY)

DATE SUBMITTED: March 30, 1984

BY: WILLIAM MATOTAN & ASSOCIATES, INC.





CITY OF ALBUQUERQUE
MUNICIPAL DEVELOPMENT DEPARTMENT
ENGINEERING DIVISION



HYDROLOGY SECTION PROJ. NO. 15 DATE: 9/23/83
PLANNING DIVISION NO. _____


CONFERENCE RECAP

SUBJECT: Brown stone Apts (224 units) located South
of Indian School West of North Division Channel

| WHO | REPRESENTING |
|-----------------------------------|-----------------------------|
| ATTENDANCE: <u>John Armstrong</u> | <u>City</u> |
| <u>Red Peterson</u> | <u>Metotax & Assoc.</u> |
| _____ | _____ |
| _____ | _____ |
| _____ | _____ |
| _____ | _____ |

FINDINGS:

- (1) Drainage Report Appropriate
- (2) Free discharge directly to storm drain if it
can be shown that system is adequate in
- (3) Summary Plot to eliminate lots.



The undersigned agrees that the above findings are summarized accurately and are only subject to change if further investigation reveals that they are not reasonable or that they are based on inaccurate information.

| | |
|----------------------------|------------------------------------|
| SIGNED: <u>[Signature]</u> | SIGNED: <u>Raymond E. Peterson</u> |
| TITLE: <u>CE/Hydrology</u> | TITLE: <u>Vice President</u> |
| DATE: <u>9/23/83</u> | DATE: <u>9/23/83</u> |



City of Albuquerque

P.O. BOX 1293 ALBUQUERQUE, NEW MEXICO 87103

DESIGN HYDROLOGY SECTION
123 Central NW, Albuquerque, NM 87102
(505) 766-7644

April 10, 1984

Mr. William I. Matotan
230 Truman Street NE
Albuquerque, NM 87108

REF: CASA SANDIA APARTMENTS DRAINAGE REPORT (J15-D17)

Dear Mr. Matotan:

These are my comments on the above mentioned report as received 4/2/84:

1. Free discharge from the site has not been justified:

- a) Water leaving the site will not be picked up by inlet #3 (capacity 3.5 cfs per report) and will cross University Boulevard.
 - i) Pre-design conference recap did not allow flows to be discharged into street. Discharge directly to storm drain only was allowed, but only if the system downstream was adequate.
- b) The report shows that the existing storm drain is not capable of conveying the existing flows, with the Casa Sandia Apartments site developed, let alone the fully developed watershed.
 - i) Hydrograph analysis, with developed watershed, may justify free discharge but only if discharge from Casa Sandia can be shown to "beat the peak" and will not increase overland flow at the sag curve in Indian School.
 - ii) The report does not mention an easement for overland flow at the sag curve. If there is an existing easement and the existing improvements in the easement are capable of conveying the excess flows from

MUNICIPAL DEVELOPMENT DEPARTMENT

C. D. Lynne Shappard, P.E., City Engineer

ENGINEERING DIVISION

Telephone (505) 766-7457

AN EQUAL OPPORTUNITY EMPLOYER


Mr. William I. Matotan
April 10, 1984
Page -2-

the fully developed watershed, without encroachment or damage to private property, then free discharge can be justified.

- c) In general, it appears that justification for free discharge will be difficult or impossible to show, due to conditions downstream, and in lieu of that, ponding with controlled discharge will be required.

If you have any questions on the above, please feel free to call me at 766-7644.

Thank you,



John Armstrong
Civil Engineer/Hydrology

JA:mrk

cc: Brownstone Group

Mr. William I. Matotan

April 10, 1984

Page -2-

the fully developed watershed, without encroachment or damage to private property, then free discharge can be justified.

- c) In general, it appears that justification for free discharge will be difficult or impossible to show, due to conditions downstream, and in lieu of that, ponding with controlled discharge will be required.

If you have any questions on the above, please feel free to call me at 766-7644.

Thank you,



John Armstrong
Civil Engineer/Hydrology

JA:mrk

cc: Brownstone Group

**WILLIAM MATOTAN & ASSOCIATES
ENGINEERS**

230 Truman Street, N.E. Albuquerque, N.M. 87108

RODNEY E. PETERSON
Vice President

(505) 265-8467



Prelim.

**WILLIAM MATOTAN & ASSOCIATES, INC.
ENGINEERS**
230 Truman Street, N.E. - Albuquerque, N.M. 87108
Telephone 265-8467

Project Brawstone Act 3 Sheet 1 of 2
Subject: Drainage Study Job No. 720
Comp. by REP Date 12/1/83 Chk'd _____ Date _____

I. EXISTING CONDITIONS (Underdeveloped)

A. Existing Runoff Volumes (5.388 Acres)

$$V_{100} = 0.3 \times \frac{2.2}{12} \times 5.388 \times 47,560 = 12,910 \text{ cu.ft.}$$

$$V_{10} = 0.3 \times \frac{0.98}{12} \times 5.388 \times 47,560 = 5,750 \text{ Cu.ft.}$$

(Where $V = CRA$, V in cubic feet,
 C = Coefficient of Imperviousness
 R = 6 hour rainfall depth in feet)

B. Existing Discharge Conditions (5.388 Acres)

$$\text{Rainfall intensity } I = (6 \text{ hr rain}) 6.84 C_c^{-0.51}$$

$$I_{100} = 2.2 \times 6.84 \times 10^{-0.51} = 4.65 \text{ "}$$

$$I_{10} = 4.65 \times .657 = 3.06 \text{ "}$$

$$Q_{100} = 0.3 \times 4.65 \times 5.388 = 7.51 \text{ cfs}$$

$$Q_{10} = 0.3 \times 3.06 \times 5.388 = 4.95 \text{ cfs}$$

(Where $Q = CIA$, Q in cubic feet per second

C = Coefficient of Imperviousness

I = Rainfall intensity

A = Area in Acres)

**WILLIAM MATOTAN & ASSOCIATES
ENGINEERS**

230 Truman Street, N.E. Albuquerque, N.M. 87108

RODNEY E. PETERSON
Vice President

(505) 265-8467



Prelim

| | | |
|--|--------------------------------|---|
| WILLIAM MATOTAN & ASSOCIATES, INC. ENGINEERS 230 Truman Street, N.E. - Albuquerque, N.M. 87108 Telephone 265-8467 | Project <u>Brownstone Hts.</u> | Sheet <u>2</u> of <u>2</u> |
| | Subject: <u>Drainage study</u> | Job No. <u>720</u> |
| | Comp. by <u>REP</u> | Date <u>12/24/83</u> Chk'd _____ Date _____ |
| | | |

II. DEVELOPED CONDITIONS

A. Developed Runoff Volumes (5.388 Acres)

$$V_{100} = 0.8 \times \frac{2.2}{12} \times 5.388 \times 43,560 = 34,423 \text{ cu.ft.}$$

$$V_{10} = 0.8 \times \frac{0.98}{12} \times 5.388 \times 43,560 = 15,334 \text{ cu.ft.}$$

B. Developed Discharge Conditions

$$I_{100} = 4.65 \quad I_{10} = 3.06 \quad (\text{See sheet 1})$$

$$Q_{100} = 0.8 \times 4.65 \times 5.388 = 20.0 \text{ cfs}$$

$$Q_{10} = 0.8 \times 3.06 \times 5.388 = 13.19 \text{ cfs}$$

III INCREASED DEVELOPED FLOW CONDITIONS

$$V_{100} \text{ Developed} = 34,423 \text{ cu.ft.} \quad V_{10} \text{ Devel.} = 15,334 \text{ cu.ft.}$$

$$V_{100} \text{ Undeveloped} = 12,910 \text{ cu.ft.} \quad V_{10} \text{ Undeveloped} = 5,750 \text{ cu.ft.}$$

$$\text{Diff.} = 21,513 \text{ cu.ft.} \quad \text{Diff.} = 9,584 \text{ cu.ft.}$$

$$Q_{100} \text{ Devel.} = 20.0 \text{ cfs}$$

$$Q_{100} \text{ Undeveloped} = 7.5$$

$$\text{Diff.} = 12.5 \text{ cfs}$$

$$Q_{10} \text{ Devel.} = 13.2 \text{ cfs}$$

$$Q_{10} \text{ Undeveloped} = 5.0$$

$$\text{Diff.} = 8.2 \text{ cfs}$$

**WILLIAM MATOTAN & ASSOCIATES
ENGINEERS**

230 Truman Street, N.E. Albuquerque, N.M. 87108

RODNEY E. PETERSON
Vice President

(505) 265-8467



482

6-HOUR RAINFALL VOLUMES-100 YEAR FREQUENCY

Use 2.2 for all locations
west of 2.2 line



Note: to obtain 2,5,10, and 50
year values, multiply the 100
year amount by the following
factors:

| Year | 2 | 5 | 10 | 50 |
|--------|------|------|------|------|
| Factor | .445 | .541 | .657 | .920 |

Source: 1973 NOAA Atlas 2, Volume IV

PLATE 22.2 D-1

22.2

STORM RUNOFF FROM PROJECT SITE

Pages A-1 thru A-9

Added 2a, April 29, 84

WILLIAM MATOTAN & ASSOCIATES, INC.
ENGINEERS
230 Truman Street, N.E. - Albuquerque, N.M. 87108
Telephone 265-8467

Project Brownstone Casa Sandia Sheet 1 of 1
Q10 & Q100 VOLUME H, I, J. Job No. 720
By S. A. H. Chkd ✓ Date 25 Apr. 84

D. A. - "H" Indian School R.O.W. (NW Prop. cor to NW Driveway)

$$\begin{aligned}C &= 0.25 \\I &= 3.05 \\A &= 0.1901 \\Q_{10} &= 0.14 \text{ cfs}\end{aligned}$$

$$\begin{aligned}C &= 0.25 \\I &= 4.65 \\A &= 0.1901 \\Q_{100} &= 0.22 \text{ cfs}\end{aligned}$$

D. A. - "I" Indian School R.O.W. (NW Driveway to SW Driveway)

$$\begin{aligned}C &= 0.25 \\I &= 3.05 \\A &= 0.2420 \\Q_{10} &= 0.18 \text{ cfs}\end{aligned}$$

$$\begin{aligned}C &= 0.25 \\I &= 4.65 \\A &= 0.2420 \\Q_{100} &= 0.28 \text{ cfs}\end{aligned}$$

D. A. - "J" Indian School R.O.W. (SW Driveway to SW Prop. line)

$$\begin{aligned}C &= 0.25 \\I &= 3.05 \\A &= 0.2010 \\Q_{10} &= 0.15 \text{ cfs}\end{aligned}$$

$$\begin{aligned}C &= 0.25 \\I &= 4.65 \\A &= 0.2010 \\Q_{100} &= 0.23 \text{ cfs}\end{aligned}$$

Note: Areas "H", "I" & "J" to be sodded & landscaped.

STORM RUNOFF CONTRIBUTING
TO
EXISTING STORM SEWER SYSTEM NO. 129

Pages A-10 thru A-13

Revised 29 April 84

WILLIAM MATOTAN & ASSOCIATES, INC.
ENGINEERS
230 Truman Street, N.E. - Albuquerque, N.M. 87108
Telephone 265-8467

Project CASA SANDIA APTS. Sheet 1 of 4
Drainage Study Job No. 720
By REP Chk'd ✓ Date 12 Mar. 84

SUMMARY OF STORM RUNOFF CONTRIBUTING TO
EXISTING STORM SEWER SYSTEM NO. 129

Drainage
Area

Developed Conditions

| | <u>Q₁₀</u> | <u>Q₁₀₀</u> |
|------------------|-----------------------|------------------------|
| #1 | 27 | 41 |
| #2 | 60 | 91 |
| #3 | 14 | 22 |
| #4 | 8 | 12 |
| TOTALS* (cfs) | <u>109</u> | <u>166</u> |

* Rounded to 1 cfs unit.

For developed conditions: Revised 29 Apr. 84

A-10

WILLIAM MATOTAN & ASSOCIATES, INC.
ENGINEERS
230 Truman Street, N.E. - Albuquerque, N.M. 87108
Telephone 265-8457

Project CASA SANDIA APTS. Sheet 2 of 4
Subject: Drainage Study Job No. 720
Comp. by REP Date 12 Mar. 84 Chk'd ✓ Date 12 Mar.

*Existing Storm Sewer System in Project Vicinity
Contributing Drainage Areas and Composite "C" Factors*

| <u>Drainage Area</u> | <u>Area in Acres</u> (By Planimeter 1" = 200' Topo Map) | <u>Composite "C" Factor</u> (100% developed) |
|--------------------------|---|---|
| #1 | 13.61 | 0.65 |
| #2 | 32.78 | 0.60 |
| #3 | 7.80 | 0.60 |
| #4 | 3.21 | 0.82 |
| Total Area = 57.40 Acres | | |

For developed conditions: Revised 29 Apr. 84

A-11

WILLIAM MATOTAN & ASSOCIATES, INC.
ENGINEERS
230 Truman Street, N.E. - Albuquerque, N.M. 87108
Telephone 265-8467

Project CASA SANDRA AL 3. Sheet 3 of 4
Subject: Drainage Study Job No. 720
Comp. by RED Date 12 Mar 84 Chk'd ✓ Date 12 Mar.

Existing Storm Sewer System

Time of Concentration of Contributing Drainage Areas, where $T_c = (0.0078) \left(\frac{L^{0.77}}{S^{0.385}} \right)$

D.A. #1, $L = 1100'$ $S = \frac{5116 - 5076}{1100} = 0.0364'/ft.$

$T_c = (0.0078) \left(\frac{1100^{0.77}}{0.0364^{0.385}} \right) = 6.1 \text{ Min.}$

D.A. #2, $L = 2100'$ $S = \frac{5130 - 5074}{2100} = 0.0267'/ft.$

$T_c = (0.0078) \left(\frac{2100^{0.77}}{0.0267^{0.385}} \right) = 10.09 \text{ Min.}$

D.A. #3, $L = 950'$ $S = \frac{5104 - 5067}{950} = 0.0389'/ft.$

$T_c = (0.0078) \left(\frac{950^{0.77}}{0.0389^{0.385}} \right) = 5.3 \text{ Min.}$

D.A. #4, $L = 700'$ $S = \frac{5069 - 5063}{700} = 0.0086'/ft.$

$T_c = (0.0078) \left(\frac{700^{0.77}}{0.0086^{0.385}} \right) = 7.5 \text{ Min.}$

Note: T_c of 10 minutes used for computing
Rainfall intensity "I", all drainage areas.
Calculated T_c 's used to compare
inflow hydrographs to storm sewer system.

Revised 28 Apr. 84

A-12

WILLIAM MATOTAN & ASSOCIATES, INC.
ENGINEERS
230 Truman Street, N.E. - Albuquerque, N.M. 87108
Telephone 265-8467

Project CASA SANDIA APTS. Sheet 4 of 4
Subject: Drainage Study Job No. 720
Comp. by REP Date 12 Mar. 84 Chk'd ✓ Date 12 Mar.

PEAK RUN OFF for Drainage Areas Contributing to
Existing Storm Sewer System on
Indian School Road (System No. 129)

D.A. #1, Developed Condition

$$Q_{10} = (0.65)(3.05)(13.61) = 27 \text{ cfs}$$

$$Q_{100} = (0.65)(4.65)(13.61) = 41 \text{ cfs}$$

D.A. #2, Developed Condition

$$Q_{10} = (0.60)(3.05)(32.78) = 60 \text{ cfs}$$

$$Q_{100} = (0.60)(4.65)(32.78) = 91 \text{ cfs}$$

D.A. #3, Developed Condition

$$Q_{10} = (0.60)(3.05)(7.80) = 14 \text{ cfs}$$

$$Q_{100} = (0.60)(4.65)(7.80) = 22 \text{ cfs}$$

D.A. #4, Developed Condition

$$Q_{10} = (0.82)(3.05)(3.21) = 8 \text{ cfs}$$

$$Q_{100} = (0.82)(4.65)(3.21) = 12 \text{ cfs}$$

$$\text{Total Runoff } Q_{10} = 109 \text{ cfs}$$

$$\text{Total Runoff } Q_{100} = 166 \text{ cfs}$$


For developed conditions; Revised 28 Apr. 84

STREET FLOW CAPACITY

Pages A-31 thru A-34

Revised 28 Apr. 84

Street Capacity - Indian School Road 66' ft to ft
w/continuous left turn lane.
@ Critical cross section on West side of
Intersection, Indian School Rd. & University Blvd.,
immediately downstream from inlets #5 & #6
66' ft to ft



- Capacity with one lane dry, westbound, and 3 lanes dry Eastbound, max depth of flow 0.38' @ west curb.
 $Q = AV$ and $V = \frac{1.486}{0.015} R^{2/3} S^{1/2}$
 $A = 3.99$ wp = 21.4' $R = \frac{3.99}{21.4} = 0.1864$, $R^{2/3} = 0.3245$
 $S = 0.004$, $S^{1/2} = 0.0632$

$$V = \frac{1.486}{0.015} \times 0.3245 \times 0.0632 = 2.03 \text{ fps}$$

$$Q = 3.99 \times 2.03 = \underline{8.1 \text{ cfs}}$$

Runoff contributing to this street cross section
= Area #1 (see page A-13)

$$Q_{10} = 15 \text{ cfs} \quad Q_{100} = 23 \text{ cfs}$$

Capacity of inlets #3, 4, 5 and 6 immediately
upstream from this section = 48.5 cfs (see p. A-14)

Capacity of 30" RCP storm sewer @ above inlets
= 49 cfs (see p. A-29)

- Storm sewer capacity 49 cfs and inlet capacity 48.5 cfs > Q_{10} 15 cfs and Q_{100} = 23 cfs and street flow criteria not exceeded.

For Developed Condition: Revised 28 Apr. REP

WILLIAM MATOTAN & ASSOCIATES, INC.
ENGINEERS
230 Truman Street, N.E. - Albuquerque, N.M. 87108
Telephone 265-8467

Project CASA SANDIA APTS.
Drainage Study
By REP Chk'd ✓

Sheet of
Job No. 720
Date 23 Mar. 1984

Street Capacity - University Blvd. 66' # to #
w/ 22' raised median.

@ Critical cross section, approximately
300' south of intersection with Indian
School Road, sag vertical curve and
inlets #1 and #2; Drainage Area #2 outfall.

From page A-13, total runoff contributing
to this section: $Q_{10} = 60 \text{ cfs}$ $Q_{100} = 91 \text{ cfs}$

From page A-14, total inlet capacity = 53 cfs


From page A-29, storm sewer capacity = 36 cfs

\therefore @ Q_{10} , 24 cfs in excess of storm sewer
capacity flowing full, gravity flow.

and

@ Q_{100} , 55 cfs in excess of storm sewer
capacity flowing full, gravity flow.

@ Q_{100} , street overflow is to the west
via an asphalt paved, inverted crown,
driveway on the south side of office
building @ 1415 University Ave.,
to storm sewer inlets #7 and #8 at the
sag vertical curve on Indian School Road,
east side of I-25 overpass. (See Plate 4)



Capacity of driveway: $Q = AV$ $V = 1.486 \cdot R^{2/3} \cdot S^{1/2}$
 $A = 10.6$ $R = 0.8$ $R^{2/3} = 0.45$ $R^{2/3} = 0.58$
 $S = 0.015$ $S^{1/2} = 0.12$ $V = (99)(0.58)(0.12) = 6.9 \text{ fps}$

$Q = (10.8)(6.9) = 74 \text{ cfs} > Q_{100} 55 \text{ cfs overflow}$
OK

For Developed Condition: Revised 28 Apr. 84


A-32

For Developer's Conditions: Revised 28 Apr. 84

WILLIAM MATOTAN & ASSOCIATES, INC.
ENGINEERS
230 Truman Street, N.E. - Albuquerque, N.M. 87108
Telephone 265-8467

Project: CASA SANDIA APTS. Sheet _____ of _____
Subject: Drainage Study Job No. 720
Comp. by: REP Date 23 Mar. 84 Chk'd: _____ Date 23 Mar. 84

STREET FLOW DISCHARGE ON INDIAN SCHOOL RD. 600'± WEST OF UNIVERSITY BLVD.




From page A-13, Total runoff contributing to storm sewer system
at MH S-301, D.A. #1, 2, 3 and 4: $Q_{10} = 109 \text{ cfs}$ $Q_{90} = 166 \text{ cfs}$
From page A-29, capacity of 30" storm sewer downstream from
MH S-301 = 71 cfs (flowing full, gravity flow)
 $\therefore 71 \text{ cfs} < Q_{10}$ Peak flow by 38 cfs $\therefore Q_{10} 38 \text{ cfs}$ street flow
and $71 \text{ cfs} < Q_{90}$ Peak flow by 95 cfs $\therefore Q_{90} 95 \text{ cfs}$ street flow
All street flow within D.A. #1, 2, 3, 4, in excess of storm sewer
capacity, drains into this sag vertical curve and thence flows north
through the three curb cuts into the historic drainage way (old
Indian School Road paved roadway) thence westerly through
I-25 drainage structures into historic Campus Draw
drainage way on the west side of Interstate Route-25.
Note that gutter flowline on low side of street @ Inlet #7 is
0.7' higher than the gutter flowline at the low point of the sag.

WILLIAM MATOTAN & ASSOCIATES, INC.
ENGINEERS
230 Truman Street, N.E. - Albuquerque, N.M. 87108
Telephone 265-8467

Project CASA SANDIA APTS Sheet of
Drainage Study Job No. 720
By REP Chkd ✓ Date 23 Mar. 84

CAPACITY OF HISTORIC DRAINAGEWAY (old
Indian School Road paved roadway) North of Existing
Indian School Road @ East side of I-25.



Critical Cross Section
@
North Side of Lodge Bldg.
Not to Scale

$$Q = AV \quad V = \frac{1.486}{0.015} \cdot R^{2/3} S^{1/2}$$

$$A = \frac{(0.8)(60)}{2} = 24 \text{ ft}^2 \quad \text{wp} = 60' \quad R = \frac{24}{60} = 0.40 \quad R^{2/3} = 0.54$$

$$S = 0.0370/\text{ft.} \quad S^{1/2} = 0.1924 \quad V = (99)(0.54)(0.1924) = 10.3 \text{ fps}$$

$$Q = (24)(10.3) = 247 \text{ cfs} > Q_{100} 38 \text{ cfs and } Q_{100} 95 \text{ cfs}$$

Street flows from drainage areas #1, 2, 3 and 4, in excess of storm sewer capacity.

Note: This drainageway is the only outlet from the sag vertical curve on Indian School Road at the east side of the I-25 overpass and drains all street flows in Drainage Areas #1, 2, 3 and 4 that are in excess of the storm sewer capacity.

For Developed Conditions: Revised 28 Apr. 84

A-34


ON-SITE DRAINAGE STRUCTURE CAPACITIES

Pages A-35 thru A-39

Added 29 Apr. 84

WILLIAM MATOTAN & ASSOCIATES, INC.
ENGINEERS
230 Truman Street, N.E. - Albuquerque, N.M. 87108
Telephone 265-8467

Project Brownstone Casa Santa Apt. Sheet 2 of 2
Transition Cobble-Concrete Job No. 720
By S.A.M. Chkd ✓ Date 4-26-84






PLAN OF DRAINAGE SYSTEM
DOWNSTREAM FROM A.P. "A-B"
N.T.S.

A-35

WILLIAM MATOTAN & ASSOCIATES, INC.
ENGINEERS
230 Truman Street, N.E. - Albuquerque, N.M. 87108
Telephone 265-8467

Project *Brownstone Casa Sardia Apt* Sheet *1* of *2*
Transition Cobble - Concrete
By *S.A.M.* Chkd *✓* Job No. *720*
Date *4-25-84*



See sheet A-35
for Plan.

TYPICAL SECTIONS
of
DRAINAGE DITCH TRANSITIONS
N.T.S.

WILLIAM MATOTAN & ASSOCIATES, INC.
ENGINEERS
230 Truman Street, N.E. - Albuquerque, N.M. 87108
Telephone 265-8467

Project BRAHIM-TONE CASA SANJANA APT. Sheet 1 of 2
Capacity - Contribution Job No. 720
By S.A.H. Chkd ✓ Date Apr. 25 '84

A.P. "A"-B" Concrete rundown @
North driveway:

$\nabla 102.50$

$A = 1.00'$

$w/p = 3.00'$


$R = 0.3333 \text{ ft}^2 = 0.4790'$

$S_{A1} = 0.0140 \text{ ft}^2 = 0.1183'$

$f = 99.0667 (\alpha = 0.015)$

$V = 5.6137 \text{ ffs}$

$Q = 5.61 \text{ cfs (capacity)}$



100 yr. Volumes contributed to A.P. "A"-B"

D.A. "A" = 0.51 cfs

D.A. "B" = 3.79 cfs

Indian School ROW = 0.22 cfs

(4.52 cfs) contribution

✓ OK $Q_{100} < \text{Cap. of Rundown}$

A.P. "E"-F" Cobble concrete swale

$\nabla 93.83$

$A = 2.0833'$

$w/p = 5.2704'$


$R = 0.3953 \text{ ft}^2 = 0.5369'$

$S = 0.0286 \text{ ft}^2 = 0.1691'$

$f = 37.1500 (\alpha = 0.040)$

$V = 3.3731 \text{ ffs}$

$Q = 7.02 \text{ cfs (capacity)}$



100 yr Volumes contributed to A.P. "E"-F"

A.P. "A"-B" = 4.52 cfs

D.A. "F" = 0.43 cfs

D.A. "E" = 1.87 cfs

6.82 cfs (contribution)

✓ OK $Q_{100} < \text{Cap. of Swale}$

A.P. "C" Parking access

$\nabla 85.50 \text{ Bldg. 1}$

$A = 6.00'$

$w/p = 24.5052'$


$R = 0.2448 \text{ ft}^2 = 0.3895'$

$S_{A1} = 0.008 \text{ ft}^2 = 0.0694'$

$f = 99.0667 (\alpha = 0.015)$

$V = 3.4513 \text{ ffs}$

$Q = 20.7077 \text{ cfs (capacity)}$



100 yr Volumes contributed to A.P. "C"

A.P. "E"-F" = 6.82 cfs

Indian School ROW = 0.28 cfs

D.A. "C" = 9.44 cfs


16.54 cfs (contribution)

✓ OK $Q_{100} < \text{Cap. of Paved Section}$

A-37

WILLIAM MATOTAN & ASSOCIATES, INC.
ENGINEERS
230 Truman Street, N.E. - Albuquerque, N.M. 87108
Telephone 265-8467

Project Brownstone Casa Sardia Sheet 1 of 1
Parabolic Ditch Section Job No. 720
By S.A.M. C.M.D. ☒ Date 28 Apr. 87



TYPICAL SECTION
of

SODDED DRAINAGE SWALE

NTS

Note: Depths of flow will not exceed 2" for Q_{100}
& Max. Velocity will not exceed 2 fps

Sodded swale to convey small volume
"nuisance" flows through the landscaped
portions of Drainage Areas "G", "H", "I", and "J."

See Plate-7 of Drainage Report for
location of sodded drainage swales.

WILLIAM MATOTAN & ASSOCIATES, INC.
ENGINEERS
230 Truman Street, N.E. - Albuquerque, N.M. 87108
Telephone 265-8467

Project Franklin Ave Sanitary Apt. Sheet 2 of 2
Capacity - Contribution Job No. 720
By SAM Chk'd ✓ Date Apr. 25 '84

A.P. "D" Double "D" Inlet in sump condition $Q = CLH^{3/2}$
one foot available curb height for ponding

$$C = 3.0$$

$$L = (2.1250' + 6.5') = 8.6250'$$

$$H = 1.00' \quad H^{3/2} = 1.00$$

$$Q = (3.0)(8.6250)(1.00) = \underline{25.8750} \text{ cfs capacity}$$

100 yr. Volumes contributed to A.P. "D"

$$\begin{array}{rcl} \text{A.P. "C"} & = & 16.54 \text{ cfs} \\ \text{D.A. "D"} & = & 1.55 \text{ cfs} \end{array}$$

$$\underline{18.09} \text{ cfs} \cong (H \text{ of } 9.5")$$

✓ OK $Q_{100} < \text{Double "D" Inlet Cap.}$

A.P. "G"
18" RCP Connector Pipe Capacity

100 yr. Volumes contributed to A.P. "G"

$$\begin{array}{l} A = 1.7671 \\ w/p = 4.7124 \\ R = 0.3750 \quad R^{4/3} = 0.5183 \\ S = 0.0310 \quad S^{1/2} = 0.1761 \\ f = 114.0000 \quad (n = 0.013) \\ V = 10.4032 \text{ SPS} \\ Q = \underline{18.3835} \text{ cfs (capacity)} \end{array}$$

$$\begin{array}{rcl} \text{A.P. "D"} & = & 18.09 \text{ cfs} \\ \text{Indian School R.O.V.} & = & 0.23 \text{ cfs} \\ \text{D.A. "G"} & = & 0.04 \text{ cfs} \end{array}$$


$$\text{(Contribution)} \quad \underline{18.36} \text{ cfs}$$

✓ OK $Q_{100} \cong 18" \text{ RCP Capacity}$

**COMPOSITE HYDROGRAPHS
DRAINAGE AREAS 1, 2, 3 AND 4**

Pages A-40 and A-41


Added 29 Apr. 64



Note: Hydrographs set ahead to reflect lag time to peak in sub-basins DA-1 and DA-2

WILLIAM MATOTIAN & ASSOCIATES, INC.
 ENGINEERS
 330 Truman Street, N.E. - Albuquerque, N.M. 87108
 Telephone 265-9447

Project: CASA SANDIA APTS. Sheet 2 of 2
 Subject: Drainage Study Job No. 720
 Comp. by: REP Date: Apr 26 84 Date: 26 Apr 84



Note: Hydrographs set ahead to reflect lag time to peak in sub-basins DA-1 and DA-2.

WILLIAM MATOTAN & ASSOCIATES, INC.
 ENGINEERS
 230 Truman Street, N.E. - Albuquerque, N.M. 87108
 Telephone: 365-4447

Project: CASA SANDIA APTS. Sheet 1 of 2
 Subject: Drainage Study Job No. 720
 Comp. by: RBD Date: Apr. 26, 84
 Date: 20 Apr 84



CITY OF ALBUQUERQUE
MUNICIPAL DEVELOPMENT DEPARTMENT
ENGINEERING DIVISION



HYDROLOGY SECTION PROJ. NO. 115 DATE: 9/23/83

PLANNING DIVISION NO. _____

CONFERENCE RECAP

SUBJECT: Brownstone Apts (224 units) located South
of Indian School West of North Division Channel

WHO

REPRESENTING

ATTENDANCE: John Armstrong
Rod Peterson

City
Matfolar & Assoc

FINDINGS:

- 1) Drainage Report Appropriate
- 2) Free discharge directly to storm drain if it
can be shown that system is adequate
- 3) Summary Plot to eliminate lots.

The undersigned agrees that the above findings are summarized accurately and are only subject to change if further investigation reveals that they are not reasonable or that they are based on inaccurate information.

SIGNED: _____

SIGNED: _____

TITLE: CE/Hydrology

TITLE: Vice President

DATE: 9/23/83

DATE: 9/23/83



City of Albuquerque

P.O. BOX 1293 ALBUQUERQUE, NEW MEXICO 87103

DESIGN HYDROLOGY SECTION
123 Central NW, Albuquerque, NM 87102
(505) 766-7644

May 14, 1984

Mr. William Matotan, P.E.
William Matotan & Associates
230 Truman NE
Albuquerque, NM 87108


REF: CASA SANDIA DRAINAGE REPORT (J15-D17)

Dear Mr. Matotan:

The above mentioned report is hereby approved. Please be sure that copies of the latest plan, along with approved copies of "Drainage Facilities Within City Right-of-Way" documents, are attached to the permit sets prior to submittal to Hydrology for final sign-off.

If you have any questions on the above, please feel free to call me at 766-7644.

Thank you,



John Armstrong
Civil Engineer/Hydrology

JA:mrk

cc: Gale Hunsinger, Brownstone Group
Gregg Olson

MUNICIPAL DEVELOPMENT DEPARTMENT

C. Dwayne Sheppard, P.E., City Engineer

ENGINEERING DIVISION

Telephone (505) 766-7467

AN EQUAL OPPORTUNITY EMPLOYER

INFORMATION SHEET

PROJECT TITLE Casa Sirenia Apartments TYPE OF SUBMITTAL Supplement to Original Report
 ZONE ATLAS PAGE NO. J-15 CITY ADDRESS 1642 Indian E. R. NE J-15-D17
 LEGAL DESCRIPTION Brownstone Tract in the NE 1/4, NE 1/4, Sec. 16, T.10N, R. 3E.
 ENGINEERING FIRM William Matetan & Assoc. Inc. CONTACT William I. Matetan
 ADDRESS 230 Truman St. NE PHONE (505) 265-8467
 OWNER Brownstone Group CONTACT Gracie Hunsinger
 ADDRESS 230 Truman St. NE, A/B N.W. PHONE (505) 266-7955
 ARCHITECT Miguel Trujillo & Assoc. CONTACT Miguel Trujillo
 ADDRESS 8210 La Mirada NE PHONE (505) 298-7543
 SURVEYOR William Matetan & Assoc. CONTACT William I. Matetan
 ADDRESS Same as above PHONE 265-8467
 CONTRACTOR _____ CONTACT _____
 ADDRESS _____ PHONE _____


PRE-DESIGN MEETING:

☒ YES
☐ NO
☐ COPY OF CONFERENCE RECAP SHEET PROVIDED

PLEASE CHECK TYPE OF APPROVAL EXPECTED WITH THIS SUBMITTAL:

☐ SKETCH PLAT APPROVAL
☐ PRELIMINARY PLAT APPROVAL
☐ SITE DEVELOPMENT PLAN APPROVAL
☐ FINAL PLAT APPROVAL
☒ BUILDING PERMIT APPROVAL
☐ CERTIFICATE OF OCCUPANCY APPROVAL
☐ ROUGH GRADING PERMIT APPROVAL
☐ GRADING/PAVING PERMIT APPROVAL
☒ OTHER Supplement to Damage Report (SPECIFY)

DATE SUBMITTED: April 30, 1984
 BY: William Matetan & Assoc., Inc.



WILLIAM MATOTAN & ASSOCIATES • ENGINEERS
INC

230 Truman Street, N.E.


Albuquerque, New Mexico 87108

Phone (505) 265-8467



April 30, 1984

Mr. John Armstrong
City of Albuquerque
Design Hydrology Section
123 Central Ave. NW
Albuquerque, New Mexico 87102



Re: CASA SANDIA DRAINAGE REPORT (J15-D17)
City of Albuquerque Review Comments by letter of April 10,
1984

Dear Mr. Armstrong:

Subsequent to receipt of your review comments, we have revised the grading and drainage plan for subject project to handle all flows on-site and to discharge those flows from the site by direct connection to the existing storm sewer system. The previously submitted drainage report is hereby supplemented with the attached revised report documents:

1. Plate 5 - Existing 30" storm sewer and contributing drainage areas. (Revised to show "Developed Condition" runoff for the entire drainage basin, drainage areas 1, 2, 3 and 4.)
2. Plate 7 - Grading Plan, Developed Condition. (Revised to show on-site handling of all runoff, including "nuisance" flows and conveyance of all site runoff directly to existing storm sewer system with no discharge into the street.)
3. Appendix Page 9a. (Added to show drainage areas contributing to "nuisance" flows within the Indian School Road Right of Way; Areas "H", "I", and "J").
4. Appendix Pages A-10 thru A-13. (Revised to show runoff from all drainage basin areas under fully developed conditions).
5. Appendix Pages A-31 thru A-34. (Revised to analyze overland, street and storm sewer flows under developed conditions).

Page 2
Mr. John Armstrong
City of Albuquerque

April 30, 1984

6. Appendix Pages A-35 thru A-39. (Added to show details, capacities and velocities of proposed site drainage facilities).
7. Appendix Pages A-40 and A-41. (Added to show "Composite Hydrographs" for drainage areas 1, 2, 3 and 4.)

As shown on Plate-7, all flows will be conveyed by on-site surface conveyance to a "double-D" inlet at the downstream corner of Drainage Area "D". Total 100-year runoff to this proposed inlet will be about 18 cfs (see page A-39). Conveyance of flows to this inlet, including all "nuisance" flows will be accomplished by the various swales and structures shown on pages A-35 thru A-39 and Plate-7. The "Double-D" inlet will be connected to existing storm sewer inlet #3 by an 18-inch diameter connector pipe (capacity 18.4 cfs). Existing inlet #3 has an 18-inch diameter connector pipe (capacity 30 cfs, page A-23) to existing M.H. #S-201.

A "Single-D", area drain, will be located between the "Double-D" inlet and existing inlet #3 to intercept about 0.3 cfs, 100-year runoff, from drainage areas "G" and "J".

Hydrograph analysis of drainage areas #1 thru #4 show that the combined peak flows for areas #3 and #4, 30 cfs for 100-year event, will pass through M.H. #S-301, at the sag on Indian School Road, about five minutes before the combined peak for drainage areas #1 and #2, 118 cfs for 100-year event, reaches M.H. #S-201, about 700 feet upstream at the intersection of University Blvd. and Indian School Road.

Inasmuch as the capacity of the existing 30-inch storm sewer on the downstream side of M.H. #S-201 is 48 cfs (gravity flow, pipe full) 70 cfs of the 118 cfs peak flow will flow overland to inlets #7 and #8 at M.H. #S-301. The 30-inch outlet pipe from M.H. #S-301 has a capacity of 60 cfs, gravity flow-pipe full, therefore 12 cfs of the 70 cfs can enter the storm sewer leaving 58 cfs to flow overland to the north of Indian School Road via the historic drainageway between Indian School Road and Interstate Route 25 (I-25.)

Review of "Drainage Report for Netherwood Apartments" (J-15-D20) dated March 13, 1984, and "Response to City Review Comments," dated April 10, 1984, for that report, confirms recognition of the historic drainageway and describes provision for surface conveyance of 81 cfs overland flow from the sag on Indian School Road to the I-25 drainage structure which conveys flow from this drainage under I-25.

Page 3
Mr. John Armstrong
City of Albuquerque

April 30, 1984

As quoted from the section "Flood Plain Information" of that report:

"As indicated in the February 1, 1984, conference notes, this flood plain cannot be shifted onto adjacent property. Computations contained in Appendix 2 have been made to insure that 81 cfs overland flow can be conveyed safely between the northern boundary of the Oddfellows Building and the apartment units. These computations indicate that the flow depth is less than 0.5 feet. Finished floor elevations in the apartment units have been set at least one-foot above the anticipated flow depth. It should also be noted that to insure that runoff follows its historic path, the grades along the property line match closely with existing ground."

The consultant response, dated April 10, 1984, to City review comments, includes the following reference to the existing drainage structure at I-25 and available ponding upstream from that structure, within the I-25 right-of-way:

"The invert elevation of the 30" RCP is approximately 5029.0. To avoid damage to the retaining wall, ponding must not occur higher than the 5032.0 contour. I have estimated that approximately 45,000 cu. ft. of storage is provided between the 5030.0 and 5032.0 contour. Utilizing the 100-year runoff hydrograph (see enclosed), and the fact that a 30" RCP can convey 31 cfs with a head of 1.75 feet, (0.5 feet above top of the pipe), approximately 50,000 cu. ft. of storage is required. In my opinion, this provides a reasonable match."

The Grading/Drainage Plan, dated April 9, 1984, submitted with the above drainage report, shows that the historic drainageway between the sag on Indian School Road and the I-25 right-of-way line will not be blocked by permanent structures, but will be conveyed along that drainageway by means of an inverted crown pavement section from Indian School Road to a rip-rap rundown, 15-feet in width and 1-foot depth at the I-25 right-of-way.

We have recently conducted a detailed field survey of the conditions existing within the I-25 right-of-way and confirm that the inlet flowline elevation of the 30" RCP is 5028.71; the top of shoulder pavement elevation, 17 feet west of the culvert inlet, is 5035.2; roadway embankment elevation, 15 feet east of the edge of pavement, is 5032.7; low elevation

April 30, 1984

of ponding area, 10 feet east and 20 feet north of the culvert inlet is 5028.1; and approximately 45,000 cu. feet of ponding exists within the I.25 right-of-way below elevation 5032.

Based on the above analysis and for the following summarized reasons, it is recommended that the revised grading and drainage plan for the Casa Sandia Project be approved to allow direct discharge into the existing storm sewer system without requirements for on-site ponding:

1. Increase to basin flows will not result in encroachment or potential damage to private property.
2. Proposed facilities within the downstream historic drainageway are being designed on the basis of 81 cfs overland flow for the 100-year event. Our studies indicate a more probable overland runoff peak of about 58 cfs for that event, about 30% less.
3. Ponding capacity exists with the I-25 right-of-way, at the 30" pipe, to contain the 100-year overland flow from the sag on Indian School Road, in excess of the storm sewer capacity. Water surface of the ponding would be 15 feet or more from the edge of the highway shoulder pavement and about 2.5' below the shoulder elevation. Total volume of the 100-year ponding would be discharged through the 30" culvert in less than 2 hours.
4. The fully developed Casa Sandia Project will increase flows to the drainage basin by only 8.7 cfs, about 5% of the fully developed basin flows for the 100-year event.
5. Rough grading of the site received approval based on no site ponding and rough grading construction has been completed.
6. Due to extreme grade differential across the site, on-site ponding is extremely difficult, would require extensive retaining walls, would probably require a significant reduction in the number of apartment and would make the economic viability of the project doubtful.

Page 5
Mr. John Armstrong
City of Albuquerque

April 30, 1984

Your timely review of our original drainage report is deeply appreciated and we look forward to your response to our revised plan in order that a building permit can be issued for the project at the earliest possible date.

Very truly yours,

WILLIAM MATOTAN & ASSOCIATES, INC.


William I. Matotan, P.E. & L.S.
President

WIM:jal

Enclosures

cc w/enc.:


Mr. Richard Rushing, Project Coordinator, Brownstone Group
Mr. Gale Hunsinger, Project Superintendent, Brownstone Group
Job File 720

DRAINAGE REPORT

FOR

CASA SANDIA APARTMENTS (J15-D17)
AN APARTMENT COMPLEX IN THE
CITY OF ALBUQUERQUE, NEW MEXICO

MARCH, 1984




WILLIAM MATOTAN AND ASSOC., INC.
ENGINEERS
ALBUQUERQUE, NEW MEXICO

DRAINAGE REPORT

FOR

CASA SANDIA APARTMENTS (J15-D17)
AN APARTMENT COMPLEX IN THE
CITY OF ALBUQUERQUE, NEW MEXICO

MARCH, 1984



WILLIAM MATOTAN AND ASSOC., INC.
ENGINEERS
ALBUQUERQUE, NEW MEXICO

DRAINAGE REPORT
FOR
CASA SANDIA APARTMENTS

PREPARED FOR:
THE BROWNSTONE GROUP
3130 SOUTHWEST FREEWAY, SUITE 204
HOUSTON, TEXAS 77098

MARCH 1984

PREPARED BY:
WILLIAM MATOTAN & ASSOCIATES, INC.
230 TRUMAN STREET, N. E.
ALBUQUERQUE, NEW MEXICO 87108



William I. Matotan
WILLIAM I. MATOTAN
N.M. P.E. NO. 1593

145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000

DRAINAGE REPORT
FOR
CASA SANDIA APARTMENTS

INDEX

| | <u>Page</u> |
|---|-------------|
| I. GENERAL | |
| A. Site Description and Location | 1 |
| B. Zoning | 2 |
| C. Methods of Analysis | 2 |
| II. ON-SITE CONDITIONS | |
| A. Undeveloped Flows | 4 |
| B. Developed Flows | 6 |
| C. Adequacy of Downstream Drainage System | 9 |
| 1. General | 9 |
| 2. Existing Storm Sewer System | 9 |
| 3. Street Flow Capacity | 14 |
| III. OFF-SITE CONDITIONS | |
| A. General | 16 |
| IV. EROSION CONTROL | |
| A. Rough Grading | 17 |
| B. Construction Phase | 17 |
| C. Permanent Phase | 17 |
| V. CONCLUSIONS | 18 |
| VI. RECOMMENDATIONS | 18 |

APPENDIX

| | <u>Page</u> |
|---|-------------|
| STORM RUNOFF FROM PROJECT SITE | A1-A9 |
| STORM RUNOFF CONTRIBUTING TO EXISTING STORM SEWER SYSTEM NO. 129 | A10-A13 |
| CAPACITY OF EXISTING STORM SEWER SYSTEM NO. 129 | A14-A30 |
| STREET FLOW CAPACITY | A31-A34 |

PLATES

| | | |
|----------|---|--|
| PLATE 1 | - | VICINITY MAP. |
| PLATE 2 | - | SCS SOILS MAP. |
| PLATE 3 | - | FLOOD HAZARD BOUNDARY MAP. |
| PLATE 4 | - | EXISTING STORM SEWER SYSTEM NO. 129. |
| PLATE 5 | - | EXISTING 30" STORM SEWER AND CONTRIBUTING DRAINAGE AREAS. |
| PLATE 6 | - | INDIAN SCHOOL ROAD - PLAN AND PROFILE. |
| PLATE 7 | - | GRADING PLAN - DEVELOPED CONDITION. |
| PLATE 8 | - | SITE LAYOUT PLAN. |
| PLATE 9 | - | SUMMARY PLAT OF BROWNSTONE TRACT. |
| PLATE 10 | - | LANDSCAPE PLAN. |

DRAINAGE REPORT
FOR
CASA SANDIA APARTMENTS

I. GENERAL

This report presents a comprehensive analysis of the drainage control, flood control and erosion control constraints on and impacts resulting from the planned construction of a 218-unit apartment complex within the limits of the City of Albuquerque, New Mexico.

Plans for the proposed development have been prepared in accordance with criteria and guidelines established by the City of Albuquerque, New Mexico State Highway Department and Albuquerque Metropolitan Arroyo Flood Control Authority (AMAFCA).

A. Site Description and Location.

The site is triangular in shape and contains 5.4361 acres. It is bounded on the south by the existing Citadel Apartment complex (at the intersection of University Boulevard, N. E., and Indian School Road, N. E.), on the westerly side by Indian School Road, N. E., and on the easterly side by the AMAFCA North Diversion Channel. The site is identified on zone atlas map J-15-Z. (See Vicinity Map, Plate 1.)

The site slopes generally from east to west with a maximum difference in elevation across the site of about 30 feet from the southeast corner (at the AMAFCA North

A. Site Description and Location (continued).

Diversion Channel) to the southwest corner at Indian School Road. Slopes vary from about 4% to 6%.

Soil classes for the site are designated as "BKD", Bluepoint Series and "Cu", Cut and Fill land, in the SCS soils report, sheet 31, for Bernalillo County. (Plate 2.) Soil cover is sparse with an estimated 10% cover of native veds and grasses.

Current flood hazard boundary maps do not indicate flooding on or adjacent to the site due to a 100-year frequency rainfall event. (Plate 3.)

B. Zoning.

By action of the Environmental Planning Commission on October 20, 1983, zoning of the site was changed from C-3 to R-3. Findings of the Commission were as follows:

1. The requested R-3 zoning is appropriate to and compatible with surrounding zoning.

2. The reported R-3 zoning is more appropriate to the site than C-3 zoning.

C. Methods of Analysis.

In general, criteria outlined in Sections 22.2 and 22.3 of the City of Albuquerque Development Process Manual (DPM) was used to evaluate existing and developed

C. Methods of Analysis (continued).

runoff for the project site.

Specifically:

1. Six-hour rainfall volumes from Plate 22.2 D-1.
2. Rainfall intensities from Plate 22.2 D-2.
3. Peak Flowrate Computations by Rational Formula, Section 22.2, page 17.
4. Inlet capacities by weir formula, Section 22.3, page 17 and grate capacities from Plates 22.3 D-5 and 22.3 D-6.
5. Concrete connector pipe flow from Plate 22.3 D-8.
6. "C" Factors to be used with Rational Formula from Handbook of Applied Hydrology, by Chow.
7. Time of Concentration, "Tc", from Section 22.2, page 3.

As-built construction drawings for New Mexico Project I-025-4 (29) 222 and Special Assessment District 166A, were utilized for analysis of the existing Indian School Road-University Boulevard storm sewer system.

C. Methods of Analysis (continued).

Volume I, Plate 2 of the Albuquerque Master Drainage Study, showing existing and proposed storm drainage facilities in the project vicinity, was reviewed and a portion thereof included as Plate 3 of this report.

Field investigations were conducted to confirm on-site and off-site runoff conditions and conditions of the existing downstream storm sewer system.

Plates 4 and 5 of this report show the existing off-site storm sewer system layout and contributing drainage areas. Plate 7 shows the existing and developed contours and site discharge analysis points.

II. ON-SITE CONDITIONS

A. Undeveloped Flows.

Historically, storm water runoff from the site and from lands to the east of the site was conveyed westerly, by natural minor arroyos into Campus Draw. Campus Draw being a major, south to north, drainageway through that part of the City. Subsequent construction of the AMAFCA North Diversion Channel diverted all upstream runoff from the site and construction of Indian School Road provided downstream interception of runoff from the site.

Runoff from the project site now discharges directly onto Indian School Road. Indian School Road being an asphalt paved arterial, 66 feet in width from flowline to flowline of gutters. (The existing layout plan and profile

A. Undeveloped Flows (continued).

of Indian School Road, along the downstream (westerly) side of the site is shown on Plate 6.)

About 50 feet downstream from the southwest corner of the site, street flow from Indian School Road enters the intersection of Indian School Road and University Boulevard. Street runoff is intercepted by storm sewer inlets at each corner of that intersection.

The storm drain inlets in that intersection have been numbered 3, 4, 5 and 6 for purposes of this report and are shown, together with details of the entire storm drain system, on Plates 5 and 6 of this report.

Undeveloped site runoff peaks are as follows:

| | |
|---------------------|--------------|
| 10-year frequency: | Q = 6.27 cfs |
| 100-year frequency: | Q = 9.58 cfs |

Areas contributing to the above runoff are:

1. Project site = 5.4361 acres
2. Off-site = 0.4573 acres

The off-site area contribution is from a strip of undeveloped land, about 25 feet wide, east of the project, lying between the east property line and the west side of the AMAFCA North Diversion Channel.

Computations of the undeveloped runoff are included in the Appendix of the report, pages A-1 through A-9.

B. Developed Flows.

The developed site will consist of seven separate drainage areas. Drainage area designations and boundaries are shown on the "Grading Plan - Developed Condition", Plate 6 of this report.

A summary of the developed drainage areas and respective peak runoff is shown on pages A-1 and A-1a of the Appendix. Computations of developed peak runoff are included in the Appendix, pages A-2 through A-9.

Total developed runoff peaks are as follows:

| | |
|---------------------|---------------|
| 10-year frequency: | Q = 11.57 cfs |
| 100-year frequency: | Q = 17.63 cfs |

Areas contributing to the above runoff are:

| | |
|--------------|----------------|
| Project site | = 5.4361 acres |
| Off-site | = 0.4573 acres |

It is proposed that the 0.45-acre, undeveloped, off-site area (land of AMAFCA) draining onto the project site, will be sodded with Kentucky Bluegrass and maintained by the project owner. Runoff from the off-site contributing area will be reduced from the undeveloped 100-year peak flow of 0.74 cfs to a developed 100-year peak flow of 0.42 cfs. The reduced runoff, after development, will result from the lesser "c" factor (runoff coefficient), estimated as 0.20 for the turfed condition, as opposed to a "c" factor estimated as 0.35 for the existing undeveloped "bare earth" condition.

B. Developed Flows (continued).

Site grading and landscape plans are presently being reviewed by both AMAFCA and the Albuquerque office of the Corps of Engineers. Tentative approval to sod the 0.45-acre AMAFCA strip, as part of this project, was given by AMAFCA prior to finalizing the landscape plan.

A summary of the total developed pervious and impervious acreage for each of the project drainage areas is shown on page A-1a of the Appendix. Pervious areas were considered to be those sodded and landscaped areas around the buildings and outside of parking areas, drives and sidewalks. A "c" factor of 0.20 was used in runoff computations for all pervious areas. Impervious areas were considered to be all paved drives and parking areas, concrete curbs and gutters, retaining walls, concrete walks, building roofs and roof overhangs. Various "c" factors, ranging between 0.82 and 0.90 were used in runoff computations for impervious areas.

As shown on Plate 7 of this report, developed runoff from Drainage Areas "B" through "E" will free discharge directly to Indian School Road at four locations labeled A.P. (analysis points) "B" through "E".

Drainage area "B" runoff will discharge at the north entrance drive, A.P. "B", at a 10-year peak rate of 2.48 cfs and a 100-year peak rate of 3.79 cfs.

Drainage area "C" runoff will discharge at the south entrance drive, A.P. "C", about 370 feet south of and downstream from A.P. "B", at a 10-year peak rate of 6.19 cfs and 100-year peak rate of 9.44 cfs.

B. Developed Flows (continued).

Drainage Area "D" will discharge into the Indian School Road Right-of-Way at A.P. "D", about 230 feet south of and downstream from the south entrance drive. Runoff from Area "D" will be conveyed to the street by a concrete-cobbled rundown, City of Albuquerque Standard Sidewalk Culvert and 2-foot wide curb opening. The 10-year peak discharge rate will be 1.02 cfs and 100-year peak rate 1.55 cfs.

Drainage Area "E" will discharge into the Indian School Road Right-of-Way at A.P. "E", about 220 feet south of and downstream from the north entrance drive. Runoff from Area "E" will be conveyed to the street in the same manner as described above for Area "D". The 10-year peak discharge rate will be 1.23 cfs and 100-year peak rate 1.87 cfs.

Runoff from drainage area "A", at the extreme north end of the site, will sheet flow into a sodded and landscaped area along Indian School Road at a 10-year peak rate of 0.34 cfs and 100-year peak rate of 0.51 cfs.

Runoff from drainage area "F" will sheet flow into a sodded and landscaped area, about 170 feet in length, between the north and south entrance drives, at a 10-year peak rate of 0.28 cfs and 100-year peak rate of 0.43 cfs.

Runoff from drainage area "G", at the southwest corner of the site, will sheet flow into a sodded and landscaped area along Indian School Road at a 10-year peak rate of 0.03 cfs and 100-year peak rate of 0.04 cfs.

B. Developed Flows (continued).

In summary, total developed peak flow rates discharging to Indian School Road and the existing storm sewer system are 5.3 cfs greater than the historic undeveloped rate for the 10-year runoff event and 8 cfs greater for the 100-year event.

C. Adequacy of Downstream Drainage System.

1. General

The existing downstream drainage system is shown on Plate 4, "Existing Storm Sewer System No. 129" and Plate 5, "Existing 30" Storm Sewer and Contributing Drainage Areas."

Four drainage areas have been identified as contributing to the system. Boundaries of the four areas together with acreages and peak runoff rates for the 10-year and 100-year frequency rainfall are shown on Plate 5.

Area runoff computations are shown on Appendix pages A-10 through A-13, storm sewer capacity computations on pages A-14 through A-30 and street flow capacity computations on pages A-31 through A-34.

"Developed condition" flows from the project site contribute to Drainage Area 1 and have been used in all downstream drainage analysis computations.

2. Existing Storm Sewer System

The original storm sewer system on Indian

2. Existing Storm Sewer System (continued)

School Road was constructed during the 1960's, concurrent with the re-alignment and construction of Indian School Road under New Mexico Project I-025-4 (29) 222. It consisted of about 1280' of 30-inch-diameter reinforced concrete pipe main, four manholes and two combination drop inlets. The 30-inch-diameter main extended from a "free outlet" at the upstream end of three 120-inch-diameter culvert pipes (draining from southeast to northwest under I-25) easterly to the intersection of Indian School Road and University Boulevard where it terminated at a manhole on the west side of the intersection (City M.H. #S-201). One combination drop inlet, D.I.C. 61-1, Type II (numbered inlet #4 in this report) was installed in the northeast curb return of that intersection, on Indian School Road, and the second drop inlet, D.I.C. 61-1, Type II, (numbered inlet #7 in this report), was installed in the north curb of Indian School Road, at a sag curve, about 600 feet west of University Boulevard.

In 1970, the 30-inch-diameter main was extended about 330 feet to the south on University Boulevard, concurrent with the construction of University Boulevard, under City Paving District No. 166A, and terminated at a manhole, (no City manhole number, numbered "Sta. H25 for this report) in a sag vertical curve. Three combination inlets, double "C" type, (inlets numbered 3, 5 and 6 in this report), were constructed in the intersection of Indian School Road and University Boulevard, one each at the southeast, southwest and northwest corners of the intersection. Two drop inlets, one a combination type 2-double "C", (inlet number 2, this report), installed in the low point of the west curb and one grated type, single "C", (inlet number 1, this report) installed in the gutter of a

2. Existing Storm Sewer System (continued)

driveway on the east side of University Boulevard, both about 250 feet south of Indian School Road.

One additional drop inlet, a grated type double "D", (inlet number 8, this report) was found during a field investigation, behind the curb, on the south side of Indian School Road, north of the entrance drive to the St. Paul Lutheran Church. No plans could be found for this inlet.

It was noted during the field investigation for this report that inlet #7 flowline, in the sag vertical curve and low side of the super-elevated roadway (bottom of east approach to the Indian School Road bridge over I-25), is about 8 inches higher in elevation than the low portion of the roadway sag. The existing drainage outlet for that portion of Indian School Road consists of three curb cuts, one about 30' long, immediately upstream, to the west of the inlet and two curb cuts, about 35' long and 30' long, upstream, to the east of the inlet. (See sketch on Appendix page A-33). All 100-year frequency street flows, in excess of the storm sewer capacity, from drainage areas #1, #3 and #4, (including all of Indian School Road, between I-25 and the AMAFCA North Diversion Channel), together with street overflow from the sag south of Indian School Road on University Boulevard (drainage area #2) discharges to the north and west through those curb cuts.

Overflow from drainage area #2, at the street sag on University Boulevard, flows west in an asphalt paved, inverted crown driveway, along the south side of an office building at 1415 University Boulevard, N. E., thence across Indian School Road through the curb

2. Existing Storm Sewer System (continued)

cuts mentioned above.

It is estimated that for the 10-year event, about 8 cfs from drainage area #2 would discharge to Indian School Road via the above-described route and for the 100-year event, about 31 cfs would be discharged. Capacity of the inverted crown driveway is estimated at 74 cfs or 43 cfs greater than the estimated 100-year peak flow rate (Appendix page A-32).

The only existing surface discharge point from the downstream end of drainage area #2 is the one described above, which appears to be a historic drainageway for surface runoff in this area. The Master Drainage Plan for the City of Albuquerque shows a proposed future 36-inch diameter storm sewer line, with the upstream end intercepting drainage area #2 flows at the sag point in University Boulevard, described above, and conveying that runoff west along the present surface flow route to Indian School Road, thence along the south side of Indian School Road to a point of discharge at the inlet to three 120-inch-diameter existing culverts under I-25 at "Campus Draw."

It should be noted that none of the storm water runoff from the Casa Sandia Apartment project will contribute to Drainage Area #2 or to the proposed future storm sewer.

The total area contributing to the Indian School Road drainage system, between the AMAFCA North Diversion Channel and Interstate Route-25 (including the Casa Sandia project site as part of Drainage Area #1)

2. Existing Storm Sewer System (continued)

is about 57.4 acres (Appendix page A-11).

Estimated peak storm runoff from the above area: (Appendix page A-10).

10-year frequency = 91 cfs
100-year frequency = 138 cfs

Total estimated storm sewer system inlet capacity is estimated to be 138 cfs (assuming the inlet connector pipe capacity governs when it is less than inlet grate capacity.) (Appendix page A-14).

No inlet capacity has been allowed for the "throat" inlet at the curb. This capacity is considered to be equal to that lost by clogging of the grate during runoff periods.

Maximum capacity of the 30-inch storm sewer main, assuming pipe flowing full under gravity flow conditions is 71 cfs. (Appendix page A-29).

Maximum street flow would be the difference between the storm sewer capacity and peak storm runoff and is estimated to be 20 cfs for the 10-year frequency and 67 cfs for the 100-year frequency peak runoff.

The above peak street flow would occur at the previously-described sag on Indian School Road, about 600 feet west of University Boulevard. Flows discharge north through the three existing curb cuts into the historic drainageway (old Indian School paved roadway), thence westerly along the old roadway pavement to the I-25 drainage

2. Existing Storm Sewer System (continued)

structures that convey the runoff under the I-25 roadway into the historic Campus Draw drainageway on the west side of the interstate.

Capacity of the existing asphalt paved drainageway (old Indian School Road) is estimated to be 247 cfs, four times greater than the estimated 57 cfs peak flow for the 100-year frequency storm event. (Appendix page A-34).

3. Street Flow Capacity

Runoff from the project site contributes to Indian School Road flows only. Analysis of the capacity of Indian School Road indicates only two critical points for maintaining one dry driving lane in each direction during the 10-year peak runoff. One point being the section of Indian School Road west of the intersection with University Boulevard and immediately downstream from storm sewer inlets #5 and #6. (Appendix page A-31). At that point, the roadway has a continuous cross slope to the north curb and is at the downstream discharge for Drainage Area #1.

The street capacity is estimated to be 8.1 cfs when one dry driving lane exists in each direction. Under the above flow conditions, the entire east-bound half of the street (33 feet) would be dry and the inside 12-foot, west-bound driving lane would be dry. Depth of flow at the north curb would be 0.38' (4½ inches).

With flow two inches above the north (low)

3. Street Flow Capacity (continued)

curb, about 48 feet of the 66 feet total width would be wet and peak street flow would be about 75 cfs.

Capacity of storm sewer inlets #3, #4, #5 and #6, immediately upstream from this section is about 49 cfs. Estimated peak flows for drainage area #1, including developed flows from the Casa Sandia project, are 27 cfs for the 10-year and 41 cfs for the 100-year frequency. Street flow would be the difference between the peak drainage area flows and the flow capacity of the storm sewer system which would indicate zero street flow at the critical section. In other words, the storm sewer system immediately upstream from the critical section will handle all peak runoff from drainage area #1 for both the 10-year and the 100-year frequency events.

The second critical point for street flow on Indian School Road is about 600 feet west of the above-described point, at the sag vertical curve at the east approach to the bridge over I-25. This location has been discussed earlier relative to drainage north and west through three existing curb cuts in the north curb, thence along the historic drainageway in the paved roadway of old Indian School Road. It is important to note that the old Indian School Road drainageway is the only surface flow outlet from the sag vertical curve on Indian School Road and that it conveys all surface flows, that exceed the storm sewer capacity, from drainage areas #1, #2, #3 and #4. It is estimated that about 12 cfs would be flowing across the super-elevated street section at that point during the 10-year frequency event and that the maximum depth in the street would be about two inches. This depth would occur

3. Street Flow Capacity (continued)

during the first 10 to 15 minutes of the runoff event and would decrease rapidly thereafter as the storm intensity decreased.

For the 100-year peak flow, it is estimated that a peak flow of about 55 cfs would sheet flow across Indian School Road at a maximum depth of about four inches.

III. OFF-SITE CONDITIONS

A. General.

The only offsite area contributing runoff to the project site is a strip of undeveloped AMAFCA land about 25 feet wide and about 800 feet in length along the easterly side of the project. It consists of about 0.46 acres and contributes about 0.49 cfs peak flow during the 10-year event and about 0.74 cfs during the 100-year event.

Along the south boundary of the site, on the adjoining lands of the Citadel Apartment Complex, an asphalt-lined, inverted crown, drainage swale conveys runoff from that property westerly to Indian School Road.

Indian School Road borders the project site along the westerly side, for the entire length of the project and conveys the only runoff discharge from the project.

IV. EROSION CONTROL

A. Rough Grading

A "rough grading plan" was previously submitted to the City and approved for construction. That plan included construction of earth dikes along the tops of all embankment areas to prevent erosion of the embankments and to ensure that eroded material will not be drained onto the roadway of Indian School Road.

B. Construction Phase

During the construction phase, all embankments will be protected from erosion by means of ditches and dikes. Sand cover will be spread over bare earth where deemed necessary to prevent runoff and erosion and, if deemed necessary, temporary on-site ponding will be utilized.

C. Permanent Phase

All bare earth areas will be sodded and landscaped.

Where vertical grade changes greater than 18 inches occur, they will be retained by concrete retaining walls.

No slopes over three feet in height will be steeper than 3:1 and slopes less than three feet high will not be steeper than 2:1.

V. CONCLUSIONS

Detailed investigations and analysis of off-site conditions, existing storm sewers and street flow capacities, indicates that free discharge of storm runoff from the developed project site is feasible and will have only a minimal impact on existing downstream drainage facilities.

VI. RECOMMENDATIONS

It is recommended that the City of Albuquerque approve this drainage report and permit the free discharge of runoff from the project site into the adjacent City street and downstream storm sewer facility.

APPENDIX

STORM RUNOFF FROM PROJECT SITE

Pages A-1 thru A-9

WILLIAM MATOTAN & ASSOCIATES, INC.
ENGINEERS
230 Truman Street, N.E. - Albuquerque, N.M. 87108
Telephone 265-8467

Project CASA SANDIA APTS. Sheet 1 of 9
Subject: Drainage Study Job No. 720
Comp. by REP Date 12 Mar 84 Chk'd ✓ Date 12 Mar 84

SUMMARY OF STORM RUNOFF from PROJECT SITE

| Drainage Area | Exist. Condition | | Developed Condition | |
|---------------|------------------|------------------|---------------------|------------------|
| | Q ₁₀ | Q ₁₀₀ | Q ₁₀ | Q ₁₀₀ |
| "A" | 0.38 cfs | 0.58 cfs | 0.34 cfs | 0.51 cfs |
| "B" | 1.29 | 1.98 | 2.48 | 3.79 |
| "C" | 3.23 | 4.93 | 6.19 | 9.44 |
| "D" | 0.52 | 0.80 | 1.02 | 1.55 |
| "E" | 0.63 | 0.96 | 1.23 | 1.87 |
| "F" | 0.18 | 0.27 | 0.28 | 0.43 |
| "G" | 0.04 | 0.06 | 0.03 | 0.04 |
| TOTALS (Cfs) | <u>6.27</u> | <u>9.58</u> | <u>11.57</u> | <u>17.63</u> |

WILLIAM MATOTAN & ASSOCIATES, INC.
ENGINEERS
230 Truman Street, N.E. - Albuquerque, N.M. 87108
Telephone 265-8467

Project CASA SANDIA APARTMENTS Sheet of
Drainage Study Job No. 720
By REP Chk'd ✓ Date Mar. 6, 1984

SUMMARY OF PROJECT DRAINAGE AREAS

| Area Designation | Pervious (Acres) | Impervious (Acres) | Total Acres |
|---------------------|---------------------|-----------------------|-------------|
| "A" Off-site | 0.1004 | 0 | 0.1004 |
| On-site | 0.1967 | 0.0618 | 0.2585 |
| Sub-total | 0.2971 | 0.0618 | 0.3589 |
| "B" Off-site | 0.182 | 0 | 0.182 |
| On-site | 0.1433 | 0.8918 | 1.0351 |
| Sub-total | 0.3253 | 0.8918 | 1.2171 |
| "C" Off-site | 0.1749 | 0 | 0.1749 |
| On-site | 0.6290 | 2.2251 | 2.8541 |
| Sub-total | 0.8039 | 2.2251 | 3.0290 |
| "D" Off-site | 0 | 0 | 0 |
| On-site | 0.1184 | 0.3730 | 0.4914 |
| Sub-total | 0.1184 | 0.3730 | 0.4914 |
| "E" Off-site | 0 | 0 | 0 |
| On-site | 0.1537 | 0.4390 | 0.5927 |
| Sub-total | 0.1537 | 0.4390 | 0.5927 |
| "F" Off-site | 0 | 0 | 0 |
| On-site | 0.0725 | 0.092 | 0.1645 |
| Sub-total | 0.0725 | 0.092 | 0.1645 |
| "G" Off-site | 0 | 0 | 0 |
| On-site | 0.0392 | 0.0006 | 0.0398 |
| Sub-total | 0.0392 | 0.0006 | 0.0398 |
| Sub-total, Off-site | 0.4573 | 0 | 0.4573 |
| Sub-total, On-site | 1.3528 | 4.0833 | 5.4361 |
| TOTAL | 1.8101 | 4.0833 | 5.8934 |

WILLIAM MATOTAN & ASSOCIATES, INC.
ENGINEERS
230 Truman Street, N.E. - Albuquerque, N.M. 87108
Telephone 265-8467

Project CASA SANDIA APTS Sheet 2 of 9
Subject: Drainage Study Job No. 720
Comp. by REP Date 7 Mar. 64 Chk'd ✓ Date 7 Mar. 64

Rainfall Volumes (from DPM, Vol. 2, Plate 22.2 D-1)

6-Hour Rainfall Volumes

$$100 \text{ Yr. Frequency} = 2.2''$$

$$50 \text{ '' ''} = (2.2'')(0.92) = 2.02''$$

$$10 \text{ '' ''} = (2.2'')(0.657) = 1.44''$$

$$5 \text{ '' ''} = (2.2'')(0.544) = 1.19''$$

$$2 \text{ '' ''} = (2.2'')(0.445) = 0.98''$$

Rainfall Intensity

From DPM, Vol. 2, Plate 22.2 D-2

$$I_{100} = (6 \text{ hr. rainfall})(6.84)(t_c)^{-0.51}$$

where I_{100} = Rainfall Intensity (Dimensionless), 100 yr. fr.

t_c = Time of Concentration in Minutes

$$I_{10} = (I_{100})(0.657)$$

Drainage Area Runoff (Use Rational Formula)

$$Q = CIA$$

Q = Peak runoff in cubic feet per second (cfs)

C = Runoff Coefficient

I = Rainfall intensity in inches per hour for the design frequency and time of concentration

A = Drainage Area in acres

WILLIAM MATOTAN & ASSOCIATES, INC.
ENGINEERS
230 Truman Street, N.E. - Albuquerque, N.M. 87108
Telephone 265-8467

Project CASA SANDIA APTS Sheet 3 of 9
Subject: Drainage Study Job No. 720
Comp. by: REP Date Mar. 84 Chk'd ✓ Date 7 Mar.

Time of Concentration

From OPM, Vol. 2, Sec. 22.2, p. 3

$$T_c = (0.0078) \left(\frac{L^{0.77}}{S^{0.385}} \right) \text{ where:}$$

T_c = Time of Concentration in minutes

L = length of drainage basin, in feet

S = slope of drainage basin, in feet of rise per foot of length

D.A. "A", $L = 175'$ $S = \frac{11.5 - 6.5}{175} = 0.03'/ft.$

$$T_c = (0.0078) \frac{175^{0.77}}{0.03^{0.385}} = 1.6 \text{ Min. Use } \underline{\underline{10 \text{ Min.}}}$$

D.A. "B", $L = 415'$ $S = \frac{11.5 - 02.7}{415} = 0.02'/ft.$

$$T_c = (0.0078) \frac{415^{0.77}}{0.02^{0.385}} = 3.6 \text{ Min. Use } \underline{\underline{10 \text{ Min.}}}$$

D.A. "C", $L = 900'$ $S = \frac{11.5 - 84.5}{900} = 0.03'/ft.$

$$T_c = (0.0078) \frac{900^{0.77}}{0.03^{0.385}} = 5.6 \text{ Min. Use } \underline{\underline{10 \text{ Min.}}}$$

D.A. "D", $L = 230'$ $S = \frac{85.7 - 82.0}{230} = 0.02'/ft.$

$$T_c = (0.0078) \frac{230^{0.77}}{0.02^{0.385}} = 2.3 \text{ Min. Use } \underline{\underline{10 \text{ Min.}}}$$

WILLIAM MATOTAN & ASSOCIATES, INC.
ENGINEERS
230 Truman Street, N.E. - Albuquerque, N.M. 87108
Telephone 265-8467

Project CASA SANDIA APTS. Sheet 4 of 9
Subject: Drainage Study Job No. 720
Comp. by REL Date 7 Mar 84 Chk'd ✓ Date 7 Apr.

Time of Concentration (Cont'd)

D.A. "E", $L = 265'$ $S = \frac{106.3 - 95}{265} = 0.04'/ft.$

$T_c = (0.0078) \frac{265^{0.77}}{0.04^{0.385}} = 2.6 \text{ Min. Use } \underline{\underline{10 \text{ Min.}}}$

D.A. "F", $L = 110'$ $S = \frac{103.0 - 99}{110} = 0.04'/ft.$

$T_c = (0.0078) \frac{110^{0.77}}{0.04^{0.385}} = 1.0 \text{ Min. Use } \underline{\underline{10 \text{ Min.}}}$

D.A. "G", $L = 75'$ $S = \frac{83.75 - 80.5}{75} = 0.04'/ft.$

$T_c = (0.0078) \frac{75^{0.77}}{0.04^{0.385}} = 0.7 \text{ Min. Use } \underline{\underline{10 \text{ Min.}}}$

WILLIAM MATOTAN & ASSOCIATES, INC.
ENGINEERS
230 Truman Street, N.E. - Albuquerque, N.M. 87108
Telephone 241-8467

Project CASA SANPIA ARTS. Sheet 5 of 9
Subject: Drainage Study Job No. 720
Comp. by REL Date 29 Feb 68 Chk'd ✓ Date 29 Feb.

* "C" Factors (to be used in Rational Form $Q = CIA$)

| <u>Type of Drainage Area</u> | <u>Runoff Coefficient, "C"</u> | |
|------------------------------|--------------------------------|-----------------|
| Lawns, sandy soil, steep | 0.15-0.20 | <u>Use 0.20</u> |
| Streets: | | |
| Asphaltic | 0.70-0.95 | <u>Use 0.82</u> |
| Concrete | 0.80-0.95 | <u>Use 0.90</u> |
| Roofs | 0.75-0.95 | <u>Use 0.85</u> |
| Unimproved Areas | 0.10-0.75 | <u>Use 0.35</u> |

* From "Handbook of Applied Hydrology" by Ven Te Chow,
Professor of Hydraulic Engineering, University of Illinois; pub.
McGraw-Hill Book Company

WILLIAM MATOTAN & ASSOCIATES, INC.
ENGINEERS
230 Truman Street, N.E. - Albuquerque, N.M. 87108
Telephone 265-8467

Project CASA SANDIA APTS. Sheet 6 of 9
Subject: Drainage Study Job No. 720
Comp. by REP Date 7 Mar 84 Chk'd ✓ Date 7 Mar.

Project Site Drainage Areas
and Developed Composite "C" Factors

| <u>Drainage Area</u> | <u>Area in Acres</u> | <u>Composite "C" Factor (Developed Condition)</u> |
|----------------------|--|---|
| "A" | $\begin{array}{r} \text{Offsite} = 0.1004 \\ \text{Onsite} = 0.2585 \\ \hline \text{Total} = 0.3589 \end{array}$ | 0.31 |
| "B" | $\begin{array}{r} \text{Offsite} = 0.182 \\ \text{Onsite} = 1.0351 \\ \hline \text{Total} = 1.2171 \end{array}$ | 0.67 |
| "C" | $\begin{array}{r} \text{Offsite} = 0.1749 \\ \text{Onsite} = 2.8541 \\ \hline \text{Total} = 3.0290 \end{array}$ | 0.67 |
| "D" | $\begin{array}{r} \text{Offsite} = 0 \\ \text{Onsite} = 0.4914 \\ \hline \text{Total} = 0.4914 \end{array}$ | 0.68 |
| "E" | $\begin{array}{r} \text{Offsite} = 0 \\ \text{Onsite} = 0.5927 \\ \hline \text{Total} = 0.5927 \end{array}$ | 0.68 |
| "F" | $\begin{array}{r} \text{Offsite} = 0 \\ \text{Onsite} = 0.1645 \\ \hline \text{Total} = 0.1645 \end{array}$ | 0.56 |
| "G" | $\begin{array}{r} \text{Offsite} = 0 \\ \text{Onsite} = 0.0398 \\ \hline \text{Total} = 0.0398 \end{array}$ | 0.21 |

Total Area onsite = 5.4361

Total Area Offsite = 0.4573

Rainfall Intensity

$T_c = 10 \text{ Minutes all areas "A" through "G"}$
 $\therefore I_{100} = (2.2)(6.84)(10)^{-0.51} = 4.65$
 and $I_{10} = (4.65)(0.657) = 3.05$

Drainage Area Peak Runoff ($Q = CIA$)

D. A. "A" (Includes 0.10 Ac. offsite undeveloped area)

1. Exist. Condition ($C = 0.35$)

$$Q_{100} = (0.35)(4.65)(0.3589) = 0.58 \text{ cfs}$$

$$Q_{10} = (0.35)(3.05)(0.3589) = 0.38 \text{ cfs}$$

2. Developed Condition ($C = 0.31$)

$$Q_{100} = (0.31)(4.65)(0.3589) = 0.51 \text{ cfs}$$

$$Q_{10} = (0.31)(3.05)(0.3589) = 0.34 \text{ cfs}$$

D. A. "B" (includes 0.182 Ac. offsite undeveloped area)

1. Exist. Condition ($C = 0.35$)

$$Q_{100} = (0.35)(4.65)(1.2171) = 1.98 \text{ cfs}$$

$$Q_{10} = (0.35)(3.05)(1.2171) = 1.29 \text{ cfs}$$

2. Developed Condition ($C = 0.67$)

$$Q_{100} = (0.67)(4.65)(1.2171) = 3.79 \text{ cfs}$$

$$Q_{10} = (0.67)(3.05)(1.2171) = 2.48 \text{ cfs}$$

WILLIAM MATOTAN & ASSOCIATES, INC.
ENGINEERS
230 Truman Street, N.E. - Albuquerque, N.M. 87108
Telephone 265-8467

Project CASA SANDIA HTS. Sheet 8 of 9
Subject: Drainage Study Job No. 720
Comp. by REP Date 7 Mar. 54 Chk'd ✓ Date 7 Mar.

Drainage Area Peak Runoff (Cont'd)

D.A. "C" (Includes 0.1749 acres offsite undeveloped area)

1. Exist. Condition ($C=0.35$)

$$Q_{100} = (0.35)(4.65)(3.029) = 4.93 \text{ cfs}$$

$$Q_{10} = (0.35)(3.05)(3.029) = 3.23 \text{ cfs}$$

2. Developed Condition

$$Q_{100} = (0.67)(4.65)(3.029) = 9.44 \text{ cfs}$$

$$Q_{10} = (0.67)(3.05)(3.029) = 6.19 \text{ cfs}$$

D.A. "D" (No offsite flows contribute to this area)

1. Exist. Condition ($C=0.35$)

$$Q_{100} = (0.35)(4.65)(0.4914) = 0.80 \text{ cfs}$$

$$Q_{10} = (0.35)(3.05)(0.4914) = 0.52 \text{ cfs}$$

2. Developed Condition ($C=0.68$)

$$Q_{100} = (0.68)(4.65)(0.4914) = 1.55 \text{ cfs}$$

$$Q_{10} = (0.68)(3.05)(0.4914) = 1.02 \text{ cfs}$$

D.A. "E" (No offsite flows contribute to this area)

1. Exist. Condition ($C=0.35$)

$$Q_{100} = (0.35)(4.65)(0.5927) = 0.96 \text{ cfs}$$

$$Q_{10} = (0.35)(3.05)(0.5927) = 0.63 \text{ cfs}$$

2. Developed Condition ($C=0.68$)

$$Q_{100} = (0.68)(4.65)(0.5927) = 1.87 \text{ cfs}$$

$$Q_{10} = (0.68)(3.05)(0.5927) = 1.23 \text{ cfs}$$

Drainage Area Peak Runoff (Cont'd)

D. A. "F" (No offsite flows contribute to this area)

1. Exist. Condition (C=0.35)

$$Q_{100} = (0.35)(4.65)(0.1645) = 0.27 \text{ cfs}$$

$$Q_{10} = (0.35)(3.05)(0.1645) = 0.18 \text{ cfs}$$

2. Developed Condition (C=0.56)

$$Q_{100} = (0.56)(4.65)(0.1645) = 0.43 \text{ cfs}$$

$$Q_{10} = (0.56)(3.05)(0.1645) = 0.28 \text{ cfs}$$

D. A. "G" (No offsite flows contribute to this area)

1. Exist. Condition (C=0.35)

$$Q_{100} = (0.35)(4.65)(0.0398) = 0.06 \text{ cfs}$$

$$Q_{10} = (0.35)(3.05)(0.0398) = 0.04 \text{ cfs}$$

2. Developed Condition (C=0.21)

$$Q_{100} = (0.21)(4.65)(0.0398) = 0.04 \text{ cfs}$$

$$Q_{10} = (0.21)(3.05)(0.0398) = 0.03 \text{ cfs}$$

**STORM RUNOFF CONTRIBUTING
TO
EXISTING STORM SEWER SYSTEM NO. 129**

WILLIAM MATOTAN & ASSOCIATES, INC.
ENGINEERS
230 Truman Street, N.E. - Albuquerque, N.M. 87108
Telephone 265-8467

Project CASA SANDIA APTS. Sheet 1 of 4
Drainage Study Job No. 720
By REP Chk'd ✓ Date 12 Mar. 84

SUMMARY OF STORM RUNOFF CONTRIBUTING TO
EXISTING STORM SEWER SYSTEM NO. 129

Drainage Area Existing Conditions (except Casa Sandia Project site considered 100% developed)

| | <u>Q₁₀</u> | <u>Q₁₀₀</u> |
|------------------|-----------------------|------------------------|
| #1 | 27 | 41 |
| #2 | 44 | 67 |
| #3 | 12 | 18 |
| #4 | <u>8</u> | <u>12</u> |
| TOTALS* (cfs) | <u>91</u> | <u>138</u> |

* Rounded to 1 cfs unit.

WILLIAM MATOTAN & ASSOCIATES, INC.
ENGINEERS
230 Truman Street, N.E. - Albuquerque, N.M. 87108
Telephone 265-8467

Project CASA SANDIA APTS. Sheet 2 of 4
Subject: Drainage Study Job No. 720
Comp. by REP Date 12 Mar. 84 Chk'd ✓ Date 12 Mar.

*Existing Storm Sewer System in Project Vicinity
Contributing Drainage Areas and Composite "C" Factors*

| <u>Drainage Area</u> | <u>Area in Acres</u> (By Planimeter 1" = 200' Topo Map) | <u>Composite "C" Factor</u> |
|--------------------------|---|-----------------------------|
| #1 | 13.61 | 0.65 * |
| #2 | 32.78 | 0.44 |
| #3 | 7.80 | 0.48 |
| #4 | 3.21 | 0.82 |
| Total Area = 57.40 Acres | | |

* CASA SANDIA APT. Project considered fully developed.

WILLIAM MATCIAN & ASSOCIATES, INC.
ENGINEERS
230 Truman Street, N.E. - Albuquerque, N.M. 87108
Telephone 265-8467

Project CNA SAUND APTS. Sheet 3 of 4
Subject: Drainage Study Job No. 720
Comp. by RED Date 12 Mar 84 Chk'd ✓ Date 12 Mar.

Existing Storm Sewer System

Time of Concentration of Contributing Drainage Areas, where $T_c = (0.0078) \left(\frac{L^{0.77}}{S^{0.385}} \right)$

D.A. #1, $L = 1100'$ $S = \frac{5116 - 5076}{1100} = 0.0364'/ft.$

$T_c = (0.0078) \left(\frac{1100^{0.77}}{0.0364^{0.385}} \right) = 6.1 \text{ Min. Use } 10 \text{ Min.}$

D.A. #2, $L = 2100'$ $S = \frac{5130 - 5074}{2100} = 0.0267'/ft.$

$T_c = (0.0078) \left(\frac{2100^{0.77}}{0.0267^{0.385}} \right) = 10.09 \text{ Min. Use } 10 \text{ Min.}$

D.A. #3, $L = 950'$ $S = \frac{5104 - 5067}{950} = 0.0389'/ft.$

$T_c = (0.0078) \left(\frac{950^{0.77}}{0.0389^{0.385}} \right) = 5.3 \text{ Min. Use } 10 \text{ Min.}$

D.A. #4, $L = 700'$ $S = \frac{5069 - 5063}{700} = 0.0086'/ft.$

$T_c = (0.0078) \left(\frac{700^{0.77}}{0.0086^{0.385}} \right) = 7.5 \text{ Min. Use } 10 \text{ Min.}$

WILLIAM MATOTAN & ASSOCIATES, INC.
ENGINEERS
230 Truman Street, N.E. - Albuquerque, N.M. 87108
Telephone 265-8467

Project CASA SANDIA APTS. Sheet 4 of 4
Subject: Drainage Study Job No. 720
Comp. by REP Date 12 Mar 84 Chk'd ✓ Date 12 Mar

PEAK RUN OFF for Drainage Areas Contributing to
Existing Storm Sewer System on
Indian School Road (System No. 129)

D.A. #1, Existing Condition (except project site
considered 100% developed). $Q = CIA$

$$Q_{10} = (0.65)(3.05)(13.61) = 26.98 \text{ cfs}$$

$$Q_{100} = (0.65)(4.65)(13.61) = 41.14 \text{ cfs}$$

D.A. #2, Existing Conditions

$$Q_{10} = (0.44)(3.05)(32.76) = 43.99 \text{ cfs}$$

$$Q_{100} = (0.44)(4.65)(32.76) = 67.07 \text{ cfs}$$

D.A. #3, Existing Conditions

$$Q_{10} = (0.48)(3.05)(7.80) = 11.42 \text{ cfs}$$

$$Q_{100} = (0.48)(4.65)(7.80) = 17.41 \text{ cfs}$$

D.A. #4, Existing Conditions

$$Q_{10} = (0.82)(3.05)(3.21) = 8.03 \text{ cfs}$$

$$Q_{100} = (0.82)(4.65)(3.21) = 12.24 \text{ cfs}$$

$$\text{Total Runoff } Q_{10} = 90.42 \text{ cfs}$$

$$\text{Total Runoff } Q_{100} = 127.86 \text{ cfs}$$

**CAPACITY
OF
EXISTING STORM SEWER SYSTEM NO. 129**

Pages A-14 thru A-30

WILLIAM MAJOTA & ASSOCIATES, INC.
ENGINEERS
230 Truman Street, N.E. - Albuquerque, N.M. 87108
Telephone 265-8467

Project CASA SANDIA
Drainage Study
By REP Chkd ✓

Sheet 1 of 15
Job No. 720
Date 21 Mar. 84

SUMMARY OF STORM SEWER INLET CAPACITIES

| <u>Inlet No.</u> | <u>Connector Pipe Capacity in cfs</u> | <u>Inlet Capacity in cfs</u> | <u>Use for Analysis - cfs</u> |
|------------------|---------------------------------------|------------------------------|-------------------------------|
| 1 | 17 | 10 | 10 |
| 2 | 52 | 43 | 43 |
| 3 | 30 | 3.5 | <u>3.5</u> |
| 4 | 36 | 15 | 15 |
| 5 | 35 | 15 | 15 |
| 6 | 33 | 15 | 15 |
| 7 | 27 | 20 | 20 |
| 8 | 17 | 48 | <u>17</u> |

Total System Inlet Capacity = 138.5 cfs

Existing Grated Inlet Capacities - In Sump Condition

Use inlet capacity analysis as outlined in
Dept. of the Army Technical Manual TM 5-820-4,
"Drainage and Erosion Control," pages 37-50

For Inlets in sag (sump) condition:

$$\text{Capacity } Q = CLH^{3/2}$$

where:

Q = Capacity in cfs

C = 3.0

L = gross perimeter of grated opening
in feet (ignoring bars and omit side
against curb for combination inlet)

H = depth of ponded water in feet

Inlet #1 = Single "D" (in driveway of Citadel Apts.)

Grate = 3'-4" x 2'

$L = (3'-4") (2) + 2' + 2' = 10.87'$

$H = 0.44'$

$Q = (3.0)(10.87)(0.44)^{3/2} = 9.5 \text{ cfs}$

Use 10 cfs

Note: Maximum available ponding at this inlet
= 0.44' which is the crown height above
the grate it. Above that depth flows
are to the west into Inlet #2.

Inlet #2 = 2 Double "C" Inlets - (Combination curb inlet
and grated gutter inlet)

Grate = 2 - 6'x10" x 2'

$L = 2(6.83') + 2' + 2' = 17.66'$

$H = 0.87'$

$Q = (3)(17.66)(0.87)^{3/2} = 42.99 \text{ cfs}$

Use 43 cfs

Inlet #B = Double "D" Inlet, grated inlet back of curb
in sump.

Grate = 6'-10" x 2'

$L = 2(6.83') + 2' + 2' = 17.66'$

$H = 0.87'$

$Q = (3)(17.66)(0.87)^{3/2} = 42.99 \text{ cfs}$

Use 43 cfs


3 of 15

22.3


GRATING CAPACITIES FOR TYPE DOUBLE "C," AND "D"



GRATING & GUTTER PLAN



TYPICAL HALF STREET SECTION (ABOVE BASIN)



D = DEPTH OF FLOW (FT.) ABOVE NORMAL GUTTER GRADE


Inlet #3 = Gutter Flow
Double "C"
S = 0.0084
Q = 3.5 cfs

4 of 15
22.3


GRATING CAPACITIES FOR TYPE DOUBLE "C," AND "D"



GRATING & GUTTER PLAN



TYPICAL HALF STREET SECTION (ABOVE BASIN)



D=DEPTH OF FLOW (FT.) ABOVE NORMAL GUTTER GRADE

Inlet #4 = Gutter Flow
S=0.0033 DIC 61-1 Type II
Q=15 cfs


5 of 15

22.3


GRATING CAPACITIES FOR TYPE DOUBLE "C," AND "D"



GRATING & GUTTER PLAN



TYPICAL HALF STREET SECTION (ABOVE BASIN)



D = DEPTH OF FLOW (FT.) ABOVE NORMAL GUTTER GRADE

Inlet #5 = Gutter Flow
Double "C"
 $s = 0.004$
 $Q = 15 \text{ cfs}$



6

6 of 15
22.3

GRATING CAPACITIES FOR TYPE DOUBLE "C," AND "D"



GRATING & GUTTER PLAN

TYPICAL HALF STREET SECTION
(ABOVE BASIN)

D = DEPTH OF FLOW (FT.) ABOVE NORMAL GUTTER GRADE

INLET #6 = gutter flow
double "C"

S = 0.004

Q = 15 cfs

7


7 of 15

22.3


GRATING CAPACITIES FOR TYPE DOUBLE "C," AND "D"



GRATING & GUTTER PLAN



TYPICAL HALF STREET SECTION (ABOVE BASIN)




D = DEPTH OF FLOW (FT.) ABOVE NORMAL GUTTER GRADE
INLET #7 = Gutter Flow
61-1 Type II
 $S = 0.015$
 $Q = 20 \text{ cfs}$

DESIGN OF SPUN CONCRETE
CONNECTOR PIPES FLOWING FULL

LENGTH (FEET)

0 25 50 75 100 125 150 175 200


Page G-35



Q = 17 cfs

D = 15"
L = 65'
H = 7.1'

74.8' # Grate
+ 0.87 Top Curb
75.74 = El. W.S. 100



Inlet #1

Inlet Capacity Q = 10 cfs < Connector Pipe Q = 17 cfs.
∴ Use Inlet Capacity of 10 cfs for system analysis.


A-21

DESIGN OF SPUN CONCRETE
CONNECTOR PIPES FLOWING FULL

LENGTH (FEET)

0 25 50 75 100 125 150 175 200


Page 2-35



$Q=52 \text{ cfs}$

$L=20'$

$73.93 = \# \text{ Grate}$
 $+ 0.87 \text{ Top Curb}$
 $74.80 \text{ El. W.S.}_{100}$



$\text{Inv. } 66.12$
 $@ \text{MH } 1425$
 on Univ. Blvd.
 $(\text{P.D. } 166A) 78$

Inlet #2

Inlet Capacity $Q = 43 \text{ cfs} < \text{Connector Pipe } Q = 52 \text{ cfs}$
 \therefore use Grated Inlet Capacity $Q = 43 \text{ cfs}$ for System Analysis A-22

DESIGN OF SPUN CONCRETE

CONNECTOR PIPES FLOWING FULL

El. 68.62 H.W. @ Upstream Manhole
 -5.94 Friction loss 60 cfs
 = El. 62.68 Hyd. Grade @ Manhole <
 Crown of 30" @ M.H. = El. 65.95

H

0.5

0.6

0.7

0.8

0.9

1.0

1.5

2.0

2.5

3.0

3.5

4.0

4.5

5.0

5.5

6.0

6.5

7.0

7.5

8.0

8.5

9.0

9.5

10.0

$$Q = \frac{A\sqrt{2gH}}{\sqrt{1.2 + \frac{0.021L}{D^5}}}$$

EXAMPLE

H=1.0, Q=20, L=125
 USE D=27"

Inv. 30" = 63.45

+ 2.50

Hyd. Grade = 65.95

77.43 W.S. 100

65.95 Hyd. Gr.

11.48 = H

D=18"


L=80'

H=11.48

76.56 R. Grate

+ 0.87 Top Curb

77.43 = El. W.S. 100



Inlet #3

Inv. 63.45
@ M.H. S-201

LENGTH (FEET)

0

25

50

75

100


125

150

175

200

Page G-35



78



Inlet Capacity $Q = 3.5$ cfs < Connector Pipe $Q = 30$ cfs
 \therefore USE Grated Inlet Capacity $Q = 3.5$ cfs for system analysis, A-23

DESIGN OF SPUN CONCRETE
CONNECTOR PIPES FLOWING FULL

0 25 50 75 100 125 150 175 200

LENGTH (FEET)

Page G-35



78

Inlet #4

Inlet Capacity = 15 cfs < Connector Pipe $Q = 36 \text{ cfs}$
 \therefore Use Grated Inlet Capacity, $Q = 15 \text{ cfs}$ for system analysis


A-24

12 of 15
22.3

DESIGN OF SPUN CONCRETE CONNECTOR PIPES FLOWING FULL

LENGTH (FEET)

Page G-35



Inlet #5
Inlet Capacity: $Q = 15 \text{ cfs} < \text{Connector Pipe Capacity } Q = 35 \text{ cfs}$
∴ Use Grated Inlet Capacity $Q = 15 \text{ cfs}$ for system analysis. A-25

13 of 15


22.3

DESIGN OF SPUN CONCRETE CONNECTOR PIPES FLOWING FULL

LENGTH (FEET)

0 25 50 75 100 125 150 175 200

Page G-35



Inlet #6
 Inlet capacity = 15 cfs < Connector Pipe Capacity = 33 cfs
 ∴ Use Grated Inlet Capacity $Q=15 \text{ cfs}$ for system analysis


A-26

DESIGN OF SPUN CONCRETE
CONNECTOR PIPES FLOWING FULL

LENGTH (FEET)

0 25 50 75 100 125 150 175 200

Page G-35



Inlet #7

78

Inlet capacity = 20 cfs < Connector Pipe Capacity = 27 cfs
∴ Use Grate Inlet Capacity Q = 20 cfs for system analysis.




A-27

DESIGN OF SPUN CONCRETE
CONNECTOR PIPES FLOWING FULL

LENGTH (FEET)

0 25 50 75 100 125 150 175 200

Page G-35



Inlet #8

Inlet capacity = 43 cfs > Connector Pipe Capacity Q=17 cfs
∴ Use Connector Pipe Capacity Q=17 cfs for system analysis.

A-28

WILLIAM MATOTAN & ASSOCIATES, INC.
ENGINEERS
230 Truman Street, N.E. - Albuquerque, N.M. 87108
Telephone 265-8467

Project CASA SANDIA APTS. Sheet of
Drainage Study Job No. 220
By REP Chk'd ✓ Date 27 Mar. 84

STORM SEWER SYSTEM No. 129

CAPACITY OF EXISTING 30" R.C.P. MAIN LINE

Assuming Open channel flow conditions, pipe
flowing Full. Use Mannings Formula

$$V = \frac{1.486}{n} R^{2/3} S^{1/2} \quad Q = AV$$

where: V = Velocity in fps

Q = discharge in cfs

n = coefficient of friction = 0.013

R = Area over wetted perimeter
= $4.91' / 7.85' = 0.63$ for 30" dia.

S = slope of pipe invert in feet per foot

A = cross sectional Area = $4.91'$ for 30" dia.

| M.H. to M.H. | $\frac{1.486}{n}$ | $R^{2/3}$ | S | $S^{1/2}$ | V (fps) | Q (cfs) |
|--------------|-------------------|-----------|--------|-----------|-----------|-----------|
| 1+25 | 114 | 0.73 | 0.0077 | 0.0877 | 7.3 | 35.8 |
| 5-201 | 114 | 0.73 | 0.014 | 0.1183 | 9.8 | 48.3 |
| 5-200 | 114 | 0.73 | 0.0142 | 0.1192 | 9.9 | 48.7 |
| 5-301 | 114 | 0.73 | 0.0304 | 0.1744 | 14.5 | 71.2 |
| 5-300 | 114 | 0.73 | 0.0225 | 0.1500 | 12.5 | 61.2 |

Free outlet
@ 3-120" CMP's

Note: Under flow conditions for both 100 yr.
and 10 yr. runoff, head conditions
would exist and discharge of the
30" line would be greater than
indicated above.

WILLIAM MATOTAN & ASSOCIATES, INC.
ENGINEERS
230 Truman Street, N. E. - Albuquerque, N. M. 87108
Telephone 265-8467

Project CASA SANDIA APD Sheet _____ of _____
Subject Drainage Study Job No. 720
Comp. by REP Date 22 May 87 Chk'd ✓ Date 23 Mar.

Evaluation of Friction Head Loss in Existing 30" Storm Sewer System

Using Scobey's formula for concrete pipe:

$$Q = 0.00546 C_s d^{2.625} H_f^{0.5} *$$

and

$$H_f = \left(\frac{Q}{0.00546 C_s d^{2.625}} \right)^2$$

where:

Q = Discharge in cfs

C_s = Scobey's coefficient, use 0.37 *

H_f = Loss of head in feet per 1000 feet

d = diameter of pipe in inches

| Q (cfs) | H_f (ft./1000') | H_f (ft./100') |
|-----------|-------------------|------------------|
| 20 | 1.72 | 0.172 |
| 40 | 6.89 | 0.689 |
| 60 | 15.50 | 1.550 |
| 80 | 27.57 | 2.757 |
| 100 | 43.08 | 4.308 |
| 120 | 62.04 | 6.204 |

* from "Handbook of Hydraulics" by Davis & Sorenson,
Third Edition


STREET FLOW CAPACITY

Pages A-31 thru A-34

WILLIAM MATOTAN & ASSOCIATES, INC.
ENGINEERS
230 Truman Street, N.E. - Albuquerque, N.M. 87108
Telephone 265-8467

Project CASA SANITA APTS. Sheet of
Drainage Study Job No. 220
By RSP Chk'd ✓ Date 27 Mar 84

Street Capacity - Indian School Road, 66' E to E
w/continuous left turn lane.
@ Critical cross section on West side of
Intersection, Indian School Rd. & University Blvd.,
immediately downstream from inlets #5 & #6



1. Capacity with one lane dry, westbound,
and 3 lanes dry Eastbound, max. depth of
flow 0.38' @ west curb.

$$Q = AV \text{ and } V = \frac{1.486}{0.015} R^{2/3} S^{1/2}$$

$$A = 3.99 \text{ ft}^2 \text{ wp} = 21.4' \text{ } R = \frac{3.99}{21.4} = 0.1864, R^{2/3} = 0.3245$$

$$S = 0.004, S^{1/2} = 0.0632$$

$$V = \frac{1.486}{0.015} \times 0.3245 \times 0.0632 = 2.03 \text{ fps}$$

$$Q = 3.99 \times 2.03 = \underline{8.1 \text{ cfs}}$$

Runoff contributing to this street cross section
= Area #1 (See page A-13)

$$Q_{10} = 27 \text{ cfs } Q_{100} = 41 \text{ cfs}$$

Capacity of inlets #3, 4, 5 and 6 immediately
upstream from this section = 48.5 cfs (See p. A-14)

Capacity of 30" RCP storm sewer @ above inlets
= 49 cfs (see p. A-29)

- ∴ Storm sewer capacity 49 cfs and
inlet capacity 48.5 cfs > Q_{10} 27 cfs and Q_{100} = 41 cfs
and street flow criteria not exceeded.

Street Capacity - University Blvd. 66' # to #
w/ 22' raised median.

@ Critical cross section, approximately
300' south of intersection with Indian
School Road, sag vertical curve and
inlets #1 and #2; Drainage Area #2 outfall.

From page A-13, total runoff contributing
to this section: $Q_{10} = 44 \text{ cfs}$ $Q_{100} = 67 \text{ cfs}$

From page A-14, total inlet capacity = 53 cfs


From page A-29, storm sewer capacity = 36 cfs

\therefore @ Q_{10} , 8 cfs in excess of storm sewer
capacity flowing full, gravity flow.

and

@ Q_{100} , 31 cfs in excess of storm sewer
capacity flowing full, gravity flow.


@ Q_{100} , street overflow is to the west
via an asphalt paved, inverted crown,
driveway on the south side of office
building @ 1415 University Ave.,
to storm sewer inlets #7 and #8 at the
sag vertical curve on Indian School Road,
east side of I-25 overpass. (see Plate 4)



Capacity of driveway: $Q = AV$ $V = 1.486 \cdot R^{2/3} \cdot S^{1/2}$
 $A = 10.6 \text{ ft}^2$ $R = 10.8 \text{ ft}$ $R^{2/3} = 0.45$ $R^{2/3} = 0.58$
 $S = 0.015$ $S^{1/2} = 0.12$ $V = (99)(0.58)(0.12) = 6.9 \text{ fps}$


$Q = (10.6)(6.9) = 74 \text{ cfs} > Q_{100} 31 \text{ cfs overflow}$
OK

STREET FLOW DISCHARGE ON INDIAN SCHOOL RD.
600'± WEST OF UNIVERSITY BLVD.



From page A-13, Total runoff contributing to storm sewer system at MH 5-301, D.A. #1, 2, 3 and 4: $Q_{10} = 90$ cfs $Q_{100} = 128$ cfs
From page A-29, capacity of 30" storm sewer downstream from MH 5-301 = 71 cfs (flowing full, gravity flow)
 $\therefore 71 \text{ cfs} < Q_{10}$ Peak flow by 19 cfs $\therefore Q_{10}$ 19 cfs street flow
and $71 \text{ cfs} < Q_{100}$ Peak flow by 57 cfs $\therefore Q_{100}$ 57 cfs street flow
All street flow within D.A. #1, 2, 3, 4, in excess of storm sewer capacity, drains into this sag vertical curve and thence flows north through the three curb cuts into the historic drainageway (old Indian School Road parallel roadway) thence westerly through I-25 drainage structures into historic Campus Drive drainage way on the west side of Interstate Route-25.
Note that gutter flowline on low side of street @ Inlet #7 is 0.7' higher than the gutter flowline at the low point of the sag.

CAPACITY OF HISTORIC DRAINAGEWAY (old Indian School Road paved roadway) North of Existing Indian School Road @ East side of I-25.



Critical Cross Section
@
North Side of Lodge Bldg.
Not to Scale

$$Q = AV \quad V = \frac{1.486 \cdot R^{2/3} S^{1/2}}{0.015}$$

$$A = \frac{(0.8)(60)}{2} = 24' \quad wp = 60' \quad R = \frac{24}{60} = 0.40 \quad R^{2/3} = 0.54$$


$$S = 0.0370'/ft. \quad S^{1/2} = 0.1924 \quad V = (99)(0.54)(0.1924) = 10.3 \text{ fps}$$

$$Q = (24)(10.3) = \underline{247 \text{ cfs}} > Q_{10} 19 \text{ cfs and } Q_{100} 57 \text{ cfs}$$

Street flows from drainage areas #1, 2, 3 and 4, in excess of storm sewer capacity.

Note: This drainage way is the only outlet from the sag vertical curve on Indian School Road at the east side of the I-25 overpass and drains all street flows in Drainage Areas #1, 2, 3 and 4 that are in excess of the storm sewer capacity.

PLATES




Scale 1:1

Legend
1. 10 ft
2. 10 ft
3. 10 ft
4. 10 ft
5. 10 ft
6. 10 ft
7. 10 ft
8. 10 ft
9. 10 ft
10. 10 ft
11. 10 ft
12. 10 ft
13. 10 ft
14. 10 ft
15. 10 ft
16. 10 ft
17. 10 ft
18. 10 ft
19. 10 ft
20. 10 ft
21. 10 ft
22. 10 ft
23. 10 ft
24. 10 ft
25. 10 ft
26. 10 ft
27. 10 ft
28. 10 ft
29. 10 ft
30. 10 ft
31. 10 ft
32. 10 ft
33. 10 ft
34. 10 ft
35. 10 ft
36. 10 ft
37. 10 ft
38. 10 ft
39. 10 ft
40. 10 ft
41. 10 ft
42. 10 ft
43. 10 ft
44. 10 ft
45. 10 ft
46. 10 ft
47. 10 ft
48. 10 ft
49. 10 ft
50. 10 ft
51. 10 ft
52. 10 ft
53. 10 ft
54. 10 ft
55. 10 ft
56. 10 ft
57. 10 ft
58. 10 ft
59. 10 ft
60. 10 ft
61. 10 ft
62. 10 ft
63. 10 ft
64. 10 ft
65. 10 ft
66. 10 ft
67. 10 ft
68. 10 ft
69. 10 ft
70. 10 ft
71. 10 ft
72. 10 ft
73. 10 ft
74. 10 ft
75. 10 ft
76. 10 ft
77. 10 ft
78. 10 ft
79. 10 ft
80. 10 ft
81. 10 ft
82. 10 ft
83. 10 ft
84. 10 ft
85. 10 ft
86. 10 ft
87. 10 ft
88. 10 ft
89. 10 ft
90. 10 ft
91. 10 ft
92. 10 ft
93. 10 ft
94. 10 ft
95. 10 ft
96. 10 ft
97. 10 ft
98. 10 ft
99. 10 ft
100. 10 ft

Map prepared by
JANUARY 1975

J-15-2

BERNALILLO COUNTY AND PARTS OF SANDOVAL AND VALENCIA



LEGEND

- 100 YEAR FLOOD HAZARD AREA
- 10 YEAR FLOOD HAZARD AREA
- PROPOSED FLOOD DRAINAGE IMPROVEMENTS
- ANALYSIS POINT

COMPILED BY PHOTOGRAMMETRIC METHODS FROM AERIAL PHOTOGRAPHS
TAKEN MARCH 1964, BY KODAK & POLY ENGINEERING, ALBUQUERQUE,
N.M.




CASA SANDIA
PROJECT SITE


APR 02 1964
WATER DIVISION

J-15

FLOOD HAZARD
BOUNDARY MAP
PLATE 3



ALBUQUERQUE MASTER DRAINAGE STUDY



NOTE:

1. Data shown hereon obtained from as built drawings of New Mexico Project I-025-4(29)222, SQA 166A, and field investigation. Inlet #8 not shown on available plans of record.
2. Existing curb and gutter not shown for clarity.
3. University Blvd. width is 66' E to E.
4. Indian School Road width is 66' E to E.