



FLOOD WALL
SCALE: N.T.S.

GENERAL NOTES

- ① CONSTRUCT 6" HIGH WALL TO PREVENT CROSS LOT DRAINAGE, SEE DETAIL. CONSTRUCT CONCRETE STAIRS.
- ② CONSTRUCT 6" TO 1'-4" HIGH WALL TO PREVENT CROSS LOT DRAINAGE, SEE DETAIL.

LEGEND

	EXISTING ELEVATIONS
	PROPOSED TOP OF CURB
	PROPOSED FLOWLINE
	PROPOSED TOP OF FLOOD WALL
	PROPOSED BOTTOM OF FLOOD WALL
	PROPOSED GRADE
	EXISTING CONTOUR
	FLOW DIRECTION

CAUTION:
NOTE THAT ALL EXISTING UTILITIES MAY NOT BE SHOWN. ALL EXISTING SERVICE CONNECTIONS ARE NOT SHOWN. ANY EXISTING UTILITIES THAT ARE SHOWN ARE APPROXIMATE LOCATION ONLY. IT SHALL BE THE SOLE RESPONSIBILITY OF THE CONTRACTOR TO CONTACT ALL THE UTILITY OWNERS AND TO CONDUCT ALL NECESSARY FIELD INVESTIGATIONS PRIOR TO ANY EXCAVATIONS TO DETERMINE THE ACTUAL LOCATION OF UTILITIES AND OTHER IMPROVEMENTS.

FILE: 010401 - GAHP-CRESPIN -SITE 	DRAINAGE AND GRADING PLAN FOR HIGH ST AND CRESPIN		DATE/REVISIONS:
	Applied Engineering & Surveying, Inc. 1605 BLAIR DRIVE NE ALBUQUERQUE, NEW MEXICO 87112 PH: (505)237-1456		SHEET NUMBER:
			1

