

August 26, 2010

James H. Littlejohn, P.E. Littlejohn Engineering 1935 21st Ave South Nashville, TN 37212

Re: New Mexico Donor Services, 1609 University Blvd NE,

Request for Permanent C.O.—Approved

Engineer's Stamp dated: 9-14-09, (J-15/D094)

Certification dated: 8-24-10

Dear Mr. Littlejohn,

Based upon the information provided in your submittal, received 8-26-10, the above referenced Certification is approved for a release of a Permanent Certificate of

Occupancy by Hydrology.

PO Box 1293

If you have any questions, you can contact me at 924-3695.

Albuquerque

Sincerely,

NM 87103

Curtis Cherne, P.E.


Senior Engineer, Planning Dept.

Development and Building Services

www.cabq.gov

C: CO Clerk—Katrina Sigala

File




Superintendent

2854 LOGAN STREET • NASHVILLE, IN 37211
PHONE: 615/333-5990 FAX: 615/333-7830
CELL: 614/783-8456 EMAIL: ROYMOR@AOL.COM

DRAIN/IGE AND TRANSPORTATION INFORMATION SHEET (REV 12/2005)

PROJECT TITLE: NICH HICKICO LINCY XIVVIC	
DRB#:NAEPC#:	WORK ORDER#:
CITY ADDRESS: WE LINVERSITY BIVE NE	Elfxiaucrauc. NM 87102
BNGINEERING FIRM: LAH-leichn Enancecina	CONTACT:) 1 ru L 141/6 joi y'i
ADDRESS: 1935 275 (100 XWI)	PHONE: 115-3855-1141
OWNER: D.C.1 Dance Services, Inc.	CONTACT:
ADDRESS: <u>Ligido Estret</u> CITY, STATE: <u>Nicistralió y Tigit</u>	PHONE: Luis - 37.7 - 300.1 ZIP CODE: 3.72.03
ARCHITECT: Jack. Ficcitain & (L'Edicalis	CONTACT: Track Freeinker)
ADDRESS: 211 2:21vd. (1 vc. inlov-1-1) CITY, STATE: Nacionalic Til	PHONE: しょう・ジ2句-2年
SURVEYOR: allich Laure Gerveiher Inc.	CONTACT: Tim (Ticky (France)
CITY, STATE: Cilibalque a MY	PHONE: 505.3283000
CONTRACTOR: LUIR NAGRAMAN & CITY, STATE: NASHVIHE TIN	CONTACT: PHONE: いらうういいい
DRAINAGE REPORT DRAINAGE PLAN: 1st SUBMITTAL DRAINAGE PLAN: RESUBMITTAL CONCEPTUAL G & D PLAN GRADING PLAN EROSION CONTROL PLAN ENGINEER'S CERT (HYDROLOGY) CLOMR/LOMR TRAFFIC CIRCUI ATION LAYOUT ENGINEER'S CERT (TCL) ENGINEER'S CERT (DRB SITE PLAN) OTHER (SPECIFY) SIA PRIMAGE REPORT SIA PRIMAGE PLAN: 1st SUBMITTAL S. I. S. I.	PE. OF APPROVAL SOUGHT: MINANCIAL GUARANTEE RELEASE BIJMINARY PLAT APPROVAL DIV. PLAN FOR SUB'D APPROVAL DIV. FOR BLDG. PERMIT APPROVAL EXCR PLAN APPROVAL JUNDATION PERMIT APPROVAL JUNDATION PERMIT APPROVAL RUTFICATE OF COMMAN (PERMIT) ADING PERMIT APPROVAL ADING PERMIT APPROVAL FIX ORDER APPROVAL HER (SPECIFY) AUG 2 0 2010 HYDROLOGY SECTION
CATE SUBMITTED: Lequests for approvals of Site Devel agreet Plans and/or Subdivision Plats shall be a	BY:
ention, and scope to the proposed development defines the degree of drainage details quired based on the following: 1. Conceptual Grading and Drainage Plan: Required for approval of Site Development Drainage Plans: Required for approval of Site Development Drainage Plans: Required for building permits, grading permits, paving permits. 3. Drainage Report: Required for subdivision containing more than ten (10) loss.	de Common Plans greater than five (5) acres and Sector Plans.
all Roy Wurthins In	HYDROLOGY SECTION Gut
erry Mrs. Drai	nai ,
CASIMU (1)	Cvh ():
2, 0/1911a Wtta	



DRAINAGE CERT W/ SURVEY WORK BY OTHERS

12/28/01

DRAINAGE CERTIFICATION

I, JAMES H. LITTLEJOHN, NMPE 14788 OF THE FIRM LITTLEJOHN ENGINEERING, HEREBY CERTIFY TO THE BEST OF MY KNOWLEDGE AND BELIEF THAT THIS PROJECT HAS BEEN GRADED AND WILL DRAIN IN SUBSTANTIAL COMPLIANCE WITH AND IN ACCORDANCE WITH THE DESIGN INTENT OF THE APPROVED PLAN DATED 12-15-09. THE RECORD INFORMATION EDITED ONTO THE ORIGINIAL DESIGN DOCUMENT HAS BEEN OBTAINED BY NMPS TIM ALDRICH OF THE FIRM ALDRICH LAND SURVEYING, INC. I FURTHER CERTIFY THAT A MEMBER OF THE PROJECT TEAM VISITED THE PROJECT SITE ON 8-3-2010 AND HAVE DETERMINED BY VISUAL INSPECTION THAT THE SURVEY DATA PROVIDED IS REPRESENTATIVE OF ACTUAL SITE CONDITIONS AND IS TRUE AND CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF. THIS CERTIFICATION IS SUBMITTED IN SUPPORT OF A REQUEST FOR A FINAL CERTIFICATE OF OCCUPANCY.


THE RECORD INFORMATION PRESENTED HEREON IS NOT NECESSARILY COMPLETE AND INTENDED ONLY TO VERIFY SUBSTANTIAL COMPLIANCE OF THE GRANDING AND DRAINAGE ASPECTS OF THE PROJECT. THOSE RELYING ON THIS RECORD DOCUMENT ARE ADVISED TO OBTAIN INDEPENDENT VERIFICATION OF ITS ACCURACY BEFORE USING IT FOR ANY OTHER PURPOSE.

JAMES H. LITTLEJOHN, NMPE 14788

8/24/10

DATE







September 15, 2009

James H. Littlejohn, P.E. Littlejohn Engineering Associates 1935 Twenty-First Ave South Nashville, TN 37212

Re: New Mexico Donor Services

Engineer's Stamp date 9-14-09 (J15/D094)

Dear Mr. Littlejohn,

Based upon the information provided in your submittal received 9-15-09, the above referenced plan is approved for Building Permit. Please attach a copy of this approved plan to the construction sets prior to sign-off by Hydrology.

Prior to Certificate of Occupancy release, Engineer Certification per the DPM checklist will be required.

PO Box 1293

If you have any questions, you can contact me at 924-3695.

Albuquerque

NM 87103

www.cabq.gov

Sincerely,

Curtis A. Cherne, P.E.

Cut a. Chem

Senior Engineer, Planning Dept.

Development and Building Services

C: file



AMMENDMENT 2

TO

DRAINAGE REPORT

FOR


NEW MEXICO

DONOR SERVICES

1509 University Boulevard N.E. Albuquerque, Bernalillo County, New Mexico


July 23, 2009

Amendment 1: August 27, 2009 Amendment 2: September 14, 2009



Prepared by:

Littlejohn Engineering Associates, Inc. 1935 21st Avenue South Nashville, Tennessee 37212 (615) 385-4144



HYDROLOGY SECTION New Mexico Donor Services 1509 University Boulevard N.E. Albuquerque, Bernalillo County, New Mexico Drainage Report

Overview

This 2.33± acre referenced site is located at Section 16, Township 10 North, Range 3 East, New Mexico Principal Meridian City of Albuquerque, Bernalillo County, New Mexico, tract B-1A at 1509 University Boulevard N.E. The existing site is currently an undeveloped dirt lot, and it is located in the middle of a developed area.

For this project a 15,556 sq ft donor services facility is going to be constructed along with associated sidewalks, drives, landscape areas, and storm drainage.

The runoff from the site is going to discharge to the Department of Transportation right-of-way, and the DOT has agreed that detention is not required.

Runoff Analysis

Existing Conditions

As stated previously the property is currently an undeveloped dirt lot with "poor" vegetation, and it is in the middle of a developed area. The site discharges to the drainage ditch for I-25 in the DOT right-of-way on the west side of the property. However, approximately 1.87 acres of off-site runoff drains through the site from the neighboring property to the east.

The site is located in zone 2. The entire 2.33 acres on-site area consists of land treatment C. The neighboring off-site area consists of 1.03 acres of land treatment D and 0.84 acres of land treatment C.

According to Table A-9, the peak discharge for the 100-yr storm for this site is 3.14 cfs/acre. For land treatment C and 4.70 cfs/acre for land treatment D.

Therefore, the total peak discharge, Qp, is:

Qp=(3.14 cfs/ac * 2.33 ac)+(4.70 cfs/ac * 1.03 ac)+(3.14 cfs/ac * 0.84 ac)=14.79 cfs

Proposed Conditions

When the site is developed, it will consist of approximately 1.45 acres of land treatment D and 0.88 acres of land treatment C. The offsite area will still drain through the site, and the outfall point will remain the same. Therefore, the total peak discharge, Qp, for the proposed conditions will be:

Qp=(4.70 cfs/ac *1.45 ac)+(3.14 cfs/ac *0.88 ac)+(4.70 cfs/ac *1.03 ac)+(3.14 cfs/ac *0.84 ac)=17.06 cfs

The total increase in peak discharge is 2.27 cfs. Therefore, there is very little increase of runoff for the developed site.

Pipe Sizing

The site is designed to capture runoff in underground storm sewer pipes that discharge to the state right-of-way. The storm sewer system was designed for the 100-yr storm event.

The drainage areas for each inlet are shown on Attachment 5, the Storm Sewer Drainage Area Map. The rational method was used to calculate the flow and the following table summarizes the calculations:

Inlet	Rational	Intensity	Area	Peak Flow
	Coefficient	I100	A	Q100
	C100	(in/hr)	(acres)	(cfs)
A2	0.88	5.05	0.18	0.80
A3	0.92	5.05	0.03	0.14
A4	0.87	5.05	0.10	0.44
A5	0.79	5.05	1.13	4.51
A6	0.77	5.05	0.38	1.48
B1	0.77	5.05	0.63	2.45
B2	0.92	5.05	0.34	1.58
B3	0.80	5.05	0.42	1.70
C2	0.93	5.05	0.10	0.47
C3	0.93	5.05	0.08	0.38
D2	0.93	5.05	0.08	0.38
D3	0.93	5.05	0.10	0.47

The calculated flows were modeled in StormCAD and the pipe sizes were analysed. The results from StormCAD are included as attachment 4 in this report. Standard loss coefficients were used for headloss.

Summary

In summary, this site will use underground storm sewer pipes to capture the runoff and discharge it to the ditch along I-25. The small increase in flow from the developed site is within the capacity of the drainage ditch, and therefore detention is not required.

Attachments

Attachment 1 StormCAD Calculations

Attachment 2 Storm Sewer Drainage Area Map

Attachment 1

StormCAD

Pipe Sizing Calculations

FlexTable: Conduit Table (27037_2009-09-14_calcs_re storm pipe sizing.stc)

Current Time: 0.000 min

						•											
	Label	Start	Invert	•	Stop	Invert	Leng	jth :	Slope	Diameter	Material	Manning's	Upstream	Upstream	System	System	System
		Node	(Upstrea	m)	Node	(Downstrear	n) (ft)		culated)	(in)		n	Inlet C	Inlet Area	CA	Intensity	Flow
			(ft)			(ft)		((ft/ft)					(acres)	(acres)	(in/hr)	Time
_							 		•								(min)
	P1	A6	71.	.07	A5	69.	77 :	26.0	0.050	15.0	Concrete	0.013	(N/A)	(N/A)	0.000	8.000	0.000
	P2	A5	69.	.57	A4	68.	56 10	01.0	0.010	18.0	Concrete	0.013	(N/A)	(N/A)	0.000	8.000	0.595
	P3	A4	68.	.36	A3	67.	33 10	03.0	0.010	18.0	Concrete	0.013	(N/A)	(N/A)	0.000	8.000	0.861
	P4	A3	67.	.13	A2	65.	75 1	38.0	0.010	18.0	Concrete	0.013	(N/A)	(N/A)	0.000	8.000	1.128
ļ	P5	A2	57.	.90	A1	55.	00	58.0	0.050	18.0	Concrete	0.013	(N/A)	(N/A)	0.000	8.000	1.485
1	P6	B3	70.	.94	B2	70.	49	45.0	0.010	15.0	Concrete	0.013	(N/A)	(N/A)	0.000	8.000	0.000
	P7	B2	70.	.29	B1	68.	57 1	72.0	0.010	15.0	Concrete	0.013	(N/A)	(N/A)	0.000	8.000	0.169
	P8	B1	68.	.37	A2	67.	48	59.0	0.015	15.0	Concrete	0.013	(N/A)	(N/A)	0.000	8.000	0.711
ł	P9	C3	72.	.49	C2	71.	91	58.0	0.010	6.0	PVC	0.010	(N/A)	(N/A)	0.000	8.000	0.000
	P10	C2	71.	.91	C1	70.	43	74.0	0.020	6.0	PVC	0.010	(N/A)	(N/A)	0.000	8.000	0.258
	P11	C1	70.	.43	A2	69.	14	43.0	0.030	6.0	PVC	0.010	(N/A)	(N/A)	0.000	8.000	0.468
	P12	D3	73.	.09	D2	72.	49	60.0	0.010	6.0	PVC	0.010	(N/A)	(N/A)	0.000	8.000	0.000
	P13	D2	72.	.49	D1	71.	68	54.0	0.015	6.0	PVC	0.010	(N/A)	(N/A)	0.000	8.000	0.253
	P14	D1	71	.68	A5	70.	50	59.0	0.020	6.0	PVC	0.010	(N/A)	(N/A)	0.000	8.000	0.427
	Flow	Ca	pacity	Ele	vation	Elevation	Hydraulic	Hydraulid	Cover	Cover	Velocity						
	(ft³/s)		II Flow)		ound	Ground	Grade	Grade	(Start)	(Stop)	(Average)						
	÷	(1	ft³/s)	•	Start)	(Stop)	Line (In)	Line	(ft)	(ft)	(ft/s)						
				•	(ft)	(ft)	(ft)	(Out) (ft)									
1		<u></u>	14 44		76 50	72.20	74 55	1	1 4 4 0	2 20	7.50	7					
		18	14.44		76.50		71.55	70.58		1	7.58						
	6.8	· · · · · · ·	10.50		73.30	}	70.58	69.44		1 :	6.33						
	7.2		10.50		73.70	1	69.41		1		6.42						
	7.4		10.50		74.10		68.19			4.45	6.44						
	14.8	i	23.49		71.70		59.30			1	14.05						
		70	6.46		74.50	<u> </u>	71.46		i	2.76	4.44						
	3.2		6.46		74.50	[71.02		1		5.29						
	5.7		7.93		71.90	l :	69.34	i			7.04	1					
	0.3		0.73		75.10		72.80	ł			3.75	1					
	3.0		1.03		75.75		72.36			1	5.86						
	3.0		1.26		73.05	1	70.88		1	1	6.90						
	0.4		0.73		75.50	,	73.44				3.95						
	0.8	35	0.89		75.90	75.50	72.94	72.07	' 2.91	3.32	5.18						

Page 1 of 1

1.03

75.50

73.30

72.13

70.85

2.30

5.86

3.32


0.85

Attachment 2

Storm Sewer

Drainage Area Map

- -



August 26, 2010

James H. Littlejohn, P.E. Littlejohn Engineering Associates 1935 21st Ave. South Nashville, TN 37212

Re: NM Donor Services, 1609 University Blvd NE

Permanent Certificate of Occupancy – Transportation Development

Engineer's Stamp dated 12-15-09 (J15-D094)

Certification dated 08-24-10

Dear Mr. Littlejohn,

Based upon the information provided in your submittal received 08-26-10, Transportation Development has no objection to the issuance of a Permanent Certificate of Occupancy. This letter serves as a "green tag" from Transportation Development for a Permanent Certificate of Occupancy to be issued by the Building and Safety Division.

Albuquerque

PO Box 1293

If you have any questions, you can contact me at 924-3991.

NM 87103

Kristal D. Metro, P.E.


Sincerely,

www.cabq.gov

Traffic Engineer, Planning Dept.

Development and Building Services

C: CO Clerk
File



TRAFFIC CERTIFICATION

I, <u>JAMES H. LITTLEJOHN</u>, NMPE <u>14788</u> OF THE FIRM <u>LITTLEJOHN ENGINEERING</u>, HEREBY CERTIFY TO THE BEST OF MY KNOWLEDGE AND BELIEF THAT THIS PROJECT IS IN SUBSTANTIAL COMPLIANCE WITH AND IN ACCORDANCE WITH THE DESIGN INTENT OF THE TCL APPROVED PLAN DATED 9/17/2009.

THE RECORD INFORMATION EDITED ONTO THE ORIGINAL DESIGN DOCUMENT HAS BEEN OBTAINED BY <u>TIM ALDRICH</u> OF THE FIRM <u>ALDRICH LAND SURVEYING, INC.</u> I FURTHER CERTIFY THAT A MEMBER OF THE PROJECT TEAM VISITED THE PROJECT SITE ON <u>8-3-2010</u> AND HAVE DETERMINED BY VISUAL INSPECTION THAT THE SURVEY DATA PROVIDED IS REPRESENTATIVE OF ACTUAL SITE CONDITIONS AND IS TRUE AND CORRECT TO THE BEST OF THEIR KNOWLEDGE AND BELIEF. THIS CERTIFICATION IS SUBMITTED IN SUPPORT OF A REQUEST FOR <u>A FINAL CERTIFICATE OF OCCUPANCY</u>.

THE RECORD INFORMATION PRESENTED HEREON IS NOT NECESSARILY COMPLETE AND INTENDED ONLY TO VERIFY SUBSTANTIAL COMPLIANCE OF THE TRAFFIC ASPECTS OF THIS PROJECT. THOSE RELYING ON THIS RECORD DOCUMENT ARE ADVISED TO OBTAIN INDEPENDENT VERIFICATION OF ITS ACCURACY BEFORE USING IT FOR ANY OTHER PURPOSE.

SIGNATURE OF ENGINEER OR ARCHITECT

8/24/10

DATE



j

AUG 26 2010

HYDROLOGY SECTION



August 26, 2009

James H. Littlejohn, P.E. Littlejohn Engineering Associates 1935 21st Ave. South Nashville, TN 37212

NM Donor Services, 1613 University Blvd NE, Traffic Circulation Layout Re: Engineer's Stamp dated 08-06-09 (J15-D094)

Dear Mr. Littlejohn,

Based upon the information provided in your submittal received 08-19-09, the above referenced plan cannot be approved for Building Permit until the following comments are addressed:

PO Box 1293

1. List radii for all curves shown; for passenger vehicles, the minimum end island radius is 15 feet.

Albuquerque

2. Please include two copies of the traffic circulation layout at the next submittal.

NM 87103

Provide details for all wheelchair ramps; define the maximum slope.

4. Build notes, referring to the specific city standards, must be provided for all items proposed within the right of way (sidewalk, curb cuts, etc.).

5. All wheelchair ramps located within the city right of way must have truncated domes.

www.cabq.gov

Clarify how the two-directional traffic transitions to one-directional traffic.

7. Since University Boulevard is a minor arterial roadway, a minimum radius of 20 feet is required at the entrance (see Chapter 23, Section 6, Part B of the City of Albuquerque Development Process Manual).

If you have any questions, you can contact me at 924-3991.

Sincerely,

Kristal D. Metro, P.E.

Traffic Engineer, Planning Dept. Development and Building Services

File



December 17, 2009

James H. Littlejohn, P.E. Littlejohn Engineering Associates 1935 21st Ave. South Nashville, TN 37212

Re:

NM Donor Services, 1613 University Blvd NE, Traffic Circulation Layout

Engineer's Stamp dated 12-15-09 (J15-D094)

Dear Mr. Littlejohn,

The TCL submittal received 12-16-09 is approved for Building Permit. The plan is stamped and signed as approved. A copy of this plan will be needed for each of the building permit plans. Please keep the original to be used for certification of the site for final C.O. for Transportation. Public infrastructure or work done within City Right-of-Way shown on these plans is for information only and is not part of approval. A separate DRC and/or other appropriate permits are required to construct these items.

PO Box 1293

If a temporary CO is needed, a copy of the original TCL that was stamped as approved by the City will be needed. This plan must include a statement that identifies the outstanding items that need to be constructed or the items that have not been built in "substantial compliance," as well as the signed and dated stamp of a NM registered architect or engineer. Submit this TCL with a completed <u>Drainage and Transportation Information Sheet</u> to Hydrology at the Development Services Center of Plaza Del Sol Building.

Albuquerque

When the site is completed and a final C.O. is requested, use the original City stamped approved TCL for certification. A NM registered architect or engineer must stamp, sign, and date the certification TCL along with indicating that the development was built in "substantial compliance" with the TCL. Submit this certification TCL with a completed <u>Drainage and Transportation Information Sheet</u> to Hydrology at the Development Services Center of Plaza Del Sol Building.

www.cabq.gov

NM 87103

Once verification of certification is completed and approved, notification will be made to Building Safety to issue Final C.O. To confirm that a final C.O. has been issued, call Building Safety at 924-3306.

Sincerely,

Kristal D. Metro, P.E.

Traffic Engineer, Planning Dept.

Development and Building Services

C:

File

----Original Message-----

From: Afaghpour, Reza, NMDOT <Reza.Afaghpour@state.nm.us>

To: roywor@aol.com

Cc: Crum, Aurelia, NMDOT <Aurelia.Crum@state.nm.us>

Sent: Fri, Aug 20, 2010 1:27 pm Subject: New Mexico Donor Services

NMDOT has approved the drainage for the New Mexico Donor Services site plan. There exists 1-18" CMC with riprap at outlet on the east side of I-25; this structure is acceptable. No additional work is required for this development site.

If you have any questions, please call me @ 505 490-2752. Thank you.

Reza Afaghpour, PE NMDOT Drainage Bureau


Confidentiality Notice: This e-mail, including all attachments is for the sole use of the intended recipient(s) and may contain confidential and privileged information. Any unauthorized review, use, disclosure or distribution is prohibited unless specifically provided under the New Mexico Inspection of Public Records Act. If you are not the intended recipient, please contact the sender and destroy all copies of this message. -- This email has been scanned by the Sybari - Antigen Email System.

RECENTED

AUG 2 0 2010

HYDROLOGY SECTION

DRAIN/IGE AND TRANSPORTATION IN (REV 12/2005)	VEORMATION SHEET 515/D094
PROJECT TITLE: <u> </u>	ZONE MAP: J115:-2- D9 4 WORK ORDER#:
LEGAL DESCRIPTION: See (Literalise of CITY ADDRESS: Missing ilminerating Bind No.	iquerque, NM 87102
ENGINEERING FIRM: Little je han Engineering ADDRESS: 1935 215 (100 Audin CITY, STATE: NAShunic 100 201217.	CONTACT: 11/6 joly 1 PHONE: 1115-3813-41144 ZIP CODE: 31212.
OWNER: 120-1 Dance Scrutcos, Inc. ADDRESS: 1400 Hages Street CITY, STATE: Nicotuale, 121	CONTACT: PHONE: Luis・337 - 3041 ZIP CODE: 27202
ARCHITECT: Jack Treenvery (Coecaks) ADDRESS: Zil 221d Cive Niovaly CITY, STATE: Nachville, Til	CONTACT: 付金を下ででいなの) PHONE: 1/15・329-2-12-1 ZIP CODE: 3/12/03
SURVEYOR: Cidina land Carveying Inc ADDRESS: 4100 Montgomery PAVA CITY, STATE: Cilbuquerque, 1414	CONTACT: Lim (Aldvict) PHONE: 505-328-3082 ZIP CODE: 21101
CONTRACTOR: LLN R MEGANICH & GESLEY Inc. ADDRESS: 2854 Light Stock CITY, STATE: Nashville. Till	CONTACT: PHONE: いらうさいいらい ZIP CODE: うじょり
DRAINAGE REPORT DRAINAGE PLAN: 1st SUBMITTAL DRAINAGE PLAN: 1st SUBMITTAL DRAINAGE PLAN: 1st SUBMITTAL CONCEPTUAL G & D PLAN GRADING PLAN EROSION CONTFOL PLAN ENGINEER'S CEFT (HYDROLOGY) CLOMR/LOMR TRAFFIC CIRCUI ATION LAYOUT ENGINEER'S CEFT (TCL) ENGINEER'S CEFT (DRB SITE PLAN) OTHER (SPECIFY) WOFK CONTHER	FAPPROVAL SOUGHT: IANCIAL GUARANTEE RELEASE IINARY PLAT APPROVAL PLAN FOR SUB'D APPROVAL FOR BLDG. PERMIT APPROVAL R PLAN APPROVAL PLAT APPROVAL ATION PERMIT APPROVAL NG PERMIT APPROVAL ICATE OF OCCUPANCY (PERM) ICATE OF OCCUPANCY (TEMP) NG PERMIT APPROVAL PERMIT APPROVAL ORDER APPROVAL (SAPONOTION)
WAS A PRE-DESIGN CONTERENCE ATTENDED: YESNOCOPY PROVIDED DATE SUBMITTED:	AUG 26 2010
Requests for approvals of Site Devel Rment Plans and/or Subdivision Plats shall be accomm location, and scope to the proposed development defines the degree of drainage detail. One required based on the following: 1. Conceptual Grading and Drainage Plan: Required for approval of Site Develops 2. Drainage Plans: Required for building permits, grading permits, paving permits and 3. Drainage Report: Required for subdivision containing more than ten (10) fots or of	ment Plans greater than five (5) acres and Sector Plans.
30" TEMP LRANTED FOR HYDROLOGY	w/B3-5
- KATRINA NEEDS LETTER FOR BO	
- BRAD NEEDS CONCURRENCE FR LRADINIL/ DRAINAGE PLAN FOR	
- 30 DAY JERBAL W/ KATRI	



September 17, 2009

James H. Littlejohn, P.E. Littlejohn Engineering Associates 1935 21st Ave. South Nashville, TN 37212

Re:

NM Donor Services, 1613 University Blvd NE, Traffic Circulation Layout Engineer's Stamp dated 09-08-09 (J15-D094)

Dear Mr. Littlejohn,

The TCL submittal received 09-15-09 is approved for Building Permit. The plan is stamped and signed as approved. A copy of this plan will be needed for each of the building permit plans. Please keep the original to be used for certification of the site for final C.O. for Transportation. Public infrastructure or work done within City Right-of-Way shown on these plans is for information only and is not part of approval. A separate-DRC and/or other appropriate permits are required to construct these items.

PO Box 1293

If a temporary CO is needed, a copy of the original TCL that was stamped as approved by the City will be needed. This plan must include a statement that identifies the outstanding items that need to be constructed or the items that have not been built in "substantial compliance," as well as the signed and dated stamp of a NM registered architect or engineer. Submit this TCL with a completed <u>Drainage and Transportation Information Sheet</u> to Hydrology at the Development Services Center of Plaza Del Sol Building.

Albuquerque

NM 87103

When the site is completed and a final C.O. is requested, use the original City stamped approved TCL for certification. A NM registered architect or engineer must stamp, sign, and date the certification TCL along with indicating that the development was built in "substantial compliance" with the TCL. Submit this certification TCL with a completed <u>Drainage and Transportation Information Sheet</u> to Hydrology at the Development Services Center of Plaza

Del Sol Building.

www.cabq.gov

Once verification of certification is completed and approved, notification will be made to Building Safety to issue Final C.O. To confirm that a final C.O. has been issued, call Building Safety at 924-3306.

Sincerely,

Kristal D. Metro, P.E.

Traffic Engineer, Planning Dept.

Development and Building Services

C:

File

5/5

AMMENDMENT 2

TO

DRAINAGE REPORT

FOR


NEW MEXICO

DONOR SERVICES

1509 University Boulevard N.E. Albuquerque, Bernalillo County, New Mexico


July 23, 2009

Amendment 1: August 27, 2009 Amendment 2: September 14, 2009



Prepared by:

Littlejohn Engineering Associates, Inc. 1935 21st Avenue South Nashville, Tennessee 37212 (615) 385-4144



New Mexico Donor Services 1509 University Boulevard N.E. Albuquerque, Bernalillo County, New Mexico Drainage Report

Overview

This 2.33± acre referenced site is located at Section 16, Township 10 North, Range 3 East, New Mexico Principal Meridian City of Albuquerque, Bernalillo County, New Mexico, tract B-1A at 1509 University Boulevard N.E. The existing site is currently an undeveloped dirt lot, and it is located in the middle of a developed area.

For this project a 15,556 sq ft donor services facility is going to be constructed along with associated sidewalks, drives, landscape areas, and storm drainage.

The runoff from the site is going to discharge to the Department of Transportation right-of-way, and the DOT has agreed that detention is not required.

Runoff Analysis

Existing Conditions

As stated previously the property is currently an undeveloped dirt lot with "poor" vegetation, and it is in the middle of a developed area. The site discharges to the drainage ditch for I-25 in the DOT right-of-way on the west side of the property. However, approximately 1.87 acres of off-site runoff drains through the site from the neighboring property to the east.

The site is located in zone 2. The entire 2.33 acres on-site area consists of land treatment C. The neighboring off-site area consists of 1.03 acres of land treatment D and 0.84 acres of land treatment C.

According to Table A-9, the peak discharge for the 100-yr storm for this site is 3.14 cfs/acre. For land treatment C and 4.70 cfs/acre for land treatment D.

Therefore, the total peak discharge, Qp, is:

Qp=(3.14 cfs/ac * 2.33 ac)+(4.70 cfs/ac * 1.03 ac)+(3.14 cfs/ac * 0.84 ac)=14.79 cfs

Proposed Conditions

When the site is developed, it will consist of approximately 1.45 acres of land treatment D and 0.88 acres of land treatment C. The offsite area will still drain through the site, and the outfall point will remain the same. Therefore, the total peak discharge, Qp, for the proposed conditions will be:

Qp=(4.70 cfs/ac *1.45 ac)+(3.14 cfs/ac *0.88 ac)+(4.70 cfs/ac *1.03 ac)+(3.14 cfs/ac *0.84 ac)=17.06 cfs

The total increase in peak discharge is 2.27 cfs. Therefore, there is very little increase of runoff for the developed site.

Pipe Sizing

The site is designed to capture runoff in underground storm sewer pipes that discharge to the state right-of-way. The storm sewer system was designed for the 100-yr storm event.

The drainage areas for each inlet are shown on Attachment 5, the Storm Sewer Drainage Area Map. The rational method was used to calculate the flow and the following table summarizes the calculations:

Inlet	Rational	Intensity	Area	Peak Flow
	Coefficient	I100	Α	Q100
	C100	(in/hr)	(acres)	(cfs)
A2	0.88	5.05	0.18	0.80
A3	0.92	5.05	0.03	0.14
A4	0.87	5.05	0.10	0.44
A5	0.79	5.05	1.13	4.51
A6	0.77	5.05	0.38	1.48
B1	0.77	5.05	0.63	2.45
B2	0.92	5.05	0.34	1.58
B3	0.80	5.05	0.42	1.70
C2	0.93	5.05	0.10	0.47
C3	0.93	5.05	0.08	0.38
D2	0.93	5.05	0.08	0.38
D3	0.93	5.05	0.10	0.47

The calculated flows were modeled in StormCAD and the pipe sizes were analysed. The results from StormCAD are included as attachment 4 in this report. Standard loss coefficients were used for headloss.

Summary

In summary, this site will use underground storm sewer pipes to capture the runoff and discharge it to the ditch along I-25. The small increase in flow from the developed site is within the capacity of the drainage ditch, and therefore detention is not required.

Attachments

Attachment 1 StormCAD Calculations

Attachment 2 Storm Sewer Drainage Area Map

Attachment 1

StormCAD

Pipe Sizing Calculations

FlexTable: Conduit Table (27037_2009-09-14_calcs_re storm pipe sizing.stc)

Current Time: 0.000 min

Label Start Invert Node (Upstream) Node (Downstream) (ft) (ft) (Tft) (Tf	0.595 0.861 1.128 1.485 0.000 0.169 0.711 0.000 0.258
P1	Time (min) 0.000 0.595 0.861 1.128 1.485 0.000 0.169 0.711 0.000 0.258
P1	0.000 0.595 0.861 1.128 1.485 0.000 0.169 0.711 0.000 0.258
P2 A5 69.57 A4 68.56 101.0 0.010 18.0 Concrete 0.013 (N/A) (N/A) 0.000 8.000 P3 A4 68.36 A3 67.33 103.0 0.010 18.0 Concrete 0.013 (N/A) (N/A) 0.000 8.000 P4 A3 67.13 A2 65.75 138.0 0.010 18.0 Concrete 0.013 (N/A) (N/A) 0.000 8.000 P5 A2 57.90 A1 55.00 58.0 0.050 18.0 Concrete 0.013 (N/A) (N/A) 0.000 8.000 P6 B3 70.94 B2 70.49 45.0 0.010 15.0 Concrete 0.013 (N/A) (N/A) 0.000 8.000 P7 B2 70.29 B1 68.57 172.0 0.010 15.0 Concrete 0.013 (N/A) (N/A) 0.000 8.000 P8 B1 68.37 A2 67.48 59.0 0.015 15.0 Concrete 0.013 (N/A) (N/A) 0.000 8.000 P9 C3 72.49 C2 71.91 58.0 0.010 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.000 P10 C2 71.91 C1 70.43 74.0 0.020 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.000 P11 C1 70.43 A2 69.14 43.0 0.030 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.000 P12 D3 73.09 D2 72.49 60.0 0.010 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.000 P13 D2 72.49 D1 71.68 54.0 0.015 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.000 P13 D2 72.49 D1 71.68 54.0 0.015 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.000 P13 D2 72.49 D1 71.68 54.0 0.015 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.000 P13 D2 72.49 D1 71.68 54.0 0.015 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.000 P14 D1 71.68 A5 70.50 59.0 0.020 6.0 PVC 0.010 (N/A) (N/A) (N/A) 0.000 8.000 P14 D1 71.68 A5 70.50 59.0 0.020 6.0 PVC 0.010 (N/A) (N/A) (N/A) 0.000 8.000 P14 D1 71.68 A5 70.50 59.0 0.020 6.0 PVC 0.010 (N/A) (N/A) (N/A) 0.000 8.000 P14 D1 71.68 A5 70.50 59.0 0.020 6.0 PVC 0.010 (N/A) (N/A) (N/A) 0.000 8.000 P14 D1 71.68 A5 70.50 59.0 0.020 6.0 PVC 0.010 (N/A) (N/A) (N/A) 0.000 8.000 P14 D1 71.68 A5 70.50 59.0 0.020 6.0 PVC 0.010 (N/A) (N/A) (N/A) 0.000 8.000 P14 D1 71.68 A5 70.50 59.0 0.020 6.0 PVC 0.010 (N/A) (N/A) (N/A) 0.000 8.000 P14 D1 71.68 A5 70.50 59.0 0.020 6.0 PVC 0.010 (N/A) (N/A) (N/A) 0.000 8.000 P14 D1 71.68 A5 70.50 59.0 0.020 6.0 PVC 0.010 (N/A) (N/A) (N/A) 0.000 8.000 P14 D14 P14 D1 P14 P14 D1 P14 P14 P14 P14 P14 P14 P14 P14 P14 P1	0.000 0.595 0.861 1.128 1.485 0.000 0.169 0.711 0.000 0.258
P2 A5 69.57 A4 68.56 101.0 0.010 18.0 Concrete 0.013 (N/A) (N/A) 0.000 8.000 P3 A4 68.36 A3 67.33 103.0 0.010 18.0 Concrete 0.013 (N/A) (N/A) 0.000 8.000 P4 A3 67.13 A2 65.75 138.0 0.010 18.0 Concrete 0.013 (N/A) (N/A) 0.000 8.000 P5 A2 57.90 A1 55.00 58.0 0.050 18.0 Concrete 0.013 (N/A) (N/A) 0.000 8.000 P6 B3 70.94 B2 70.49 45.0 0.010 15.0 Concrete 0.013 (N/A) (N/A) 0.000 8.000 P7 B2 70.29 B1 68.57 172.0 0.010 15.0 Concrete 0.013 (N/A) (N/A) 0.000 8.000 P8 B1 68.37 A2 67.48 59.0 0.015 15.0 Concrete 0.013 (N/A) (N/A) 0.000 8.000 P9 C3 72.49 C2 71.91 58.0 0.010 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.000 P10 C2 71.91 C1 70.43 74.0 0.020 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.000 P11 C1 70.43 A2 69.14 43.0 0.030 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.000 P12 D3 73.09 D2 72.49 60.0 0.010 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.000 P13 D2 72.49 D1 71.68 54.0 0.015 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.000 P13 D2 72.49 D1 71.68 54.0 0.015 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.000 P13 D2 72.49 D1 71.68 54.0 0.015 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.000 P13 D2 72.49 D1 71.68 54.0 0.015 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.000 P14 D1 71.68 A5 70.50 59.0 0.020 6.0 PVC 0.010 (N/A) (N/A) (N/A) 0.000 8.000 P14 D1 71.68 A5 70.50 59.0 0.020 6.0 PVC 0.010 (N/A) (N/A) (N/A) 0.000 8.000 P14 D1 71.68 A5 70.50 59.0 0.020 6.0 PVC 0.010 (N/A) (N/A) (N/A) 0.000 8.000 P14 D1 71.68 A5 70.50 59.0 0.020 6.0 PVC 0.010 (N/A) (N/A) (N/A) 0.000 8.000 P14 D1 71.68 A5 70.50 59.0 0.020 6.0 PVC 0.010 (N/A) (N/A) (N/A) 0.000 8.000 P14 D1 71.68 A5 70.50 59.0 0.020 6.0 PVC 0.010 (N/A) (N/A) (N/A) 0.000 8.000 P14 D1 71.68 A5 70.50 59.0 0.020 6.0 PVC 0.010 (N/A) (N/A) (N/A) 0.000 8.000 P14 D1 71.68 A5 70.50 59.0 0.020 6.0 PVC 0.010 (N/A) (N/A) (N/A) 0.000 8.000 P14 D1 71.68 A5 70.50 59.0 0.020 6.0 PVC 0.010 (N/A) (N/A) (N/A) 0.000 8.000 P14 D14 P14 D1 P14 P14 D1 P14 P14 P14 P14 P14 P14 P14 P14 P14 P1	0.595 0.861 1.128 1.485 0.000 0.169 0.711 0.000 0.258
P3 A4 68.36 A3 67.33 103.0 0.010 18.0 Concrete 0.013 (N/A) (N/A) 0.000 8.000 P4 A3 67.13 A2 65.75 138.0 0.010 18.0 Concrete 0.013 (N/A) (N/A) 0.000 8.000 P5 A2 57.90 A1 55.00 58.0 0.050 18.0 Concrete 0.013 (N/A) (N/A) 0.000 8.000 P6 B3 70.94 B2 70.49 45.0 0.010 15.0 Concrete 0.013 (N/A) (N/A) 0.000 8.000 P7 B2 70.29 B1 68.57 172.0 0.010 15.0 Concrete 0.013 (N/A) (N/A) 0.000 8.000 P8 B1 68.37 A2 67.48 59.0 0.015 15.0 Concrete 0.013 (N/A) (N/A) 0.000 8.000 P9 C3 72.49 C2 71.91 58.0 0.010 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.000 P10 C2 71.91 C1 70.43 74.0 0.020 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.000 P11 C1 70.43 A2 69.14 43.0 0.030 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.000 P12 D3 73.09 D2 72.49 60.0 0.010 6.0 PVC 0.010 (N/A) (N/A) (N/A) 0.000 8.000 P13 D2 72.49 D1 71.68 54.0 0.015 6.0 PVC 0.010 (N/A) (N/A) (N/A) 0.000 8.000 P14 D1 71.68 A5 70.50 59.0 0.020 6.0 PVC 0.010 (N/A) (N/A) (N/A) 0.000 8.000 P14 D1 71.68 A5 70.50 59.0 0.020 6.0 PVC 0.010 (N/A) (N/A) (N/A) 0.000 8.000 P14 D1 71.68 A5 70.50 59.0 0.020 6.0 PVC 0.010 (N/A) (N/A) (N/A) 0.000 8.000 P14 D1 71.68 A5 70.50 59.0 0.020 6.0 PVC 0.010 (N/A) (N/A) (N/A) 0.000 8.000 P14 D1 71.68 A5 70.50 59.0 0.020 6.0 PVC 0.010 (N/A) (N/A) (N/A) 0.000 8.000 P14 D1 71.68 A5 70.50 59.0 0.020 6.0 PVC 0.010 (N/A) (N/A) (N/A) 0.000 8.000 P14 D1 71.68 A5 70.50 59.0 0.020 6.0 PVC 0.010 (N/A) (N/A) (N/A) 0.000 8.000 P14 D1 71.68 A5 70.50 59.0 0.020 6.0 PVC 0.010 (N/A) (N/A) (N/A) 0.000 8.000 P14 D1 71.68 A5 70.50 59.0 0.020 6.0 PVC 0.010 (N/A) (N/A) (N/A) 0.000 8.000 P14 D1 71.68 A5 70.50 59.0 0.020 6.0 PVC 0.010 (N/A) (N/A) (N/A) 0.000 8.000 P14 D1 71.68 A5 70.50 59.0 0.020 6.0 PVC 0.010 (N/A) (N/A) (N/A) 0.000 8.000 P15 P14 D1 71.68 A5 70.50 59.0 0.020 6.0 PVC 0.010 (N/A) (N/A) (N/A) 0.000 8.000 P15 P14 D1 71.68 A5 70.50 59.0 0.020 6.0 PVC 0.010 (N/A) (N/A) (N/A) 0.000 8.000 P15 P14 D1 71.68 A5 70.50 59.0 0.020 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.000 P15 P14 D1 71.68 A5 70.50 59.0 0.020 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.000 P15 P14 D1 71.68 A5 70.50 59.0 0.020 6.0 PVC 0.010 (N/A) (N/A)	0.861 1.128 1.485 0.000 0.169 0.711 0.000 0.258
P4 A3 67.13 A2 65.75 138.0 0.010 18.0 Concrete 0.013 (N/A) (N/A) 0.000 8.00 P5 A2 57.90 A1 55.00 58.0 0.050 18.0 Concrete 0.013 (N/A) (N/A) 0.000 8.00 P6 B3 70.94 B2 70.49 45.0 0.010 15.0 Concrete 0.013 (N/A) (N/A) 0.000 8.00 P7 B2 70.29 B1 68.57 172.0 0.010 15.0 Concrete 0.013 (N/A) (N/A) 0.000 8.00 P8 B1 68.37 A2 67.48 59.0 0.015 15.0 Concrete 0.013 (N/A) (N/A) 0.000 8.00 P9 C3 72.49 C2 71.91 58.0 0.010 6.0 PVC 0.010 (N/A) (N/A) 0.00 8.00 P10 C2	1.128 1.485 0.000 0.169 0.711 0.000 0.258
P5 A2 57.90 A1 55.00 58.0 0.050 18.0 Concrete 0.013 (N/A) (N/A) 0.000 8.000 P6 B3 70.94 B2 70.49 45.0 0.010 15.0 Concrete 0.013 (N/A) (N/A) 0.000 8.000 P7 B2 70.29 B1 68.57 172.0 0.010 15.0 Concrete 0.013 (N/A) (N/A) 0.000 8.000 P8 B1 68.37 A2 67.48 59.0 0.015 15.0 Concrete 0.013 (N/A) (N/A) 0.000 8.000 P9 C3 72.49 C2 71.91 58.0 0.010 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.000 P10 C2 71.91 C1 70.43 74.0 0.020 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.000 P11 C1 70.43 A2 69.14 43.0 0.030 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.000 P12 D3 73.09 D2 72.49 60.0 0.010 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.000 P13 D2 72.49 D1 71.68 54.0 0.015 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.000 P13 D2 72.49 D1 71.68 54.0 0.015 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.000 P14 D1 71.68 A5 70.50 59.0 0.020 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.000 P14 D1 71.68 A5 70.50 59.0 0.020 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.000 P14 D1 71.68 A5 70.50 59.0 0.020 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.000 P14 D1 71.68 A5 70.50 59.0 0.020 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.000 P14 D1 71.68 A5 70.50 59.0 0.020 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.000 P14 D1 71.68 A5 70.50 59.0 0.020 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.000 P14 D1 71.68 A5 70.50 59.0 0.020 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.000 P14 D1 71.68 A5 70.50 59.0 0.020 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.000 P14 D1 71.68 A5 70.50 59.0 0.020 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.000 P14 D1 71.68 A5 70.50 59.0 0.020 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.000 P14 D1 71.68 A5 70.50 59.0 0.020 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.000 P14 D1 71.68 A5 70.50 59.0 0.020 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.000 P14 D1 71.68 A5 70.50 59.0 0.020 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.000 P14 D1 71.68 A5 70.50 59.0 0.020 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.000 P14 D1 71.68 A5 70.50 59.0 0.020 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.000 P14 D1 71.68 A5 70.50 59.0 0.020 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.000 P14 D1 71.68 A5 70.50 59.0 0.020 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.000 P14 D1 71.68 A5 70.50 59.0 0.020 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.000 P14 D14 D14 D14 D14 D14 D14 D14 D14 D1	1.485 0.000 0.169 0.711 0.000 0.258
P6 B3 70.94 B2 70.49 45.0 0.010 15.0 Concrete 0.013 (N/A) (N/A) 0.000 8.00 P7 B2 70.29 B1 68.57 172.0 0.010 15.0 Concrete 0.013 (N/A) (N/A) 0.000 8.00 P8 B1 68.37 A2 67.48 59.0 0.015 15.0 Concrete 0.013 (N/A) (N/A) 0.000 8.00 P9 C3 72.49 C2 71.91 58.0 0.010 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.00 P10 C2 71.91 C1 70.43 74.0 0.020 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.00 P11 C1 70.43 A2 69.14 43.0 0.030 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.00 P12 D3 73.09	0.000 0.169 0.711 0.000 0.258
P7 B2 70.29 B1 68.57 172.0 0.010 15.0 Concrete 0.013 (N/A) (N/A) 0.000 8.00 P8 B1 68.37 A2 67.48 59.0 0.015 15.0 Concrete 0.013 (N/A) (N/A) 0.000 8.00 P9 C3 72.49 C2 71.91 58.0 0.010 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.00 P10 C2 71.91 C1 70.43 74.0 0.020 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.00 P11 C1 70.43 74.0 0.020 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.00 P12 D3 73.09 D2 72.49 60.0 0.010 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.00 P13 D2 72.49 D1 71.68	0.169 0.711 0.000 0.258
P8 B1 68.37 A2 67.48 59.0 0.015 15.0 Concrete 0.013 (N/A) (N/A) 0.000 8.000 P10 C2 71.91 C1 70.43 74.0 0.020 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.000 P11 C1 70.43 A2 69.14 43.0 0.030 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.000 P12 D3 73.09 D2 72.49 60.0 0.010 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.000 P13 D2 72.49 D1 71.68 54.0 0.015 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.000 P14 D1 71.68 A5 70.50 59.0 0.020 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.000 PVC 0.010 (N/A) (N/A) 0.000 PVC 0.010 (N/A) (N/	0.711 0.000 0.258
P8 B1 68.37 A2 67.48 59.0 0.015 15.0 Concrete 0.013 (N/A) (N/A) 0.000 8.00 P9 C3 72.49 C2 71.91 58.0 0.010 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.00 P10 C2 71.91 C1 70.43 74.0 0.020 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.00 P11 C1 70.43 A2 69.14 43.0 0.030 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.00 P12 D3 73.09 D2 72.49 60.0 0.010 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.00 P13 D2 72.49 D1 71.68 54.0 0.015 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.00 P14 D1 71.68	0.000 0.258
P9 C3 72.49 C2 71.91 58.0 0.010 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.00 P10 C2 71.91 C1 70.43 74.0 0.020 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.00 P11 C1 70.43 A2 69.14 43.0 0.030 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.00 P12 D3 73.09 D2 72.49 60.0 0.010 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.00 P13 D2 72.49 D1 71.68 54.0 0.015 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.00 P14 D1 71.68 A5 70.50 59.0 0.020 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.00 Flow Capacity Elevation	0.000 0.258
P10 C2 71.91 C1 70.43 74.0 0.020 6.0 PVC 0.010 (N/A) 0.000 8.000 P11 C1 70.43 A2 69.14 43.0 0.030 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.000 P12 D3 73.09 D2 72.49 60.0 0.010 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.000 P13 D2 72.49 D1 71.68 54.0 0.015 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.000 P14 D1 71.68 A5 70.50 59.0 0.020 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.000 Flow Capacity Elevation Hydraulic Cover Cover Cover Velocity (ft³/s)s (Full Flow) Ground Ground Grade Grade (Start) (Stop)	0.258
P11	
P12 D3 73.09 D2 72.49 60.0 0.010 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.00 P13 D2 72.49 D1 71.68 54.0 0.015 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.00 P14 D1 71.68 A5 70.50 59.0 0.020 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.00 Flow Capacity Elevation Hydraulic Hydraulic Cover Cover Velocity (ft³/s) (Full Flow) Ground Ground Grade Grade (Start) (Stop) (Average)	1 -1 -1
P13 D2 72.49 D1 71.68 54.0 0.015 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.00 P14 D1 71.68 A5 70.50 59.0 0.020 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.00 Flow Capacity Elevation Hydraulic Hydraulic Cover Cover Velocity (ft³/s) (Full Flow) Ground Grade Grade (Start) (Stop) (Average)	0.000
P14 D1 71.68 A5 70.50 59.0 0.020 6.0 PVC 0.010 (N/A) (N/A) 0.000 8.00 Flow Capacity Elevation Elevation Hydraulic Hydraulic Cover Cover Velocity (ft³/s) (Full Flow) Ground Ground Grade Grade (Start) (Stop) (Average)	1
Flow Capacity Elevation Elevation Hydraulic Hydraulic Cover Cover Velocity (ft³/s) (Full Flow) Ground Ground Grade Grade (Start) (Stop) (Average)	
(ft³/s) (Start) (Stop) Line (In) Line (ft) (ft) (ft/s)	
(ft) (ft) (Out)	
(ft)	
1.48 14.44 76.50 73.30 71.55 70.58 4.18 2.28 7.58	
6.84 10.50 73.30 73.70 70.58 69.44 2.23 3.64 6.33	
7.28 10.50 73.70 74.10 69.41 68.25 3.84 5.27 6.42	
7.42 10.50 74.10 71.70 68.19 66.68 5.47 4.45 6.44	
14.80 23.49 71.70 57.50 59.30 55.91 12.30 1.00 14.05	
1.70 6.46 74.50 74.50 71.46 71.02 2.31 2.76 4.44	
3.28 6.46 74.50 71.90 71.02 69.34 2.96 2.08 5.29	
5.73 7.93 71.90 71.70 69.34 68.27 2.28 2.97 7.04	
0.38 0.73 75.10 75.75 72.80 72.36 2.11 3.34 3.75	
0.85 1.03 75.75 73.05 72.36 70.78 3.34 2.12 5.86	
0.85 1.26 73.05 71.70 70.88 69.44 2.12 2.06 6.90	
0.47 0.73 75.50 75.90 73.44 72.94 1.91 2.91 3.95	
0.85 0.89 75.90 75.50 72.94 72.07 2.91 3.32 5.18	
0.85 1.03 75.50 73.30 72.13 70.85 3.32 2.30 5.86	

Attachment 2

Storm Sewer

Drainage Area Map