## CITY OF ALBUQUERQUE

Planning Department
Brennon Williams, Director



Mayor Timothy M. Keller

April 16, 2021

Freddie Montoya, RA Freddie Montoya-Architect 2336 Sunshine Rd SW Albuquerque, NM 87XXX

Re: TI Glaz-Teck Industries 6700 Bluewater Rd NW Traffic Circulation Layout Architect's Stamp 04-15-2021 (K10-D062)

Dear Mr. Montoya,

Based upon the information provided in your submittal received 04-15-2021, the above referenced plan cannot be approved for Building Permit until the following comments are addressed:

- List the number of parking spaces required by the IDO as well as the proposed number of parking spaces including bicycle and motorcycle parking and <u>discuss with Zoning</u>.
- 2. Identify the right of way width, medians, curb cuts, and <u>street widths</u> on Airport and Bluewater Road.
- The ADA accessible spaces must include an access aisle. Van accessible aisles should be 8ft wide; all others should be 5ft wide.
- 4. The ADA accessible parking sign must have the required language per 66-7-352.4C NMSA 1978 "Violators Are Subject to a Fine and/or Towing." Please call out detail and location of signs.
- 5. ADA curb ramps must be <u>updated to current standards</u> (*Verify*) and have <u>truncated</u> domes installed at the corner of Airport and Bluewater Road.
- 6. All bicycle racks shall be designed according to the following guidelines:
  - b. The bicycle frame shall be supported horizontally at two or more places. Comb/toaster racks are not allowed.

a. The rack shall be a minimum 30 inches tall and 18 inches wide.

- c. The rack shall be designed to support the bicycle in an upright position. See the IDO for additional information.
- d. The rack allows varying bicycle frame sizes and styles to be attached.
- e. The user is not required to lift the bicycle onto the bicycle rack.
- f. Each bicycle parking space is accessible without moving another bicycle.
- 7. Bicycle racks shall be sturdy and anchored to a concrete pad.
- 8. A 1-foot clear zone around the bicycle parking stall shall be provided.
- 9. Bicycle parking spaces shall be at least 6 feet long and 2 feet wide.

PO Box 1293

Albuquerque

NM 87103

www.cabq.gov

## CITY OF ALBUQUERQUE

Planning Department Brennon Williams, Director



Mayor Timothy M. Keller

- 10. Show all drive aisle widths. Some dimensions are not shown.
- 11. The minimum drive aisle dimensions are shown below

| ii .                  | Minimum Drive Aisle Width |
|-----------------------|---------------------------|
| Two Way Traffic       | 22'                       |
| Main Circulation Road | 24'                       |
| Fire Lane             | 20'                       |

- 12. List radii for all curves shown; for passenger vehicles. Radius for delivery trucks, fire trucks, etc. is 25 ft. or larger.
- 13. Per the IDO, a 6 ft. wide ADA accessible pedestrian pathway is required from the public sidewalk to the building entrances. Please clearly show this pathway and provide details.
- 14. Per DPM, a <u>6 ft. wide ADA accessible pedestrian pathway is required from the ADA parking stall access aisles to the building entrances</u>. Please clearly show this pathway and provide details. <u>Provide a pathway from the 6ft wide ADA parking access aisle to the bldg. entrance</u>.
- 15. ADA accessible pedestrian pathway should not be placed behind parking space or adjacent to a vehicular way. Vehicle and pedestrian/wheel chair conflicts should be avoided as much as possible.
- **16.** All sidewalks along Airport Road: Provide existing width and on Bluewater Road approaching corner ADA ramp need to show the width transitions from a wider to a smaller width (**coa std dwg 2432**).
- 17. Key Note 30: Reference coa std dwg 2431.
- **18. Key Note 15:** Provide detail to ensure ADA requirements are met.
- 19. Key Note 87: Striping detail will need to be provided (color of stripe and width)
- 20. Provide a copy of refuse approval.
- 21. Please provide a sight distance exhibit
- 22. Show the clear sight triangle and add the following note to the plan: "Landscaping and signage will not interfere with clear sight requirements. Therefore, signs, walls, trees, and shrubbery between 3 and 8 feet tall (as measured from the gutter pan) will not be acceptable in the clear sight triangle.
- 23. Please specify the City Standard Drawing Number when applicable.
- 24. Unused curb cuts must be replaced with sidewalk and curb & gutter. A build note must be provided referring to the appropriate City Standard drawing (If applicable).
- 25. Add a note stating "All broken or cracked sidewalk must be replaced with sidewalk and curb & gutter." A build note must be provided referring to the appropriate City Standard drawing.
- 26. Please provide a letter of response for all comments given.

PO Box 1293

Albuquerque

NM 87103

www.cabq.gov

## CITY OF ALBUQUERQUE

Planning Department Brennon Williams, Director



Mayor Timothy M. Keller

Once corrections are complete resubmit

- 1. The Traffic Circulation Layout
- 2. A Drainage Transportation Information Sheet (DTIS)
- 3. Send an electronic copy of your submittal to PLNDRS@cabq.gov.
- 4. The \$75 re-submittal fee.

for log in and evaluation by Transportation.

If you have any questions, please contact me at (505) 924-3630.

Sincerely

Nilo \$algado-Fernandez, P.E.

Senior Traffic Engineer, Planning Dept.

**Development Review Services** 

PO Box 1293

C: CO Clerk, File

Albuquerque

NM 87103

www.cabq.gov

