CITY OF ALBUQUERQUE

Planning Department Alan Varela, Director



October 24, 2024

Ronald Bohannan, P.E. Tierra West, LLC 5571 Midway Park Place NE Albuquerque, NM 87109

RE: Skyview West

Grading & Drainage Plan

Engineer's Stamp Date: 09/25/2024 (most recent)

Hydrology File: K10D070

Dear Mr. Bohannan:

Based upon the information provided in your submittal received 10/22/2024, the Grading & Drainage Plan is approved for action by the Development Facilitation Team (DFT) on Site Plan for Building Permit and by the Development Hearing Officer (DHO) on the Preliminary Plat.

As a reminder, please prepare and provide Drainage Covenants for the detention ponds and private storm drains per Chapter 17 of the DPM prior to Permanent Release of Occupancy. Please submit on the 4th floor of Plaza de Sol. A \$25 fee will be required.

Also, if the project total area of disturbance (including the staging area and any work within the adjacent Right-of-Way) is 1 acre or more, then an Erosion and Sediment Control (ESC) Plan and Owner's certified Notice of Intent (NOI) is required to be submitted to the Stormwater Quality Engineer (Doug Hughes, PE, jhughes@cabq.gov, 505-924-3420) 14 days prior to any earth disturbance.

If you have any questions, please contact me at 505-924-3362 or <u>richardmartinez@cabq.gov</u>.

Sincerely,

Albuquerque

NM 87103

www.cabq.gov

Richard Martinez, P.E. Senior Engineer, Hydrology Planning Department

hilleult



City of Albuquerque Planning Department


Development & Building Services Division

DRAINAGE AND TRANSPORTATION INFORMATION SHEET (DTIS)

10ject 11tic.	Hydrology File #
Legal Description:	
City Address, UPC, OR Parcel:	
Applicant/Agent:	Contact:
Address:	
Email:	
Applicant/Owner:	Contact:
Address:	
Email:	
TYPE OF DEVELOPMENT: Plat (# of lots)	
RE-SUBMITTAL:	YES NO
DEPARTMENT: TRANSPORTATION	HYDROLOGY/DRAINAGE
Check all that apply under Both the Type of Submittal a	and the Type of Approval Sought:
ГҮРЕ OF SUBMITTAL:	TYPE OF APPROVAL SOUGHT:
Engineering / Architect Certification	Pad Certification
Conceptual Grading & Drainage Plan	Building Permit
Grading & Drainage Plan, and/or Drainage	Grading Permit
Report Drainage Report (Worls Order)	Paving Permit
Drainage Report (Work Order)	SO-19 Permit
Drainage Master Plan	Foundation Permit
Conditional Letter of Map Revision (CLOMR)	Certificate of Occupancy - Temp Perm
Letter of Map Revision (LOMR)	Preliminary / Final Plat
Floodplain Development Permit	Site Plan for Building Permit - DFT
Traffic Circulation Layout (TCL) – Administrative	Work Order (DRC)
Traffic Circulation Layout (TCL) – DFT	Release of Financial Guarantee (ROFG)
Approval	CLOMR / LOMR
Traffic Impact Study (TIS)	Conceptual TCL - DFT
Street Light Layout	OTHER (SPECIFY)

REV. 04/03/24

DATE SUBMITTED:



EROSION CONTROL NOTES:

ON SITE DURING CONSTRUCTION.

ACCEPTANCE OF ANY PROJECT.

OUTDOOR STORAGE AREA.

₹" GRAVEL

1. CONTRACTOR IS RESPONSIBLE FOR OBTAINING A TOPSOIL

2. CONTRACTOR IS RESPONSIBLE FOR MAINTAINING RUN-OFF

3. CONTRACTOR IS RESPONSIBLE FOR CLEANING ALL SEDIMENT

5. ALL EXPOSED EARTH SURFACES MUST BE PROTECTED FROM

6. ALL SLOPES NOT STABILIZED AT THE END OF THE PROJECT

SHALL BE STABILIZED IN ACCORDANCE WITH COA SPECS OR

STABILIZATION AND SITE DEVELOPMENT (SDP-1) PLAN FOR


PLACEMENT OF 4" CRUSHED RECYCLED ASPHALT IN

WIND AND WATER EROSION PRIOR TO FINAL (CITY)

7. REFERENCE LS-101 LANDSCAPE PLAN FOR FINAL

THAT GETS INTO EXISTING RIGHT-OF-WAY.

DISTURBANCE PERMIT PRIOR TO BEGINNING WORK.



DRAINAGE MANAGEMENT PLAN: SKYVIEW WEST WILL BE DEVELOPED WITH A 50,000 SF OFFICE-WAREHOUSE IN PHASE 1 WITH A POSSIBLE FUTURE 65,000 SF ADDITION IN PHASE 2, PARKING FACILITIES, DRIVE AISLES, DOCK AREAS AND OUTDOOR STORAGE. THE PURPOSE OF THIS SUBMITTAL IS TO PROVIDE THE DRAINAGE MANAGEMENT PLAN FOR APROVAL OF SITE PLAN, GRADING AND BUILDING PERMIT FOR PHASE 1.

THE SITE IS CURRENTLY UNDEVELOPED. UPLAND FLOWS FROM CENTRAL AVENUE AS WELL AS DEVELOPED AND UNDEVELOPED PROPERTIES ADJACENT TO CENTRAL AVENUE ENTER THE SITE AT THE NORTHWEST CORNER AND PASS THROUGH A SMALL DETENTION POND ON ITS WAY OUT THE SOUTH END OF THE PROPERTY WHERE IT IS ROUTED VIA SURFACE FLOW TO AND PICKED UP BY A STORM DRAIN IN COORS BOULEVARD. THE TOTAL UPLAND FLOWS ENTERING THE SITE TOTAL JUST UNDER 85 CFS.

THE PROPOSED ADDITION OF THE THREE DETENTION PONDS WILL CONTROL THE STORM WATER DISCHARGE FROM THIS SITE TO 0.1 CFS PER ACRE FOR ONSITE PLUS THE TOTAL UPLAND FLOWS ENTERING THE PROPERTY. THIS IS CONSISTENT WITH THE AMOLE-HUBBELL MASTER DRAINAGE PLAN WHICH GOVERNS DRAINAGE FOR THIS AREA. A TOTAL OF 86.31 CFS (84.95 CSF UPLAND FLOWS PLUS 1.36 CFS FOR ONSITE FLOWS) WILL BE RELEASED FROM THE SUBJECT PROPERTY ALONG THE HISTORIC ROUTE AT THE SOUTHERN BOUNDARY OF THE SITE. THESE FLOWS WILL BE ROUTED VIA A CONCRETE CHANNEL FROM POND NO. 2 TO THE HISTORIC LOW SPOT ALONG THE SOUTHERN BOUNDARY OF THE SITE. THE FLOWS WILL EXIT THE CHANNEL THROUGH A 50' WEIR TO AID IN CONTROLLING EROSION ON THE ADJACENT PROPERTY TO THE SOUTH.


GRAPHIC SCALE (IN FEET) 1 inch = 50 ft.

4. REPAIR OF DAMAGED FACILITIES AND CLEANUP OF SEDIMENT ACCUMULATIONS ON ADJACENT PROPERTIES AND IN PUBLIC CONCRETE CHANNEL CROSS SECTION FACILITIES IS THE RESPONSIBILITY OF THE CONTRACTOR.



CAUTION

ALL EXISTING UTILITIES SHOWN WERE OBTAINED FROM RESEARCH, AS-BUILTS, SURVEYS OR INFORMATION PROVIDED BY OTHERS. IT SHALL BE THE SOLE RESPONSIBILITY OF THE CONTRACTOR TO CONDUCT ALL NECESSARY FIELD INVESTIGATIONS PRIOR TO AND INCLUDING ANY EXCAVATION, TO DETERMINE THE ACTUAL LOCATION OF UTILITIES AND OTHER IMPROVEMENTS, PRIOR TO STARTING THE WORK. ANY CHANGES FROM THIS PLAN SHALL BE COORDINATED WITH AND APPROVED BY THE ENGINEER.



RONALD R. BOHANNAN

P.E. #7868

?'S	SKYVIEW WEST ALBUQUERQUE, NM	<i>DRAWN BY</i> pm
444	GRADING	<i>DATE</i> 10-21-24
	PLAN	DRAWING
NEW ER		SHEET #
	TIERRA WEST, LLC	GR-1

5571 MIDWAY PARK PL NE ALBUQUERQUE, NEW MEXICO 87109 (505) 858-3100 JOB # www.tierrawestllc.com 2023062

LEGEND


 BOUNDARY LINE BUILDING EXISTING CURB & GUTTER PROPOSED HYDRANT AREA INLET EXISTING SAS MH EXISTING GATE VALVE EXISTING WATERLINE EXISTING SAS — 5000— EXISTING INDEX CONTOUR EXISTING CONTOUR ------5000 PROPOSED INDEX CONTOUR DRAINAGE EASEMENT


— → 6' DESIGNER FENCE

CURB & GUTTER

NOTICE TO CONTRACTORS

- 1. AN EXCAVATION/CONSTRUCTION PERMIT WILL BE REQUIRED BEFORE BEGINNING ANY WORK WITHIN CITY RIGHT-OF-WAY.
- 2. ALL WORK DETAILED ON THESE PLANS TO BE PERFORMED, EXCEPT AS OTHERWISE STATED OR PROVIDED HERON, SHALL BE CONSTRUCTED IN ACCORDANCE WITH COA SPECIFICATIONS
- 3. TWO WORKING DAYS PRIOR TO ANY EXCAVATION, CONTRACTOR MUST CONTACT LINE LOCATING SERVICE, 765-1234, FOR LOCATION OF EXISTING UTILITIES.
- 4. PRIOR TO CONSTRUCTION, THE CONTRACTOR SHALL EXCAVATE AND VERIFY THE HORIZONTAL AND VERTICAL LOCATIONS OF ALL CONNECTIONS. SHOULD A CONFLICT EXIST, THE CONTRACTOR SHALL NOTIFY THE ENGINEER SO THAT THE CONFLICT CAN BE RESOLVED WITH A MINIMUM AMOUNT OF DELAY.
- 5. BACKFILL COMPACTION SHALL BE ACCORDING TO TRAFFIC/STREET USE.
- 6. MAINTENANCE OF THESE FACILITIES SHALL BE THE RESPONSIBILITY OF THE OWNER OF THE PROPERTY
- 7. WORK ON ARTERIAL STREETS SHALL BE PERFORMED ON A 24-HOUR BASIS.








Project: Sky View Drainage Simulation Run: Run 2


Start of Run: 01Oct2024, 00:00 End of Run: 020ct2024, 00:05 Compute Time:DATA CHANGED, RECOMPUTE Control Specifications:Control 1


Developed Basin Model: Meteorologic Model: Met 1

Show Elements: All Elements Volume Units: IN ACRE-FT Sorting: Watershed Explorer V Time of Peak Hydrologic Drainage Area Peak Discharge Volume Element (MI2) (CFS) (IN) OffSite-B1 0.02865 29.6 1 October 2024, 0... 0.92 Offsite-B2 0.01133 21.4 1 October 2024, 0... 1.73 Offsite-B5 2.1 2.31 0.00082 1 October 2024, 0... Junction-1 0.04080 53.1 1 October 2024, 0... 1.18 Offsite-B4 0.01102 18.8 1 October 2024, 0... 1.57 71.9 1 October 2024, 0... Junction-2 0.05182 1.26 Onsite-B-D 0.00046 0.4 1 October 2024, 0... 0.82 Junction-3 0.05228 72.3 1 October 2024, 0... 1.26 1 October 2024, 0... Onsite-B-E 0.00116 1.1 0.82 Junction-4 73.4 1 October 2024, 0... 1.25 0.05344 Onstie-B-B 0.00861 16.6 1 October 2024, 0... 1.72 Onsite-B-A 3.7 1 October 2024, 0... 2.08 0.00163 Onstie-B-C 0.5 1 October 2024, 0... 0.00022 2.17 Pond-1 0.06390 66.0 1 October 2024, 0... 1.33 5.3 1 October 2024, 0... 1.23 Onsite-B-F 0.00358 Offsite-B6 0.00173 2.6 1 October 2024, 0... 1.23 Onsite-B-G 2.2 1 October 2024, 0... 1.23 0.00151 Onsite-B-I 2.1 1 October 2024, 0... 1.23 0.00144 Onsite-B-H 0.6 1 October 2024, 0... 0.82 0.00068 Pond-2 74.9 1.32 0.07284 1 October 2024, 0... Outlet 0.07284 74.9 1 October 2024, 0... 1.32 Offsite-B3 65.8 1 October 2024, 0... 2.23 0.02718









VOLUME CALCULATIONS

SKYVIEW WEST

POND 1

Ab - Bottom Of The Pond Surface Area

At - Top Of The Pond Surface Area

D - Water Depth

Dt - Total Pond Depth

C - Change In Surface Area / Water Depth

ACTUAL	DEPTH	VOLUME	Q
ELEV.	(FT)	(AC-FT)	(CFS)
5080.00	0	0	0.000
5081.00	1.00	0.1017	0.000
5082.00	2.00	0.2405	0.000
5083.00	3.00	0.4165	0.000
5084.00	4.00	0.6296	53.814
5085.00	4.50	0.7500	58.950
5086.00	6.00	1.1671	72.199
5086.70	6.70	1.3904	77.612
5087.00	7.00	1.4916	79.819
5088.00	8.00	1.8533	86.773

Orifice Equation

$$Q = CA SQRT(2gH)$$

$$C = 0.6$$

Diameter (in) 36
Area (ft^2)= 7.068583471
 $g = 32.2$

H (Ft) = Depth of water above center of orifice

Q(CFS)= Flow

I

VOLUME CALCULATIONS

SKYVIEW WEST

POND 2

Ab - Bottom Of The Pond Surface Area

At - Top Of The Pond Surface Area

D - Water Depth

Dt - Total Pond Depth

C - Change In Surface Area / Water Depth

Volume =
$$Ab * D + 0.5 * C * D^2$$

 $C = (At - Ab) / Dt$
 $Ab = 1,682.00 \text{ B.O.P.} = 5080.00$
 $At = 10,922.00 \text{ T.O.P.} = 5088.00$
 $Dt = 8.00$
 $C = 1155.00$
 $Dt = 5,080.00$

ACTUAL	DEPTH	VOLUME	Q
ELEV.	(FT)	(AC-FT)	(CFS)
5080.00	0	0	0.000
5080.00	0.00	0.0000	0.000
5081.00	1.00	0.0519	0.000
5082.00	2.00	0.1303	0.000
5083.00	3.00	0.2352	0.000
5083.94	3.94	0.3579	0.000
5084.00	4.00	0.3666	0.000
5085.00	5.00	0.5245	0.000
5086.00	6.00	0.7090	0.000
5087.00	7.00	0.9199	32.380
5088.00	8.00	1.1574	86.310

Orifice Equation

$$Q = CA SQRT(2gH)$$

$$C = 0.6$$

Diameter (in) 0
Area (ft^2)= 0
 $g = 32.2$

H(Ft) = Depth of water above center of orifice

Q(CFS)= Flow

VOLUME CALCULATIONS

SKYVIEW WEST

POND 3

Ab - Bottom Of The Pond Surface Area

At - Top Of The Pond Surface Area

D - Water Depth

Dt - Total Pond Depth

C - Change In Surface Area / Water Depth

Volume =
$$Ab * D + 0.5 * C * D^2$$

 $C = (At - Ab) / Dt$
 $Ab = 4,369.00 \text{ B.O.P.} = 5084.00$
 $At = 10,692.00 \text{ T.O.P.} = 5088.00$
 $Dt = 4.00$
 $C = 1580.75$
 $B \text{ Elev.} = 5,084.00$

ACTUAL	DEPTH	VOLUME	Q
ELEV.	(FT)	(AC-FT)	(CFS)
5084.00	0	0	0.000
5084.78	0.78	0.0893	0.000
5085.00	1.00	0.1184	0.000
5086.00	2.00	0.2732	0.000
5087.00	3.00	0.4642	0.000
5088.00	4.00	0.6915	0.000

Orifice Equation


$$Q = CA SQRT(2gH)$$

$$C = 0.6$$

Diameter (in) 14
Area (ft^2)= 1.069014167
 $g = 32.2$

H(Ft) = Depth of water above center of orifice

Q (CFS)= Flow



Weighted E Method

Zone: Zone 1

Developed Onsite

		Basin Are	а				Treati	ments					100-Year	
Basin	Area	Area	Area	Treati	ment A	Treati	nent B	Treatr	nent C	Treati	nent D	Weighted E	Volume	Flow
	(sf)	(acres)	(sq miles)	%	(acres)	%	(acres)	%	(acres)	%	(acres)	(ac-ft)	(ac-ft)	cfs
Α	45,527	1.045	0.00163	0%	0.00	24%	0.25	0%	0.00	76%	0.79	1.878	0.164	3.81
В	240,162	5.513	0.00861	0%	0.00	8%	0.44	50%	2.76	42%	2.32	1.474	0.677	18.40
С	6,181	0.142	0.00022	0%	0.00	0%	0.00	25%	0.04	75%	0.11	1.918	0.023	0.54
D	12,786	0.294	0.00046	0%	0.00	100%	0.29	0%	0.00	0%	0.00	0.730	0.018	0.63
E	32,264	0.741	0.00116	0%	0.00	100%	0.74	0%	0.00	0%	0.00	0.730	0.045	1.60
Sub totals											3.22		0.926	24.99
F	99,902	2.293	0.00358	0%	0.00	0%	0.00	100%	2.29	0%	0.00	0.950	0.182	6.58
G	42,218	0.969	0.00151	0%	0.00	0%	0.00	100%	0.97	0%	0.00	0.950	0.077	2.78
Н	19,028	0.437	0.00068	0%	0.00	100%	0.44	0%	0.00	0%	0.00	0.730	0.027	0.94
I	40,200	0.923	0.00144	0%	0.00	0%	0.00	100%	0.92	0%	0.00	0.950	0.073	2.65
											0.00		0.358	12.96
J	33,722	0.774	0.00121	0%	0.00	0%	0.00	100%	0.77	0%	0.00	0.950	0.061	2.22
K	19,990	0.459	0.00072	0%	0.00	100%	0.46	0%	0.00	0%	0.00	0.730	0.028	0.99
Sub totals											0.00		0.089	3.21
TOTALS	591,980	13.59									3.22			41.16

Equations:

STORM WATER QUALITY VOLUME REQUIRED STORM WATER QUALITY VOLUME PROVIDED

4,904 CU.FT. 96,877 CU.FT.

Weighted E = Ea*Aa + Eb*Ab + Ec*Ac + Ed*Ad / (Total Area)
Volume = Weighted D * Total Area
Flow = Qa * Aa + Qb * Ab + Qc * Ac + Qd * Ad

REQUIRED	100YR,6HR		PROVIDED	IMPERV.	10-DAY	MAX	TOP OF	OVERFLOW
VOLUME	MAX Q		VOLUME	AREA (D)	VOLUME	WSE	POND	WEIR
		NORTH						
0.926	24.993	POND	1.853	3.22	1.390	5086.70	5088.00	
		DIRECT						
		DISCHA						
0.358	12.956	RGE	1.157	0.00	0.358	5083.94	5088.00	
		WEST						
0.089	3.213	POND	0.692	0.00	0.089	5084.78	5088.00	

V 10-DAY=V6HR+AD(P10DAYS-P6HR)/12 IN/FT P10DAYS = 3.90 IN P6HR = 2.17 IN Q weir = 1.6LH3/2

Weighted E Method

Zone: Zone 1

Existing Upland Basins Draining to Site

		Basin Are	а		Treatments 100-Year									
Basin	Area	Area	Area	Treatr	nent A	Treatr	nent B	Treatr	ment C	Treatr	nent D	Weighted E	Volume	Flow
	(sf)	(acres)	(sq miles)	%	(acres)	%	(acres)	%	(acres)	%	(acres)	(ac-ft)	(ac-ft)	cfs
1	798,601	18.333	0.02865	75%	13.75	0%	0.00	22%	4.03	3%	0.55	0.689	1.052	35.02
2	315,804	7.250	0.01133	0%	0.00	45%	3.26	0%	0.00	55%	3.99	1.561	0.943	23.48
3	757,620	17.393	0.02718	0%	0.00	15%	2.61	0%	0.00	85%	14.78	2.014	2.918	66.54
4	307,340	7.056	0.01102	0%	0.00	55%	3.88	0%	0.00	45%	3.18	1.410	0.829	21.46
5	22,920	0.526	0.00082	0%	0.00	10%	0.05	0%	0.00	90%	0.47	2.089	0.092	2.06
6	48,169	1.106	0.00173	0%	0.00	0%	0.00	100%	1.11	0%	0.00	0.950	0.088	3.17
7	591,980	13.590	0.02123	0%	0.00	23%	3.13	54%	7.34	23%	3.13	1.196	1.355	40.69
TOTALS	2842434.00	65.25	0.10											192.43

Equations:

Weighted E = Ea*Aa + Eb*Ab + Ec*Ac + Ed*Ad / (Total Area)

Volume = Weighted D * Total Area

Flow = Qa * Aa + Qb * Ab + Qc * Ac + Qd * Ad

Weighted E Method


Zone: Zone 1


Existing Upland Basins Draining to Site

		Basin Are	а				Treat	ments							
Basin	Area	Area	Area	Treat	ment A	Treati	ment B	Treati	ment C	Treati	ment D	Weighted E	Volume	Flow	Discharge with
	(sf)	(acres)	(sq miles)	%	(acres)	%	(acres)	%	(acres)	%	(acres)	(ac-ft)	(ac-ft)	cfs	Ponding (CFS)
1	798,601	18.333	0.02865	75%	13.75	0%	0.00	22%	4.03	3%	0.55	0.689	1.052	35.02	35.02
2	315,804	7.250	0.01133	0%	0.00	45%	3.26	0%	0.00	55%	3.99	1.561	0.943	23.48	23.48
3	757,620	17.393	0.02718	0%	0.00	15%	2.61	0%	0.00	85%	14.78	2.014	2.918	66.54	0.00
4	307,340	7.056	0.01102	0%	0.00	55%	3.88	0%	0.00	45%	3.18	1.410	0.829	21.46	21.46
5	22,920	0.526	0.00082	0%	0.00	10%	0.05	0%	0.00	90%	0.47	2.089	0.092	2.06	2.17
6	48,169	1.106	0.00173	0%	0.00	0%	0.00	100%	1.11	0%	0.00	0.950	0.088	3.17	2.83
7	591,980	13.590	0.02123	0%	0.00	23%	3.13	54%	7.34	23%	3.13	1.196	1.355	40.69	1.36
TOTALS	2842434.00	65.25	0.10											192.43	86.31

Equations:

Weighted E = Ea*Aa + Eb*Ab + Ec*Ac + Ed*Ad / (Total Area)
Volume = Weighted D * Total Area
Flow = Qa * Aa + Qb * Ab + Qc * Ac + Qd * Ad





PROJECT INFORMATION

NEW OFFICE/WAREHOUSE 7226 CENTRAL AVE., SW ALBUQUERQUE, NEW MEXICO BRUNACINI DEVELOPMENT TATE FISHBURN ARCHITECT LEGAL DESCRIPTION: TRACTS 54, 55 & 1 TOWN OF ATRISCO

GRANT UNIT 6

NO REQUIREMENT

REQUIRED 11 SPACES

CURRENT ZONING CLASSIFICATION: NR-C 13.59 ACRES **BUILDING AREA:** OFFICE 2,937 GSF WAREHOUSE PHASE 1 47,063 GSF WAREHOUSE PHASE 2 65,000 GSF 115,000 GSF

PARKING ANALYSIS: OFF-STREET PARKING 3.5:1000 = 11 SPACES

112,063 GSF

TOTAL SPACES PROVIDED 75 SPACES HANDICAP PARKING (50-100 PRVD) = REQUIRED 4 SPACE TOTAL (1 VAN) PROVIDED 4 SPACE TOTAL (1 VAN) $(1-25 \text{ RQD}) = \text{REQUIRED} \quad 1 \text{ SPACE}$ MOTORCYCLE PARKING

PROVIDED 1 SPACE 10% OF REQ'D or 3 = REQUIRED 3 SPACES PROVIDED 3 SPACES

	Curve Table									
Curve #	Length	Radius	Delta	Chord Length	Chord Direction					
C1	42.49' {42.45'}	25.00'	97'22'49"	37.56	S 59'14'35" E					
C2	39.23' {39.30'}	270.00'	819'32"	39.20'	S 06'23'24" E					
СЗ	72.75' {72.68'}	330.00'	12'37'50"	72.60'	S 08'32'33" E					
C4	76.76' {76.39'}	330.00'	13"19'36"	76.58	S 21'31'15" E					
C5	62.50' {62.50'}	270.00'	13"15'47"	62.36	S 21'33'10" E					
C6	72.89' {72.68'}	330.00'	12'39'18"	72.74	S 21"13"01" E					
C7	59.49' {59.47'}	270.00	12'37'24"	59.37	S 21"13"58" E					


	Line Table	
Line #	Direction	Length (ft)
L1	N 89'18'08" W ((N 89'48'32" W))	129.99' (130.4')
L2	N 14'33'44" W *(N 14'34'27" W)*	126.15
L3	N 14'41'34" W *(N 14'34'27" W)*	57.64' *(55.40')*
L4	N 14'03'07" W *{N 15'06' W}*	40.73'
L5	N 74.53'24" E *[N 74.53'24" E]*	40.01' *[40.00']*
L6	S 72.06'00" W (*S 71.44'20" W*)	64.65'
L7	N 14'20'05" W (*N 15'02'48" W*)	24.13' (*24.13'*)
L8	S 71"16'46" W *[S 71"44'20" W]*	40.11' *[40.06']*
L9	N 14"20'05" W (*S 15'02'48" E*)	59.86' (*60.00'*)
L10	N 14'27'22" W *{N 15'06' W}*	100.08'
L11	N 14'27'31" W	139.76'

KEYED NOTES

- 1) CONCRETE CURB, TYP.
- (2) (3) BICYCLE PARKING STALLS W/ 1' CLEAR ZONE AROUND STALL, REFER DETAIL 3/SDP-2
- 3 HC PARKING, RAMP & SIGN, REFER DETAIL 1/SDP-2
- (4) (1) 4'X20' MOTORCYCLE PARKING SPACE & SIGN, REFER DETAIL 4/SDP-1, PARKING SPACE SHALL HAVE THE LETTERS 'MC' IN CAPITAL LETTERS, EACH OF WHICH SHALL BE AT LEAST ONE FOOT HIGH AND AT LEAST 2' WIDE PLACED AT THE REAR OF THE PARKING SPACE SO AS TO BE CLOSE TO WHERE VEHICLES REAR TIRE WOULD BE PLACED
- 5) 2" ASPHALT PAVING OVER 4" BASE COURSE
- 6) SIDEWALK & RAMPS PER COA STD DWG 2430 & 2415. ALL SIDEWALKS MUST HAVE A MIN. 4' PATHWAY AROUND ALL OBSTRUCTIONS WITHIN ROW. ROW DEDICATION MAY BE REQUIRED AND ALL WORK WITHIN ROW SHALL BE DONE UNDER A CITY WORK ORDER WITH ALL INFRASTRUCTURE ITEMS PLACED ON AN INFRASTRUCTURE LIST.
- 7) ENTRANCE DRIVE PER COA STD DWG 2426
- (8) REFUSE CONTAINER LOCATION
- (9) 4" CRUSHED RECYCLED ASPHALT
- (10) 10' WIDE CONCRETE SIDEWALK
- 11) RAMPS PER COA STD DWG 2430 & 2415
- (12) CONCRETE DRIVE @ TRUCK DOCK
- (13) ELEC. TRANSFORMER LOCATION
- (16) NEW FIRE HYDRANT LOCATION (PRIVATE)
- 18 LINE OF FUTURE EXPANSION

INDEX TO DRAWINGS

SITE DEVELOPMENT PLAN SITE DETAILS **BUILDING ELEVATIONS** GRADING & DRAINAGE PLAN MASTER UTILITY PLAN LANDSCAPE PLAN





ENGINEERSEAL

PROJECT

PROJECT NO. PR-2022-007299

APPLICATION NO. SI-2024-00931-SITE PLAN-DFT

IS AN INFRASTRUCTURE LIST REQUIRED? () YES () NO IF YES, THEN A SET OF APPROVED DRC PLANS WITH A WORK ORDER IS REQUIRED FOR ANY CONSTRUCTION WITHIN PUBLIC RIGHT-OF-WAY OR FOR CONSTRUCTION OF PUBLIC IMPROVEMENTS.

DFT SITE DEVELOPMENT PLAN APPROVAL:

Ernest armyo Aug 28, 2024 TRAFFIC ENGINEER, TRANSPORTATION DIVISION Aug 29, 2024 ABCWUA Whitney Bular Aug 28, 2024 PARKS & RECREATION DEPARTMENT Aug 28, 2024

HYDROLOGY HI Plen Aug 28, 2024 CODE ENFORCEMENT

*ENVIRONMENTAL HEALTH DEPARTMENT (CONDITIONAL)

SOLID WASTE MANAGEMENT Aug 28, 2024

PLANNING DEPARTMENT *ENVIRONMENTAL HEALTH, IF NECESSARY

LEGEND

PROPERTY LINE

----- EASEMENT LINE

LANDSCAPED AREA

6' DESIGNMASTER FENCING, CLASSIC AND GATES AS NOTED SEE DETAIL 4/SDP-2

8' TALL OPAQUE FENCING AND GATES AS NOTED SEE DETAIL 4/SDP-2

PONDING PONDING AREA

SITE DISTANCE AND SITE TRIANGLE BASED ON COA DPM 7-4(I)(5)(iii) and 7-4(I)(5)(iv), LANDSCAPING AND SIGNAGE WILL NOT INTERFERE WITH CLEAR SIGHT REQUIREMENTS, THEREFORE SIGNS, WALLS, TREES, AND SHRUBBERY BETWEEN 3 AND 8 FEET TALL (AS MEASURED FROM THE GUTTER PAN) WILL NOT BE ACCEPTABLE IN THE CLEAR SITE

HANDICAP PARKING PAVEMENT MARKING

EXTERIOR LIGHT POLE LOCATION. SEE GENERAL NOTES FOR EXTERIOR LIGHTING REQUIREMENTS.

EXISTING FIRE HYDRANT GENERAL NOTES

ALBUQUERQUE IDO.

- 1. THIS SITE PLAN MEETS THE REQUIREMENTS OF THE CITY OF
- ALL SITE LIGHTING SHALL COMPLY WITH IDO SECTION 14-16-5-8. OUTDOOR AND SITE LIGHTING. PLACEMENT OF FIXTURES & STANDARDS SHALL CONFORM TO STATE &
- LOCAL SAFETY & ILLUMINATION REQUIREMENTS. 4. ALL LIGHT FIXTURES SHALL BE FULLY SHIELDED HORIZONTAL LAMPS WITH NO LIGHT, LENS OR BULB PROTRUDING BELOW THE BOTTOM OF THE CUT-OFF FIXTURE IN ORDER THAT NO FUGITIVE LIGHT SHALL
- ESCAPE BEYOND THE PROPERTY LINE AND NO SITE LIGHTING LIGHT SOURCE SHALL BE VISIBLE FRO THE SITE PERIMETER. ROOF TOP AND GROUND MOUNTED EQUIPMENT SHALL BE SCREENED FROM THE PUBLIC VIEW BY MATERIALS OF THE SAME NATURE AS THE BUILDINGS BASIC MATERIALS. THE TOP OF ALL ROOFTOP EQUIPMENT SHALL BE BELOW THE TOP OF THE PARAPET OR SCREENED FROM VIEW FROM PUBLIC RIGHTS-OF-WAY AND THE SITE ACCESS EASEMENT.
- SITE HANDICAP RAMPS SHALL BE BUILT BY COA STANDARD DRAWING 7. ALL IMPROVEMENTS LOCATED IN THE RIGHT OF WAY MUST BE

INCLUDED ON THE WORK ORDER.

AUGUST 9, 2024 1"=60'-0" OR AS NOTED

BR

SO

REVISIONS

B

DRAWING NAME SITE DEVELOPMENT

PLAN

