#### Location

The site is Lot 1, Block 18, Huning Highland Addition located at 405 Walter Street SE (southwest corner of Walter St and Lead Ave). See attached Zone Atlas page number K-14 for exact location.

The purpose of this drainage report is to present a grading and drainage solution for the proposed site. We are requesting rough grading approval, as well as building permit approval.

#### **Existing Drainage Conditions**

The site for the most part drains north to Lead Avenue at a flow rate of 0.26 cf.. From there the runoff drains west. Based on the flood plain map 35001C0334E the site does not fall within a 100-year floodplain. No offsite enters this site.

#### Proposed Conditions and On-Site Drainage Management Plan

The on-site drainage pattern will remain the same. The runoff for the most part will drain to the existing Alley to the west and then north to Lead Avenue at developed flow rate of 0.63 cfs. Only 9.50% (0.06 cfs) of the site will drain to Walter Street and then from there the runoff enters Lead Avenue. Under the developed conditions the runoff only increases by 0.36 cfs, and this increase will not have any impact on the street flow capacity nor the downstream storm sewer system.

#### **Calculations**

FINISH

City of Albuquerque, Development Process Manual, Section 22.2, Hydrology Section, was used for runoff calculations.

#### **RUNOFF CALCULATIONS** (INPUT DATA FOR AHYMO CALCULATIONS)

The site is @ Zone 2

DEPTH (INCHES) @ 100-YEAR STORM P60 = 2.01 inches

P360 = 2.35 inches

P1440 = 2.75 inches

DEPTH (INCHES) @ 10-YEAR STORM

P60 =  $2.01 \times 0.667$ = 1.34 inches

P360 = 1.57

P1440 = 1.83

#### PROPOSED LAND TREATMENT

A=0%, B=23%, C=23%, D=54%

### AHYMO INPUT FILE

* ZONE 2	***************
* 100-YEAR,	6-HR STORM (UNDER EXISITING CONDITIONS)
START RAINFALL	TIME=0.0  TYPE=1 RAIN QUARTER=0.0 IN  RAIN ONE=2.01 IN RAIN SIX=2.35 IN  RAIN DAY=2.75 IN DT=0.03333 HR
* ON-SITE COMPUTE NM HYD	ID=1 HYD NO=103.0 AREA=0.000254 SQ MI PER A=100.00 PER B=0.00 PER C=0.00 PER D=0.00 TP=0.1333 HR MASS RAINFALL=-1
******	************
* 10-YEAR, ********	6-HR STORM (UNDER EXISTING CONDITIONS)
START RAINFALL	TIME=0.0  TYPE=1 RAIN QUARTER=0.0 IN  RAIN ONE=1.34 IN RAIN SIX=1.57 IN  RAIN DAY=1.83 IN DT=0.03333 HR
* ON-SITE COMPUTE NM HYD	ID=1 HYD NO=113.0 AREA=0.000254 SQ MI PER A=100.00 PER B=0.00 PER C=0.00 PER D=0.00 TP=0.1333 HR MASS RAINFALL=-1
*****	*************
* 100-YEAR, *******	6-HR STORM (UNDER PROPOSED CONDITIONS)
START	TIME=0.0
RAINFALL	TYPE=1 RAIN QUARTER=0.0 IN RAIN ONE=2.01 IN RAIN SIX=2.35 IN RAIN DAY=2.75 IN DT=0.03333 HR
* ON-STIE	
COMPUTE NM HYD	ID=1 HYD NO=112.0 AREA=0.000254 SQ MI PER A=0.00 PER B=23.00 PER C=23.00 PER D=54.0 TP=0.1333 HR MASS RAINFALL=-1
	************
* 10-YEAR, *******	6-HR STORM (UNDER PROPOSED CONDITIONS)
START	TIME=0.0
RAINFALL	TYPE=1 RAIN QUARTER=0.0 IN RAIN ONE=1.34 IN RAIN SIX=1.57 IN RAIN DAY=1.83 IN DT=0.03333 HR
* ON-SITE	
COMPUTE NM HYD	ID=1 HYD NO=113.1 AREA=0.000254 SQ MI PER A=0.00 PER B=23.00 PER C=23.00 PER D=54.0 TP=0.1333 HR MASS RAINFALL=-1

# SUMMARY OUTPUT FILE

AHYMO PROGRAM SUMMARY TABLE (AHYMO_97) - INPUT FILE = 636  FROM TO PEAK RUNOFF RUNOFF PEAK PER PEAK PEAK PER PEAK PEAK PER PEAK PEAK PER PEAK PEAK PEAK PEAK PEAK PEAK PEAK PEAK													
HYDROGRAPH ID ID AREA DISCHARGE VOLUME RUNOFF PEAK PER COMMAND IDENTIFICATION NO. NO. (SQ MI) (CFS) (AC-FT) (INCHES) (HOURS) ACRE NOTATION  START  RAINFALL TYPE= 1  COMPUTE NM HYD 103.00 - 1 .00025 .26 .007 .53121 1.533 1.601 PER IMP= .00  RAIN6= 2.350  COMPUTE NM HYD 113.00 - 1 .00025 .06 .002 .12517 1.533 3.84 PER IMP= .00  START  RAINFALL TYPE= 1  COMPUTE NM HYD 112.00 - 1 .00025 .63 .021 1.57315 1.500 3.889 PER IMP= 54.00  START  RAINFALL TYPE= 1  COMPUTE NM HYD 112.00 - 1 .00025 .63 .021 1.57315 1.500 3.889 PER IMP= 54.00  START  RAINFALL TYPE= 1  COMPUTE NM HYD 112.00 - 1 .00025 .63 .021 1.57315 1.500 3.889 PER IMP= 54.00  RAIN6= 1.570  RAINFALL TYPE= 1  COMPUTE NM HYD 113.10 - 1 .00025 .63 .021 1.57315 1.500 RAIN6= 1.570			TABLE (	_ОМҮНА	_97) -		- -	VERSION: 199					
START  RAINFALL TYPE= 1  COMPUTE NM HYD 103.00 - 1 .00025 .26 .007 .53121 1.533 1.601 PER IMP= .00  START  RAINFALL TYPE= 1  COMPUTE NM HYD 113.00 - 1 .00025 .06 .002 .12517 1.533 .384 PER IMP= .00  START  RAINFALL TYPE= 1  COMPUTE NM HYD 112.00 - 1 .00025 .63 .021 1.57315 1.500 3.889 PER IMP= 54.00  START  RAINFALL TYPE= 1  COMPUTE NM HYD 113.10 - 1 .00025 .63 .021 1.57315 1.500 3.889 PER IMP= 54.00  RAINFALL TYPE= 1  COMPUTE NM HYD 113.10 - 1 .00025 .63 .021 1.57315 1.500 3.889 PER IMP= 54.00  RAINFALL TYPE= 1  COMPUTE NM HYD 113.10 - 1 .00025 .000 .000 .000 .000 .000 .000 .0	COMMAND			ID	ID		DISCHARGE	VOLUME		PEAK	PER		
RAINFALL TYPE= 1  COMPUTE NM HYD								•	,,	(1100110)	110111	14011111	CON
COMPUTE NM HYD 103.00 - 1 .00025 .26 .007 .53121 1.533 1.601 PER IMP= .00 TIME= .00 RAIN6= 1.570 COMPUTE NM HYD 113.00 - 1 .00025 .06 .002 .12517 1.533 .384 PER IMP= .00 RAIN6= 1.570 COMPUTE NM HYD 112.00 - 1 .00025 .63 .021 1.57315 1.500 3.889 PER IMP= 54.00 RAINFALL TYPE= 1 COMPUTE NM HYD 112.00 - 1 .00025 .63 .021 1.57315 1.500 3.889 PER IMP= 54.00 RAINFALL TYPE= 1 COMPUTE NM HYD 113.10 - 1 .00025 .00025 .000												TIME=	.00
START  RAINFALL TYPE= 1  COMPUTE NM HYD 113.00 - 1 .00025 .06 .002 .12517 1.533 1.601 PER IMP= .00  RAIN6= 1.570  START  RAINFALL TYPE= 1  COMPUTE NM HYD 112.00 - 1 .00025 .63 .021 1.57315 1.500 3.889 PER IMP= 54.00  START  RAINFALL TYPE= 1  COMPUTE NM HYD 113.10 - 1 .00025 .63 .021 1.57315 1.500 3.889 PER IMP= 54.00  RAINFALL TYPE= 1  COMPUTE NM HYD 113.10 - 1 .00025 .63 .021 1.57315 1.500 RAIN6= 1.570												RAIN6=	
RAINFALL TYPE= 1  COMPUTE NM HYD 113.00 - 1 .00025 .06 .002 .12517 1.533 .384 PER IMP= .00  START  RAINFALL TYPE= 1  COMPUTE NM HYD 112.00 - 1 .00025 .63 .021 1.57315 1.500 3.889 PER IMP= 54.00  START  RAINFALL TYPE= 1  COMPUTE NM HYD 113.10 - 1 .00025 .63 .021 1.57315 1.500 3.889 PER IMP= 54.00  RAINFALL TYPE= 1  COMPUTE NM HYD 113.10 - 1 .00025 .63 .021 0.57315 1.500 RAINFALL TYPE= 1		HYD	103.00	-	1	.00025	.26	.007	.53121	1.533	1.601	PER IMP=	.00
COMPUTE NM HYD 113.00 - 1 .00025 .06 .002 .12517 1.533 .384 PER IMP= .00 START  RAINFALL TYPE= 1  COMPUTE NM HYD 112.00 - 1 .00025 .63 .021 1.57315 1.500 3.889 PER IMP= 54.00 START  RAINFALL TYPE= 1  COMPUTE NM HYD 113.10 - 1 .00025 .63 .021 1.57315 1.500 RAIN6= 1.570		1455 1										TIME=	.00
START  RAINFALL TYPE= 1  COMPUTE NM HYD 112.00 - 1 .00025 .63 .021 1.57315 1.500 3.889 PER IMP= .00  RAIN6= 2.350  START  RAINFALL TYPE= 1  COMPUTE NM HYD			112 00		1	00005						RAIN6=	1.570
RAINFALL TYPE= 1  COMPUTE NM HYD 112.00 - 1 .00025 .63 .021 1.57315 1.500 3.889 PER IMP= 54.00  START  RAINFALL TYPE= 1  COMPUTE NM HYD 113.10 - 1 .00035 .000 .000 .000 .000 .000 .000 .0		пти	113.00	-	1	.00025	.06	.002	.12517	1.533	.384	PER IMP=	.00
COMPUTE NM HYD 112.00 - 1 .00025 .63 .021 1.57315 1.500 3.889 PER IMP= 54.00 START  RAINFALL TYPE= 1  COMPUTE NM HYD 113.10 - 1 .00025 .63 .021 1.57315 1.500 RAIN6= 1.570		VDF= 1											.00
START  RAINFALL TYPE= 1  COMPUTE NM HYD 113 10 - 1 00025 .00 .00 .00 .00 .00 .00 .00 .00 .00 .0			112 00	_	1	00025	62	001					2.350
RAINFALL TYPE= 1  COMPUTE NM HYD 113 10 - 1 20035 200 212 212 212 212 212 212 212 212 212			112.00		1	.00025	. 63	.021	1.57315	1.500	3.889		
COMPUTE NM HVD 113 10 - 1 00035 20 010		YPE= 1											
			113.10	-	1	00025	30	012	00760	1 500			
FINISH 1.500 2.327 PER IMP= 54.00					-	.00025	.30	.012	.89762	1.500	2.327	PER IMP=	54.00

#### NOTICE TO CONTRACTORS

1. AN EXCAVATION/CONSTRUCTION PERMIT WILL BE REQUIRED BEFORE BEGINNING ANY WORK WITHIN CITY RIGHT-OF-WAY.

2. ALL WORK DETAILED ON THESE PLANS TO BE PERFORMED, EXCEPT AS OTHERWISE STATED OR PROVIDED HEREON, SHALL BE CONSTRUCTED IN ACCORDANCE WITH CITY OF ALBUQUERQUE INTERIM STANDARD SPECIFICATIONS FOR PUBLIC WORKS CONSTRUCTION,

3. TWO WORKING DAYS PRIOR TO ANY EXCAVATION, CONTRACTOR MUST CONTACT NEW MEXICO ONE CALL SYSTEM AT 260-1990 FOR UTILITY LOCATING SYSTEM.

4. PRIOR TO CONSTRUCTION, THE CONTRACTOR SHALL EXCAVATE AND VERIFY THE HORIZONTAL AND VERTICAL LOCATIONS OF ALL CONSTRUCTIONS. SHOULD A CONFLICT EXIST, THE CONTRACTOR SHALL NOTIFY THE ENGINEER SO THAT THE CONFLICT CAN BE RESOLVED WITH A MINIMUM AMOUNT OF DELAY.

- 5. BACKFILL COMPACTION SHALL BE ACCORDING TO TRAFFIC/STREET USE.
- 6. MAINTENANCE OF THESE FACILITIES SHALL BE THE RESPONSIBILITY OF THE OWNER OF THE PROPERTY SERVED.
- 7. WORK ON ARTERIAL STREETS SHALL BE PERFORMED ON A 24-HOUR BASIS.

LEAD AVE.

√HW=88.00

F=4988.20

FF=4988.20 87.75

THW=88.00

PROPOSED RET. WALL \_

- PROVIDE WALL OPENINGS

18" MAX. HEADERWALL ----

(USE LANDSCAPING

RAILROAD TIES FOR

CONSTRTUCTION OF

BACK OF SD/WK (PL)

MATCH GRADE @

MATCH GRADE @ ALLEY

\_\_THE WALL)


ROUGH GRADING APPROVAL

MATCH GRADE @ PL

DATE

GRAPHIC SCALE

SCALE: 1"=20'



LEGAL DESCRIPTION: LOT 1, BLOCK 18, HUNINGS HIGHLAND ADDITION

ADDRESS:

405 WALTER ST. SE

EROSION CONTROL PLAN AND POLLUTION PREVENTION NOTES

1. CONTRACTOR IS RESPONSIBLE FOR OBTAINING A TOPSOIL DISTURBANCE PERMIT PRIOR TO BEGINNING WORK.

2. CONTRACTOR IS RESPONSIBLE FOR CLEANING ALL SEDIMENT OUT OF EXISTING RIGHT-OF-WAY.

3. CONTRACTOR IS RESPONSIBLE FOR MAINTAINING ALL STORM

RUNOFF ON SITE.

4. REPAIR OF DAMAGED FACILITIES AND CLEAN-UP OF SEDIMENT ACCUMULATION ON ADJACENT PROPERTIES AND IN PUBLIC FACILITIES IS THE RESPONSIBILITY OF THE CONTRACTOR.

5. ALL EXPOSED EARTH SURFACES MUST BE PROTECTED FROM WIND AND WATER EROSION PRIOR TO FINAL ACCEPTANCE OF ANY

6. ALL THE DISTURBED AREAS MUST BE REVEGETATED.

7. THE TOTAL DISTURBANCE ON SITE IS LESS THAN ONE ACRE

## LEGEND

CONTROL OF THE CONTRO -5102 --- EXISTING CONTOUR (MINOR) - BOUNDARY LINE

--- -- EASEMENT

---- EXISTING POWER LINES PROPOSED RETAINING WALL

EXISTING DROP INLET EXISTING POWER POLE

UTILITY PEDESTAL ELECTRICAL TRANSFORMER

TOP OF RETAINING WALL TOP OF FOOTING

THW=34.00

TOP OF HEADERWALL PROPOSED CONCRETE



ADVANCED **ENGINEERING** and CONSULTING, LLC

AUG 2 8 2006

SHAHAB BIAZAR P.E. #13479

4416 ANAHEIM AVE., NE ALBUQUERQUE, NEW MEXICO 87113

# LEAD STUDIOS

GRADING AND DRAINAGE PLAN DRAWING: DRAWN BY: DATE: 200636-GD.DWG SBB 1 OF 1

3' MAX RET. WALL PROVIDE RAILING OR GARDEN WALL AS /TW = 90.10NECESSARY (DESIGN BY OTHERS) FF=90.80 MATCH GRADE @ BACK DESIGN BY OTHERS OF SD/WK= 88.25 TF = 87.43EXISTING SD/WK

FF=4990.80

| FF=4990.80 /

SECTION A-A

N.T.S