

LEGAL DESCRIPTION: Parcela Lettered "A" and "B" in Block Numbered Thirty Eight (38) of Valley View Addition an Addition to the City of Albuquerque, NM, as the Same are Shown and Designated on the Summary Replat Thereof, Filed in the Office of the County Clerk of Bernalillo County, NM on January 18, 1984 as Documented No 84 3941 in Plat Book C23, Page 14

C-2

C2

18-85-174

WAL-MART

AND BRATH

17

GILL

- C-

KEYED NOTES

1 EXISTING TRASH ENCLOSURE TO REMAIN. INSTALL TRENCH DRAIN AT FRONT OF TRASH ENCLOSURE, REF. UTILITY PLAN, SHEET C-301.

C.T

ALLIN

CZ

C-2

VICINITY MAP - Zone Map K-17-Z

84-85 287

Ctt

The Case

CZ

62

- 2 INSTALL MEDIAN CURB/GUTTER (6" HIGH) PER COA STD DWG 24158
- 3. INSTALL PARALLEL CURB RAMP PER NMDOT STD DWCS 608-001, SHEETS 1-12. DETECTABLE WARNING SURFACE NOT REQUIRED FOR PRIVATE RAMPS. MATCH ADJACENT SIDEWALK WDTH.
- 4 INSTALL CONCRETE SIDEWALK PER COA STD DWG 2430.
- 5 ASPHALT PAVEMENT PER DETAIL, SHEET C-102.

C-1

NION C

/IEW

62

- 6 INSTALL 4" WIDE PAINT STRIPES AT 45" ANGLE TO PARKING STRIPES, SPACED AT 1'-6" (WHITE PAINT IN PARKING LOT, BLUE PAINT IN ACCESSIBLE PARKING AREAS), MIN. TWO COATS.
- 7. PAINTED INTERNATIONAL WHEELCHAIR SYMBOL (BLUE) PER ADA STANDARDS MIN. TWO COATS.
- 8 INSTALL H/C SIGNAGE PER DETAIL, SHEET C-102, ADD VAN ACCESSIBLE SIGNAGE WHERE NOTED. SIGNAGE SHALL BE MOUNTED TO BUILDING, H/C SIGN MUST INCLUDE LANGUAGE PER 66-7-352.4C NMSA 1978 MOLATORS ARE SUBJECT TO A FINE AND/OR TOWING."
- S INSTALL 4" WIDE PAINT STRIPES (WHITE) FOR ALL PARKING SPACES. MIN. TWO

10 PAINT WORDS 'NO PARKING' WITH LETTERS AT LEAST ONE FOOT HIGH AND 2 INCHES WIDE. MIN. TWO COATS.

11. INSTALL BIKE RACK PER DETAIL ON SHEET C-102. THREE (3) SPACES MINIMUM

12. MOTORCYCLE PARKING; 2 SPACES, ADD PAINT LABEL (2 COATS) AND SIGNAGE PER COA CODE. SIGN DETAIL ON SHEET C-102.

13. INSTALL PRE-CAST WHEEL STOP PER DETAIL, SHEET C-102 TYP 3

14 LANDSCAPED AREA. REF. LANDSCAPE PLAN,

15. INSTALL STD CURB/GUTTER (8" HIGH) PER COA STD DWG 2415A

16.6' WIDE TEXTURED PAVEMENT SIDEWALK CROSSING PER DETAIL ON SHEET C-102.

T. ENSTING SIDEWALK TO REMAIN.

- 18. 11'X11' MINI CLEAR SIGHT TRIANGLE AT DRIVEWAYS. 35'x35' CLEAR SIGHT TRIANGLE AT STREET INTERSECTIONS. LANDSCAPING, FENCING, AND SIGNAGE WILL NOT INTERFERE WITH CLEAR SIGHT REQUIREMENTS. THEREFORE: SIGNS, WALLS, TREES, AND SHRUBBERY BETWEEN 3 AND 8 FEET TALL (AS MEASURED FROM THE GUTTER PAN) WILL NOT BE ACCEPTABLE IN THE CLEAR SIGHT TRIANGLE.
- 19 6' WIDE CURB CUT FOR ADA ROUTE. NO RAMP REQUIRED.

20 EXISTING LIGHT POLE TO REMAIN.

21 EXISTING POLE SIGN TO REMAIN.

22. INSTALL CONCRETE PAVEMENT FOR ADA PARKING AREA PER DETAIL SHEET C-102

23 INSTALL 2' WIDE CONCRETE FLUME PER DETAIL, SHEET C-102

24. EXISTING ASPHALT PAVEMENT TO REMAIN.

25 PROPOSED 6' WIDE ADA ROUTE FROM PUBLIC SIDEWALK TO BUILDING ENTRANCE

26 NSTALL 6' MDE VALLEY GUTTER PER COA STD DWG 2420.

FIRM WOOTEN ENGINEERING, HEREBY AL COMPLIANCE WITH AND IN E APPROVED SITE PLAN DATED ONALLY VISITED THE PROJECT SITE ON INSPECTION THAT THE SITE	
ACTUAL SITE CONDITIONS AND IS TRUE E AND BELIEF. THIS CERTIFICATION IS	BENCH MARKS
ERMANENT CERTIFICATE OF OCCUPANCY	A.C.S. MONUMENT "9-J17"
IN TODD WO	MONUMENT TYPE 3
I IS NOT TO VERIFY	NEW MEXICO STATE PLANE COORDINATES
	(CENTRAL ZONE-N.A.D. 1983)
CATION OF ITS	N=1,487,300.883
CATION OF ITS PURPOSE.	E=1,537,076.105
UPESSIONAL	PUB. EL=5210.959 NAVD 1988
6/16/2022	GROUND TO GRID FACTOR=0.999555559
	DELTA ALPHA ANGLE = -071'54.86"

