Table 2.1															
Elevation Storage Discharge - John Street Gravity Pond Option 1 John Street Feasibility Design Analysis Report															
Contour Elevation NAVD 1988	Depth	Contour Area	Incremental Volume	Incremental Volume	Cumulative Volume	1st Row of Ports Discharge	2nd Row of Ports Discharge	3rd Row of Ports Discharge	4th Row of Ports Discharge	Principal Spillway Grate Discharge	Principal	Total Principal Spillway / Outfall Pipe Discharge	Emergency Spillway Discharge	Total Discharge Rating Curve	Comment
		Orfice Diamet				6	6	6	0	48	12				
		Number of Op	-			4	7	6	0	1	1				
(ft)		(sq ft)	(cu ft)	(ac-ft)	(ac-ft)	(cfs)	(cfs)	(cfs)	(a)	(cfs)	(- h)	(cfs)	(cfs)	(cfs)	
(d) 4941.00	0	50	0	0.0000	0.00	(a) 0.0	(a) 0.0	(a) 0.0	(a) 0.0	(a) 0.0	(a,b) 0.0	(e) 0.0	(c) 0.0	0.0	Principal Spillway Invert/Pond Invert/1st row of ports
4941.50	0.5	3266	829	0.0190	0.00	2.6	0.0	0.0	0.0	0.0	1.3	1.3	0.0	1.3	
4942.00	1.0	6481	2437	0.0559	0.02	3.7	0.0	0.0	0.0	0.0	2.5	2.5	0.0		2nd row of ports
4943.00	2.0	10612	8547	0.1962	0.27	5.3	6.5	0.0	0.0	0.0	4.6	4.6	0.0	4.6	· · · · · · · · · · · · · · · · · · ·
4944.00	3.0	15467	13040	0.2993	0.57	6.4	9.2	5.6	0.0	0.0	5.9	5.9	0.0	5.9	
4945.00	4.0	20730	18099	0.4155	0.99	7.4	11.3	7.9	0.0	59.5	7.0	7.0	0.0	7.0	3rd row of ports
4946.00	5.0	23604	22167	0.5089	1.49	8.3	13.0	9.7	0.0	84.1	7.9	7.9	0.0	7.9	
4947.00	6.0	26543	25074	0.5756	2.07	9.1	14.6	11.2	0.0	103.1	8.7	8.7	0.0	8.7	Top of Principal Spillway Grate
4948.00	7.0	29559	28051	0.6440	2.71	9.8	15.9	12.5	0.0	119.0	9.5	9.5	0.0	9.5	
4949.00	8.0	32639	31099	0.7139	3.43	10.5	17.2	13.7	0.0	133.0	10.2	10.2	0.0	10.2	
4950.00	9.0	35789	34214	0.7854	4.21	11.2	18.4	14.8	0.0	145.7	10.8	10.8	0.0	10.8	
4951.00	10.0	38995 42252	37392 40624	0.8584	5.07 6.00	11.8 12.3	19.5 20.6	15.8 16.7	0.0 0.0	157.4 168.3	11.5 12.0	11.5 12.0	0.0	11.5 12.0	
4952.00 4953.00	11.0 12.0	42252	40024	1.0082	7.01	12.9	20.0	17.6	0.0	178.5	12.6	12.0	0.0	12.6	
4953.00	13.0	48967	47274	1.0853	8.10	13.4	22.5	18.5	0.0	188.2	13.1	13.1	0.0	13.1	
4955.00	14.0	52416	50692	1.1637	9.26	13.9	23.5	19.3	0.0	197.3	13.7	13.7	0.0	13.7	
4956.00	15.0	55893	54155	1.2432	10.51	14.4	24.3	20.1	0.0	206.1	14.2	14.2	0.0	14.2	Emergency Spillway
4956.20	15.2	56598	11249	0.2582	10.76	14.5	24.5	20.3	0.0	207.8	14.3	14.3	15.1	29.4	
4956.40	15.4	57303	11390	0.2615	11.02	14.6	24.7	20.4	0.0	209.5	14.4	14.4	42.8	57.1	
4956.60	15.6	58007	11531	0.2647	11.29	14.7	24.9	20.6	0.0	211.2	14.5	14.5	78.5	93.0	
4956.80	15.8	58712	11672	0.2680	11.56	14.8	25.0	20.7	0.0	212.9	14.5	14.5	120.9	135.5	
4957.00	16.0	59417	11813	0.2712	11.83	14.9	25.2	20.9	0.0	214.5	14.6	14.6	169.0	183.6	Top of Pond (artificial)
NOTES: (a) Orifice equation and coefficient were obtained from Equation 4-10 and Table 4-3 from "Handbook of Hydraulics" Sixth Edition, by Brater & King, 1976. $ \boxed{Q = Ca\sqrt{2gh}} C = 0.590 g=32.2 \text{ ft/sec}^2, a=area (sq ft) h=head (ft) \\ $															
k Material "n" Slope (ft/ft) (b) Manning's Equation Parameters 1.486 Concrete 0.013 0.005 Manning's Equation (equation 19.12(b)) and "k" value (page 19-4) were obtained from from "PE Civil Reference Manual" 16th edition, by Michael R. Lindeburg P.E, 2019 Flow depth increments, wetted perimeter and flow area of pipe were computed using Bentley FlowMaster.															
(c)Emergency Spillway flows were computed based on the following data used in the weir equation Q = CLH^ 1.5 C = discharge coefficient, L = spillway length perp. to flow (ft), H = head (ft) Emergency Spillway C = 2.60 L = 65 Emergency Spillway Elevation = 4956.00 Length assumed along top of pond embankment and elevations extended above emergency spillway to allow for rating curve to function if flow spills over top of emergency spillway. 4956.00															
(d) Data Source : Contours generated from DEMs provided by 2018 MRCOG. (e) The combined discharge of the reverse incline ports and the grate (A), will govern the discharge until the principal spillway outfall pipe becomes fully submerged. When the sum of (A)s is greater than outfall pipe capacity then outfall pipe capacity governs the discharge. grey box means must input data															

Contour Isevation NAVD 1988 Depth Participal Number of Openings Incremental Volume Cumulative Volume Principal Spillway Discharge Total Principal Spillway / Outfall Pipe Discharge Emergency Spillway Discharge Emergency Spillway Discharge Total Principal Spillway / Outfall Pipe Discharge Emergency Spillway Discharge Spillway Discharge Total Principal Spillway / Outfall Pipe Discharge Spillway / Outfall Pipe Discharge Spillway Discharge	ing Curve (cfs) 0.0 Wet Well Invert 16.7 Invert of Storm Drain Inle 61.1 84.1 103.1 119.0 133.0 145.7 157.4 168.3 178.5 188.2
Number of Openings 1 Image: Control of the control of	0.0 Wet Well Invert 16.7 Invert of Storm Drain Inle 61.1
(ft) (sq ft) (cu ft) (ac-ft) (ac-ft) (ac-ft) (ac-ft) (ac-ft) (ac-ft) (ac-ft) (ac-ft) (cfs) (cfs) (cfs) 4931.00 0 0 0 0.0000 0.00 0.	0.0 Wet Well Invert 16.7 Invert of Storm Drain Inle 61.1
$ \begin{array}{c c c c c c c c c c c c c c c c c c c $	0.0 Wet Well Invert 16.7 Invert of Storm Drain Inle 61.1
4931.000000.00000.000.000.00.00.00.04932.001.0842242110.09670.1016.716.716.70.016.74933.002.0987191470.21000.3161.161.10.061.14934.003.010599102350.23500.5484.184.10.084.14935.004.011342109710.25180.79103.1103.10.0103.14936.005.012102117220.26911.06119.0119.00.0119.04937.006.012878124900.28671.35133.0133.00.0133.04938.007.013670132740.30471.65145.7145.70.0145.74939.008.014478140740.32311.98157.4157.40.0157.44940.009.015302148900.34182.32168.3168.30.0168.34941.0010.016142157220.36092.68178.5178.50.0178.54943.0012.017871174350.40033.46197.3197.30.0197.34944.0013.018660183160.42053.88206.1206.10.0206.14945.0014.019663192120.44104.32214.5214.50.0 <td>16.7 Invert of Storm Drain Inle 61.1 </td>	16.7 Invert of Storm Drain Inle 61.1
4932.001.0842242110.09670.1016.716.70.016.74933.002.0987191470.21000.3161.161.10.061.14934.003.010599102350.23500.5484.184.10.084.14935.004.011342109710.25180.79103.1103.10.0103.14936.005.012102117220.26911.06119.0119.00.0119.04937.006.012878124900.28671.35133.0133.00.0133.04938.007.013670132740.30471.65145.7145.70.0145.74939.008.014478140740.32311.98157.4157.40.0157.44940.009.015302148900.34182.32168.3168.30.0168.34941.0010.016142157220.36092.68178.5178.50.0178.54942.0011.016999165710.38043.06188.2188.20.0188.24943.0012.017871174350.40033.46197.3197.30.0197.34944.0013.018760183160.42053.88206.1206.10.0206.14945.0014.019663192120.44104.32214.5214.50.0214	16.7 Invert of Storm Drain Inle 61.1
4933.002.0987191470.21000.3161.161.10.061.14934.003.010599102350.23500.5484.184.10.084.14935.004.011342109710.25180.79103.1103.10.0103.14936.005.012102117220.26911.06119.0119.00.0119.04937.006.012878124900.28671.35133.0133.00.0133.04938.007.013670132740.30471.65145.7145.70.0145.74939.008.014478140740.32311.98157.4157.40.0157.44940.009.015302148900.34182.32168.3168.30.0168.34941.0010.016142157220.36092.68178.5178.50.0178.54942.0011.016999165710.38043.06188.2188.20.0188.24943.0012.017871174350.40033.46197.3197.30.0197.34944.0013.018760183160.42053.88206.1206.10.0206.14946.0014.01963192120.44104.32214.5214.50.0214.54946.0015.020582201230.46194.78222.6222.60.0 <t< td=""><td>61.1 84.1 103.1 119.0 133.0 145.7 157.4 168.3 178.5 188.2</td></t<>	61.1 84.1 103.1 119.0 133.0 145.7 157.4 168.3 178.5 188.2
4934.003.010599102350.23500.5484.184.10.084.14935.004.011342109710.25180.79103.1103.10.0103.14936.005.012102117220.26911.06119.0119.00.0119.04937.006.012878124900.28671.35133.0133.00.0133.04938.007.013670132740.30471.65145.7145.70.0145.74939.008.014478140740.32311.98157.4157.40.0157.44940.009.015302148900.34182.32168.3168.30.0168.34941.0010.016142157220.36092.68178.5178.50.0178.54942.0011.016999165710.38043.06188.2188.20.0188.24943.0012.017871174350.40033.46197.3197.30.0197.34944.0013.018760183160.42053.88206.1206.10.0206.14945.0014.019663192120.44104.32214.5214.50.0214.54946.0015.020582201230.46194.78222.6222.60.0222.6	84.1 103.1 119.0 133.0 145.7 157.4 168.3 178.5 188.2
4935.004.011342109710.25180.79103.1103.10.0103.14936.005.012102117220.26911.06119.0119.00.0119.04937.006.012878124900.28671.35133.0133.00.0133.04938.007.013670132740.30471.65145.7145.70.0145.74939.008.014478140740.32311.98157.4157.40.0157.44940.009.015302148900.34182.32168.3168.30.0168.34941.0010.016142157220.36092.68178.5178.50.0178.54942.0011.01699165710.38043.06188.2188.20.0188.24943.0012.017871174350.40033.46197.3197.30.0197.34944.0013.018760183160.42053.88206.1206.10.0206.14945.0014.019663192120.44104.32214.5214.50.0214.54946.0015.020582201230.46194.78222.6222.60.0222.6	103.1 119.0 133.0 145.7 157.4 168.3 178.5 188.2
4936.005.012102117220.26911.06119.0119.00.0119.04937.006.012878124900.28671.35133.0133.00.0133.04938.007.013670132740.30471.65145.7145.70.0145.74939.008.014478140740.32311.98157.4157.40.0157.44940.009.015302148900.34182.32168.3168.30.0168.34941.0010.016142157220.36092.68178.5178.50.0178.54942.0011.016999165710.38043.06188.2188.20.0188.24943.0012.017871174350.40033.46197.3197.30.0197.34944.0013.018760183160.42053.88206.1206.10.0206.14945.0014.019663192120.44104.32214.5214.50.0214.54946.0015.020582201230.46194.78222.6222.60.0222.6	119.0 133.0 145.7 157.4 168.3 178.5 188.2
4937.006.012878124900.28671.35133.0133.00.0133.04938.007.013670132740.30471.65145.7145.70.0145.74939.008.014478140740.32311.98157.4157.40.0157.44940.009.015302148900.34182.32168.3168.30.0168.34941.0010.016142157220.36092.68178.5178.50.0178.54942.0011.016999165710.38043.06188.2188.20.0188.24943.0012.017871174350.40033.46197.3197.30.0197.34944.0013.018760183160.42053.88206.1206.10.0206.14945.0014.019633192120.44104.32214.5214.50.0222.64946.0015.020582201230.46194.78222.6222.60.0222.6	133.0 145.7 157.4 168.3 178.5 188.2
4938.007.013670132740.30471.65145.7145.70.0145.74939.008.014478140740.32311.98157.4157.40.0157.44940.009.015302148900.34182.32168.3168.30.0168.34941.0010.016142157220.36092.68178.5178.50.0178.54942.0011.016999165710.38043.06188.2188.20.0188.24943.0012.017871174350.40033.46197.3197.30.0197.34944.0013.018760183160.42053.88206.1206.10.0206.14945.0014.019633192120.44104.32214.5214.50.0214.54946.0015.020582201230.46194.78222.6222.60.0222.6	145.7 157.4 168.3 178.5 188.2
4939.008.014478140740.32311.98157.4157.40.0157.44940.009.015302148900.34182.32168.3168.30.0168.34941.0010.016142157220.36092.68178.5178.50.0178.54942.0011.016999165710.38043.06188.2188.2188.20.0188.24943.0012.017871174350.40033.46197.3197.30.0197.34944.0013.018760183160.42053.88206.1206.10.0206.14945.0014.019663192120.44104.32214.5214.50.0214.54946.0015.020582201230.46194.78222.6222.60.0222.6	157.4 168.3 178.5 188.2
4940.009.015302148900.34182.32168.3168.30.0168.34941.0010.016142157220.36092.68178.5178.50.0178.54942.0011.016999165710.38043.06188.2188.20.0188.24943.0012.017871174350.40033.46197.3197.30.0197.34944.0013.018760183160.42053.88206.1206.10.0206.14945.0014.019663192120.44104.32214.5214.50.0214.54946.0015.020582201230.46194.78222.6222.60.0222.6	168.3 178.5 188.2
4941.0010.016142157220.36092.68178.5178.50.0178.54942.0011.016999165710.38043.06188.2188.20.0188.24943.0012.017871174350.40033.46197.3197.30.0197.34944.0013.018760183160.42053.88206.1206.10.0206.14945.0014.019663192120.44104.32214.5214.50.0214.54946.0015.020582201230.46194.78222.6222.60.0222.6	178.5 188.2
4942.0011.016999165710.38043.06188.2188.2188.20.0188.24943.0012.017871174350.40033.46197.3197.30.0197.34944.0013.018760183160.42053.88206.1206.10.0206.14945.0014.019663192120.44104.32214.5214.50.0214.54946.0015.020582201230.46194.78222.6222.60.0222.6	188.2
4943.0012.017871174350.40033.46197.3197.30.0197.34944.0013.018760183160.42053.88206.1206.10.0206.14945.0014.019663192120.44104.32214.5214.50.0214.54946.0015.020582201230.46194.78222.6222.60.0222.6	
4944.0013.018760183160.42053.88206.1206.10.0206.14945.0014.019663192120.44104.32214.5214.50.0214.54946.0015.020582201230.46194.78222.6222.60.0222.6	197.3
4945.0014.019663192120.44104.32214.5214.50.0214.54946.0015.020582201230.46194.78222.6222.60.0222.6	
4946.00 15.0 20582 20123 0.4619 4.78 222.6 222.6 0.0 222.6	206.1
4946.00 15.0 20582 20123 0.4619 4.78 222.6 222.6 0.0 222.6	214.5
	222.6 Top of Wet Well
Orifice equation and coefficient were obtained from Equation 4-10 and Table 4-3 from "Handbook of Hydraulics" Sixth Edition, by Brater & King, 1976. $Q = Ca\sqrt{2gh}$ C = 0.590 g=32.2 ft/sec^2, a=area (sq ft) h=head (ft) Weir equation and "C" coefficients were obtained from Equation 5-10 and Table 5-3 from "Handbook of Hydraulics" Sixth Edition	' Sixth Edition, by Brater & King, 1976
Weir equation and "C" coefficients were obtained from Equation 5-10 and Table 5-3 from "Handbook of Hydraulics" Sixth Edition $a = \pi D^2 / 4$ (full area formula of a circle)	Sixth Edition, by Brater & King, 1976.
k Material "n" Slope (ft/ft)	
Manning's Equation Parameters 1.486 PVC 0.010 0.004	
nning's Equation (equation 19.12(b)) and "k" value (page 19-4) were obtained from from "PE Civil Reference Manual" 16th edition, by Michael R. Lindeburg P.E, 2019	
w depth increments, wetted perimeter and flow area of pipe were computed using Bentley FlowMaster.	

Comment	