


Alumni Drive, North of Gibson

9999 Alumni Drive SE, Albuquerque, NM 87106

TEMPORARY EROSION AND SEDIMENT CONTROL PLAN

| Page Index | |
|------------|---|
| 1 | Title Page |
| 2 | SWPPP info / ESC Std. Notes |
| 3 | Owner/Operator - Nature of Construction |
| 4-5 | ESC Map and Legend |
| 6-8 | BMP Specification Sheets |



GPS COORDINATES:

35.060295
-106.633837



[Signature]

CPESC STAMP

Alumni Drive, North of Gibson

PROJECT TITLE

AIBUQUERQUE, NM - BERNALILLO COUNTY

CITY, COUNTY, STATE

11/21/2024

DATE

Doug Lewis/J. Tolman

DRAWN BY





STORMWATER POLLUTION PREVENTION PLAN INFORMATION

| | |
|---|--|
| PERIMT NUMBER: NMR1006TZ | |
| NMR100000 STATE OF NEW MEXICO, EXCEPT INDIAN COUNTRY NMR10I000 INDIAN COUNTRY WITHIN THE STATE OF NEW MEXICO, EXCEPT NAVAJO RESERVATION LANDS THAT ARE COVERED UNDER ARIZONA PERMIT AZR10I000 AND UTE MOUNTAIN RESERVATION LANDS THAT ARE COVERED UNDER COLORADO PERMIT COR10I000. | |
| OWNER NAME: University of New Mexico | |
| OWNER POINT OF CONTACT: Teresa Constantinidis | |
| NOI PREPARED BY: Inspections Plus | |
| PROJECT/SITE NAME: Alumni Drive, North of Gibson | |
| PROJECT/SITE ADDRESS: 9999 Alumni Drive SE, Albuquerque, NM 87106 | |
| LATITUDE | 35.060295 |
| LONGITUDE | -106.633837 |
| ESTIMATED PROJECT START DATE | 11/30/2024 |
| ESTIMATED PROJECT COMPLETION DATE | 04/01/2025 |
| ESTIMATED AREA TO BE DISTURBED | 0.5 acres |
| TYPE OF CONSTRUCTION | Commercial |
| DEMOLITION OF ANY STRUCTURES, 10,000 SQ FT OF GREATER BUILT OR RENOVATED BEFORE JANUARY 1, 1980? | No |
| WAS THE PREDEVELOPMENT LAND USED FOR AGRICULTURE? | No |
| COMMENCED EARTH DISTURBING ACTIVITIES? | No |
| DISCHARGED TO MS4? MS4 NAME? | Albuquerque |
| SURFACE WATERS WITHIN 50FT? | No |
| RECEIVING WATER? | South Diversion Channel, 62' |
| IS RECEIVING WATER IMPAIRED? TIER DESIGNATION | No |
| WHAT ARE THE IMPAIRMENTS, IF ANY? | N/A |
| SWPPP CONTACT INFORMATION: | Petra Morris, AICP, 505-908-1737, pmorris1@unm.edu |
| ENDANGERED SPECIES CRITERIA: | CRITERION “A”; NO CRITICAL HABITATS CRITERION “A” |
| HISTORIC PRESRVATION CRITERIA: | PREEXISTING DEVELOPMENT |

ESC Plan Standard Notes (2023-06-16)

- All Erosion and Sediment Control (ESC) work on these plans, except as otherwise stated or provided hereon shall be permitted, constructed, inspected, and maintained in accordance with:
 - The City Ordinance § 14-5-2-11, the ESC Ordinance,
 - The EPA’s 2022 Construction General Permit (CGP), and
 - The City Of Albuquerque Construction BMP Manual.
- All BMP’s must be installed prior to beginning any earth moving activities except as specified hereon in the Phasing Plan. Construction of earthen BMP’s such as sediment traps, sediment basins, and diversion berms shall be completed and inspected prior to any other construction or earthwork. Self-inspection is required after installation of the BMPs and prior to beginning construction.
- Self-inspections - In accordance with City Ordinance § 14-5-2-11(C)(1), “at a minimum a routine self-inspection is required to review the project for compliance with the Construction General Permit once every 14 days and after any precipitation event of 1/4 inch or greater until the site construction has been completed and the site determined as stabilized by the city. Reports of these inspections shall be kept by the person or entity authorized to direct the construction activities on the site and made available upon request.
- Corrective action reports must be kept by the person or entity authorized to direct the construction activities on the site and made available upon request.
- Final Stabilization and Notice of Termination (NOT) - In accordance with City Ordinance § 14-5-2-11(C)(1), self-inspections must continue until the site is “determined as stabilized by the city.” The property owner/operator is responsible for determining when the “Conditions for Terminating CGP Coverage” per CGP Part 8.2 are satisfied and then for filing their Notice of Termination (NOT) with the EPA. Each operator may terminate CGP coverage only if one or more of the conditions in Part 8.2.1, 8.2.2, or 8.2.3 has occurred. After filing the NOT with the EPA, the property owner is responsible for requesting a Determination of Stabilization from the City.
- When doing work in the City right-of-way (e.g. sidewalk, drive pads, utilities, etc.) prevent dirt from getting into the street. If dirt is present in the street, the street should be swept daily or prior to a rain event or contractor induced water event (e.g. curb cut or water test).
- When installing utilities behind the curb, the excavated dirt should not be placed in the street.
- When cutting the street for utilities the dirt shall be placed on the uphill side of the street cut and the area swept after the work is complete. A wattle or mulch sock may be placed at the toe of the excavated dirt pile if site constraints do not allow placing the excavated dirt on the uphill side of the street cut.
- ESC Plans must show longitudinal street slope and street names. On streets where the longitudinal slope is steeper than 2.5%, wattles/mulch socks or j-hood silt fence shall be shown in the front yard swale or on the side of the street.

| | | |
|---|-------------------------------------|---|
|  | Alumni Drive, North of Gibson | |
| | PROJECT TITLE | |
| | AIBUQUERQUE, NM - BERNALILLO COUNTY | |
| | CITY, COUNTY, STATE | |
| 11/21/2024 | DATE |  |
| Doug Lewis/J. Tolman | DRAWN BY | |

Operator:

Lobo Development Corporation
801 University Boulevard SE, Suite 207
Albuquerque, NM 87106
505-925-1610

Petra Morris, AICP
Planning Director
505-908-1737
pmorris1@unm.edu

Contractor TBD
Site Supervisor TBD
Phone TBD
Email TBD

Owner:

University of New Mexico
801 University Boulevard SE, Suite 207
Albuquerque, NM 87106
505-925-1610



Teresa Constantinidis
Executive VP for Finance & Administration
505-227-7525
keelie@unm.edu


Nature of Construction Activities



Start: 11/30/2024 - End: 04/01/2025
(Dates are estimates and may be adjusted based on external factors or unexpected events)
0.5 acres total property, **0.5 acres** total and maximum area to be disturbed at any one time.
















- The **Operator, Lobo Development Corporation, and a contractor yet TBD, under the direction of the Owner, University of New Mexico** will be responsible for the development of a section of **Alumni Drive, North of Gibson Boulevard SE**. Site work will be stepped but not phased. Below are the stages of work and the approximate dates of the start/stop and the overlapping of work.
- No temporary cessation of construction activities is anticipated during this project.
- Erosion Control BMPs to use throughout all stages of work: Stabilized Construction Entrance/Exit, Street Sweeping, Silt Fence, Mulch Socks, Wetting with Water for dust control, and cut back curbs and/or sidewalks.
- Site preparation, placement of perimeter BMPs and construction support BMPs: 11/2024 – 12/2024
- Clearing, Grading, and Excavation to Prepare for Construction Activities: 12/2024 – 01/2025
- Development: Start of any utility and drainage installations curbs & gutters, sidewalks. Asphalt paving of road sections and joining to other roads and/or parking lots and drives: 01/2025 – 03/2025
- Construction activities will cease, and site clean-up and removal of all BMPs will take place: 03/2025 – 04/2025

NOTE: If no further construction is planned and commenced within 14 days of the cessation of construction activity, stabilization will take place on open soil areas with slopes greater than 5% with Hydroseed in accordance with CGP 2.2.14.



| | | |
|---|-------------------------------------|---|
|  | Alumni Drive, North of Gibson | |
| | PROJECT TITLE | |
| | AIBUQUERQUE, NM - BERNALILLO COUNTY | |
| | CITY, COUNTY, STATE | |
| | 11/21/2024 |  |
| | DATE | |
| | Doug Lewis /J. Tolman | |
| | DRAWN BY | |





| | | | |
|--|-------------------------------------|----------|--|
|  CPESC STAMP | Alumni Drive, North of Gibson | | PROJECT TITLE |
| | ALBUQUERQUE, NM - BERNALILLO COUNTY | | CITY, COUNTY, STATE |
| | 11/21/2024 | DATE |  |
| | D. Lewis / J. Tolman | DRAWN BY | |

-  Property Boundary & Limit of Disturbance (1)
-  Limit of Disturbance (2)
-  Silt Fence (3)
-  Mulch Sock (2)
-  Cut-back Curbs and/or Sidewalks (2)
-  Pre/Post-Construction Water Flow/Slope (7)
-  Receiving Water - South Diversion Channel (1)
-  Stockpiles (1)
-  Water Truck (1)
-  Street Sweeping (1)
-  Portable Toilet (1)
-  Dumpster (1)
-  Spill Kit (1)
-  Portable Concrete Washout Bin w/ Sign (1)
-  Stabilized Construction Entrance/Exit (1)

Latitude: 35.060295
Longitude: -106.633837

| | | |
|---|-------------------------------------|----------|
|   CPESC STAMP | Alumni Drive, North of Gibson | |
| | PROJECT TITLE | |
| | ALBUQUERQUE, NM - BERNALILLO COUNTY | |
| | CITY, COUNTY, STATE | |
| | 11/21/2024 | DATE |
| | D. Lewis / J. Tolman | DRAWN BY |

 **INSPECTIONS PLUS**



Revision 03 December 2020

NATIONAL POLLUTANT DISCHARGE ELIMINATION SYSTEM MANUAL
Appendix A2 - Erosion and Sediment Control

A2-8 MULCH SOCKS

A1

A2

A3



Image credit: NMDOT

DESCRIPTION

Mulch socks are erosion and sediment control materials made typically of high density polyethylene (HDPE) or biodegradable plastic filament mesh tubes filled with compost or other organic media.

PRIMARY USE

Mulch socks are primarily used to filter and slow stormwater. Uses include:

- » Filter sediment and silts from sheet stormwater flowing from disturbed sites.
- » Protect inlets from sediment.
- » Create temporary ponding areas behind socks to facilitate the deposition of suspended solids.
- » Slow stormwater runoff and reduce peak flows.
- » Filter heavy metals, pollutants and oil from stormwater when socks are filled with adsorbent media.
- » Provide temporary protection at drop inlets or culverts.
- » Create check dams or sediment traps at concrete washout areas.
- » Provide perimeter control, runoff diversion, and slope interruption.
- » Reinforce stream banks and aid in the protection and establishment of stabilizing watercourse vegetation.

APPLICATION

Strategies for successful use of mulch socks include:

- » Lay the sock upon the surface and stake the tube every 10 feet.
- » Lay the tube along contours, vegetated channels, and outside of the toes of slopes.

NMDOT TESC
(TEMPORARY EROSION AND SEDIMENT CONTROL PLAN)
SYMBOL

MS
CMS

Revision 03 December 2020

NATIONAL POLLUTANT DISCHARGE ELIMINATION SYSTEM MANUAL
Appendix A2 - Erosion and Sediment Control


A2-8 MULCH SOCKS CONTINUED

LIMITATIONS


- » Mulch socks do not provide long-term solutions for stormwater storage.
- » Mulch socks have limited usefulness in concentrated flow conditions.
- » On NMDOT projects composted mulch socks (CMS) are used exclusively; wood chip mulch socks are not allowed.

MAINTENANCE REQUIREMENTS




- » Inspect mulch socks periodically, especially after major storm events.
- » Remove sediments from behind socks after accumulation is 1/3 sock height.
- » Restake and overlap socks that are displaced due to storm events or construction disturbance.




Mulch sock - PLAN VIEW.



Mulch sock - SECTION A-A.

| | | | |
|--|-------------------------------------|----------|---|
|  James Tolman No. 10631  CPESC STAMP | Alumni Drive, North of Gibson | | PROJECT TITLE |
| | ALBUQUERQUE, NM - BERNALILLO COUNTY | | CITY, COUNTY, STATE |
| | 11/21/2024 | DATE |  INSPECTIONS PLUS |
| | D. Lewis / J. Tolman | DRAWN BY | |

Street Sweeping and Vacuuming SE-7



Description and Purpose
Street sweeping and vacuuming includes use of self-propelled and walk-behind equipment to remove sediment from streets and roadways, and to clean paved surfaces in preparation for final paving. Sweeping and vacuuming prevents sediment from the project site from entering storm drains or receiving waters.

Suitable Applications
Sweeping and vacuuming are suitable anywhere sediment is tracked from the project site onto public or private paved streets and roads, typically at points of egress. Sweeping and vacuuming are also applicable during preparation of paved surfaces for final paving.

Limitations
Sweeping and vacuuming may not be effective when sediment is wet or when tracked soil is caked (caked soil may need to be scraped loose).


- Implementation**
- Controlling the number of points where vehicles can leave the site will allow sweeping and vacuuming efforts to be focused, and perhaps save money.
 - Inspect potential sediment tracking locations daily.
 - Visible sediment tracking should be swept or vacuumed on a daily basis.

- Objectives**
- EC Erosion Control
 - SE Sediment Control
 - TR Tracking Control
 - WE Wind Erosion Control
 - NS Non-Stormwater Management Control
 - WM Waste Management and Materials Pollution Control

- Targeted Constituents**
- Sediment
 - Nutrients
 - Trash
 - Metals
 - Bacteria
 - Oil and Grease
 - Organics

- Potential Alternatives**
- None

Street Sweeping and Vacuuming SE-7



Description and Purpose
Street sweeping and vacuuming includes use of self-propelled and walk-behind equipment to remove sediment from streets and roadways, and to clean paved surfaces in preparation for final paving. Sweeping and vacuuming prevents sediment from the project site from entering storm drains or receiving waters.

Suitable Applications
Sweeping and vacuuming are suitable anywhere sediment is tracked from the project site onto public or private paved streets and roads, typically at points of egress. Sweeping and vacuuming are also applicable during preparation of paved surfaces for final paving.

Limitations
Sweeping and vacuuming may not be effective when sediment is wet or when tracked soil is caked (caked soil may need to be scraped loose).

- Implementation**
- Controlling the number of points where vehicles can leave the site will allow sweeping and vacuuming efforts to be focused, and perhaps save money.
 - Inspect potential sediment tracking locations daily.
 - Visible sediment tracking should be swept or vacuumed on a daily basis.

- Objectives**
- EC Erosion Control
 - SE Sediment Control
 - TR Tracking Control
 - WE Wind Erosion Control
 - NS Non-Stormwater Management Control
 - WM Waste Management and Materials Pollution Control

- Targeted Constituents**
- Sediment
 - Nutrients
 - Trash
 - Metals
 - Bacteria
 - Oil and Grease
 - Organics

- Potential Alternatives**
- None

A1-10 CONCRETE WASTE MANAGEMENT



DESCRIPTION
Concrete waste management reduces or prevents the discharge of pollutants to stormwater by implementing management measures.

PRIMARY USE
Concrete waste products can negatively affect the pH of water, harm aquatic life, and contribute to total suspended solids in stormwater. Concrete waste management strategies keep the discharge of concrete waste materials from affecting local stormwater and drainage systems during concrete construction operations.

Concrete construction operations that have the potential for contaminating receiving waters include, but are not limited to:

- Pouring and finishing concrete slabs on grade and concrete paving.
- Pouring vertical cast in place concrete (header curbs, concrete curbs and gutters, retaining walls, concrete footings).
- Drilling, cutting, polishing, and curing concrete.
- Washing concrete dust, and exposed aggregate concrete.
- Spilling concrete.
- Dampening freshly made concrete.
- Creating and applying concrete slurry coat.
- Building masonry structures.
- Finishing surfaces with stucco.
- Washing equipment.

- SEE ALSO**
- A1-9 Spill Prevention Plan
 - A1-11 Solid Waste Management
 - A1-12 Hazardous Waste Management

NMDOT TESC
(TEMPORARY EROSION AND SEDIMENT CONTROL PLAN)
SYMBOL
CWM

A1-10 CONCRETE WASTE MANAGEMENT CONTINUED

APPLICATION
Concrete waste management strategies include:

- Avoid mixing excess amounts of fresh concrete or cement onsite.
- Perform washout of concrete trucks offsite or in designated areas on site at least 50 feet from storm drains, open ditches or bodies of water.
- Block drop inlets and direct concrete wastewater into temporary pits where the concrete can set, be broken up, and then disposed of properly.
- Collect and return sweepings to aggregate base stockpile or dispose of properly.
- Train employees and subcontractors in proper concrete waste management.

LIMITATIONS
Offsite washout of concrete wastes may not always be possible.

MAINTENANCE REQUIREMENTS

- Ensure subcontractors properly manage concrete wastes.
- Dispose of hardened concrete on a regular basis.
- Regularly inspect drop inlet protection measures.

| | | |
|--|-------------------------------------|----------|
| | Alumni Drive, North of Gibson | |
| | PROJECT TITLE | |
| | ALBUQUERQUE, NM - BERNALILLO COUNTY | |
| | CITY, COUNTY, STATE | |
| | 11/21/2024 | DATE |
| | D. Lewis / J. Tolman | DRAWN BY |

A1-1 DUST CONTROL



DESCRIPTION
Dust control measures reduce a construction site's potential for producing airborne fugitive dust that can lead to air and water pollution. Sediments that are transported from construction sites by wind and construction vehicles that have left the site, are often re-dispersed to the air by subsequent vehicular traffic and winds. Likewise, these sediments may be transported by the next rainfall to streams and into public storm sewer systems. Implementation of control measures to minimize the generation of fugitive dust from disturbed landscapes and construction sites will also limit the quantity of sediments in stormwater.

PRIMARY USE
Dust control is used to limit and control nuisance fugitive dust from disturbed landscapes and construction sites. Project types and conditions that benefit from execution of a dust control strategy include, but are not limited to, the following:

- Grading operations (land clearing and earthmoving).
- Drilling and blasting.
- Batch drop operations (loader operation).
- Exposed, cleared, and unstabilized areas.
- Vehicle traffic on unpaved surfaces.
- Sediment tracking on paved surfaces.
- Blasting and wrecking ball operations.
- Soil and debris storage piles.

- SEE ALSO**
- A1-4 Grassland Seedbank Protection
 - A1-5 Stockpile Management
 - A2-1 Seeding
 - A2-2 Mulching

NMDOT TESC
(TEMPORARY EROSION AND SEDIMENT CONTROL PLAN)
SYMBOL
DU

A1-1 DUST CONTROL CONTINUED

APPLICATION
Dust control measures vary widely and should be selected alone or in combination for the specific project type, conditions, and resource availability. Dust control measures include, but are not limited to, the following:

- Provide covers for trucks transporting materials that contribute dust.
- Pave, apply gravel, vegetate or chemically stabilize large disturbed areas.
- Immediately water disturbed areas.
- Regularly water and dampen unstabilized areas.

Additionally, if the contractor is responsible for complying with the requirements of the air pollution control permit, the following is typically required:

- Provide dust control plans for construction or land-clearing projects.
- Conduct enforcement activities with priority given to citizen complaints.
- Conduct documentation of maintenance.

LIMITATIONS
Some dust control measures may be of limited use due to lack of resources at the site, construction sequencing, and the need to repeatedly re-implement measures during the course of construction. Limitations may include:

- Access to water.
- Availability of equipment.
- Drought.
- Frequent disturbance during construction.

MAINTENANCE REQUIREMENTS

- Inspect stabilized soils for disturbance on a regular basis.
- Wet soil and soils treated with stabilization agents.
- Regrade and reapply soil stabilizing agents.

Silt Fence

Definition
A temporary barrier of Geotextile Class "F" used to intercept sediment laden runoff from small drainage areas.

Purpose
The purpose of silt fence is to reduce runoff where velocity allow the deposition of transported sediment to occur. Limits imposed by ultraviolet light on the stability of the fabric will dictate the maximum period that the silt fence may be used.

1. Silt fence provides a barrier that can collect and hold debris and soil, preventing the material from entering critical areas, streams, streets, etc.

2. Silt fence can be used where the installation of a dike would destroy sensitive areas; woods, wetlands, etc.

Conditions where the Practice Applies
Silt Fence is limited to intercepting sheet flow runoff from limited distances according to slope. It provides filtering and velocity dissipation to promote gravity settling of sediment.

Design Criteria
Wood or Steel Posts may be used in certain instances. Silt fence should be placed as close to the contour as possible. No section of silt fence should exceed a grade of 5 percent for a distance more than 50 feet. Where ends of the geotextile fabric come together, the ends shall be overlapped, folded, and stapled to prevent sediment bypass.

* If wood post are to be used they must meet the following specifications:
1 1/4" X 1 1/2" minimum square posts, or 1 1/4" minimum diameter round post

* If metal posts are to be used they must be standard "T" or "U" post weighing not less than 1 lb. per linear foot.

The length of the flow contributing to silt fence shall conform to the following limitations.

| Slope (%) | Slope Steepness | Slope Length (Ft.) (Maximum) | Silt Fence Length (Ft.) (Maximum) |
|-----------|-----------------|------------------------------|-----------------------------------|
| 2 | 0-50:1 | Unlimited | Unlimited |
| 2-10 | 50:1-10:1 | 125 | 1,000 |
| 10-20 | 10:1-5:1 | 100 | 750 |
| 20-33 | 5:1-3:1 | 60 | 500 |
| 33-50 | 3:1-2:1 | 40 | 250 |
| 50 + | > 2:1 | 20 | 125 |

Revision 03 December 2020

NATIONAL POLLUTANT DISCHARGE ELIMINATION SYSTEM MANUAL
Appendix A1 - Construction Planning, Management and Clean Up

A1-13 STABILIZED CONSTRUCTION ENTRANCE/EXIT

DESCRIPTION
A stabilized construction entrance/exit consists of a pad of crushed stone, recycled concrete, or other rock-like material on top of a geotextile filter, which is used to facilitate the wash-down and removal of sediment and other debris from construction equipment prior to exiting the site.

PRIMARY USE
Stabilized construction entrances/exits are used to reduce offsite sediment tracking from trucks and construction equipment, and for sites where considerable truck traffic occurs each day. They also reduce the need to clean adjacent pavement as often, and help route site traffic through a single point. Stabilized construction entrances and exits are recommended for all construction sites, and may be required for Construction General Permit compliance.

APPLICATION
Strategies for successful and effective stabilized construction entrances/exits include but are not limited to:

- » Location selection able to accommodate construction traffic.
- » Appropriate selection of locally available material.

LIMITATIONS

- » Selection of the construction entrance/exit location is critical. To be effective, it must be used exclusively.
- » Stabilized access points can be expensive and must be installed in combination with one or more other sediment control techniques. It may be more cost effective, however, than labor-intensive street cleaning.

NMDOT STANDARD DRAWING

603-01-7/7 Offsite Tracking Prevention

NMDOT TESC (TEMPORARY EROSION AND SEDIMENT CONTROL PLAN) SYMBOL

SCEE

Revision 03 December 2020

NATIONAL POLLUTANT DISCHARGE ELIMINATION SYSTEM MANUAL
Appendix A1 - Construction Planning, Management and Clean Up

A1-13 STABILIZED CONSTRUCTION ENTRANCE/EXIT CONTINUED

LIMITATIONS CONTINUED

- » Site constraints may limit the recommended 50 feet entrance/exit drive length.

MAINTENANCE REQUIREMENTS

- » Inspect the stabilized construction entrance after major storm events to ascertain sediment and pollution are being effectively captured on site. When sediment or debris has substantially clogged the void area between the rocks, the aggregate mat must be washed down or replaced.
- » Re-grade and top dress stone periodically to retain the effectiveness of the entrance/exit.

Revision 03 December 2020

NATIONAL POLLUTANT DISCHARGE ELIMINATION SYSTEM MANUAL
Appendix A1 - Construction Planning, Management and Clean Up

A1-9 SPILL PREVENTION PLAN

DESCRIPTION
A spill prevention plan is an emergency plan to contain spills of dangerous, hazardous, or toxic wastes in order to mitigate environmental damage, safeguard the public and provide prompt notice to proper authorities. Hazardous chemicals include but are not limited to fertilizers, paints, oils, grease, pesticides, fuels, and construction or industrial facility chemicals.

PRIMARY USE
Spill prevention plans are applicable to all construction sites and specified in the Stormwater Pollution Prevention Plan (SWPPP). Sites closest to watercourses, canals, and reservoirs are at highest risk of contaminating surface waters with an uncontained spill.

APPLICATION
The spill prevention plan is created prior to construction and includes measures to limit the scope of spills and minimize the impact on the environment and public health. Typical spill prevention plan strategies include:

- » Designate a Pollution Prevention and Spill Response Coordinator (refer to Section I.B.2.h of the Manual).
- » Select a designated area for storage.
- » Seal and label all containers.
- » Surround storage areas by a berm with an impermeable liner. Construct berms to provide a storage volume of no less than 1.5 times the total volume of the stored material.
- » Establish cleanup procedures and have cleanup materials readily available.

NMDOT STANDARD SPECIFICATION

603 Temporary Erosion and Sediment Control

NMDOT TESC (TEMPORARY EROSION AND SEDIMENT CONTROL PLAN) SYMBOL

SPP

Revision 03 December 2020

NATIONAL POLLUTANT DISCHARGE ELIMINATION SYSTEM MANUAL
Appendix A1 - Construction Planning, Management and Clean Up

A1-9 SPILL PREVENTION PLAN CONTINUED

APPLICATION CONTINUED

- » Post cleanup procedures near where dangerous, hazardous or toxic materials are stored or used.
- » Dispose of contaminated material in accordance with state or local requirements.

Other strategies for specific situations include:

- » Small or incidental spills (<5 gallons): contain and clean the spill using facility personnel if they are able to do so without risking safety and injury.
- » Large or reportable spills (> 5 gallons): clean the spill using emergency responders and/or clean up contractors. For releases of hazardous substances, the federal government has established Superfund Reportable Quantities (RQs).
- » Releases of Hazardous Substances: if a hazardous substance is released to the environment in an amount that equals or exceeds its RQs, the release must be reported to federal authorities, unless certain reporting exemptions for hazardous substances releases also apply. Information on RQs can be found on the EPA website (<https://www.epa.gov/epcra/cercla-and-epcra-continuous-release-reporting>). In the event of a spill of a hazardous substance, notify the National Response Center (NRC) at (800) 424-8802, the New Mexico Environment Department (NMED) at (505) 827-9329, and the local fire department.

LIMITATIONS

- » No major limitations.

MAINTENANCE REQUIREMENTS

- » Inspect hazardous material storage areas frequently and after storm events.
- » Maintain storage areas in a clean and orderly fashion.
- » Maintain records of stored hazardous materials.

CERTIFIED PROFESSIONAL

CPESC®

James Tolman

No. 10631

IN EROSION AND SEDIMENT CONTROL

CPESC STAMP

Alumni Drive, North of Gibson

PROJECT TITLE

ALBUQUERQUE, NM - BERNALILLO COUNTY

CITY, COUNTY, STATE

11/21/2024

DATE

D. Lewis / J. Tolman

DRAWN BY

INSPECTIONS PLUS

Page 8 of 8