

421



PRELIMINARY DESIGN REPORT

for

**AMOLE DEL NORTE
STORM DIVERSION FACILITIES
TIERRA BAYITA DRAINAGE FACILITIES**

October 31, 1990

CITY PROJECT NO. 4076-01


Greiner Job No. G0001.01

Prepared for:

Public Works Department
City of Albuquerque
P. O. Box 1293
Albuquerque, NM 87103


Daniel L. Morehead, PE&PS
Associate Vice President


Mark S. Holstad, P.E.
Project Manager



Greiner, Inc.
5971 Jefferson Boulevard, NE, suite 101
Albuquerque, New Mexico 87109
(505) 345-3999



Greiner, Inc.
5971 Jefferson Blvd., N.E.
Suite 101
Albuquerque, New Mexico 87109
(505) 345-3999
FAX: (505) 345-8393

October 31, 1990

Mr. Loren D. Mainz, PE
Project Manager
Public Works Department
Planning Group/Hydrology Division
City of Albuquerque
P. O. Box 1293
Albuquerque, NM 87103

**RE: PRELIMINARY DESIGN SUBMITTAL
AMOLE DEL NORTE STORM DIVERSION FACILITIES, PHASE III
PROJECT #4076-01**

Dear Loren:

Greiner, Inc., is pleased to submit ten sets of the preliminary plans, preliminary estimates of cost associated calculations, and outline specifications in accordance with A/E Services Agreement 4076-01.

We appreciate the opportunity to work with the City of Albuquerque and look forward to the rapid completion of the design phase of this project.

Sincerely,

GREINER, INC.

A handwritten signature in black ink, appearing to read "Mark S. Holstad", is written over the printed name.

Mark S. Holstad, PE
Project Manager

MSH:cs

JN G0001.01

AMOLE2

TABLE OF CONTENTS

	<u>PAGE</u>
Transmittal Letter	i
Table of Contents	ii
General	1
Location Map	2
Design Criteria Determinations From Preliminary	
Analysis Phase	3
Pipe Versus Channel	
Alignment	
Crossing Structure Type	
Central Avenue Frontage Road	
Ponding Assumptions	
Sediment Removal And Control	6
Undefined Issues	6
Channel Alignment Downstream of Stinson	
Location Of Ponding At 98th And Central	
Location Of Sediment Removal And Flow Collection	
Pond At 90th And Volcano	
Preliminary Estimate of Cost	8
Appendicies	
Technical Specifications	
Hydraulic Calculations	
Preliminary Results of Geotechnical Investigation	
for Two Crossing Structures	
Minutes - Central Avenue Frontage Road Meeting	
Drainage Easement - SAD 214 Pond	
Preliminary Plans Drawing List (Plans Bound Separately)	
Channel Earthwork Cross Sections (Bound Separately)	
HYMO Input and Output (Bound Separately)	
Channel HEC-2	

GENERAL

On August 7, 1990, the Preliminary Analysis Report for Amole Del Norte Storm Diversion Facilities Tierra Bayita Facilities was submitted for review and comment. Preliminary construction plans were developed based on comments received and design guidance provided by the City. The purpose of this report is to document the analysis and decisions developed since the Preliminary Analysis Phase.

Funding is not available for the full project at this time. The project will therefore be broken into two phases, with construction of Phase IIIA as soon as the construction plans are approved and necessary easements and right-of-way can be acquired. Phase IIIB will be constructed later when funding becomes available. The breakdown between the phases is as follows (see Figure 1):

+Phase IIIA

- an open channel on the south side of Bridge Boulevard from Coors Boulevard to Unser Boulevard.
- pipe in Unser Boulevard from Bridge Boulevard to the SAD 214 Pond.
- associated rundowns, inlets and crossing structures.

+Phase IIIB

- pipe in Bridge Boulevard from Unser Boulevard to 90th Street, in 90th Street from Bridge Boulevard to north of Central Avenue and on the north side of Central Avenue from 90th to 98th.
- associated inlets.
- ponding facility north and west of 98th and Central. If design and land ownership issues can be resolved in a timely manner, this facility will be included as a part of Phase IIIA.
- flow collection and sediment removal facility at 90th and Volcano.

DESIGN CRITERIA DETERMINATIONS FROM PRELIMINARY ANALYSIS PHASE

GENERAL

There were many alternatives and recommendations presented in the Preliminary Analysis Phase report. The following decisions were reached by City Staff and/or Greiner and are used as basis for this Preliminary Design.

PIPE VERSUS CHANNEL

Channel was selected for the portion along Bridge Boulevard from the North/South Coors Detention Pond to Unser Boulevard. Pipe was selected for the remainder of the project. In each case, the selected treatment was less costly when all issues are considered, esp. right-of-way. Pipe also eliminated significant conflict with proposed roadway improvements and associated roadway access issues along Unser Boulevard north of Bridge Boulevard and along Bridge Boulevard west of Unser Boulevard.

ALIGNMENT

There were three alternate alignments presented in the Preliminary Design Analysis Report for the 90th and Central area. The selected alternate runs in Bridge to 90th, in 90th to Central and west along the north side of Central from 90th. This was identified as Alignment Alternate 2 in the Design Analysis Report. This was selected over Alternate 3, which was of roughly equivalent cost, because it only crosses Central Avenue once and does not require an easement be retained for the Bridge Boulevard alignment west of 90th. This is in accordance with the recommendation of the West Route 66 Sector Development Plan. Alternate 3 was rejected due to greater estimated cost.

CROSSING STRUCTURE TYPE

There will be channel crossing structures at Stinson Street and probably at Delgado's Wrought Iron Shop west of Stinson. The three options from the Design Analysis Report which were further considered are trapezoidal box culvert, prefabricated arch bridge and prestressed slab bridge. Trapezoidal box culvert was rejected as being not cost effective for this application. Con/Span Culvert Systems have proprietary rights to prefabricated arch bridges. Manufacturer's data give the maximum span as 24 feet, but a span of 28 feet is required for the flow depth at these locations. Additionally, the haunch of the arch interferes with the vertical profile of Stinson Street. Even if a special design were done to span 28 feet, the haunch height would increase and interfere more with the vertical profile. Prestressed slab bridges with auger

cast piles are becoming standard on City of Albuquerque drainage projects. Auger cast piles are an efficient foundation method which can be constructed in tight areas. The required span is easily obtainable with a prestressed slab bridge and are designed for low vertical clearance. Geotechnical drillings were accomplished on October 23 and 24 and preliminary indications are that either auger cast or spread footings are appropriate. The recommended design is prestressed slab with auger cast footings.

CENTRAL AVENUE FRONTAGE ROAD

The proposed storm drain west of 90th Street will be run along the alignment of the existing Central Avenue Frontage Road. The West Route 66 Sector Development Plan recommends against this frontage road, therefore it will not be replaced but instead driveways will be extended and consolidated in accordance with the West Route 66 Sector Development Plan.

PONDING ASSUMPTIONS

The Preliminary Analysis Report provided alternate hydrologic analyses comparing the use of detention ponds at 98th and Central and the existing SAD 214 Retention Pond on Unser north of Central. It has been determined to utilize both as the most cost effective means of providing storm drainage protection to the project area. The following items were considered in concluding that detention ponding areas were appropriate.

+98th and Central

- Detention ponding at this site was proposed in the original hydrologic analysis by Boyle.
- Downstream facilities are reduced in size, resulting in overall cost reduction and allowing the cost effective use of pipe where the lack of a pond would require an open channel. As noted in the previous "Pipe Versus Channel" section, an open channel has serious roadway design, right-of-way and access difficulties along Bridge Boulevard.
- It may be possible to install the ponding area initially as a retention pond prior to construction of the Phase IIIB pipe which would then convert the pond to a detention pond. This would provide significant protection to the areas east of 98th Street.
- It provides a logical location to remove a substantial sediment load from the system.

+SAD 214 Pond

- The pond is existing. The drainage easement states that City has "a permanent easement as right-of-way including the permanent right to enter upon the real estate hereinafter described at any time that it may see fit and construct, maintain and repair drainage easement".
- Reduction of the peak flow rates made possible by a detention pond has a significant impact on downstream pipe sizes. The required 108" north of Central was reduced to 72" and the required 108" south of Central was reduced to 96". Also an extremely expensive 12'x6' concrete box culvert across Central Avenue was reduced to a 91"x58" elliptical pipe.
- Maximum existing flow, without connection to the SAD 214 Pond, to the Tierra Bayita System is the approximately 305 cfs of street flow in Unser Boulevard. The existing SAD 214 Pond is adequate for existing flows draining to it and will only be inadequate upon construction of Systems 502.06 and 500.02. These systems are proposed in the West Bluff Drainage Plan and are indicated in the Location Map. There is a significant cost savings, both initially and ultimately, to size the downstream pipe to initially handle the existing street flow in Unser Boulevard and in the future, to enlarge the SAD 214 Pond and connect to the Tierra Bayita System such that released flow rates will be substantially reduced. As indicated in the HYMO printout, a peak outflow under ultimate conditions is 311 cfs and a maximum water surface of 5097.2 will allow 2.2 feet of freeboard versus the spillway elevation of 5099.4.
- Necessary pond volume can be developed by lowering the bottom of pond elevation from 5095' to 5090' without enlarging the horizontal limits of the pond.
- It is recommended that the pipe in Unser be designed for the ultimate flow of 311 cfs. Since the existing pond is adequate until Systems 502.06 and 500.02 of the West Bluff System are constructed, it is recommended that the designer of the 500.02 System also design the pond modifications and connection to the Tierra Bayita

System. It is believed that the proposed Tierra Bayita design provides adequate flexibility to the future designer.

SEDIMENT REMOVAL AND CONTROL

Experience has shown a strong need for provisions to remove sediment in some locations and to keep the sediment in the flow in other locations. In accordance with the recommendations of the Preliminary Analysis Report, sediment will be removed at the following locations:

- the existing North/South Coors Detention Pond. This facility is already maintained, therefore this is the most efficient location to remove additional sediment.
- the proposed ponding facility at 98th and Central.
- possible sedimentation and flow collection facility at 90th and Volcano. This facility would be temporary and would be abandoned when allowed by upstream development and extensions of the storm drain. The Water Utilities Division is currently considering the use of City owned property at the southwest corner of 90th and Volcano for this drainage facility. If the City owned property is not available, then vacant property north of Volcano needs to be obtained for sediment removal.
- the existing SAD 214 Pond.

A "rundown inlet" has been developed for this project. The intent of this inlet is introduce the storm runoff into the storm drain without reducing the runoff velocity. The reduction in velocity caused by typical inlet or headwall design results in sediment being "dumped" at the inlet or headwall and the flow being plugged and/or rerouted. The swales graded to the rundown inlets are intended to be flat bottomed with a lower velocity in the swale than will be maintained within the storm drain. Typical design calculations are included in this report.

UNDEFINED ISSUES

CHANNEL ALIGNMENT DOWNSTREAM OF STINSON

Detailed discussion of options has not been accomplished by the City with the owner of Delgado's Wrought Iron Shop at 3720 Bridge Boulevard SW therefore the final channel alignment downstream of Stinson Street has not been set. There are unresolved issues relative to existing structures, however it is more likely that the

channel will have to be fit between the existing PNM power lines and the existing shop building. Discussions with two local contractors indicated that a minimum of at least 6' clear is necessary from the outside lip of the channel to an obstruction if a paving machine is to be used, therefore 8' clear to the centerline of pole (7.3'+/- net clear) was provided upstream of Stinson and would also be provided downstream if a portion of Delgado's shop can be relocated. Discussions with Blake Forbes of PNM indicate a minimum clearance requirement of 2'. This will require temporary guying by PNM during channel construction. This is constructable for the channel contractor but will require more expensive hand work. A sketch design downstream of Stinson Street is provided in the preliminary construction plans based on the assumption that the shop will remain. A crossing structure will most probably be required and is only shown schematically due to lack of input by the affected property owners.

LOCATION OF PONDING AT 98TH AND CENTRAL

Alternate layouts for ponding at 98th and Central are under consideration. A PNM power line easement on the east side of 102nd Street has been identified as a possible alternate ponding site. Preliminary contacts with PNM have been positive. This location may be less costly and have much less impact on local aesthetics. Final analysis and decisions are not possible until the City of Albuquerque completes title searches on the properties under consideration. If these issues are quickly resolved, this ponding will be included in Phase IIIA.

As is noted above, design and analysis of ponding alternates at 98th and Central is being delayed. The design impact to Phase IIIA, which will be constructed as soon as possible, is negligible since the City has made a commitment to the concept of flow attenuation at this site. Additionally, the only portion of Phase IIIA affected by the flow from 98th and Central is the open channel along Bridge Boulevard. Open trapezoidal channels are very forgiving of flows in excess of the design rate.

LOCATION OF SEDIMENT REMOVAL AND FLOW COLLECTION POND AT 90TH AND VOLCANO

As noted above, the precise location of the facility at 90th and Volcano is dependant on a determination of the Water Utilities Department of their need for existing City owned property at 90th and Volcano.

PRELIMINARY ESTIMATE OF COST

	Phase IIIA	Phase IIIB
Channel Paving	565,000	-0-
Earthwork	177,000	26,000
Storm Drain Pipe and Appurtenances	780,000	1,367,000
Inlets and Connector Pipe	178,000	64,000
Water and Sewer Relocations	43,000	-0-
Paving Replacement	135,000	113,000
Dry Utility Costs	*	*
Crossing Structures	230,000	-0-
Ponds	-0-	320,000
Sub-total	2,108,000	1,890,000
Contingencies-10%	210,800	189,000
Total Construction	2,318,800	2,079,000
Survey - 3%	69,564	62,370
Testing - 1%	23,188	20,790
Inspection - 2.5%	57,970	51,975
Legal, Administrative by City		
Right of Way, Easements	*	*
Total Costs	2,469,522	2,214,135

* Unknown. No cost included in estimate.

TECHNICAL SPECIFICATIONS

STANDARD SPECIFICATIONS

INCORPORATION OF CITY OF ALBUQUERQUE STANDARD SPECIFICATIONS:
The City of Albuquerque Standard Specifications for Public Works Construction, 1986 Edition, General Conditions and Technical Specifications, as updated, are incorporated by reference, the same as if fully written herein and shall govern this Project except where revised, updated or supplemented by the Special Provisions and/or the Supplemental Technical Specifications.

The City of Albuquerque Standard Specifications for Public Works Construction, 1986 Edition, may be purchased separately by contacting the Engineering Group, Public Works Department, P.O. Box 1293, Albuquerque, New Mexico 87103.

Updates to the City of Albuquerque Standard Specifications for Public Works Construction, 1986 edition, are listed on page SS-2.

UPDATES
TO
STANDARD SPECIFICATIONS

The following is a list of Updates which have been issued to the City of Albuquerque Standard Specifications for Public Works Construction, 1986 Edition:

<u>Update No.</u>	<u>Effective Date</u>
One	March 25, 1987
Two	January 1, 1988
Three	July 1, 1988

HYDRAULIC CALCULATIONS

EXISTING LOCAL HYDROLOGY

1. SKYVIEW WEST SUBDIVISION
2. UNSER BLVD. BETWEEN CENTRAL ^{AND} ~~AT~~ BRIDGE

Job Anahe Del Norte Computed By SG Date 25 July 93
 Description Hydrology - SkyView Checked By MSB Date _____
West Subdivision Sheet 1 of 2

Use Rational Method

Area = 71.8221 Ac (From planimeter of area using
 1" = 1000' Topo map from Boyle
 report)

residential area C = .33 (From Boyle Report)

Intensity

Rainfall = 2.2" 100 yr DPM Plate 22.2 D+
 1.45 10 yr
 0.98 2 yr

All flows drain to Bridge Blvd. Using SkyView West
 Drainage Report, divide area → Unit 1, Unit 2. Then divide
 Unit 1 into 2 areas (one draining to Bridge thru east lot
 lots 67 + 68 + one draining to 75th St. (I also used
 topo from Boyle report. Areas shown on Zone Atlas
 page Attached)

① Area = 21.9 Ac L = 1600' S = .008 Tc = 15 min

② Area = 38.3 Ac L = 2000 S = .01 Tc = 16 min

③ Area = 11.6 Ac L = 950 S = .008 Tc = 10 min

Tc = .0008 $\frac{L^{.77}}{S^{.385}}$ DPM 22.2 p. 31

Intensity = ① 1.75 (2.2) = 3.85
 (1.45) = 2.54
 plate 22.2 ② 1.70 (2.2) = 3.74
 D2 (1.45) = 2.47
 ③ 2.17 (2.2) = 4.77
 (1.45) = 3.14

Job Anole C 000101

Computed By SG

Date 26 July 90

Description _____

Checked By WMA

Date _____

Sheet 2 of 2

$$\begin{aligned} \textcircled{1} \quad Q_{100} &= (.83)(3.85)(21.9) = 70 \\ Q_{10} &= " (2.54) " = 46 \end{aligned}$$

$$Q = C I A$$

$$\begin{aligned} \textcircled{2} \quad Q_{100} &= (.83)(3.74)(38.3) = 119 \\ Q_{10} &= " (2.47) " = 79 \end{aligned}$$

$$\begin{aligned} \textcircled{3} \quad Q_{100} &= (.83)(4.77)(11.6) = 46 \\ Q_{10} &= " (3.14) " = 30 \end{aligned}$$

Job AMOLE DEL NORTE

Computed By 29

Date 27 Aug 90

Description Hydrology

Checked By W/O 12

Date

Revise Sky view West Subl. Flow to
2 yr

Sheet of

Intensity

①	1.75	(.93)	=	1.72
②	1.70	(.93)	=	1.67
③	2.17	(.93)	=	2.13

22.2
D2

$Q = C I A$

$Q_2 =$

①	(.93)	(1.72)	(21.9)	=	31.3
②	(.93)	(1.67)	(38.3)	=	53.1
3	.93	(2.13)	11.6	=	20.5

2 yr
flows

Swale Capacity

use Section @ Sta 39+70

0	84.13
12	84.0
16	83.6
20	84.0
30	86.0

$N = 1.3$ $S = .008$

MAX Q = 12.5 cfs

12

@ R.R. = 43.8
@ 75th = 96.9
@ Sesau = 117.4

27Aug 1990

MANNINGS n
STA(ft) ELEV(ft) (to Next #)

0	84.13	.03
14	84	.03
24	83.6	.03
38	84	.03
30	86	.03


SQ

Rating curve for
existing swale
at Sta 34+70

Channel Slope = .008 ft./ft.

RATING CURVE

WSE(ft)	D(ft)	AREA-sf	WT.P-ft	Q-(cfs)	V-fps	Fr.#	TW(ft)
83.6	0	0	0	0	0	0	0
83.7	0	.2	6	.1	.6	.474	5.9
83.7	.1	1.1	12	1.1	.9	.533	11.9
83.9	.3	2.7	18	3.3	1.2	.57	18
84	.4	4.8	24	7.2	1.5	.598	24
84.1	.5	7.7	35.1	12.4	1.6	.6	34.3
84.2	.5	11.4	38.8	22.3	1.9	.624	37.2



SCOTT

TRACT J
BUSINESS
SU-1 FOR A PLANNED INDUSTRIAL PARK
LO 73-432

PARK
LOT 2

UNIT 2

UNIT 4

SU-1
V. E. BARR

SU-1
V. E.

SU-1
SUB D

SU-1

Job Annie Del Norte Computed By S. John Date 4 Sept 90
 Description Determine Flow in Checked By MSR Date _____
Linsar South of SADDY POND to Central Sheet _____ of _____

$$\begin{aligned}
 433 \times 124 &= 53,692 \\
 125 \times 25 &= 3,125 \\
 30 \times 20 &= 600 \\
 1/2(10) \times 37 &= 185 \\
 70 \times 40 &= 2,800 \\
 25 \times 30 &= 750 \\
 \hline
 &61,152
 \end{aligned}$$

$$\begin{aligned}
 655 \times 124 &= 81,220 \\
 70 \times 24 &= 1,680 \\
 130 \times 66 &= 11,380 \\
 130 \times 50 &= 6,500
 \end{aligned}$$

TOTAL AREA
 $162,432 \div 43 = 3,729 \text{ Ac}$

Use Rational to Determine Q_{100}

$$Q = C I A$$

$V_c = .0078 \frac{L^{.77}}{S^{.335}} - 2\text{-SEGMENTS}$ (1) $L = 350 \quad TC = 13.36$
 $S = .0176$

(2) $L = 718 \quad TC = 10.06 \text{ min}$
 $S = .0043$
13.4 min

INTENSITY - 6hr rainfall = 2.2"
 dimensionless rainfall int = 1.9

$$I_{100} = 2.2 \times 1.9 = 4.18$$

$$I_{10} = 1.45 \times 1.9 = 2.75$$


$C =$ streets, drives, etc 0.95 3.160 . 87 = composite C
 undeveloped 0.40 0.569

Assume median will be 8' wide under fully developed conditions
 use 7' on each side in R/W that is undeveloped
 $3 + 7 + 7 = 22 \times 1068 \div 2 = 24,796 \div 4 = 6,199 \text{ Ac}$
 use 10' x 130' under @ Sarricino



$Q_{100} = (.87)(4.18)(3,729) = 13.6 \text{ cfs}$ assume 2 cfs each side $d = .62$
 $Q_{10} = (2.75) = 3.9 \text{ cfs}$ assume 4.5 cfs each side $d = .49$

depth .49 leaves 7' clear (curb - 1/2" $\rightarrow$ leaves $d = .36$ $\frac{.36}{.102} = 18 \quad 25 - 18 = 7'$)

GRATING CAPACITIES FOR TYPE "A" , "C" and "D"



GRATING & GUTTER PLAN

TYPICAL HALF STREET SECTION
(ABOVE BASIN)

Greiner

Job Annie Computed By SD Johnson Date 19 Oct 90
Description C.B. at Unser / Central Checked By WJZ Date _____
to pick up local flow in Unser (S of pond) Sheet _____ of _____

$$Q_{100} = 13.6 \text{ cfs}$$
$$Q_{10} = 8.9 \text{ cfs}$$

existing road slope = 0.0043 (from SAC 214 plans)
As Built

existing C.B. type C

1/2 street is 24' wide

7 cfs in each side $D = .55$ (use DPM plate D-3 22.3)
cap = 6 cfs (DPM plate 22.3 D-5) Cor A

DROP INLETS

1. Sesame St.
2. 75th St.
3. Rundown
5. Unser Blvd (Weenah inlet)

CATCH BASIN CALCULATION SHEET

Sht. of

PROJECT Amole III A
DESIGN FREQUENCY As shownCALCULATED BY WAL
DATE 10/30/90sewer st.

FLOW DIAGRAM (Indicate street slopes)	Sym.	Drain. Area	Q		Cap. of 1/2 Street	Gutter "d"	C.B.		Connector Pipe		V Depth
			Total	Inter.			No.	Size	Head	L	
			810								
			15	7.5		0.42	1	A			
			7.5	5.5		0.34	1	2c			
			2	2		0.23	1	2c			
			9100								
			23	9		0.46	1	A			
			14	8		0.40	1	2c			
			6	5		0.32	1	2c			
			1								

CATCH BASIN CALCULATION SHEET

22.3

Sht. of

PROJECT Amo/c III A

DESIGN FREQUENCY As Shown

75454

CALCULATED BY MAK

DATE 10/30/90


DESIGN FREQUENCY <i>4.5%</i>	FLOW DIAGRAM (Indicate street slopes)	Sym.	Drain. Area	Q		Cap. of 1/2 Street	Gutter "d"	C.B.		Connector Pipe			V Depth
				Total	Inter.			No.	Size	Head	L	Dia.	
				Q ₁₀			0.62	1	A				
				39	11		0.52	1	2C				
				28	11		0.47	1	2C				
				17	8		0.39	1	2C				
				9	6		0.26	1	2C				
				3	2.5								
				0.5									
				4100			0.75	1	A				
				60	14		0.67	1	2C				
				46	15		0.58	1	2C				
				31	12		0.48	1	2C				
				19	9		0.39	1	2C				
				10	6								
				4									

Find max. flow in Bridge during Q_{10} .
 Keep one lane open $\therefore$ max. depth = $12' \times 2\% = 0.24'$ 22.3

slope = 1.3%

STREET CAPACITY

$\Rightarrow$ Allowable $Q_{10} = 1.3$ cfs in Bridge, each side
 For Q_{100} , say max. depth = 0.67' $\Rightarrow$ 42 cfs each side Q_{100}



Job Amelia 10045

Computed By 20.1

Date 28 Aug 90

Description INLET CAPACITY

Checked By MA 12

Date _____

Sheet _____ of _____

INLET CAPACITY IN SKYVIEW WEST 100 yr Flood

At 75th St $Q = 119$ cfs 60 cfs each side of street
 $S = 2\%$ (approx - scale from 1" = 100' topo)

to pick up 100 yr flow

A - 14 cfs	$S = 2\%$	$d = .75'$	$Q = 60$
B - 21 cfs	$S = 2\%$	$d = .67$	$Q = 46$
B - 15	$S = 2\%$	$d = .54$	$Q = 25$
B - 3	$S = 2\%$	$d = .4$	$Q = 10$

At SESAME STREET $Q = 46$ 23 cfs each side of street
 $S = 4\%$ (approx)

A - 9 cfs	$S = 4\%$	$d = .46$	$Q = 23$
B - 10	$S = 4\%$	$d = .40$	$Q = 14 \rightarrow 4$ to Bridge
C - 8	$S = 4\%$	$d = .40$	$Q = 14 \rightarrow 6$

use 1-A & 1-C (double) = 23 cfs each side

At RUNDOWN $Q_{100} = 70$ cfs

need info

Job _____ Computed By Seni Date 24 Oct 90
 Description Inlets at Ruckman Checked By MIR II Date _____
to Bridge in Sky View Creek Subd. Sheet _____ of _____

$$100 \text{ yr } Q = 70 \text{ cfs } d = .64$$

$$10 \text{ yr } Q = 46 \text{ cfs } d = .50$$

type D double cor STD inlet capacity

assume $S = .6$ $d = .64$ $1 - 11.5 \text{ cfs} \times 3 = \frac{70}{34.5}$

$$\frac{35.5}{15} \quad d = .4$$

$$20.5 \quad Q = 5 \times 3$$

10 year $S = .6$ $d = .50$ $1 - 8 \text{ cfs} \times 3 = \frac{46}{22}$ $d = 0.3$

$$d = .3 \quad 1 - 3 \text{ cfs} \times 3 = 9$$

100 yr

D - grate area $2' 1\frac{1}{2}" \times 6' 4\frac{3}{4}"$

$$2.125' \quad 6.396'$$

us $25"$ 2.08 $3.336, 3.96$ use type D grate dimension

$$1 - 2.08 \times 3.33$$

$$- .54 - .38$$

$$1.54 \times 2.95 = 4.5$$

$$13\frac{1}{2}" \text{ bars}$$

$$14\frac{1}{2}" \text{ bars}$$

$$- .54'$$

$$- .58'$$

$$1.54$$

$$5.81 = 8.9 \text{ ft}$$

Use $D = .6$ $Q = 34 \text{ cfs}$

use $D = 1'$ $Q = 43 \text{ cfs}$

use 3 single grates 4.5 $D = .6$ $Q = 16 \times 3 = 48$ or $\times 4 = 64$

$D = 1'$ $Q = 21 \times 3 = 63$ or $\times 4 = 84$

Capacity at rundown
in SkyView West Subd.
to Bridge Blvd.

STA(ft)	ELEV(ft)	MANNINGS n (to Next #)
0	.67	.013
0	0	.013
10	0	.013
10	.67	.013

Channel Slope = .02 ft./ft.

RATING CURVE

WSE(ft)	D(ft)	AREA-sf	WT.P-ft	Q-(cfs)	V-fps	Fr.#	TW(ft)
0	0	0	0	0	0	0	0
0	0	.5	10.1	1	2.1	1.72	10
.1	.1	1	10.2	3.4	3.4	1.92	10
.1	.1	1.5	10.2	6.7	4.4	2.04	10
.2	.2	2	10.4	10.8	5.4	2.12	10
.2	.2	2.5	10.5	15.5	6.2	2.19	10
.3	.3	3	10.6	20.9	6.9	2.24	10
.3	.3	3.5	10.7	26.9	7.6	2.29	10
.4	.4	4	10.7	33.4	8.3	2.32	10
.4	.4	4.5	10.9	40.4	8.9	2.36	10
.5	.5	5	11	47.9	9.5	2.38	10
.5	.5	5.5	11.1	55.8	10.1	2.41	10
.6	.6	6	11.2	64.1	10.6	2.43	10
.6	.6	6.5	11.2	72.8	11.2	2.45	10
.7	.7	0	0	0	11.2	2.45	0

Greiner

Job Amek G000101

Computed By S. John

Date 19 Oct 90

Description Capacity for

Checked By M. J. P.

Date _____

Necan. grates at Waser / W. J. Pond

Sheet _____ of _____

Use R 3073 L at curb + R 3079 - L across street
R 3580 ? 200

Street slope = 2%


cross slope = 2% cross slope = 1.4%

2% K = 24 - use chart for R 3079 - L - same size

1.4% K = 22

at-type 5151c


$$Q = K D^{5/3}$$



Q = 305 cfs


$$24 (.855)^{5/3} = 18.5$$

.825	= 17.4
.795	= 16.4
.765	= 15.4
.735	= 14.4
.705	= 13.4
.675	= 12.5
108.0	



Q = 44.5
D = .66

each unit = 17 3/4" wide
or 1.48' use 7 - 10.35'



152.5

$$24 (.645)^{5/3} = 11.5$$

.615	= 10.7
.585	= 9.8
.555	= 9.0
41	

@ end
3.5 cfs S = 1.4% D = .32
cap = 3 cfs

OR

A @ Beginning D = .37 Q = 18 cfs
S = 2%

152.5 - 18
134.5 - 108
26.5 - use 3 at last
cut

R-3076 3 Flange Gutter Inlet Frame and Grate



Heavy Duty

Total Weight 400 Pounds

For frame only — specify R-3076 frame only

For grate only — specify R-3076 grate only

Also available with Type L grate. See R-3079.




Curb Hoods

R-3076-4M

Heavy Duty

Total Weight 165 Pounds

Catalog # refers to hood only.




4" MOUNTABLE CURB HOOD

R-3076-6B

Heavy Duty

Total Weight 185 Pounds

Catalog # refers to hood only.




6" BARRIER CURB HOOD

R-3076-6M

Heavy Duty

Total Weight 180 Pounds

Catalog # refers to hood only.




6" MOUNTABLE CURB HOOD

R-3076-8B


Heavy Duty

Total Weight 220 Pounds

Catalog # refers to hood only.



8" BARRIER CURB HOOD



Front View

R-3077 Double Unit Inlet Frame and Grate

Heavy Duty Total Weight 750 Pounds

For full double unit — specify R-3077.

For left section (frame and grate) only — specify R-3077-L.


For left section frame only — specify R-3077-L frame only.

For right section (frame and grate) only — specify R-3077-R.


For right section frame only — specify R-3077-R frame only.

Grates are same as R-3076 unit.

Also available with Type L grate. See R-3079.



If curb hoods are required, see listing under R-3076.







INLET GRATE CAPACITIES

FOR GUTTER FLOW
and
PONDED WATER

INTE



FLOW →



S_T = TRANSVERSE GUTTER SLOPE
 S_L = LONGITUDINAL GUTTER SLOPE
K = GRATE INLET COEFFICIENT

1977 Neenah Foundry Co.



FLOW →



S_T = TRANSVERSE GUTTER SLOPE
 S_L = LONGITUDINAL GUTTER SLOPE
K = GRATE INLET COEFFICIENT

© 1976 Neenah Foundry Co.



FLOW →



S_T = TRANSVERSE GUTTER SLOPE
 S_L = LONGITUDINAL GUTTER SLOPE
K = GRATE INLET COEFFICIENT

1976 Neenah Foundry Co.

FLOW →



S_T = TRANSVERSE GUTTER SLOPE
 S_L = LONGITUDINAL GUTTER SLOPE
K = GRATE INLET COEFFICIENT

1985 Neenah Foundry Co.

RUNDOWN I NLET

1. Basic Concept
2. Inlet at Bridge / coors

Job G0001.01

Computed By MSH

Date 10-30-90

Description Rundown Inlet

Checked By _____

Date _____

Sheet 1 of 12

Problem

There is a need for an inlet which can drain an earth lined swale without being plugged by sediment. Typical solutions are inadequate, i.e.,

- turtle back or bee hive inlet requires ponding around inlet during design flows. Ponding increases depth which decreases flow velocity which drops out the sediment before the inlet.
- headwall culverts. Same thing can and will happen, e.g., 30" SD at 98th, Central on 8/22/90.

Individual sediment removal basins prior to each inlet would be a maintenance nightmare and would probably not be maintained.

Develop an inlet assuming:

- temporary in most but not all locations.
- will be converted to standard inlets when future street improvements are made.
- use standard construction materials that can be converted to a standard manhole and brought to grade for future road.

Job _____ Computed By _____ Date _____
 Description Rundown Inlet Checked By _____ Date _____
 Sheet 2 of 12


Given

Develop typical inlet based on existing swale on north side of Bridge Blvd. west of Coors. (Note: this location no longer requires an inlet due to recent installation of asphalt curb on the north side of Bridge. The concepts in the following calculations are still appropriate, however).

Develop details and present for review and comments.

Analysis

Existing earth lined swale on north side of Bridge. The slope is 1.99%.



$Q = 58 \text{ cfs}$ } ^{see attached} // Greater flows will go south
 $V = 4.3 \text{ fps}$ } ^{rating} over Bridge.
_{sheet, all.}

Collect flow with cut off wall & weir. Size minimize flow velocity disruption. See details attached. See attached rating curve. Weir 12' wide and 1' deep.

Accelerate and converge flow in rundown sloped at 20°, with 6' throat. This allows use of standard 6" ID manhole barrels with modifications on top. Larger or smaller (4" ID or 8" ID) barrels may be used in

Job _____ Computed By _____ Date _____
Description Rundown Inlet Checked By _____ Date _____
Sheet 3 of 12

other locations. As shown in the attached rating curve #12, the flow will $0.46' \pm$ (5.5") deep at the entry to the manhole.

Other Considerations

- 1) Include bars to prevent people being swept in.
- 2) Provide vented cover to provide air flow.
- 3) Detail floor to provide smooth transition to outlet pipe.
- 4) Check pipe velocities to assure that velocities are maintained that are greater than surge velocity for various flow rates. See attached sheet 4.
- 5) Check outlet pipe to assure that flow is not restricted. Rule of thumb is to check inlet control and verify that depth is less than or equal to $1.5 \times$ pipe diameter. See attached sheet 5.

Greiner

Job Amole Coors / Bridge Fix Computed By Johnson Date 10 Oct 90
 Description Check Pipe Velocity Checked By MS/P Date _____
vs Ditch Velocity - to make Sheet 4 of 12
sure pipe stays fast enough to carry sediment

42" RCP - max Q = 58 - S = 0.91%

Flow (cfs)	Depth (ft)	Velocity (fps)	Velocity in Channel
0	0	0	
10	.77	6.4	2.3
20	1.08	7.9	3.2
25	1.20	8.4	3.4
30	1.34	8.8	3.7
40	1.58	9.5	3.9
50	1.79	10.1	4.1
58	1.96	10.4	4.3

48" RCP - max Q = 116 - S = 1%

Flow	Depth	Velocity
10	0.72	6.6
20	1.00	8.0
40	1.44	9.8
60	1.80	10.9
80	2.13	11.7
100	2.46	12.4
116	2.73	12.7

Channel velocities
Same as above

Greiner

Job Amole - Bridge / Coors Fly Computed By L Johnson Date 10 Oct 90
Description Check inlet control Checked By WJH Date _____
for 42" + 48" pipes - Sheet 5 of 12

Check inlet control - see attached

36" ϕ SD Reg'd $Q = 58$ cfs (per rating curve attached for ditch)
 $\rightarrow H_w/D = 1.6$
 $H_w = 4.8$ or 1.8 depth over pipe

48" ϕ SD Reg'd $Q = 116$ cfs


$H_w/D = 1.55$
 $H_w = 6.2$ or 2.2' depth over pipe
(lower MH invert so 6.2 is ok)

use 42" ϕ SD @ $Q = 58$ cfs

$H_w/D = 1.1$
 $H_w = 3.85$

← use 42"
INSTEAD OF 36"

FIGURE 804-1D



HEADWATER DEPTH FOR
CONCRETE PIPE CULVERTS
WITH INLET CONTROL

Job G000103

Computed By MSH

Date 10-3-90


Description Amole - Bridge


Checked By shi En

Date 10/9/90

Drainage - Temp. Fix

Sheet 7 of 12





N.T.V.

Job _____

Computed By MSH


Date 10-3-90

Description _____

Checked By Shi En

Date 10/9/90

Sheet 9 of 12



10 of 12

Channel Slope = .019 ft./ft.

1000 9999 8888 7777 6666 5555 4444 3333 2222 1111 0000 999

WSE(ft)	D(ft)	AREA-sf	WT.P-ft	Q-(cfs)	V-fps	Fr.#	TW(ft)
0	0	0	0	0	0	0	0
.1	.1	.1	2.7	.1	.9	.73	2.7
.2	.2	.5	5.4	.7	1.4	.82	5.4
.3	.3	1.2	8.1	2.3	1.9	.877	8.1
.4	.4	2.1	10.8	5	2.3	.92	10.8
.5	.5	3.3	13.5	9.1	2.7	.955	13.5
.6	.6	4.8	16.2	14.8	3	.985	16.2
.7	.7	6.6	18.9	22.4	3.3	1.01	18.9
.8	.8	8.6	21.6	32	3.7	1.03	21.6
.9	.9	10.9	24.3	43.8	4	1.05	24.3
1	1	13.5	27	58.1	4.3	1.07	27

STA(ft)	ELEV(ft)	MANNINGS n (to Next #)
0	1	.017
0	0	.017
12	0	.017
12	1	.017

Channel Slope = .2 ft./ft.

RATING CURVE

WSE(ft)	D(ft)	AREA-sf	WT.P-ft	Q-(cfs)	V-fps	Fr.#	TW(ft)
0	0	0	0	0	0	0	0
.1	.1	1.2	12.2	10	8.3	4.65	12
.2	.2	2.4	12.4	31.4	13.1	5.16	12
.3	.3	3.6	12.6	61.2	17	5.47	12
.4	.4	4.8	12.8	97.8	20.3	5.67	12
.5	.5	6	13	140.4	23.4	5.83	12
.6	.6	7.2	13.2	188.4	26.1	5.95	12
.7	.7	8.4	13.4	241.1	28.7	6.04	12
.8	.8	9.6	13.6	298.3	31	6.12	12
.9	.9	10.8	13.8	359.5	33.2	6.18	12
1	1	12	14	424.4	35.3	6.23	12

12 of 12

STA(ft)	ELEV(ft)	MANNINGS n (to Next #)
0	1	.017
0	0	.017
6	0	.017
6	1	.017

Channel Slope = .2 ft./ft.

RATING CURVE

WSE(ft)	D(ft)	AREA-sf	WT.P-ft	Q-(cfs)	V-fps	Fr.#	TW(ft)
0	0	0	0	0	0	0	0
.1	.1	.6	6.2	4.9	8.2	4.6	6
.2	.2	1.2	6.4	15.4	12.8	5.06	6
.3	.3	1.8	6.6	29.6	16.4	5.3	6
.4	.4	2.4	6.8	46.9	19.5	5.45	6
.5	.5	3	7	66.8	22.2	5.55	6
.6	.6	3.6	7.2	88.8	24.6	5.61	6
.7	.7	4.2	7.4	112.8	26.8	5.65	6
.8	.8	4.8	7.6	138.5	28.8	5.68	6
.9	.9	5.4	7.8	165.6	30.6	5.69	6
1	1	6	8	194.1	32.3	5.7	6

Job Amie Dec No. 10

Computed By S. Johnson


Date 27 Oct 90

Description _____

Checked By M. J. /

Date _____

Sheet _____ of _____



② D=96

A=

V=12.25

① D=96

A=50.266

V=10.72

① D=90

A=

V=12.20

$\frac{V_2}{2.5} = 2.34$

$$* h_j = \frac{V_2^2}{2g} - \left(0.5 \frac{V_1^2}{2g} \right) = 1.43 \quad d=96$$

$$1.17 \quad d=90$$

* revision of formula in DPM to allow for 90° turn
(from Glenn Shiao)

Transition Loss - expansion

$$K_e = 3.50 (\tan \theta/2)^{1.22}$$

$$K_e = .85$$

$$\tan \theta/2 = .3125$$


don't divide by 2 since all on one side

$$h_t = K_e \frac{(V_1 - V_2)^2}{2g} = .03 \quad .01$$

$$\text{total } h = 1.19 + .03 = 1.22$$

Job Annie Computed By S. Johnson Date 27 Oct 90
 Description Junction Loss at Checked By [Signature] Date _____
Sta 126+91 Sheet _____ of _____

Sta
126+91



③ Q = 212

Dia = 48"

A = 12.566

V = 16.87

~~54~~
~~15.904~~
~~13.33~~


$$\Delta y = \frac{Q_2 V_2 - Q_1 V_1 - Q_3 V_3 \cos \theta}{\frac{1}{2} (A_1 + A_2) g}$$

$$\frac{539(10.72) - (311)(11.00) - 212(16.87) \cos 45^\circ}{\frac{1}{2} (50.266 + 28.224) \cdot 32.2} = .49$$

$$\frac{1}{2} (50.266 + 28.224) \cdot 32.2$$

Job _____ Computed By S. Johnson Date 27 Oct 90
 Description _____ Checked By MJD Date _____
 Sheet _____ of _____


Sta 129+00 Junction Box - transition
from 72" Φ pipe to 91 x 58 elliptical pipe
- use highest transition loss - L_A Q = 311



$$\tan \frac{\theta}{2} = 0.1463$$

$$K_e = .33$$

$$h_t = .0005$$



$$\tan \frac{\theta}{2} = .1979$$

$$K_e = .49$$

$$h_t = .0008$$

① transition 78" to 91 x 58 $A = 33.183$

$$\tan \theta = .2033 \quad \tan \frac{\theta}{2} = .0677 \quad V = 11.24$$

$$K_e = .52$$

$$h_t = .02$$

$$K_e = .13$$

$$h_t = .004$$

$$h_{min} = .12$$

Job Annie

Computed By Stuchison

Date 11 Oct 90

Description H.G.L. Along Doser

Checked By WJH


Date _____

Sheet 4 of 5

STA 131+40 JB - Change pipe size + shape
 91x58 to 72" ϕ (A+B) (C) 91x58 to 78" ϕ
 USE LARGEST

$$h_{MH} = .14$$

use transition loss DPM 22.3 p. 31 (plate B-2)




$$h_t = K_c \frac{(V_1 - V_2)^2}{2g}$$

VERTICAL

$$\tan \theta = .1463$$

$$K_c = .33$$

$$\text{exp. } h_t = .001$$




$$\tan \theta = 1.58/8 = 0.1975$$

$$K_c = .48$$

$$h_t = .003$$

$$K_c = .13$$

Sta 111+69.9 to 111+17.9 transition 102" to 8' trans. 96"



use DPM 22.3 p. 31 plate B-2

$$\theta = 3-34-35$$


$$K_c = .12$$

$$K_c = 3.50 (\tan \frac{\theta}{2})^{1.22}$$

$$h_t = .005$$

$$h_t = K_c \frac{(V_1 - V_2)^2}{2g}$$

Sta 127+21 to 127+41



$$\theta = 10-37-11$$

$$K_c = .45$$

$$h_t = .06$$

transition 96 to 78' in 8'
 use DPM 22.3 p. 31 pl B-2

SUMMARY OF HYDRAULIC CALCULATIONS

PROJECT: Amole

CLOSED CONDUIT 90th - Central to and
LINE: Central - 90th to 98th

BY: S.D. h...
DATE: 30 Oct 1990
SHEET: 2 OF 2

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22
STATION	STRUCI	D	Q	A	V	K	S _f	L	Δ	JUNCTION		LOSSES						Σ	E.G.	h _v	H.G.
										D	θ	h _f	h _m	h _j	h _{misc}						
73+14	W4																				
77+25	trans	2'	728	38.485	18.72	6380	.0130	411				5.34				.005		534	133.14	5.56	132.92
77+25		90"	728	44.179	16.48	7677	.0090	39				.35						.01	138.49	4.22	134.27
77+25	JD	66"	382	23.753	16.08	3358	.0129	122				1.57		1.90				.35	138.83	4.22	134.61
11+22	JB	66"	382	"	"	"	.0129	355	45'			4.58	.57		.2			1.57	140.73	4.01	138.28
																		.27	142.50	4.01	139.06
																		4.58	143.07	4.01	143.64
																		4.58	147.65	4.01	
77+64	JB	66"	384		15.32		.0125	306				4.42						4.42	140.73		
																			145.15	3.64	141.51

REMARKS:

WARNING'S:

- pipe goes to normal depth in next segment

Central

90th

Job AMOLE

Computed By L. Johnson Date 30 Oct 90

Description _____


Checked By MAJ

Date _____

Sheet _____ of _____

Sta 77+64

JUNCTION



$$\Delta y = \frac{728(18.92) - 364(15.32) - 382(16.08) \cos 45}{\frac{1}{2} (23.758 + 38.485) 32.2}$$

$$\Delta y = 3.85 @ \sec \theta = 84'' \quad \Delta y = 1.90 @ \sec \theta = 90'' \quad \Delta y = 2.65 @ \theta = 30^\circ$$

trans loss 84 → 90 .005

$$\Delta y = 2.87$$

NO

$$\frac{728(18.92) - 364(18.54) - 382(16.08) \cos 45}{\frac{1}{2} (19.635 + 38.485) 32.2}$$

NO

$$\Delta y = 1.89$$

NO

MISCELLANEOUS

Greiner

Job Amole DEL NORTE Computed By 202/Amole Date 30 Oct 90
 Description Determine Pipe Class Checked By WIS Date _____
Conc. Pipe Design Manual 5th printing Sheet _____ of _____
June 1980 p. 45

Unser

- use Sand + Gravel backfill - 110#/CF
 Assume Type C Bedding - $B_s = 1.5$
 $F.S. = 1.0$ (circular + elip.)

$$D_{0.01} = \frac{W_L + W_E}{B_s \times D} \times F.S.$$

$B_s \times D$

100#/CF

TABLE 45

	D	H	W_E	$W_E + 10\%$	W_L	$D_{0.01}$	Class
96"	8'	8'	2937	9831	750	882	CI III
96"	8'	3'	5251	5776	1500	606	"
72"	6'	6'	5053	5558	880	715	"
91"x58"		3'10'					
72"	6'	9'	8239	9063	540	1067	"

91x58 8' 11,000 12,100 810 974 CLIII
 Use Figure 155.1

$$D_{0.01} = \frac{W_L + W_E}{B_s \times S} \times F.S. = 974$$

$S = 8.83$ (add 7 1/2" wall)

Bridge

	D	H	$W_E - 100$	$W_E - 110$	W_L	$D_{0.01}$	Class
84"	7'	6'	5738	6312	960	693	III
84"	7'	9'	9242	10,166	600	1025	"
66"	5.5'	7'	5660	6226	700	840	"
60"	5'	3'	3522	3874	1680	741	"
60"	5'	2'	5268	5795	650	859	"
66"	5.5'	4'	3807	4188	1260	660	"

Job Amble Dev North Computed By C. Johnson Date 30 Aug 1970
 Description DO INLETS @ UNSER Checked By MAK Date _____
+CENTRAL HAVE CAPACITY - H.O. TO PICK UP FLOW Sheet _____ of _____

PIPES ON CENTRAL WEST OF UNSER

pick up 130 100yr flow (from H_{max}) = 193.4 cfs

130 drains to 5-48" (4') ϕ RCP's - one pipe has
 2.12' backslope

$\frac{193.4}{4}$ Assume 48.4 cfs to each pipe (excluding 1- with backslope)

$$S = Ave = 1.074$$

$$n = .013$$

$$Norm depth = 1.569$$

$$Area = 4.573 \rightarrow V = 10.6 \text{ fps}$$

THEREFORE - PIPES HAVE CAPACITY FOR 130 EASILY
 MORE CAPACITY AVAILABLE

Job _____ Computed By MSH Date 7-6-90
 Description _____ Checked By BLC Date _____
 Sheet 1 of _____

Size Unsewer Storm Drain

Due to lack of ponding and channel improvements west of Unsewer, it is very possible that the 42" SD may be running at full capacity and the street also be full to the top of sidewalk

Per attached sketch, with flow to back of sidewalk

$$\Rightarrow A = 52 \text{ SF} \\ WP = 9 \text{ ft}$$

At ponding area, street grade is 0.0105'. Flow in excess of street capacity at this point will be intercepted by the pond and channel.

By Mannings

$$V = \frac{1.486}{0.017} \left(\frac{52}{9 \text{ ft}} \right)^{2/3} \sqrt{0.0105} = 5.86 \text{ fps}$$

$$Q = VA = 5.86 \text{ fps} (52 \text{ SF}) = \underline{305} \text{ cfs street flow.}$$

Unsewer SD $\Rightarrow$ 42" @ 0.00993'


per DPM Plate 22.3 8-5, $K = 1006$

$$Q = K \sqrt{S} = 1006 \sqrt{0.00993} = \underline{100} \text{ cfs}$$

} NA due to ponding
 M&B
 10/31/90

$$\Rightarrow \text{size Unsewer line for minimum of } 305 + 100 = \underline{\underline{405 \text{ cfs}}}$$

Construction
See Sheet 2 for Layout



Construction
(Symmetrical about E)
49'-0"

Limits of Payment for Grading

Profile Grade (Typ.)
10'-0" 10'-0" 4'-0" 4'-0" 10'-0" 10'-0"

Grade Natural Ground

Varies - See Plans

Shoulder Stripe 0.2' (by Others) 5:29

Varies 6'-0" Side-walk

Grade New Const within Spec Tempers Construct

SEE DETAIL "A"

1 1/2" Asphaltic Concrete Surface Course 1800# Stability

Tack Coat (May Be Deleted By The Engineer)

2 1/2" Asphaltic Concrete Base Course 1500# Stability

6" Cement Treated Base or 4" Asphalt Treated Base

6" Compacted Subbase or 8" Compacted Subbase


6" Compacted Subgrade

See General Note # 30

4" Sidewalk


6" Compacted Subgrade

DETAIL "A"



TYPICAL SECTION WITHOUT BIKE LANE


NOT TO SCALE - CENTRAL AVENUE TO BLUEWATER ROAD



STA(ft)	ELEV(ft)	MANNINGS n (to Next #)
0	3	.03
9	0	.03
14	0	.03
23	3	.03

Earth Ditch along
Unser just north
of Bridge

Channel Slope = .003 ft./ft.

D=2'  3:1

RATING CURVE

WSE(ft)	D(ft)	AREA-sf	WT.P-ft	Q-(cfs)	V-fps	Fr.#	TW(ft)
0	0	0	0	0	0	0	0
.1	.1	.5	5.6	.2	.5	.322	5.6
.2	.2	1.1	6.2	.9	.8	.357	6.2
.3	.3	1.7	6.8	1.9	1	.379	6.8
.4	.4	2.4	7.5	3.2	1.2	.394	7.4
.5	.5	3.2	8.1	4.7	1.4	.407	8
.6	.6	4	8.7	6.6	1.6	.417	8.6
.7	.7	4.9	9.4	8.8	1.7	.425	9.2
.8	.8	5.9	10	11.3	1.9	.433	9.8
.9	.9	6.9	10.6	14.1	2	.439	10.4
1	1	8	11.3	17.2	2.1	.445	11
1.1	1.1	9.1	11.9	20.7	2.2	.451	11.6
1.2	1.2	10.3	12.5	24.5	2.3	.456	12.2
1.3	1.3	11.5	13.2	28.7	2.4	.461	12.7
1.4	1.4	12.8	13.8	33.3	2.5	.465	13.4
1.5	1.5	14.2	14.4	38.3	2.6	.469	14
1.6	1.6	15.6	15.1	43.7	2.7	.473	14.6
1.7	1.7	17.1	15.7	49.4	2.8	.477	15.2
1.8	1.8	18.7	16.3	55.6	2.9	.481	15.8
1.9	1.9						

Job Amole Del Norte Computed By L. John Date 28 Sep 1990
 Description calc channel Checked By Wall Date _____
depths - add flow south of Bridge Sheet 1 of _____
(16, 20, 21 west) at Unsen

UNS / BRIDGE ①

$$Q = 1693 \text{ } 1603$$

$$+10\% \quad 1862 \text{ } 1763$$

$$S = .004$$

$$D = 5.5'$$

$$V = 16.2$$

RunDown / Bridge ②

$$Q = 1742 \text{ } 1667$$

$$1910 \text{ } 1834$$

$$S = .004 \quad S = 1.47$$

$$D = 5.6 \quad D = 4.04$$

$$V = 16.3 \quad V = 26.22$$

Stinson / Bridge ③

$$\text{use } 1957 \text{ } 1705$$

$$Q = 1774 \text{ or } 1779$$

$$1951 \text{ } 1757$$

$$S = 1.47 \quad 1.876$$

$$D = 4.08$$

$$V = 26.37$$

Channel - 10' bottom / 2:1 SS / SEE ATTACHED RATING CURVES

FB $0.7(2.0 + 0.025 \sqrt{d^{1/3}})$ DPM 22.3 p. 61

① $S = .004 \quad FB = 1.90$

② a) $S = .004 \quad FB = 1.91$

b) $S = .0147 \quad FB = 2.13$

③ a) $S = 1.47 \quad FB = 2.14$

Super Elev $S = 1.3 \quad \frac{V^2(b+2ZD)}{gr}$ DPM 22.3 p. 59

① $R = 3750 \quad 1.3 \quad \frac{16.2(10 + 2(2)5.5)}{32.2(3750)} = .006$

② a) $R = 3750 \quad 16.3 \quad 5.6 = .006$

LE $L_E = 0.32(b+2ZD) \frac{V}{D}$ DPM 22.3 p. 61

① $L_E = 70.73 \quad \text{use } 72' \quad \text{use } R = 2(3750) = 7500$

② a) $L_E = 71.4149$

PRELIMINARY RESULTS OF GEOTECHNICAL
INVESTIGATION FOR TWO CROSSING STRUCTURES

V Vinyard & Associates, Inc.

4415-D Hawkins, NE
Albuquerque, New Mexico 87109
(505) 345-1937

A
Geotechnical Engineering • Materials Testing • Environmental Engineering

October 25, 1990

Greiner Engineering, Inc.
5971 Jefferson Street, NE
Suite 101
Albuquerque, New Mexico 87109

Attention: Mr. Mark Holstead

Subject: Preliminary Results of Geotechnical Investigation for Two
Crossing Structures Associated with the Amole del Norte
Storm Diversion Facilities, Phase III, Vinyard &
Associates' Project No.: 90-1-81

Gentlemen:

Vinyard & Associates, Inc. has completed the field investigation for the proposed crossing structures over the Amole del Norte Storm Diversion Channel. This letter presents the results of our field investigation and preliminary recommendations for crossing structure foundation design. At the time this letter was prepared, a final decision if the crossing structures were to be bridges or box culverts had not been made.

To evaluate subsurface conditions, two test holes were drilled. One test hole was located near the intersection of Bridge Boulevard and Stinson Street and a second near 3720 Bridge Boulevard, SW (Delgado's Wrought Iron Shop). Both test holes were advanced to a depth of forty feet.

The soils encountered at both sites were very similar. The soil profile consisted of silty to very silty fine sands with some slightly gravelly lenses. The soils were loose near the ground surface and medium dense at greater depths. Soils were slightly moist. No groundwater or bedrock was encountered.

If a box culvert is constructed the structure may be supported on compacted natural ground or conventional spread footings as appropriate.

If a bridge is constructed the proposed structure may be supported on either augered, pressure grouted piles or conventional spread footings bearing on a minimum of four feet of compacted fill. Either foundation system will provide stable support.


V
&
A

Greiner Engineering, Inc.
Page 2

Selection of a foundation system may be based upon cost and speed of construction.

Detailed results of our investigation and complete geotechnical recommendations for design will be presented in our forthcoming geotechnical report for the project. In the interim should any questions arise, please call.

Sincerely,
Vinyard & Associates, Inc.



Martin D. Vinyard, P. E.

File: 90-1-81.pre

MINUTES - CENTRAL AVENUE
FRONTAGE ROAD MEETING

Minutes

Time: 10:00 AM to 11:00 AM
Date: 9/14/90
Place: Public Works Conference Room, 5th Floor
City/County Building
Topic: Amole Del Norte Drainage
Facilities, Phase III
Central Avenue Frontage Road
Attendance: Jerold Widdison, Transportation Planning
Richard Dourte, Public Works
Loren Meinz, Hydrology Division
Kapil Goyal, Hydrology Division
Mark Holstad, Greiner, Inc.

Discussion:

1. Reviewed recommendations of the West Route 66 Sector Development Plan. Pertinent items were: (*italics added for emphasis*)

a) Page 47,

"The Segment Two portion of the roadway is a raised rural section with drainage culvert under the road. There is a fragment of a frontage road existing between Unser Boulevard and approximately 106th Street on the north side of Central Avenue. This frontage road lies below the grade of Central Avenue and inappropriately acts as a drainage ponding area during heavy storms. *This frontage road is not constructed as a permanent facility. Changes to the existing frontage road will not occur immediately and will be handled on a case-by-case basis as properties develop or redevelop.*"

b) Page 48,

"The ultimate design for Central Avenue is recommended to be an urban section with curb, gutter, and sidewalk. It will include a six-lane divided roadway from the river to Unser Boulevard, and a four-lane divided roadway west of Unser to the I-40 interchange with possible expansion to six lanes beyond the normal 20-year planning horizon."

Greiner

Minutes

September 14, 1990

Page 2

c) Page 49,


"Central Avenue's *ultimate design* in Segment Two will require median cuts at 1/8-mile intervals and driveway consolidation to the *maximum extent possible* as determined on a case-by-case basis by the Transportation Development Division of the Albuquerque Public Works Department."

2. Determined to remove frontage road and to not replace it where the new storm drain will be run. Extend and consolidate driveways to provide access to adjoining properties.
3. Review NMSHTP authority to affect street design in this section.

Distribution: Attendees

Note: Please comment immediately if discrepancies are noted.

Prepared by Mark Holstad, 9/21/90



AMOLE/minutes

PRELIMINARY PLANS DRAWING LIST

INDEX TO DRAWINGS

NO.	DESCRIPTION
1.	TITLE SHEET
2.	SHEET LAYOUT & LEGEND
3.	BRIDGE BLVD. - STA. 9+00 TO STA. 20+00
4.	BRIDGE BLVD. - STA. 20+00 TO STA. 32+00
5.	BRIDGE BLVD. - STA. 32+00 TO STA. 44+00
6.	UNSER BLVD. - STA. 10+25 TO STA. 23+00
7.	UNSER BLVD. - STA. 23+00 TO STA. 35+00
8.	UNSER BLVD. = STA. 35+00 TO STA. 45+00
9.	BRIDGE BLVD. - STA. 44+00 TO STA. 56+00
10.	BRIDGE BLVD. - STA. 56+00 TO STA. 68+00
11.	BRIDGE BLVD. STA. 68+00 TO STA. 78+30
12.	BRIDGE BLVD. - STA. 10+00 TO STA. 17+00
13.	BRIDGE BLVD. - STA. 17+00 TO STA. 29+00
14.	BRIDGE BLVD - STA. 29+00 TO STA. 37_50
15.	90TH ST. - STA. 10+30 TO STA. 15+53
16.	STORM DRAIN PROFILES
17.	TYPICAL CHANNEL DETAILS
18.	MISCELLANEOUS DETAILS
19.	PIPE PENETRATION AND MISC. DETAILS
20.	NO TYPICAL BRIDGE SECTIONS
21.-25.	CHANNEL CROSS SECTIONS

DRAINAGE EASEMENT - SAD 214 POND

TAX CODE NO: NONE

LEGAL: TRACT A-1
ATRISCO BUSINESS PARK

GRANTOR/GRANTEE: WESTLAND DEVELOPMENT
CO. INC.

PROJECT NAME: DRAINAGE EASEMENT

FILE NO.: K-10-128

FOR
DRAINAGE

THIS INDENTURE made and executed this 12th day of
February Inc., 1984 by and between WESTLAND
DEVELOPMENT CO., INC. in the County of Bernalillo and State
of New Mexico hereinafter called the Grantors and THE CITY OF
ALBUQUERQUE, NEW MEXICO, a municipal corporation, hereinafter
called Grantee.

WITNESSETH, that for valuable considerations the
receipt of which is hereby acknowledged the Grantors have this
day bargained and sold and by these presents do sell, convey and
deliver unto the City of Albuquerque a permanent easement as
right-of-way including the permanent right to enter upon the real
estate hereinafter described at any time that it may see fit and
construct, maintain and repair drainage easement across, through,
and under the lands hereinafter described and the further right
to remove trees, bushes, undergrowth and obstructions interfering
with the location, construction and maintenance of said easement.

The land affected by the grant of this easement and right-
of-way is located in the County of Bernalillo and State of New
Mexico and is more particularly described as follows:

SEE ATTACHED EXHIBITS "A" AND "A-1"

TO HAVE AND TO HOLD the said right and easement for the
uses and purposes aforesaid, unto Grantee its successors and assigns
for so long as said easement shall not be abandoned for use as a
right-of-way for aforesaid drainage. In the event other drainage
facilities replace this easement, this easement will be relinquished
by Grantee.

The Grantors do hereby covenant with Grantee that they are
lawfully seized and possessed of the real estate above described and
that they have a good and lawful right to convey it or any part hereof,
that it is free from all encumbrances except those of record and taxes
due and owing the Treasurer of Bernalillo County and that they will
forever warrant and defend the title thereto against the lawful claims
of all persons whomsoever.

As a part of the consideration for this grant, the Grantors do hereby release any and all claims for damages for whatsoever cause incidental to the exercise of the rights herein granted provided, however, that the Grantee agrees to save Grantors harmless from any and all liability that may arise as a result of the construction and use of the easement for the purposes set forth.

IN WITNESS WHEREOF, the parties have set their hands and seals this 17th day of July, 1984.

WESTLAND DEVELOPMENT CO. INC.

BY: Dil E. Cardona

STATE OF NEW MEXICO)
COUNTY OF BERNALILLO) ss.

The foregoing instrument was acknowledged before me this 17th day of July, 1984 by Westland Development Co. Inc.

Notary Public

My Commission Expires:

H4 FEB 16 AB 06

9A 528-531
Smith

That certain parcel of land situate within projected Sections 21 and 22, T 10 N, R 2E, N.M.P.M., Town of Atrisco Grant, City of Albuquerque, Bernalillo County, New Mexico being comprised of the north 130 feet of the south 205 feet more or less of Parcel "A-1" as shown and designated on the plat entitled "Replat of Parcel "A" Tracts G, an Un-named tract, K, L, and Portions of Bluewater Road NW, and Unser Boulevard NW, Unit No. 2, Atrisco Business Park" as filed for Public Record in the office of the Bernalillo County Clerk on July 19, 1982.

BEGINNING at the southeast corner of said Tract "A-1",

Thence N 14° 59' 00" W along the east property line of said Parcel "A-1" a distance of 75.00 feet to the POINT OF BEGINNING;

Thence S 75° 13' 20" W along the northern boundary of 75 foot drainage easement on the south 75 feet of Parcel "A-1" a distance of 950.82 feet;

Thence N 14° 48' 40" W along the west boundary of Parcel "A-1", also being the east right-of-way line of Unser Boulevard a distance of 130.00 feet.

Thence N 75° 13' 20" E along a line parallel with the south boundary of Parcel "A-1" a distance of 950.35 feet;

Thence S 14° 59' 00" E along the east boundary of Parcel "A-1" a distance of 130.00 feet to the POINT OF BEGINNING.

The above delineated property parcel of land contains 2.8369 acres, more or less. Said parcel is known as "additional easement required for the Unser Boulevard temporary retention pond."

EXHIBIT "A"

ATRISCO BUSINESS PARK
UNIT 2

TRACT A-1

56:056
M.75.13.20E

Proposed New R/W

2,00,000 MS

2.8369 ac.

05082' 575'13'20"N

Exist. R/W?

75.

Existing 75' Drainage Easement

63	162	191	1508	1558	1538
					SINSEH = HEISEN
					713860HE

TRACY A

First P/W

C-37

٢٠٣

TOWN OF	AIRISCO	GRANT	UNIT 4.
---------	---------	-------	---------

UNIT 4



1533. MR. STEVEN